LiquidHaskell: Experience with Refinement Types in the Real World

Niki Vazou, Eric L. Seidel, Ranjit Jhala

Szabó Márk

Haskell Background

Haskell's Type System

Haskell is a **statically typed** language.

- Every expression has a type.
- Types are checked before the program runs.
- Types are often inferred automatically.

Basic Types

Some common built-in types:

```
Int        -- integer
Float      -- floating point number
Double     -- floating point number
Num        -- [Int, Float, Double, ...]
Bool       -- True or False
Char       -- single character
String     -- text
```

Type Annotations

The operator `::` means “has type”.

```
age :: Int
age = 23

name :: String
name = "Mark"

active :: Bool
active = True
```

Function Types

The arrow (→) separates input and output types.

```
add :: Int -> Int -> Int
add x y = x + y
```

- First Int: first argument
- Second Int: second argument
- Last Int: result

Equivalent in a C-like language:

```
int add(int x, int y) { return x + y; }
```

Type Inference

Haskell can infer many types automatically.

```
1 age = 23
2 double x = x * 2
```

In GHCi we can inspect inferred types:

```
1 :t True
2 True :: Bool
3
4 :t "hello"
5 "hello" :: String
6
7 :t double
8 double :: Num a => a -> a
```

Limits of The Type System

We can’t define constraints for the types of a function like:

- Conditions about the value: `x > 0`
- Relationships between values: `a > b`

To check for positive we need to check inside the function:

```haskell
sqrtRoot :: Double -> Double
sqrtRoot x
  | x > 0 = sqrt x
  | otherwise = error "x must be greater than 0"
```

Refinement Types and LiquidHaskell

LiquidHaskell

Many of these properties and relationships can be verified using a combination of **Refinement Types** and **external SMT solvers**.

This paper introduces and experiments with **LiquidHaskell** a refinement typechecker used to verify more than **10.000** lines of Haskell code across popular libraries.

Including: *bytestring*, *text*, *vector-algorithms* and *xmonad*.

Refinement Types

Refinement types:

- contain a **predicate** which is assumed to be true for any element of the refined type.
- can express **preconditions** when used as function arguments or **postconditions** when used as return types.

Examples:

positive natural numbers

$x : \{n \in \mathbb{N} \mid n > 0\}$

even natural numbers

$x : \{n \in \mathbb{N} \mid n \bmod 2 = 0\}$

result is a positive number

$f : \mathbb{N} \to \{y \in \mathbb{N} \mid y > 0\}$

result > input

$f(x : \mathbb{N}) : \mathbb{N} \to \{y \in \mathbb{N} \mid y > x\}$


LiquidHaskell Architecture

Core

- Core is a simpler intermediate representation (GHC translates Haskell source to it)
- Source locations are preserved for error reporting

Constraints

- Refinement types are translated into logical constraints
- These constraints describe the properties that must hold




LiquidHaskell Architecture

Solution

- A fixpoint algorithm processes the constraints
- Any *SMT-LIB2* compatible solver checks whether the constraints can be satisfied (eg.: *Z3*, *CVC4*, …)

Result

- **SAFE** or **UNSAFE**: based on the verification of the refinement properties
- Errors are mapped back to their source-code locations



LiquidHaskell

LiquidHaskell is an **optional** type checker for Haskell. Refinement types are written inside **comments**, so they are optional and normal Haskell compilers can ignore them:

```
1 {-@ ... @-}
```

Execution

LiquidHaskell performs static verification before the Haskell program is executed. It does not become part of the executable or perform any checks during runtime.

LiquidHaskell Basics

```
1  {-@ type Natural = {v:Int | v >= 0} @-}
2  {-@ type Pos = {v:Int | v > 0} @-}
3
4  {-@ increment :: Natural -> Pos @-}
5  increment :: Int -> Int
6  increment x = x + 1
7
8  good1 = increment 0
9  good2 = increment 4
10
11 -- verification will fail here stating: Type Mismatch
12 bad = increment (-1)
```

LiquidHaskell Basics

```
1  {-@ type Natural = {v:Int | v >= 0} @-}
2  {-@ type Pos = {v:Int | v > 0} @-}
3
4  {-@ divide :: n:Natural -> d:Pos -> {v:Natural | v <= n} @-}
5  divide :: Int -> Int -> Int
6  divide x y = x `div` y
7
8  good = divide 5 2
9
10 -- With LH -> Type Mismatch before executing the code
11 -- Without LH -> runtime error: divide by zero
12 bad = divide 5 0
```

LiquidHaskell Parameterized Types

Type parameters are written as lowercase and **value parameters** are written as uppercase.

- **Type parameter:** *Int*, *Bool*, *[Int]*
- **Value parameter:** *0*, *10*, *100*

```
1 {-@ type NonEmpty a = {v:[a] | len v > 0} @-}
2
3 {-@ numbers :: NonEmpty Int @-}
4 numbers :: [Int]
5 numbers = []
6
7 {-@ letters :: NonEmpty Char @-}
8 letters :: [Char]
9 letters = ['a', 'b', 'c']
```

LiquidHaskell Parameterized Types

```
1  {-@ type Rng Low High = {v:Int | v >= Low && v <= High} @-}
2
3  {-@ grade :: Rng 0 100 -> Int @-}
4  grade :: Int -> Int
5  grade score
6      | score >= 90 = 5
7      | score >= 75 = 4
8      | score >= 60 = 3
9      | score >= 50 = 2
10     | otherwise   = 1
11
12 good = grade 85
13 bad = grade 120
```

LiquidHaskell Parameterized Types

```
1  -- a: element type, N list length
2  {-@ type ListN a N = {v:[a] | len v == N} @-}
3
4  {-@ numbers :: ListN Int 3 @-}
5  numbers :: [Int]
6  numbers = [1, 2, 3]
7
8  {-@ letters :: ListN Char 2 @-}
9  letters :: [Char]
10 letters = ['a', 'b']
11
12 {-@ invalid :: ListN Bool 3 @-}
13 invalid :: [Bool]
14 invalid = [True, False]
```

LiquidHaskell Type Aliases

Type Aliases: used for reusability and readability.

```
1  -- with type alias
2  {-@ predicate Between Low High V = V >= Low && V <= High @-}
3  {-@ type Rng Low High = {v:Int | Between Low High v} @-}
4
5  -- we can use the predicate inline as well
6  {-@ grade :: Rng 0 100 -> {v:Int | Between 1 2 v} @-}
7  grade :: Int -> Int
8  grade score
9      | score >= 50 = 2
10     | otherwise   = 1
11
12 good = grade 85
13 bad = grade 120
```

Contracts and Verification

LiquidHaskell Function Contracts

- **Precondition:** Constraint on the function's inputs.
- **Postcondition:** Constraint on the function's output.
- **Dependent types:** Output constraints can refer to input values.

```
1  {-@ type Rng Low High = {v:Int | v >= Low && v <= High} @-}
2
3  {-@ range :: lo:Int
4            -> hi:{Int | hi >= lo}
5            -> [Rng lo hi] @-}
6  range :: Int -> Int -> [Int]
7  range lo hi = [lo..hi]
8
9  -- [1..5] -> [1, 2, 3, 4, 5]
10 -- [5..1] -> []
```

LiquidHaskell Verification: Contracts

```
1  {-@ type Rng Low High = {v:Int | v >= Low && v <= High} @-}
2
3  {-@ range :: lo:Int
4            -> hi:{Int | lo <= hi}
5            -> [Rng lo hi] @-}
6  range :: Int -> Int -> [Int]
7  range lo hi = [lo..hi]
8
9  good = range 1 5
10 bad = range 5 1
```

- **SAFE:** range 1 5 satisfies the precondition $1 \leq 5$.
- **UNSAFE:** range 5 1 violates the precondition $5 \not\leq 1$.

LiquidHaskell Verification: Limitations

- Haskell's `[lo..hi]` is alias for `enumFromTo lo hi`.
- LiquidHaskell relies on refinement specifications to reason about library functions.
- Without a sufficiently precise specification for `enumFromTo`, it cannot prove that every element satisfies `Rng lo hi`.

```
1 -- Cannot verify the postcondition
2 range lo hi = [lo..hi]
```

Important

UNSAFE does not necessarily mean the code is wrong. It can mean LiquidHaskell cannot prove its correctness.

LiquidHaskell Verification: Recursive Range

```
1 {-@ range :: lo:Int
2           -> hi:{Int | lo <= hi}
3           -> [Rng lo hi] @-}
4 range :: Int -> Int -> [Int]
5 range lo hi
6   | lo <= hi = lo : range (lo + 1) hi
7   | otherwise = []
```

- At `lo == hi`, the recursive call is `range (hi + 1) hi`.
- Its precondition requires $hi + 1 \leq hi$, which is false.

LiquidHaskell Verification: Fixing the Boundary

```
{-@ range :: lo:Int
          -> hi:{Int | lo <= hi}
          -> [Rng lo hi] @-}
range :: Int -> Int -> [Int]
range lo hi
  | lo < hi   = lo : range (lo + 1) hi
  | otherwise = [lo]
```

- When `lo < hi`, integer arithmetic gives $lo + 1 \leq hi$.
- Otherwise, the precondition implies `lo == hi`; return the endpoint.
- Every returned element satisfies $lo \leq v \leq hi$.
- By default, LiquidHaskell tries to prove termination using a **decreasing argument**, but here `lo` increases instead.

LiquidHaskell Termination

Haskell only evaluates expressions when their results are needed (*non-strict evaluation*).

- Some functions may run forever without producing a result.
- **LiquidHaskell:** Must ensure that functions terminate to safely verify certain properties.
- By default, LiquidHaskell proves termination of each recursive function.

Termination metric

A termination metric is a value that:

- Gets smaller with **every** recursive call.
- Cannot decrease forever (e.g., a non-negative integer).

LiquidHaskell Termination: Factorial

A simple termination metric is a **non-negative integer**.

```
1 {-@ fac :: n:Nat -> Nat / [n] @-}
2 fac :: Int -> Int
3 fac 0 = 1
4 fac n = n * fac (n - 1)
```

- `Nat`: integers greater than or equal to zero.
- `/ [n]`: use the argument `n` as the termination metric.
- The base case returns immediately.
- The recursive case decreases `n` by 1 each call.

LiquidHaskell Termination: Proof Obligations

Refinement checking establishes the facts needed for `fac`:

- The input contract gives $n \geq 0$.
- In the recursive branch, $n \neq 0$, so $n > 0$.
- The next argument remains non-negative: $n - 1 \geq 0$.
- The metric strictly decreases: $n - 1 < n$.

Why this proves termination

A strictly decreasing sequence of non-negative integers cannot continue forever. At zero, the base case stops recursion.

LiquidHaskell Verification: Proving Termination

```
1 {-@ range :: lo:Int
2           -> hi:{Int | lo <= hi}
3           -> [Rng lo hi] / [hi - lo] @-}
4 range :: Int -> Int -> [Int]
5 range lo hi
6   | lo < hi   = lo : range (lo + 1) hi
7   | otherwise = [lo]
```

- `/ [hi - lo]` supplies an explicit **termination metric**.
- The precondition ensures $hi - lo \geq 0$.
- Each recursive call strictly decreases the metric:

$$hi - (lo + 1) = (hi - lo) - 1.$$

- At `lo == hi`, the metric is zero and recursion stops.

Refining Data and Interfaces

LiquidHaskell Measures

So far, the specifications have been limited to comparisons and arithmetic operations on **primitive** values. **Measures** describe **inductive properties** of algebraic data types.

```
1 {-@ measure myLen @-}
2 myLen :: [a] -> Int
3 myLen []     = 0
4 myLen (x:xs) = 1 + myLen xs
```

- One equation for each data constructor: `[]` and `(:)`.
- Each right-hand side must belong to the restricted refinement logic.
- `measure myLen` makes this Haskell function available in refinements; it must obey the measure restrictions.

LiquidHaskell Measures: Minimum Length

```
1 {-@ type MinLength a N = {v:[a] | myLen v >= N} @-}
2
3 {-@ good :: MinLength Int 3 @-}
4 good :: [Int]
5 good = [1, 2, 3, 4]
6
7 {-@ bad :: MinLength Int 3 @-}
8 bad :: [Int]
9 bad = [1, 2]
```

- `a` is the element type; `N` is the minimum length.
- **SAFE:** `good` has length 4, and $4 \geq 3$.
- **UNSAFE:** `bad` has length 2, and $2 < 3$.

LiquidHaskell Measures: Constructor Refinements

Each list constructor gives LiquidHaskell a **length fact**:

```
[]  :: {v:[a] | myLen v == 0}

(:) :: x:a -> xs:[a]
    -> {v:[a] | myLen v == 1 + myLen xs}
```

- `[]`: the length is zero.
- `x:xs`: the length is one more than `xs`.
- These facts are available when building or pattern matching on lists.

LiquidHaskell Measures: Using a Constructor Fact

Adding an element increases the minimum length.

```
1 {-@ prepend :: a -> MinLength a 2 -> MinLength a 3 @-}
2 prepend :: a -> [a] -> [a]
3 prepend x xs = x : xs
4
5 good = prepend 1 [2, 3]
6 bad = prepend 1 [2]
```

- Input contract: $myLen\ xs \geq 2$.
- Constructor fact: $myLen\ (x : xs) = 1 + myLen\ xs \geq 3$.

LiquidHaskell Measures: Function Contracts

Measures relate the **structure of inputs and outputs**.

```
1  -- Appending adds the lengths
2  {-@ append :: xs:[a] -> ys:[a]
3             -> {v:[a] | myLen v == myLen xs + myLen ys} @-}
4
5  -- Mapping preserves the length
6  {-@ map :: (a -> b) -> xs:[a]
7          -> {v:[b] | myLen v == myLen xs} @-}
8
9  -- Filtering cannot increase the length
10 {-@ filter :: (a -> Bool) -> xs:[a]
11            -> {v:[a] | myLen v <= myLen xs} @-}
```

LiquidHaskell Refined Data Types

Every value of a data type may need to satisfy an **invariant**.

```
1 data CSV a = CSV { cols :: [String], rows :: [[a]] }
```

- `cols`: the column names in the header.
- `rows`: the table's rows, containing values of type `a`.
- Haskell allows rows of different lengths.

CSV invariant

Every row must have exactly as many entries as the header has column names.

LiquidHaskell Refined Data Types: Definition

A field's refinement can refer to an **earlier field**.

```
1 {-@ type ListL a X = {v:[a] | len v == len X} @-}
2
3 {-@ data CSV a = CSV { cols :: [String]
4                     , rows :: [ListL a cols] } @-}
```

- `ListL a X`: a list with the same length as `X`.
- `rows`: a list of rows, each matching the length of `cols`.
- `len` is LiquidHaskell's built-in list length measure.

LiquidHaskell Refined Data Types: Verification

```
1 good = CSV ["Month", "Days"]
2              [ ["Jan", "31"]
3              , ["Feb", "28"]
4              , ["Mar", "31"] ]
5
6 bad =  CSV ["Month", "Days"]
7             [ ["Jan", "31"]
8             , ["Feb", "28"]
9             , ["Mar"] ]
```

LiquidHaskell Refined Data Types: Global Invariants

Like measures, refined data definitions strengthen **constructor types**.

```
1 -- Refined constructor type
2 CSV :: cols:[String] -> rows:[ListL a cols] -> CSV a
```

- Construction checks every row against the header length.
- Pattern matching makes this relationship available to the checker.
- No extra annotation is needed on individual CSV values.

Global guarantee: LiquidHaskell rejects CSV-typed expressions that violate this invariant.

LiquidHaskell Refined Type Classes

A **type class** defines a shared interface for different types.

```
1 class Reward a where
2   reward :: a -> Int -> Int
```

- `a`: the type that determines the reward policy.
- `reward`: takes a policy value and the current points.
- Each instance provides its own implementation.

Shared rule: points must be non-negative and cannot decrease.

LiquidHaskell Refined Type Classes: Contract

Refinements specify a **shared contract** for the class method.

```
{-@ class Reward a where
      reward :: a -> points:{Int | points >= 0}
             -> {v:Int | v >= points}
@-}
```

- **Precondition:** input points must be non-negative.
- **Postcondition:** the result cannot be smaller than the input.
- Every instance must satisfy the **same contract**.

LiquidHaskell Refined Type Classes: Bool Instance

A Boolean flag decides whether to add a bonus.

```
1 instance Reward Bool where
2   reward bonus points
3     | bonus     = points + 10
4     | otherwise = points
```

- `True`: add 10 points.
- `False`: keep the original points.
- Both branches satisfy $v \geq \mathit{points}$.

LiquidHaskell checks the instance against the class contract.

LiquidHaskell Refined Type Classes: Verification

```
1 good :: Int
2 good = reward True 20
3
4 bad :: Int
5 bad = reward True (-1)
```

- **SAFE:** `good` passes non-negative points and returns 30.
- **UNSAFE:** `bad` violates the precondition $points \geq 0$.

LiquidHaskell Refined Type Classes: Invalid Instance

What if we replace the bonus with a deduction?

```
1 -- alternative implementation:
2 instance Reward Bool where
3   reward bonus points
4     | bonus     = points - 10
5     | otherwise = points
```

- The first branch violates $v \geq points$.
- Callers must meet the precondition.
- Instances must prove the postcondition.

Totality and Advanced Termination

LiquidHaskell Totality: Missing Patterns

A function can pass Haskell's type checker but still fail on some inputs.

```
1 head :: [a] -> a
2 head (x:_) = x
3
4 good = head [1, 2, 3]
5 bad = head []
```

- The definition only handles non-empty lists.
- An empty list causes a **pattern-match exception**.
- Totality checking must prove that this failure cannot happen.

LiquidHaskell Totality: Core Translation

GHC makes the missing case explicit in Core:

```
1 head d = case d of
2   x:xs -> x
3   []   -> patError "head"
```

- Both list constructors now have a branch.
- `patError` throws an exception describing the failed match.
- To rule out this exception, prove that the error branch is **unreachable**.

LiquidHaskell Totality: Making Head Safe

Restrict the input to **non-empty lists**.

```
1 {-@ type NonEmpty a = {v:[a] | len v > 0} @-}
2 {-@ head :: NonEmpty a -> a @-}
3 head :: [a] -> a
4 head (x:_) = x
```

- The input contract gives $len\ v > 0$.
- The empty branch gives $len\ v = 0$: a contradiction.
- The error call is unreachable.

LiquidHaskell Termination: Processing Batches

Consider a simplified **batch worker** that counts completed jobs.

- `b`: batches remaining, including the current batch.
- `j`: jobs remaining in the current batch.
- Completing a job decreases `j`, while `b` stays unchanged.
- Moving to the next batch decreases `b` and resets `j` to 3.

Two batches of three jobs

$(2,3) \to (2,2) \to (2,1) \to (2,0) \to (1,3) \to \cdots \to (1,0)$.

Neither argument strictly decreases at every call. We supply a **custom termination metric**: the pair `[b, j]`.

LiquidHaskell Termination: Lexicographic Ordering

Compare the **batch count first**, then the job count.

```
1 {-@ jobs :: b:Nat -> j:Nat -> Nat / [b, j] @-}
2 jobs :: Int -> Int -> Int
3 jobs b j
4   | b == 0    = 0
5   | j > 0     = 1 + jobs b (j - 1)
6   | b == 1    = 0
7   | otherwise = jobs (b - 1) 3
8 -- jobs 2 3 == 6
```

LiquidHaskell Termination: Why the Pair Decreases

`/ [b, j]` uses **lexicographic ordering**: compare `b` first, and compare `j` only when `b` is unchanged.

- `jobs b (j - 1)`: the first component stays equal, the second decreases.
- `jobs (b - 1) 3`: the first component decreases.
- Both components remain non-negative.
- At `b == 0`, or when the last batch is empty (`b == 1` and `j == 0`), recursion stops.