API Authentication Specification

Integration: Dentira Care & Ortho Nu
Document Version: 1.0
Date: April 21, 2026

This document outlines the authentication specification required for Ortho Nu to securely communicate with the Dentira Care API. The integration utilizes the standard Client Credentials flow to obtain a bearer token, which is then used to authorize subsequent API requests.

1. Environments

The API is available in two environments. Ortho Nu must direct all authentication and subsequent API requests to the appropriate base URL.

Environment	Base URL (Host)	Purpose
Sandbox	https://vendor-care-sbx.dentira.com	Development, testing, and integration verification.
Production	https://vendor.care.dentira.com	Live operations and real data exchange.

2. Authentication Credentials

The following Client ID and Client Secret pairs are assigned to Ortho Nu for authenticating against the respective environments.

Sandbox Credentials

• Client ID: ortho_nu

• Client Secret: teez5cah5aeRoocup5iet5dip4uuChohTeeraivuji0mei0yahmeiQu1tuawaiph

Production Credentials

• Client ID: ortho_nu

• Client Secret: <redacted> (To be provided securely via encrypted channels)

3. Token Request Endpoint

To obtain an authorization token, make a standard POST request to the authentication endpoint using the client credentials.

POST /auth/token

Request Headers

Header	Value	Required
Content-Type	application/json	Yes

Request Body Payload

The body must be formatted as a JSON object containing the client credentials and the flow type.

```
{
  "client_id": "<client_id>",
  "client_secret": "<client_secret>",
  "flow": "CLIENT_CREDENTIALS"
}
```

Expected Response

Upon successful authentication, the API will return a JSON response containing the access token.

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5c...",
  "token_type": "Bearer",
  "expires_in": 3600
}
```

4. Using the Token

Once the access_token is obtained, Ortho Nu must include it in the headers of all subsequent requests to Dentira Care's protected API endpoints.

Pass the token in the Authorization header using the Bearer scheme:

```
Authorization: Bearer <access_token>
```

Security Best Practices

• Tokens have a limited lifespan (indicated by expires_in). Cache the token and only request a new one when the current token is near expiration.

• Never expose the client_secret or access_token in client-side code, public repositories, or unsecured logs.

• All requests must be made over HTTPS.