



北京航空航天大学
BEIHANG UNIVERSITY

ACM/ICPC

沈中海
计算机学院

Splay:

```
#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
#define N 6000000
#define INF 999999999
using namespace std;
long long root, n, m, flag2[N], list[N], fa[N], l[N], r[N], size[N], f[N][3], g[N], flag[N], sum[N],
a[N];
char s[20];
long long read(){
    long long p=0, q=1;
    char ch=getchar();
    while (ch<'0' || ch>'9'){
        if (ch=='-') q=-1;
        ch=getchar();
    }
    while (ch>='0' && ch<='9') p=p*10+ch-'0', ch=getchar();
    return p*q;
}
void update(long long t){
    if (l[t]) fa[l[t]]=t;
    if (r[t]) fa[r[t]]=t;
    sum[t]=sum[l[t]]+sum[r[t]]+a[t];
    size[t]=size[l[t]]+size[r[t]]+1;
    f[t][0]=max(f[l[t]][0],sum[l[t]]+f[r[t]][0]+a[t]);
    f[t][1]=max(f[r[t]][1],sum[r[t]]+f[l[t]][1]+a[t]);
    f[t][2]=f[l[t]][1]+f[r[t]][0]+a[t];
    f[t][2]=max(f[t][2],max(f[l[t]][2],f[r[t]][2]));
}
void pushdown(long long t){
    if (flag[t]){
        if (l[t]) flag[l[t]]^=1;
        if (r[t]) flag[r[t]]^=1;
        swap(l[t],r[t]);
        swap(f[l[t]][0],f[l[t]][1]);
        swap(f[r[t]][0],f[r[t]][1]);
        flag[t]=0;
    }
}
if (flag2[t]){
    if (l[t]){
        sum[l[t]]=g[t]*size[l[t]];
        if (g[t]>0)
```

```

        f[l[t]][0]=f[l[t]][1]=f[l[t]][2]=sum[l[t]];
    else
        f[l[t]][0]=f[l[t]][1]=0, f[l[t]][2]=g[t];
    g[l[t]]=a[l[t]]=g[t];
    flag2[l[t]]=1;
}
if (r[t]){
    sum[r[t]]=g[t]*size[r[t]];
    if (g[t]>0)
        f[r[t]][0]=f[r[t]][1]=f[r[t]][2]=sum[r[t]];
    else
        f[r[t]][0]=f[r[t]][1]=0, f[r[t]][2]=g[t];
    g[r[t]]=a[r[t]]=g[t];
    flag2[r[t]]=1;
}
flag2[t]=g[t]=0;
}
}
long long build(long long le, long long ri){
    if (le>ri) return 0;
    long long mid=le+ri>>1;
    l[mid]=build(le,mid-1);
    r[mid]=build(mid+1,ri);
    update(mid);
    return mid;
}
void insert(long long &t, long long k, long long p){
    if (!t){
        if (!size[t=p]){
            size[t]=1;
            f[t][0]=f[t][1]=a[t]>0?a[t]:0;
            f[t][2]=sum[t]=a[t];
        }
        return;
    }
    pushdown(t);
    if (size[l[t]]+1<=k) insert(r[t],k-size[l[t]]-1,p);
    else insert(l[t],k,p);
    update(t);
}
void zig(long long t){
    long long f1=fa[t], f2=fa[f1];
    if (f2)
        if (l[f2]==f1) l[f2]=t;else r[f2]=t;

```

```

    fa[t]=f2;
    l[f1]=r[t];
    r[t]=f1;
    update(f1);
    update(t);
}

void zag(long long t){
    long long f1=fa[t], f2=fa[f1];
    if (f2)
        if (l[f2]==f1) l[f2]=t;else r[f2]=t;
    fa[t]=f2;
    r[f1]=l[t];
    l[t]=f1;
    update(f1);
    update(t);
}

void splay(long long t){
    long long ri=1;
    list[1]=t;
    for (long long i=1;fa[list[i]];i++) list[++ri]=fa[list[i]];
    for (long long i=ri;i-->1) pushdown(list[i]);
    long long f1=fa[t], f2=fa[f1];
    while (f2){
        if (l[f2]==f1)
            if (l[f1]==t) zig(f1), zig(t);
            else zag(t), zig(t);
        else
            if (r[f1]==t) zag(f1), zag(t);
            else zig(t), zag(t);
        f1=fa[t];f2=fa[f1];
    }
    if (f1)
        if (l[f1]==t) zig(t);else zag(t);
    root=t;
}

long long find(long long t, long long k){
    pushdown(t);
    while (size[l[t]]+1!=k){
        if (size[l[t]]+1<k)
            k-=size[l[t]]+1, t=r[t];
        else
            t=l[t];
        pushdown(t);
    }
}

```

```

        return t;
    }
    void del(long long x, long long y){
        splay(x);
        fa[r[x]]=0;
        splay(y);
        l[r[root=x]=y]=0;
        update(y);
        update(x);
    }
    void modify(long long x, long long y, long long z){
        splay(x);
        fa[r[x]]=0;
        splay(y);
        r[root=x]=y;
        flag2[l[y]]=1;
        g[l[y]]=a[l[y]]=z;
        sum[l[y]]=size[l[y]]*z;
        if (z>0)
            f[l[y]][0]=f[l[y]][1]=f[l[y]][2]=sum[l[y]];
        else
            f[l[y]][0]=f[l[y]][1]=0, f[l[y]][2]=z;
        update(y);
        update(x);
    }
    void reverse(long long x, long long y){
        splay(x);
        fa[r[x]]=0;
        splay(y);
        fa[r[root=x]=y]=x;
        flag[l[y]]^=1;
        swap(f[l[y]][0],f[l[y]][1]);
        update(y);
        update(x);
    }
    void calc(long long x, long long y){
        splay(x);
        fa[r[x]]=0;
        splay(y);
        fa[r[root=x]=y]=x;
        printf("%d\n", sum[l[y]]);
        update(y);
        update(x);
    }
}

```

```

void print(long long t){
    if (!t) return;
    pushdown(t);
    print(l[t]);
    printf("%d ", a[t]);
    print(r[t]);
}

int main(){
    freopen("sequence4.in", "r", stdin);
    freopen("1.ans", "w", stdout);
    n=read();m=read();
    for (long long i=1;i<=n;i++) a[i]=read();
    f[0][2]=-INF;
    root=build(1,n);
    a[N-3]=a[N-2]=-INF;
    insert(root,0,N-3);
    insert(root,n+1,N-2);
    for (long long i=1;i<=m;i++){
        scanf("%s", s);
        if (s[0]=='I'){
            long long pos=read(), tot=read(), n2=n+tot, root2;
            if (!tot) continue;
            for (long long i=n+1;i<=n2;i++) a[i]=read();
            root2=build(n+1,n2);
            insert(root,pos+1,root2);
            splay(root2);
            n=n2;
        }
        if (s[0]=='D'){
            long long x=read(), y=read()+x+1;
            if (x+1==y) continue;
            x=find(root,x);
            y=find(root,y);
            del(x,y);
        }
        if (s[2]=='K'){
            long long x=read(), y=read()+x+1, z=read();
            if (x+1==y) continue;
            x=find(root,x);
            y=find(root,y);
            modify(x,y,z);
        }
        if (s[0]=='R'){
            long long x=read(), y=read()+x+1;

```

```

        if (x+1==y) continue;
        x=find(root,x);
        y=find(root,y);
        reverse(x,y);
    }
    if (s[0]=='G'){
        long long x=read(), y=read()+x+1;
        x=find(root,x);
        y=find(root,y);
        calc(x,y);
    }
    if (s[2]=='X'){
        printf("%d\n", f[root][2]);
    }
}
return 0;
}

```

LCT :

```

#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
#define mo 51061
#define N 200000
typedef unsigned int ll;
using namespace std;
int n, q, size[N], l[N], r[N], fa[N], rev[N], list[N];
ll sum[N], f[N], at[N], mt[N];
int read(){
    int p=0;
    char ch=getchar();
    while (ch<'0' || ch>'9') ch=getchar();
    while (ch>='0' && ch<='9') p=p*10+ch-'0', ch=getchar();
    return p;
}
bool isroot(int t){
    return (l[fa[t]]!=t) && (r[fa[t]]!=t);
}
void calc(int u, int m, int a){
    if (!u) return;
    f[u]=(f[u]*m+a)%mo;
    sum[u]=(sum[u]*m+a*size[u])%mo;
    at[u]=(at[u]*m+a)%mo;
}

```

```

        mt[u]=(mt[u]*m)%mo;
    }
void update(int t){
    if (l[t]) fa[l[t]]=t;
    if (r[t]) fa[r[t]]=t;
    sum[t]=(f[t]+sum[l[t]]+sum[r[t]])%mo;
    size[t]=1+size[l[t]]+size[r[t]];
}
void pushdown(int t){
    if (rev[t]){
        swap(l[t],r[t]);
        if (l[t]) rev[l[t]]^=1;
        if (r[t]) rev[r[t]]^=1;
        rev[t]=0;
    }
    int ta=at[t], tm=mt[t];
    if (ta || tm!=1){
        calc(l[t],tm,ta);
        calc(r[t],tm,ta);
    }
    at[t]=0;mt[t]=1;
}
void zig(int t){
    int f1=fa[t], f2=fa[f1];
    if (!isroot(f1))
        if (l[f2]==f1) l[f2]=t;else r[f2]=t;
    fa[t]=f2;
    l[f1]=r[t];
    r[t]=f1;
    update(f1);
    update(t);
}
void zag(int t){
    int f1=fa[t], f2=fa[f1];
    if (!isroot(f1))
        if (l[f2]==f1) l[f2]=t;else r[f2]=t;
    fa[t]=f2;
    r[f1]=l[t];
    l[t]=f1;
    update(f1);
    update(t);
}
void splay(int t){
    int ri=1;

```



```

list[1]=t;
for (int i=1;!isroot(list[i]);i++) list[++ri]=fa[list[i]];
for (int i=ri;i--){
    pushdown(list[i]);
}
int f1=fa[t], f2=fa[f1];
while (!isroot(t) && !isroot(f1)){
    if (l[f2]==f1)
        if (l[f1]==t) zig(f1), zig(t);
        else zag(t), zig(t);
    else
        if (r[f1]==t) zag(f1), zag(t);
        else zig(t), zag(t);
    f1=fa[t];f2=fa[f1];
}
if (!isroot(t))
    if (l[f1]==t) zig(t);else zag(t);
}
void access(int u){
    for (int v=0;u;v=u,u=fa[u]){
        splay(u);
        r[u]=v;
        update(u);
    }
}
void makeroot(int u){
    access(u);
    splay(u);
    rev[u]^=1;
}
void split(int u, int v){
    makeroot(u);
    access(v);
    splay(v);
}
void link(int u, int v){
    makeroot(u);
    fa[u]=v;
}
void cut(int u, int v){
    split(u,v);
    fa[u]=l[v]=0;
    update(v);
}

```

```

void modify(int u, int v, int m, int a){
    split(u,v);
    calc(v,m,a);
}
int main(){
    n=read();q=read();
    for (int i=1;i<=n;i++) size[i]=f[i]=sum[i]=mt[i]=1;
    for (int i=1;i<n;i++){
        int u=read(), v=read();
        link(u,v);
    }
    for (int i=1;i<=q;i++){
        char s[2];
        scanf("%s", s);
        int u=read(), v=read();
        if (s[0]=='+'){
            int c=read();
            modify(u,v,1,c);
        }
        if (s[0]=='-'){
            cut(u,v);
            u=read();v=read();
            link(u,v);
        }
        if (s[0]=='*'){
            int c=read();
            modify(u,v,c,0);
        }
        if (s[0]=='/'){
            split(u,v);
            printf("%d\n", sum[v]);
        }
    }
    return 0;
}

```

Suffix array:

```

#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
using namespace std;

```

```

int ls, a[3000], wv[3000], sa[3000], rk[3000], y[3000], r[3000], h[3000];
char s[3000];
int main(){
    while (scanf("%s", s)){
        ls=strlen(s);
        int m=max(ls,26);
        for (int i=0;i<2*ls;i++) rk[i]=-1;
        for (int i=0;i<m;i++) wv[i]=0;
        for (int i=0;i<ls;i++) a[i]=s[i]-'a';
        for (int i=0;i<ls;i++) wv[a[i]]++;
        for (int i=1;i<m;i++) wv[i]+=wv[i-1];
        for (int i=0;i<ls;i++) sa[--wv[a[i]]]=i;
        rk[sa[0]]=0;
        for (int i=1;i<ls;i++) rk[sa[i]]=rk[sa[i-1]]+(a[sa[i]]!=a[sa[i-1]]);
        for (int j=1;j<ls;j*=2){
            int p=0;
            for (int i=ls-j;i<ls;i++) y[++p]=i;
            for (int i=0;i<ls;i++)
                if (sa[i]>=j) y[++p]=sa[i]-j;
            for (int i=0;i<m;i++) wv[i]=0;
            for (int i=0;i<ls;i++) wv[rk[i]]++;
            for (int i=1;i<m;i++) wv[i]+=wv[i-1];
            for (int i=ls;i-->0) sa[--wv[rk[y[i]]]]=y[i];
            r[sa[0]]=0;
            for (int i=1;i<ls;i++)
                r[sa[i]]=r[sa[i-1]]+(rk[sa[i-1]]!=rk[sa[i]] || rk[j+sa[i-1]]!=rk[j+sa[i]]);
            for (int i=0;i<ls;i++)
                rk[i]=r[i];
        }
        int j=0;
        for (int i=0;i<ls;i++)
            if (rk[i]<ls-1){
                for (;j+sa[rk[i]+1]<ls && j+i<ls && a[j+sa[rk[i]+1]]==a[i+j];++j);
                h[rk[i]]=j?-1:0;
            }
        for (int i=0;i<ls-1;i++) cout<<h[i]<<endl;
    }
    return 0;
}

```

Miller-Rabin:

```
#include <iostream>
```

```

#include <cstdio>
#include <algorithm>
#include <cmath>
#include <cstring>
#include <map>
using namespace std;

const int times = 20;
int number = 0;

map<long long, int>m;
long long Random( long long n )          //生成[ 0 , n ]的随机数
{
    return ((double)rand( ) / RAND_MAX*n + 0.5);
}

long long q_mul( long long a, long long b, long long mod ) //快速计算 (a*b) % mod
{
    long long ans = 0;
    while(b)
    {
        if(b & 1)
        {
            b--;
            ans =(ans+ a)%mod;
        }
        b /= 2;
        a = (a + a) % mod;
    }
    return ans;
}

long long q_pow( long long a, long long b, long long mod ) //快速计算 (a^b) % mod
{
    long long ans = 1;
    while(b)
    {
        if(b & 1)
        {
            ans = q_mul( ans, a, mod );
        }
        b /= 2;
        a = q_mul( a, a, mod );
    }
}

```

```

    }
    return ans;
}

```

bool witness(long long a, long long n)//miller_rabin 算法的精华

{//用检验算子 a 来检验 n 是不是素数

long long tem = n - 1;

int j = 0;

while(tem % 2 == 0)

{

tem /= 2;

j++;

}

//将 n-1 拆分为 $a^r * s$

long long x = q_pow(a, tem, n);//得到 $a^r \bmod n$

if(x == 1 || x == n - 1) return true; //余数为 1 则为素数

while(j--) //否则试验条件 2 看是否有满足的 j

{

x = q_mul(x, x, n);

if(x == n - 1) return true;

}

return false;

}

bool miller_rabin(long long n) //检验 n 是否是素数

{

if(n == 2)

return true;

if(n < 2 || n % 2 == 0)

return false;

//如果是 2 则是素数，如果 <2 或者是 >2 的偶数则不

是素数

for(int i = 1; i <= times; i++) //做 times 次随机检验

{

long long a = Random(n - 2) + 1; //得到随机检验算子 a

if(!witness(a, n))

//用 a 检验 n 是否是素数

return false;

}

return true;

}

```

int main( )
{
    long long tar;
    cout<<rand()<<endl;
    cout<<RAND_MAX<<endl;
    cout<<Random( 100 - 2 )<<endl;
    cout<<Random( 100 - 2 )<<endl;
    while(cin >> tar)
    {
        if(miller_rabin( tar )) //检验 tar 是不是素数
            cout << "Yes, Prime!" << endl;
        else
            cout << "No, not prime.." << endl;
    }
    return 0;
}

```

树链剖分:

```

#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
#include <algorithm>
#define N 31000
#define M 100000
#define INF 999999
typedef long long ll;
using namespace std;
int n, cnt, son[N], sum[N*4], dep[N], fa[N], f[N*4], nex[M], nu[M], dfn[N], pre[N], top[N];
char s[10];
int read(){
    int p=0, q=1;
    char ch=getchar();
    while (ch<'0' || ch>'9'){
        if (ch=='-') q=-1;
        ch=getchar();
    }
    while (ch>='0' && ch<='9') p=p*10+ch-'0', ch=getchar();
    return p*q;
}
void add(int u, int v){
    nex[++cnt]=nex[u];nex[u]=cnt;nu[cnt]=v;
}
void dfs1(int u, int father){

```

```

    son[u]=1;
    int p=0;
    for (int j=nex[u];j!=nex[j]){
        int v=nx[j];
        if (v==father) continue;
        fa[v]=u;
        dep[v]=dep[u]+1;
        dfs1(v,u);
        son[u]+=son[v];
        if (son[v]>son[p]) p=v;
    }
    pre[u]=p;
}

void dfs2(int u, int father){
    if (!u) return;
    if (pre[father]==u) top[u]=top[father];else top[u]=u;
    dfn[u]=++cnt;
    dfs2(pre[u],u);
    for (int j=nex[u];j!=nex[j]){
        int v=nx[j];
        if (v==father || v==pre[u]) continue;
        dfs2(v,u);
    }
}

void update(int t, int l, int r, int x, int y){
    if (l==r){
        f[t]=sum[t]=y;
        return;
    }
    int mid=l+r>>1;
    if (x<=mid) update(t<<1,l,mid,x,y);else update((t<<1)+1,mid+1,r,x,y);
    sum[t]=sum[t<<1]+sum[(t<<1)+1];
    f[t]=max(f[t<<1],f[(t<<1)+1]);
}

int get_max(int t, int l, int r, int le, int ri){
    if (le<=l && r<=ri) return f[t];
    int mid=l+r>>1, p=-INF;
    if (le<=mid) p=max(p,get_max(t<<1,l,mid,le,ri));
    if (ri>mid) p=max(p,get_max((t<<1)+1,mid+1,r,le,ri));
    return p;
}

void query_max(int u, int v){
    int f1=top[u], f2=top[v], ans=-INF;
    while (f1!=f2)

```

```

        if (dep[f1]<dep[f2])
            ans=max(ans,get_max(1,1,n,dfn[f2],dfn[v])),
            v=fa[f2],
            f2=top[v];
        else
            ans=max(ans,get_max(1,1,n,dfn[f1],dfn[u])),
            u=fa[f1],
            f1=top[u];
        ans=max(ans,get_max(1,1,n,min(dfn[u],dfn[v]),max(dfn[u],dfn[v])));
        printf("%d\n", ans);
    }
}

int get_sum(int t, int l, int r, int le ,int ri){
    if (le<=l && r<=ri) return sum[t];
    int mid=l+r>>1, p=0;
    if (le<=mid) p+=get_sum(t<<1,l,mid,le,ri);
    if (ri>mid) p+=get_sum((t<<1)+1,mid+1,r,le,ri);
    return p;
}

void query_sum(int u, int v){
    int f1=top[u], f2=top[v], ans=0;
    while (f1!=f2)
        if (dep[f1]<dep[f2])
            ans+=get_sum(1,1,n,dfn[f2],dfn[v]),
            v=fa[f2],
            f2=top[v];
        else
            ans+=get_sum(1,1,n,dfn[f1],dfn[u]),
            u=fa[f1],
            f1=top[u];
    ans+=get_sum(1,1,n,min(dfn[u],dfn[v]),max(dfn[u],dfn[v]));
    printf("%d\n", ans);
}

int main(){
    cnt=n=read();
    for (int i=1;i<n;i++){
        int u=read(), v=read();
        add(u,v);
        add(v,u);
    }
    dfs1(1,0);
    dfs2(1,cnt=0);
    for (int i=1;i<=n;i++)
        update(1,1,n,dfn[i],read());
    for (int q=read();q;q--){

```



```

        scanf("%s", s);
        int u=read(), v=read();
        if (s[0]=='C') update(1,1,n,dfn[u],v);
        if (s[1]=='M') query_max(u,v);
        if (s[1]=='S') query_sum(u,v);
    }
    return 0;
}

```

Dinic:

```

#include <iostream>
#include <cstdlib>
#include <cstring>
#include <cstdio>
#include <algorithm>
#define N 10000
#define M 200000
#define INF 1e9
using namespace std;
int head[N],next[M],to[M],len[M],pr[M];
int n,m,cnt,S,T,m1en;
int tim[1000][1000];
int dis[N],pre[N],q[M];
bool vis[N];
inline void add(int u,int v,int r,int w)
{
    to[cnt]=v; len[cnt]=r; pr[cnt]=w; next[cnt]=head[u]; head[u]=cnt++;
    to[cnt]=u; len[cnt]=0; pr[cnt]=-w; next[cnt]=head[v]; head[v]=cnt++;
}
inline void read()
{
    memset(head,-1,sizeof head); cnt=0;
    scanf("%d%d",&m,&n);
    S=0; T=n+n*m+1;
    for(int i=1;i<=n;i++)
        for(int j=1;j<=m;j++)
            scanf("%d",&tim[i][j]);
    for(int i=1;i<=n;i++) add(S,i,1,0);
    for(int i=n+n*m;i>=n+1;i--) add(i,T,1,0);
    for(int i=1;i<=n;i++)
        for(int j=1;j<=m;j++)
            for(int k=1;k<=n;k++)
                add(i,j*n+k,1,(n-k+1)*tim[i][j]);
}

```

```

inline bool spfa(){
    memset(pre,-1,sizeof(pre));
    memset(dis,0x3f,sizeof(dis));
    int h=1, t=2, sta;
    q[1]=S;dis[S]=0;vis[S]=true;
    while (h<t){
        sta=q[h++];vis[sta]=false;
        for (int i=head[sta];~i;i=next[i])
            if (len[i] & dis[to[i]] >dis[sta]+ pr[i]){
                dis[to[i]]=dis[sta]+pr[i];
                pre[to[i]]=i;
                if (!vis[to[i]]) q[t++]=to[i], vis[to[i]]=true;
            }
    }
    return pre[T]!=-1;
}

inline void updata(){
    mlen=INF;
    for (int i=pre[T];i;i=pre[to[i^1]])
        mlen=min(mlen,len[i]);
    for (int i=pre[T];i;i=pre[to[i^1]])
        len[i]-=mlen, len[i^1]+=mlen;
}

inline void go(){
    int ans=0;
    while (spfa()) updata(), ans+=dis[T]*mlen;
    printf("%.2lf\n", double(ans)/n);
}

int main(){
    read();
    go();
    return 0;
}

```

Qsort:

```

#include <ctime>
#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
using namespace std;
int n, a[11000];
void qsort(int l, int r){

```

```

    int i=l, j=r, x=a[l+r>>1];
    while (i<=j){
        while (a[i]<x && i<r) i++;
        while (a[j]>x && j>l) j--;
        if (i<=j) swap(a[i++],a[j--]);
    }
    if (i<r) qsort(i,r);
    if (j>l) qsort(l,j);
}
int main(){
    srand(unsigned(time(NULL)));
    n=300;
    for (int i=1;i<=n;i++) a[i]=rand()%100;
    qsort(1,n);
    for (int i=1;i<=n;i++) cout<<a[i]<<' ';
    return 0;
}

```

整体二分:

```

#include <map>
#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
#include <algorithm>
#define N 80010
#define S 2000000
using namespace std;
int n, m, T, x, gt, cnt, DFN, LSH;
int a[N], k[N], u[N], v[N], c[N], ans[N], q[N];
int fa[N][21], dep[N], trans[N*2], lsh[N*2], nex[N*3], nu[N*3], dfn[N][2];
map<int,int> mp;
char s[S+100];
struct qlz_ques{
    int k, u, v, n;
}l[N*6], b1[N*6], b2[N*6];
int read(){
    int p=0;
    while (s[x]<'0' || s[x]>'9') x++;
    while (s[x]>='0' && s[x]<='9') p=p*10+s[x++]-'0';
    return p;
}
void add_edge(int u, int v){
    nex[++cnt]=nex[u];nex[u]=cnt;nu[cnt]=v;
}

```

```

}
void dfs(int u, int father){
    dfn[u][0]=++DFN;
    fa[u][0]=father;
    for (int i=1;fa[fa[u][i-1]][i-1];i++)
        fa[u][i]=fa[fa[u][i-1]][i-1];
    //cout<<DFN<<' '<<u<<endl;
    for (int j=nex[u];j=nex[j]){
        int v=nex[j];
        if (v==father) continue;
        dep[v]=dep[u]+1;
        dfs(v,u);
    }
    dfn[u][1]=DFN+1;
}
int LCA(int u, int v){
    if (dep[u]<dep[v]) swap(u,v);
    //cout<<u<<' '<<v<<endl;
    for (int i=20;i>=0;i--){
        if (dep[fa[u][i]]>=dep[v]) u=fa[u][i];
    }
    if (u==v) return u;
    for (int i=20;i>=0;i--){
        if (fa[u][i]!=fa[v][i]) u=fa[u][i], v=fa[v][i];
    }
    return fa[u][0];
}
void add(int k, int u, int v){
    l[++gt].k=k, l[gt].u=u, l[gt].v=v;
}
void update(int u, int v){
    for (int i=u;i<=n;i+=i&(-i)) c[i]+=v;
}
int sum(int u){
    int p=0;
    for (int i=dfn[u][0];i-=i&(-i)) p+=c[i];
    return p;
}
void solve(int le, int ri, int L, int R){
    //cout<<le<<' '<<ri<<' '<<L<<' '<<R<<endl;
    if (le>ri) return;
    if (L==R){
        for (int i=le;i<=ri;i++)
            if (l[i].n) ans[l[i].n]=L;
        return;
    }
}

```

```

int mid=L+R>>1, ct1=0, ct2=0;
for (int i=le;i<=ri;i++){
    if (l[i].n){
        int u=l[i].u, v=l[i].v, lca=LCA(u,v),k=sum(u)+sum(v)-sum(lca)-sum(fa[lca][0]);
        if (k>=l[i].k)
            b2[++ct2]=l[i];
        else
            l[i].k-=k,
            b1[++ct1]=l[i];
    }
    else
        if (l[i].v>mid || l[i].v<=-mid)
            b2[++ct2]=l[i],
            update(l[i].u,l[i].v>0?-1:-1);
        else
            b1[++ct1]=l[i];
}
for (int i=1;i<=ct1;i++) l[le+i-1]=b1[i];
for (int i=1;i<=ct2;i++) l[le+ct1+i-1]=b2[i];
for (int i=le;i<=ri;i++)
    if (!l[i].n && (l[i].v>mid || l[i].v<=-mid))
        update(l[i].u,l[i].v>0?-1:1);
solve(le,le+ct1-1,L,mid);
solve(le+ct1,ri,mid+1,R);
}
int main(){
    freopen("network10.in","r",stdin);
    freopen("整体二分.out","w",stdout);
//read
    fread(s,1,S,stdin);
    cnt=n=read();m=read();
    for (int i=1;i<=n;i++)
        lsh[++LSH]=a[i]=read();
    for (int i=1;i<=m;i++){
        int u=read(), v=read();
        add_edge(u,v);
        add_edge(v,u);
    }
    for (int i=1;i<=m;i++)
        k[i]=read(),
        u[i]=read(),
        v[i]=read(),
        (!k[i]?lsh[++LSH]=v[i]:0);
}

```

```

//lsh
dfs(dep[1]=1,0);
sort(lsh+1,lsh+1+LSH);
trans[mp[0]=++T]=0;
for (int i=1;i<=LSH;i++)
    if (lsh[i]!=lsh[i-1]) trans[mp[lsh[i]]=++T]=lsh[i];
for (int i=1;i<=n;i++)
    add(0,dfn[i][0],mp[a[i]]),
    add(0,dfn[i][1],-mp[a[i]]);
for (int i=1;i<=m;i++)
    if (k[i])
        add(k[i],u[i],v[i]),
        l[gt].n=i,
        q[i]=1;
    else
        add(0,dfn[u[i]][0],-mp[a[u[i]]]),
        add(0,dfn[u[i]][1],mp[a[u[i]]]),
        add(0,dfn[u[i]][0],mp[a[u[i]]=v[i]]),
        add(0,dfn[u[i]][1],-mp[v[i]]);
//work
solve(1,gt,0,T);
//int tot=0;
for (int i=1;i<=m;i++)
    if(q[i]){
        //tot++;
        if (ans[i]) printf("%d\n", trans[ans[i]]);
        else printf("invalid request!\n");
    }
//cout<<n<<' '<<m<<' '<<tot<<' '<<m-tot<<endl;
return 0;
}

```

主席树:

```

#include <map>
#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
#include <algorithm>
#define N 80010
#define M 8001000
#define S 2000000
using namespace std;

```

```

int n, m, T, x, cnt, DFN, LSH, ct_in, ct_out, cnt_tree;
int f[M], ls[M], rs[M];
int fa[N][21], dep[N], trans[N*2], lsh[N*2], a[N], nex[N*3], nu[N*3], root[N], bit[N], b1[N*2],
b2[N*2], dfn[N][2];
char s[S+100];
map<int,int> mp;
struct qlz_in{
    int n, dfn;
}in[N];
struct qlz_out{
    int n, dfn;
}out[N];
struct qlz_ques{
    int k, u, v;
}l[N];
int read(){
    int p=0;
    while (s[x]<'0' || s[x]>'9') x++;
    while (s[x]>='0' && s[x]<='9') p=p*10+s[x++]-'0';
    return p;
}
void add_edge(int u, int v){
    nex[++cnt]=nex[u];nex[u]=cnt;nu[cnt]=v;
}
bool cmp_in(qlz_in a, qlz_in b){return a.dfn<b.dfn;}
bool cmp_out(qlz_out a, qlz_out b){return a.dfn<b.dfn;}
void dfs(int u, int father){
    fa[u][0]=father;
    for (int i=1;fa[fa[u][i-1]][i-1];i++)
        fa[u][i]=fa[fa[u][i-1]][i-1];
    in[++ct_in].dfn=dfn[u][0]=++DFN;
    //cout<<DFN<<' '<<u<<endl;
    in[ct_in].n=u;
    for (int j=nex[u];j;j=nex[j]){
        int v=nu[j];
        if (v==father) continue;
        dep[v]=dep[u]+1;
        dfs(v,u);
    }
    out[++ct_out].dfn=dfn[u][1]=DFN+1;
    out[ct_out].n=u;
}
void add_b1(int u, int &ct1){
    if (root[dfn[u][0]]) b1[++ct1]=root[dfn[u][0]];
}

```

```

        for (int i=dfn[u][0];i-=i&(-i))
            if (bit[i]) b1[++ct1]=bit[i];
    }
    void add_b2(int u, int &ct2){
        if (root[dfn[u][0]]) b2[++ct2]=root[dfn[u][0]];
        for (int i=dfn[u][0];i-=i&(-i))
            if (bit[i]) b2[++ct2]=bit[i];
    }
    int LCA(int u, int v){
        if (dep[u]<dep[v]) swap(u,v);
        //cout<<u<<' '<<v<<endl;
        for (int i=20;i>=0;i--)
            if (dep[fa[u][i]]>=dep[v]) u=fa[u][i];
        if (u==v) return u;
        for (int i=20;i>=0;i--)
            if (fa[u][i]!=fa[v][i]) u=fa[u][i], v=fa[v][i];
        return fa[u][0];
    }
    void solve(int u, int v, int k){
        int ct1=0, ct2=0, l=0, r=T, lca=LCA(u,v);
        add_b1(u,ct1);
        add_b1(v,ct1);
        add_b2(lca,ct2);
        add_b2(fa[lca][0],ct2);
        //cout<<u<<' '<<v<<' '<<k<<' '<<lca<<endl;
        //for (int i=1;i<=ct1;i++) cout<<b1[i]<<' ';cout<<endl;
        //for (int i=1;i<=ct2;i++) cout<<b2[i]<<' ';cout<<endl;
        while (l<r){
            int mid=l+r>>1, p=0;
            for (int i=1;i<=ct1;i++) p+=f[rs[b1[i]]];
            for (int i=1;i<=ct2;i++) p-=f[rs[b2[i]]];
            //cout<<l<<' '<<r<<' '<<mid<<' '<<p<<' '<<k<<endl;
            if (p<k){
                for (int i=1;i<=ct1;i++)
                    b1[i]=ls[b1[i]],
                    (!b1[i]?b1[i--]=b1[ct1--]:0);
                for (int i=1;i<=ct2;i++)
                    b2[i]=ls[b2[i]],
                    (!b2[i]?b2[i--]=b2[ct2--]:0);
                k-=p;
                r=mid;
            }
            else{
                for (int i=1;i<=ct1;i++)

```



```

        b1[i]=rs[b1[i]],
        (!b1[i]?b1[i--]=b1[ct1--]:0);
    for (int i=1;i<=ct2;i++){
        b2[i]=rs[b2[i]],
        (!b2[i]?b2[i--]=b2[ct2--]:0);
    }
    l=mid+1;
}
}
if (l) printf("%d\n", trans[l]);
else printf("invalid request!\n");
}

void update(int x, int y, int z){
    int ct=0, l=0, r=T;
    for (int i=x;i<=DFN;i+=i&(-i)){
        if (!bit[i]) bit[i]=++cnt_tree;
        f[b1[+ct]=bit[i]]+=z;
    }
    while (l<r){
        int mid=l+r>>1;
        if (y<=mid){
            r=mid;
            for (int i=1;i<=ct;i++){
                if (!ls[b1[i]]) ls[b1[i]]=++cnt_tree;
                f[b1[i]=ls[b1[i]]]+=z;
            }
        }
        else{
            l=mid+1;
            for (int i=1;i<=ct;i++){
                if (!rs[b1[i]]) rs[b1[i]]=++cnt_tree;
                f[b1[i]=rs[b1[i]]]+=z;
            }
        }
    }
}

int main(){
    freopen("network10.in","r",stdin);
    freopen("p1146_主席树静态建树查询优化.out","w",stdout);
    //read
    fread(s,1,S,stdin);
    cnt=n=read();m=read();
    for (int i=1;i<=n;i++){
        lsh[+LSH]=a[i]=read();
    }
    for (int i=1;i<=n;i++){

```

```

        int u=read(), v=read();
        add_edge(u,v);
        add_edge(v,u);
    }
    for (int i=1;i<=m;i++)
        l[i].k=read(),
        l[i].u=read(),
        l[i].v=read(),
        (!l[i].k?lsh[++LSH]=l[i].v:0);
//lsh
    sort(lsh+1,lsh+1+LSH);
    trans[mp[0]=++T]=0;
    for (int i=1;i<=LSH;i++)
        if (lsh[i]!=lsh[i-1]) trans[mp[lsh[i]=++T]=lsh[i];
    for (int i=1;i<=n;i++) a[i]=mp[a[i]];
//build
    dfs(dep[1]=1,0);
    sort(in+1,in+1+n,cmp_in);
    sort(out+1,out+1+n,cmp_out);
    int j=1;
    for (int i=1;i<=n;i++){
        int k=root[in[i].dfn]=++cnt_tree, kk=root[in[i].dfn-1], l=0, r=T, v=a[in[i].n];
        while (l<r){
            int mid=l+r>>1;
            if (v<=mid)
                rs[k]=rs[kk],
                f[k=ls[k]=++cnt_tree]=f[kk=ls[kk]]+1,
                r=mid;
            else
                ls[k]=ls[kk],
                f[k=rs[k]=++cnt_tree]=f[kk=rs[kk]]+1,
                l=mid+1;
        }
        while (out[j].dfn==in[i].dfn){
            kk=root[in[i].dfn], k=root[in[i].dfn]=++cnt_tree, l=0, r=T, v=a[out[j++].n];
            while (l<r){
                int mid=l+r>>1;
                if (v<=mid)
                    rs[k]=rs[kk],
                    f[k=ls[k]=++cnt_tree]=f[kk=ls[kk]]-1,
                    r=mid;
                else
                    ls[k]=ls[kk],
                    f[k=rs[k]=++cnt_tree]=f[kk=rs[kk]]-1,

```

```

        l=mid+1;
    }
}
}
//work
for (int i=1;i<=m;i++)
    if (l[i].k)
        solve(l[i].u,l[i].v,l[i].k);
    else{
        int u=l[i].u, v=mp[l[i].v];
        update(dfn[u][0],a[u],-1);
        update(dfn[u][1],a[u],1);
        update(dfn[u][0],a[u]=v,1);
        update(dfn[u][1],a[u],-1);
    }
return 0;
}

```

Cdq(三维偏序):

```

#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
#include <algorithm>
#define N 600
#define M 500000
using namespace std;
int n, m, x, cnt, ans[M], q[M], c[N][N];
char s[6000010];
struct qlz{
    int n, v, x, y, c, x1, x2, y1, y2;
}l[M], b1[M], b2[M];
inline int read(){
    int p=0;
    while (s[x]<'0' || s[x]>'9') x++;
    while (s[x]>='0' && s[x]<='9') p=p*10+s[x++]-'0';
    return p;
}
inline bool cmp(qlz a, qlz b){return a.c<b.c;}
inline void update(int x, int y, int z){
    for (int i=x;i<=n;i+=i&(-i))
        for (int j=y;j<=n;j+=j&(-j))
            c[i][j]+=z;
}

```

```

}
inline int sum(int x, int y){
    int p=0;
    for (int i=x;i;i-=i&(-i))
        for (int j=y;j;j-=j&(-j))
            p+=c[i][j];

    return p;
}
inline void solve(int le, int ri, int L, int R){
    if (le>ri) return;
    if (L==R){
        for (int i=le;i<=ri;i++)
            if (!l[i].v) ans[l[i].n]=L;
        return;
    }
    int mid=L+R>>1;
    int ct1=0, ct2=0;
    for (int i=le;i<=ri;i++)
        if (l[i].v){
            if (l[i].v<=mid)
                b1[++ct1]=l[i],
                update(l[i].x, l[i].y, 1);
            else
                b2[++ct2]=l[i];
        }
    else{
        int k=sum(l[i].x2, l[i].y2)+sum(l[i].x1-
1, l[i].y1-1)-sum(l[i].x1-1, l[i].y2)-sum(l[i].x2, l[i].y1-1);
        if (k>=l[i].c)
            b1[++ct1]=l[i];
        else
            l[i].c-=k,
            b2[++ct2]=l[i];
    }

    for (int i=1;i<=ct1;i++) l[le+i-1]=b1[i];
    for (int i=1;i<=ct2;i++) l[le+ct1+i-1]=b2[i];
    //memcpy(l+le, b1+1, sizeof(l[0])*ct1);
    //memcpy(l+le+ct1, b2+1, sizeof(l[0])*ct2);
    for (int i=le;i<=ri;i++)
        if (l[i].v && l[i].v<=mid) update(l[i].x, l[i].y, -1);
    solve(le, le+ct1-1, L, mid);
    solve(le+ct1, ri, mid+1, R);
}
int main(){

```

```

fread(s, 1, 6000000, stdin);
n=read();m=read();
for (int i=1;i<=n;i++)
    for (int j=1;j<=m;j++)
        l[++cnt].c=read(),
        l[cnt].x=i,
        l[cnt].y=j;
sort(l+1, l+1+cnt, cmp);
for (int i=1;i<=cnt;i++) q[l[i].v]=l[i].c;
for (int i=1;i<=m;i++)
    l[++cnt].x1=read(),
    l[cnt].y1=read(),
    l[cnt].x2=read(),
    l[cnt].y2=read(),
    l[cnt].c=read(),
    l[cnt].n=i;
solve(1, cnt, 1, n*n);
for (int i=1;i<=m;i++) printf("%d\n", q[ans[i]]);
return 0;
}

```

Kmp:

```

#include <cstdio>
#include <cstring>
#include <cstdlib>
#include <iostream>
#define N 1010000
#define mo 1000000007
typedef long long ll;
using namespace std;
int ls, n, f[N], p[N];
char s[N];
int read() {
    int p=0;
    char ch=getchar();
    while (ch<'0' || ch>'9') ch=getchar();
    while (ch>='0' && ch<='9') p=p*10+ch-'0', ch=getchar();
    return p;
}
void pre() {
    ls=strlen(s+1);
    int j=0;
    f[1]=1;

```

```

        for (int i=2;i<=ls;i++) {
            while (j && s[j+1]!=s[i]) j=p[j];
            f[i]=f[p[i]=j+=s[j+1]==s[i]]+1;
        }
    }
}

void solve() {
    ll ans=1;
    int j=0;
    for (int i=2;i<=ls;i++) {
        while (j && s[j+1]!=s[i]) j=p[j];
        if (s[j+1]==s[i]) j++;
        while ((j<<1)>i && j) j=p[j];
        ans=ans*(f[j]+1)%mo;
    }
    cout<<ans<<endl;
}

void __init() {
    for (int i=read();i;i--) {
        scanf("%s", s+1);
        pre();
        solve();
    }
}

int main() {
    __init();
    return 0;
}

```