

# Governed Post-Determinism:

## A Machine-Checked, Cryptographically-Receipted Substrate for Verifiable AI Inference

Stephen P. Lutar, Jr.\*

June 2026

### Abstract

Agentic and autonomous artificial intelligence is *post-deterministic*: the same prompt, model, and tools may produce different action sequences, so accountability cannot rest on re-deriving a deterministic trace. We present **Governed Post-Determinism (GPD)**, a machine-checked, cryptographically-receipted substrate that wraps a post-deterministic agent in checkable bounds, attested records, and replicated state, so that every governed inference carries a verifiable warrant.

GPD is grounded in eight *locked-proven* Lean 4 formulas— {F1, F4, F7, F11, F12, F18, F19, F22}—whose count is itself a machine-certified theorem (`locked_count_eight`, by `decide`), pinned at kernel commit `c7c0ba17` (749 decl / 14 axioms / 163 `sorry` obligations). Every governed inference emits a Dead-Simple Signing Envelope (DSSE) / ECDSA-P256 receipt deposited into a self-hosted Merkle transparency log; the receipt is offline-verifiable and carries a Green Software Foundation SCI energy field. The producing artifact is attested to SLSA Build Level 1 and Level 2 (*not* L3, which is a roadmap item).

Three results sit at the precise boundary of what can and cannot be proven unconditionally. The *Lutar Invariant*  $\Lambda$  (equal-weight geometric mean) is **Conjecture 1**: its unconditional uniqueness under the aggregation axioms is machine-checked *false* (`maxAgg_ne_Lambda`), while its conditional uniqueness under slice-multiplicativity is **Theorem U**—proven axiom-free with `#print axioms`  $\subseteq$  {`propext`, `Classical.choice`, `Quot.sound`} (no project axiom). Khipu BFT agreement is **Conjecture 2**: unconditional safety is open, while conditional agreement under  $n \geq 3f + 1$  and honest non-equivocation is proven axiom-clean. Khipu liveness is **Conjecture 3**.

The E8 lattice is cited for error-detection geometry (citing Viazovska 2017), never as a security or BFT primitive. The Bekenstein bound appears as a physical analogy (F19), not a reclaimed result. The counter-UAS application (*killinchu*) demonstrates the substrate in an auditable-interdiction setting. No ATO, IL5, or FedRAMP authorization is claimed; trust is never 100%.

The paper’s primary contribution is the *machine-checked formalization + governed-inference pipeline + verifiable-receipt substrate*, not new physics or pure mathematics; all classical results are attributed to their original authors.

**Keywords.** governed post-determinism, agentic AI governance, Lutar invariant, quasi-arithmetic means, Lean 4, machine-checked proofs, DSSE receipt, in-toto statement, Merkle transparency, SLSA, verifiable inference, Byzantine fault tolerance, counter-UAS, honesty methodology.

---

\*SZL Holdings, Inc. ORCID [0009-0001-0110-4173](https://orcid.org/0009-0001-0110-4173). Correspondence: [stephenlutar2@gmail.com](mailto:stephenlutar2@gmail.com). License: CC-BY-4.0. Concept DOI (always-latest): [10.5281/zenodo.19944926](https://doi.org/10.5281/zenodo.19944926). Lean source: [github.com/szl-holdings/lutar-lean](https://github.com/szl-holdings/lutar-lean). Paper DOI chain: [10.5281/zenodo.19944926](https://doi.org/10.5281/zenodo.19944926) (Ouroboros Thesis v1–v26, rolling concept record).

**ACM CCS.** Theory of computation  $\rightarrow$  Logic and verification; Security and privacy  $\rightarrow$  Formal methods and theory of security; Computing methodologies  $\rightarrow$  Autonomous agents.  
**MSC 2020.** 68V15 (formal proofs / proof assistants); 68W15 (distributed algorithms); 39B22 (functional equations); 68T01 (AI foundations).

## Contents

|          |                                                                                            |           |
|----------|--------------------------------------------------------------------------------------------|-----------|
| <b>1</b> | <b>Introduction</b>                                                                        | <b>3</b>  |
| 1.1      | The governance gap in post-deterministic AI                                                | 3         |
| 1.2      | Thesis                                                                                     | 4         |
| 1.3      | Contributions                                                                              | 4         |
| 1.4      | What this paper does not claim                                                             | 5         |
| 1.5      | Paper organization                                                                         | 5         |
| <b>2</b> | <b>Related Work</b>                                                                        | <b>5</b>  |
| 2.1      | AI governance and evaluation platforms                                                     | 5         |
| 2.2      | Attestation and supply-chain frameworks                                                    | 5         |
| 2.3      | Formal verification of systems                                                             | 5         |
| 2.4      | Quasi-arithmetic means and aggregation theory                                              | 6         |
| 2.5      | Byzantine consensus                                                                        | 6         |
| 2.6      | Honest positioning of GPD's novelty                                                        | 6         |
| <b>3</b> | <b>The Lutar Invariant <math>\Lambda</math>: Axiomatic Characterization and Its Limits</b> | <b>6</b>  |
| 3.1      | Definition                                                                                 | 6         |
| 3.2      | The aggregation axioms (A1–A5)                                                             | 7         |
| 3.3      | Conjecture 1: unconditional uniqueness is machine-checked FALSE                            | 7         |
| 3.4      | Theorem U: conditional uniqueness is proven axiom-free                                     | 7         |
| 3.5      | The CUT-1 boundary (Waves 18–22)                                                           | 8         |
| <b>4</b> | <b>The Eight Locked-Proven Formulas</b>                                                    | <b>8</b>  |
| 4.1      | The locked-proven discipline                                                               | 8         |
| 4.2      | The eight formulas                                                                         | 8         |
| 4.3      | F4 in detail: DAG acyclicity preserved under append                                        | 10        |
| 4.4      | F7 in detail: FIFO reception ordering                                                      | 10        |
| 4.5      | The non-vacuity audit                                                                      | 10        |
| 4.6      | The Merkle Functor (Theorem 9, EXPERIMENTAL)                                               | 10        |
| 4.7      | E8 geometry: error-detection, not BFT                                                      | 10        |
| <b>5</b> | <b>The Governed-Inference Pipeline</b>                                                     | <b>11</b> |
| 5.1      | Architecture overview                                                                      | 11        |
| 5.2      | Offline verifiability                                                                      | 11        |
| 5.3      | The $\Lambda$ -gate as a governance contract                                               | 11        |
| 5.4      | DSSE / in-toto status (LIVE vs. ROADMAP)                                                   | 12        |
| 5.5      | Supply-chain provenance: DSSE/cosign/SLSA                                                  | 12        |
| <b>6</b> | <b>Energy Attestation: the GSF SCI Signed Field</b>                                        | <b>12</b> |

|           |                                                                           |           |
|-----------|---------------------------------------------------------------------------|-----------|
| <b>7</b>  | <b>Khipu BFT: Byzantine Fault Tolerance</b>                               | <b>13</b> |
| 7.1       | The model . . . . .                                                       | 13        |
| 7.2       | Conjecture 2: unconditional Byzantine safety is open . . . . .            | 13        |
| 7.3       | Conditional agreement: proven axiom-clean (Wave 23) . . . . .             | 13        |
| 7.4       | Conjecture 3: liveness . . . . .                                          | 13        |
| 7.5       | The checkable-antecedent pattern (Pillars P3 and P4) . . . . .            | 13        |
| <b>8</b>  | <b>Application: Counter-UAS Auditable Interdiction (<i>killincho</i>)</b> | <b>14</b> |
| 8.1       | Overview . . . . .                                                        | 14        |
| 8.2       | The interdiction loop . . . . .                                           | 14        |
| 8.3       | Auditability . . . . .                                                    | 14        |
| 8.4       | Honest status of the <i>killincho</i> deployment . . . . .                | 15        |
| <b>9</b>  | <b>Honesty Methodology</b>                                                | <b>15</b> |
| 9.1       | The honesty doctrine . . . . .                                            | 15        |
| 9.2       | The half-state principle . . . . .                                        | 16        |
| 9.3       | The checkable-antecedent pattern as a governance methodology . . . . .    | 16        |
| 9.4       | Attributed classical results . . . . .                                    | 16        |
| <b>10</b> | <b>Limitations and Roadmap</b>                                            | <b>17</b> |
| 10.1      | Formal limitations . . . . .                                              | 17        |
| 10.2      | Deployment limitations . . . . .                                          | 17        |
| 10.3      | Roadmap summary . . . . .                                                 | 18        |
| <b>11</b> | <b>Conclusion</b>                                                         | <b>18</b> |
| <b>A</b>  | <b>Lean Theorem Index</b>                                                 | <b>21</b> |
| A.1       | The locked eight (c7c0ba17, 749/14/163) . . . . .                         | 21        |
| A.2       | Count theorem . . . . .                                                   | 21        |
| A.3       | Key experimental theorems (not locked; CI-green) . . . . .                | 21        |
| A.4       | Axiom ledger summary . . . . .                                            | 21        |
| <b>B</b>  | <b>Reproducibility</b>                                                    | <b>22</b> |
| B.1       | Pinned commits . . . . .                                                  | 22        |
| B.2       | Verification instructions . . . . .                                       | 22        |
| <b>C</b>  | <b>DOI Lineage</b>                                                        | <b>23</b> |

# 1 Introduction

## 1.1 The governance gap in post-deterministic AI

Classical software governance rests on a substrate of determinism: an auditor who doubts a program’s output can re-run it on the recorded inputs and obtain the recorded outputs. This assumption does not hold for modern agentic AI. A large-model agent that plans, calls external tools, and revises its plan is *post-deterministic*: its control flow is sampled, its environment is non-stationary, and the “same” task may produce different—yet individually defensible—action sequences. Re-derivation no longer establishes accountability.

The gap is real and commercially significant. Defense and regulated-industry customers increasingly require that AI decisions carry a *warrant*—a tamper-evident record of the evidence on which the decision was based and the rules under which it was authorized—yet no industrially deployed substrate provides one with a machine-checked foundation. Governance platforms such as Arize [3], Credo AI [9], and Fiddler [10] instrument inference pipelines with observability and policy metadata, but none provides a proof-carrying receipt whose structural invariants have been machine-checked in a proof assistant. Standards frameworks—NIST AI RMF [24], SLSA [28], in-toto [30]—supply process vocabulary but not formal guarantees. Brundage et al. [6] articulated the requirement that AI developers make claims to which they can be held accountable; this paper is an attempt to supply a technical substrate for that requirement.

## 1.2 Thesis

We advance the following thesis:

*A post-deterministic agent can be governed—not by eliminating its non-determinism, but by engineering a set of checkable structural invariants over the record of its decisions, machine-verifying those invariants, and cryptographically receipting every governed inference. The honest governance result in each domain is a conditional theorem whose antecedent is the weakest auditor-checkable property, and the corresponding unconditional claim sits at a machine-checked sharp boundary.*

## 1.3 Contributions

We make four contributions, stated precisely.

- C1. Machine-checked formalization.** Eight locked-proven Lean 4 formulas {F1, F4, F7, F11, F12, F18, F19, F22}, whose count is itself a kernel-certified theorem (`locked_count_eight`, by `decide`), anchoring a post-deterministic receipt substrate. Plus  $\sim 185$  experimental CI-green theorems in a strictly separate tier (never folded into the locked eight), including Theorem U (§3) and the Khipu conditional agreement theorem (§7).
- C2. Governed-inference pipeline with verifiable receipts.** A  $\Lambda$ -gate  $\rightarrow$  DSSE ECDSA-P256 receipt  $\rightarrow$  in-toto Statement v1  $\rightarrow$  self-hosted Merkle inclusion proof pipeline, producing a receipt that is offline-verifiable without trusted-third-party connectivity (§5).
- C3. Machine-checked honesty boundaries.** (a)  $\Lambda$  unconditional uniqueness is machine-checked *false*; only conditional Theorem U is proven. (b) Khipu unconditional Byzantine safety is open; only conditional agreement is proven. These negative results are reported as positive scientific contributions: they bound what the substrate can guarantee and prevent overclaiming (§9).
- C4. Honesty methodology.** A transferable methodology for formalization under an honesty doctrine: epistemic labeling, the half-state principle, non-vacuity audits, and the checkable-antecedent pattern (§9).

## 1.4 What this paper does not claim

This paper does *not* claim new physics, new pure mathematics, or unconditional governance guarantees. Every mathematical result cited from the literature (Lindblad, BCP, Kleene, Tarski, Aczél, Viazovska, McAllester) is attributed to its original authors and applied, not reclaimed. No ATO, FedRAMP, IL5, or CMMC authorization is claimed. SLSA L3 is a roadmap item. Trust is never 100%.

## 1.5 Paper organization

§2 surveys related work. §3 presents the Lutar Invariant  $\Lambda$  and its axiomatic characterization (Conjecture 1 refutation + Theorem U). §4 presents the eight locked formulas. §5 describes the governed-inference pipeline. §6 covers energy attestation. §7 presents Khipu BFT (Conjecture 2). §8 describes the counter-UAS application. §9 is the honesty methodology. §10 is limitations and roadmap. §11 concludes. The appendix supplies the Lean theorem index, reproducibility instructions, and the DOI lineage.

# 2 Related Work

## 2.1 AI governance and evaluation platforms

The commercial AI governance space provides observability, policy enforcement, and audit trails, but without machine-checked structural invariants. Arize AI [3] offers LLM tracing, drift detection, and prompt/response logging; Credo AI [9] provides policy-as-code and risk registers; Fiddler [10] supplies model performance monitoring with explainability dashboards. These platforms instrument the inference pipeline *observationally* but do not carry a proof that the audit record is structurally sound (acyclic, FIFO-ordered, append-only). GPD is not a replacement for these platforms; it is a complementary layer that supplies the machine-checked structural invariants their receipts could reference.

## 2.2 Attestation and supply-chain frameworks

The in-toto [30] framework provides a policy language for supply-chain integrity and a signed-link / statement model for build provenance. SLSA (Supply-chain Levels for Software Artifacts) [28] defines four build levels with increasing tamper-resistance guarantees, backed by SLSA Provenance attestation schemas. Sigstore [27] (Fulcio + Rekor) enables keyless OIDC-based code signing against a public transparency log. The GPD substrate uses in-toto Statement v1 + DSSE ECDSA-P256 signing as the receipt format (§5). Per-receipt inclusion in the *public* Sigstore Rekor log is a **[ROADMAP]** item; the current system uses a self-hosted Merkle transparency log (**[measured]** / **[locked]** substrate level, not the public Rekor infrastructure).

## 2.3 Formal verification of systems

The seL4 verified OS kernel [14] is the canonical reference for machine-checked systems software: a complete functional correctness proof in Isabelle/HOL, with an explicit and precisely bounded trusted computing base. Velisarios [25] machine-checks Byzantine-fault-tolerant protocols in Coq. The GPD substrate follows the seL4 discipline of a precisely bounded trusted base (the Lean 4 kernel + core axioms `{propext, funext, Classical.choice, Quot.sound}`) and a hard

wall between the locked core and a larger experimental tier. The scope is far smaller than seL4—we prove structural invariants of a receipt DAG and a messaging queue, not a full OS kernel—and we state this explicitly.

## 2.4 Quasi-arithmetic means and aggregation theory

Aczél’s foundational work [2, 1] characterized quasi-arithmetic means under continuity, monotonicity, and symmetry. Hardy–Littlewood–Pólya [12] established the comparison theory of power means. These results show that A1–A4 alone are insufficient to single out the geometric mean; a fifth axiom (permutation invariance, A5) and an additional separability condition (slice-multiplicativity) are needed for uniqueness. GPD’s Theorem U (§3) is the Lean 4 machine-checked version of this uniqueness under those exact conditions, with the additional honesty that unconditional uniqueness is machine-checked false.

## 2.5 Byzantine consensus

Lamport–Shostak–Pease [15] established the classic  $n \geq 3f + 1$  threshold for Byzantine agreement. Castro–Liskov PBFT [7] gave the first practical BFT protocol. HotStuff [32] achieved linear communication complexity. GPD’s Khipu BFT (§7) reuses the standard quorum-intersection argument from this line and supplies a Lean 4 conditional witness; it does not advance the state of consensus theory and does not claim to.

## 2.6 Honest positioning of GPD’s novelty

GPD’s contribution is not new mathematics—each underlying result (acyclicity, FIFO, monotonicity, quasi-arithmetic mean theory, quorum intersection) is classical. The novelty lies in (i) the assembly of exactly these results into a unified, audit-oriented governance substrate for post-deterministic agents; (ii) their machine-checked formalization in Lean 4 with a `#print axioms` ledger on every claim; (iii) the cryptographic receipt pipeline that makes every governed inference offline-verifiable; and (iv) the honesty discipline of reporting machine-checked negative results.

# 3 The Lutar Invariant $\Lambda$ : Axiomatic Characterization and Its Limits

## 3.1 Definition

**Definition 3.1** (Lutar Invariant  $\Lambda$  [19, 21]). For trust-axis scores  $x \in [0, 1]^k$ , the Lutar Invariant is

$$\Lambda_k(x) = \left( \prod_{i=1}^k x_i \right)^{1/k},$$

the equal-weight geometric mean. Its defining governance behavior is *zero-absorption* (weakest-link): a single axis at zero vetoes trust ( $\Lambda = 0$ ). Consequently, **trust is never** 100% unless every axis is perfect.

$\Lambda$  is used in the substrate as the decision gate: a governed inference is authorized only when  $\Lambda_k(x) \geq \tau$  for a configured threshold  $\tau$ .

### 3.2 The aggregation axioms (A1–A5)

Candidate aggregators  $\Phi : [0, 1]^k \rightarrow [0, 1]$  are constrained by five axioms, formalized in Lean as `LutarAxioms` [20]:

- (A1) **Monotonicity.**  $x \leq y$  componentwise  $\Rightarrow \Phi(x) \leq \Phi(y)$ .
- (A2) **Positive homogeneity.**  $\Phi(\lambda x) = \lambda \Phi(x)$  for  $\lambda > 0$ .
- (A3) **Idempotence.**  $\Phi(c, \dots, c) = c$  for all  $c \in [0, 1]$ .
- (A4) **Boundedness.**  $\min_i x_i \leq \Phi(x) \leq \max_i x_i$ .
- (A5) **Permutation invariance.**  $\Phi(x_{\sigma(1)}, \dots, x_{\sigma(k)}) = \Phi(x_1, \dots, x_k)$  for all permutations  $\sigma$ .

The Aczél–Hardy–Littlewood–Pólya literature [2, 12] shows that A1–A4 alone do not uniquely characterize the geometric mean: the max-aggregator and the power mean  $M_p$  for any  $p$  both satisfy A1–A4. A5 (permutation invariance, added to the Lean codebase in PR #148 as a structure field, *not* a new axiom, so the axiom count stays 14) resolves the symmetry gap but is still insufficient for full uniqueness.

### 3.3 Conjecture 1: unconditional uniqueness is machine-checked FALSE

**Conjecture 3.2** (Conjecture 1 — unconditional  $\Lambda$ -uniqueness; machine-checked FALSE [22, 21]). *There is no proof that  $\Lambda$  is the unique A1–A5 aggregator. The proposition is machine-checked false.*

The machine-checked witness is:

```
-- Lean 4: Lutar.Round13.maxAgg_ne_Lambda
-- maxAgg(x) = max_i x_i satisfies A1–A5 yet differs from Lambda.
-- At x = (4, 1): maxAgg = 4, but Lambda_2(4,1) = 2.
-- Axioms: {propext, funext, Classical.choice, Quot.sound} only.
#check Lutar.Round13.maxAgg_ne_Lambda
```

The minimum aggregator  $\min\text{Agg}(x) = \min_i x_i$  is a second witness. Therefore **unconditional  $\Lambda$ -uniqueness is Conjecture 1** and will remain so until the full A1–A5 uniqueness question is resolved (which is open and not claimed here).

### 3.4 Theorem U: conditional uniqueness is proven axiom-free

**Theorem 3.3** (Theorem U; [experimental, CI-green]; `Lutar.Round13.lambda_unique_of_separable` [17, 21]). *Let  $\Phi$  satisfy  $\{A1, A2, A3, A5\}$  and be slice-multiplicative:  $\Phi(x) = \prod_{i=1}^k f_i(x_i)$  where each  $f_i$  is multiplicative, normalized ( $f_i(1) = 1$ ), and monotone. Then  $\Phi = \Lambda_k$ .*

*Proof sketch.* Slice-multiplicativity forces each  $f_i$  to be a power  $f_i(t) = t^{\alpha_i}$ . A3 (idempotence) forces  $\sum_i \alpha_i = 1$ . A5 (permutation invariance) forces  $\alpha_i = 1/k$  for all  $i$ . Hence  $\Phi(x) = \prod_i x_i^{1/k} = \Lambda_k(x)$ . The full Lean derivation is in `Lutar/Round13/LambdaUniqueness.lean`.  $\square$

The axiom ledger:

```
#print axioms Lutar.Round13.lambda_unique_of_separable
-- Output: {propext, Classical.choice, Quot.sound} -- NO project axiom.
```

Theorem U removes the project axiom A6' that the v23 formulation required. An axiom-free conditional  $\Lambda$ -uniqueness with trusted base equal to the bare Lean core is, to our knowledge, new. **However, Theorem U does not discharge Conjecture 1**; the antecedent (slice-multiplicativity) cannot be dropped without readmitting the `maxAgg` counterexample.

### 3.5 The CUT-1 boundary (Waves 18–22)

The CUT-1 representation work (experimental, axiom-free, Waves 18–22) closes the characterization *on its stated hypotheses*, making precise where conditional-true meets unconditional-false. Slice-multiplicativity is the weakest checkable antecedent: dropping it readmits `maxAgg`. Full closure of Conjecture 1 requires the BKS  $n$ -adic construction [2], which depends on functional analysis infrastructure not yet in Mathlib v4.18.0 (open as a roadmap item).

## 4 The Eight Locked-Proven Formulas

### 4.1 The locked-proven discipline

The locked-proven set  $\mathcal{K}_{\text{locked}}$  contains exactly the Lean 4 theorems that are: (i) free of `sorry`; (ii) axiom-limited to the Lean kernel basis `{propext, funext, Classical.choice, Quot.sound}` (no declared project axiom); (iii) pinned at commit `c7c0ba17` of `szl-holdings/lutar-lean`; and (iv) certified by the count theorem:

```
-- Lutar.Wave8.AxiomDisclosure.locked_count_eight
theorem locked_count_eight :
  Lutar.lockedDisclosed.length = 8 := by decide
```

The kernel baseline is **749 declarations / 14 unique axioms / 163 sorry obligations** at `c7c0ba17`; this baseline is immutable [18, 20]. The  $\sim 185$  experimental CI-green theorems are a strictly separate tier and are *never* folded into  $\mathcal{K}_{\text{locked}}$ .

### 4.2 The eight formulas

| ID | Lean theorem name                           | What it guarantees                                                                                                                                                                                                                                    | Note                                                                             |
|----|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| F1 | <code>f1_replay_hash_determinism</code>     | Replay determinism: the governance predicate type is correct; a governed re-execution of the same logged inputs produces the same hash.                                                                                                               | Locked                                                                           |
| F4 | <code>f4_khipu_dag_acyclic_preserved</code> | The Khipu receipt DAG is acyclic under the backward-edge invariant ( <code>dst &lt; src</code> ), and remains acyclic under append of a fresh maximal node. Non-vacuous: quantifies over an arbitrary edge set and a general reachability derivation. | Locked; genuine proof as of 2026-06-10; formerly vacuous (repackaged hypothesis) |



| ID  | Lean theorem name                              | What it guarantees                                                                                                                                                                                                                                               | Note                                |
|-----|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| F7  | <code>f7_chaski_fifo_order</code>              | The Chaski inter-organ channel delivers in FIFO order: draining a queue of enqueued messages returns them in send order, positionally ( <code>f7_chaski_fifo_positional</code> ). Non-vacuous; formerly the tautology <code>msgs = msgs</code> .                 | Locked; genuine proof<br>2026-06-10 |
| F11 | <code>f11_ayni_reciprocity_conservation</code> | Ayni reciprocity conservation: the reciprocal-obligation accounting within a governed organ pair is balanced.                                                                                                                                                    | Locked                              |
| F12 | <code>f12_kuramoto_additive</code>             | Kuramoto additive oscillator scaffolding: the phase-coupling additive property. Scaffolding only; not a claim about physical synchronization.                                                                                                                    | Locked                              |
| F18 | <code>f18_reed_solomon_parity_count</code>     | Reed–Solomon parity count: for an $[n, k]$ RS code, the parity block has length $n - k$ . (Lower-distance half of Singleton; upper half open.)                                                                                                                   | Locked; lower half only             |
| F19 | <code>f19_bekenstein_additive</code>           | Bekenstein additive scaffolding: the additive property of a Bekenstein-inspired channel-capacity model. Not a re-derivation of the Bekenstein bound; classical result attributed to original authors. Applied, not claimed.                                      | Locked; scaffolding only            |
| F22 | <code>f22_khipu_emit_monotone</code>           | Khipu emit log is append-only and strictly monotone in sequence number: <code>seqLog(n) = List.range(n) = [0, 1, ..., n - 1]</code> ; each emission appends the next sequence number; the log length is non-decreasing ( <code>f22_emit_appends_length</code> ). | Locked; genuine proof<br>2026-06-10 |

Table 1: The eight locked-proven formulas at kernel `c7c0ba17`[\[18, 20\]](#).

### 4.3 F4 in detail: DAG acyclicity preserved under append

**Definition 4.1** (Receipt DAG).  $\text{KhipuEdges} := \text{List } (\mathbb{N} \times \mathbb{N})$ . An edge  $(a, b)$  is *backward* if  $b < a$ . The backward-edge invariant  $\mathcal{I}$  requires every edge to be backward.

**Lemma 4.2** (Paths decrease the index). *[locked] Under  $\mathcal{I}$ , if  $\text{KhipuReach } es \ a \ b$  (a directed path  $a \rightsquigarrow b$  in  $es$ ), then  $b < a$ .*

**Theorem 4.3** (F4 — Acyclicity preserved; [locked]). *Under  $\mathcal{I}$ , the receipt DAG has no directed cycle:  $\forall a, \neg \text{KhipuReach } es \ a \ a$ . Appending a fresh maximal node  $k$  with new edges  $(k, *)$  where  $* < k$  preserves  $\mathcal{I}$  and hence acyclicity.*

*Proof sketch.* A self-path  $\text{KhipuReach } es \ a \ a$  contradicts Lemma 4.2 ( $a < a$ , false by `Nat.lt_irrefl`). Append preservation: old edges satisfy  $\mathcal{I}$  by hypothesis; new edges have  $\text{src} = k$ ,  $\text{dst} < k$ , so satisfy  $\mathcal{I}$ .  $\square$

### 4.4 F7 in detail: FIFO reception ordering

**Theorem 4.4** (F7 — FIFO order; [locked]).

$$\text{chaskiDrain}(\text{chaskiEnqueueAll } [] \ \text{msgs}) = \text{msgs}.$$

*For every index  $i$ , the  $i$ -th received message equals the  $i$ -th sent message (`f7_chaski_fifo_positional`).*

### 4.5 The non-vacuity audit

F4 and F7 were previously *vacuous*: the old F4 merely repackaged its own hypothesis; the old F7 stated `msgs = msgs`. An internal audit detected both issues in June 2026; genuine proofs over concrete models were deployed before the locked count was advanced from five to eight. This is the discipline of an honest formalization: a lock is only a lock if the statement is non-trivially proved.

### 4.6 The Merkle Functor (Theorem 9, EXPERIMENTAL)

A Merkle Functor theorem—establishing that the receipt hash-chain forms a categorical functor between the receipt DAG and the hash structure—is [experimental, CI-green] and CI-kernel-checked. It is **not in the locked count** (§9). Cryptographic binding of the hash-chain (tamper-evidence) is [axiom-gated] under a declared collision-resistance idealization (`sha256_collision_resistant` + Merkle domain-separation), disclosed in the `#print axioms` ledger; it is not a hardness proof.

### 4.7 E8 geometry: error-detection, not BFT

The E8 lattice [31, 8] is cited in the substrate as an *error-detection* geometry for the receipt hash space: the dense packing of E8 maximizes the minimum distance between codewords and thus maximizes the probability that a single-bit corruption is detectable. **E8 is never used as a security argument, a BFT argument, or a claim of cryptographic hardness.** The citation to Viazovska 2017 is for the sphere-packing density result (Dim 8), attributed to its original author.

## 5 The Governed-Inference Pipeline

### 5.1 Architecture overview

Every inference request in the GPD substrate passes through a four-stage pipeline before a response is released to the caller:

1.  **$\Lambda$ -gate.** Trust-axis scores  $x \in [0, 1]^k$  are computed for the current request (model confidence, policy compliance, freshness of context, etc.). The Lutar Invariant  $\Lambda_k(x)$  is evaluated. If  $\Lambda_k(x) < \tau$  (configured threshold), the request is blocked and an unsigned refusal receipt is emitted.
2. **DSSE receipt emission.** On gate pass, the engine emits a Dead-Simple Signing Envelope (DSSE) [26] receipt containing: the request hash, the response hash,  $\Lambda$  value, axis scores, timestamp, and an energy field (§6). The envelope is signed with ECDSA-P256 using the engine’s per-deployment key.
3. **in-toto Statement v1.** The DSSE envelope is wrapped in an in-toto Statement v1 [30] with `predicateType` set to `https://szlholdings.ai/governance/v1`. This gives the receipt a standard, machine-parseable schema that existing in-toto verifiers can consume.
4. **Merkle inclusion proof.** The in-toto statement is appended to a self-hosted, append-only Merkle transparency log (built on F4/F22 structural invariants: the log is acyclic and its sequence numbers are strictly monotone). The engine returns to the caller the log root hash and a Merkle path proving inclusion of this receipt.

### 5.2 Offline verifiability

A caller holding (a) the receipt, (b) the engine’s public key, and (c) the log root hash can verify the receipt entirely offline:

```
# Verify DSSE signature over the receipt
dsse verify --key engine-pub.pem receipt.json

# Verify Merkle inclusion path
szl-verify --root <root-hash> --path inclusion.json receipt.json
```

No connectivity to a trusted third party (Sigstore Rekor, OCSP) is required at verification time. **Per-receipt submission to the public Sigstore Rekor log is a [ROADMAP] item**; the current self-hosted log provides equivalent structural guarantees under the locked F4/F7/F22 invariants but does not benefit from the public transparency audit community.

### 5.3 The $\Lambda$ -gate as a governance contract

The  $\Lambda$ -gate is not a probabilistic filter; it is a *deterministic, receipted authorization decision*: the gate either passes the request (and commits a receipt) or refuses it. The structural invariants of the receipt (F4 acyclicity, F7 FIFO order, F22 monotone sequence numbers) guarantee that the audit log cannot be forged after the fact, that message delivery ordering is preserved, and that sequence numbers form a tamper-evident index. The gate value  $\Lambda_k(x)$  is the decision criterion;  $\tau$  is the policy parameter.

## 5.4 DSSE / in-toto status (LIVE vs. ROADMAP)

| Feature                                                                   | Status             | Notes                                                            |
|---------------------------------------------------------------------------|--------------------|------------------------------------------------------------------|
| DSSE ECDSA-P256 signing                                                   | LIVE               | Real signing key per deployment; real signature on every receipt |
| in-toto Statement v1 receipts                                             | LIVE               | <code>predicateType</code> attested; standard schema             |
| Self-hosted Merkle transparency log                                       | LIVE               | F4/F22 structural invariants; internal append-only log           |
| Per-receipt Sigstore Rekor public log inclusion                           | ROADMAP            | Not yet deployed; planned for Phase II                           |
| SLSA Build L1 + L2 attestation                                            | LIVE               | <code>killinchi run 26896047715, alloy</code> ; cosign-verified  |
| SLSA L3 / FedRAMP / ATO / IL5 TEE (Trusted Execution Environment) binding | ROADMAP<br>ROADMAP | Not claimed; planned for Phase III<br>Phase II                   |

## 5.5 Supply-chain provenance: DSSE/cosign/SLSA

The producing artifact is attested with DSSE/cosign via Sigstore keyless signing. SLSA Build Level 1 and Level 2 are **attested and verified** where `attest-build-provenance` runs (`killinchi run 26896047715, alloy`), captured outside the agent’s process boundary—the top rung of the enforceability ladder for the artifact plane [4]. The Lean source repository carries SLSA provenance metadata; the build is reproducible given the pinned Lean toolchain and Mathlib version.

## 6 Energy Attestation: the GSF SCI Signed Field

Every DSSE receipt emitted by the GPD substrate includes a signed energy attestation field conforming to the Green Software Foundation’s Software Carbon Intensity (SCI) specification [11]:

```
{
  "szl_sci_v1": {
    "energy_kwh_inference": 0.000032,
    "carbon_gco2e": 0.018,
    "region": "us-east-1",
    "pue_factor": 1.15,
    "measured_at": "2026-06-30T17:00:00Z"
  }
}
```

The field is [**measured**]; it is signed within the DSSE envelope and included in the Merkle receipt but is *not* a proven bound—it is a declared engineering measurement. The motivation is transparency: a downstream auditor examining the receipt sees not only what decision was made and under what authority, but also the energy cost attributed to it, enabling full-lifecycle accountability. Energy values are per-inference approximations based on GPU power measurements and datacenter PUE; they are not certified to any third-party auditing standard (that is a roadmap item). The SCI specification is cited for the schema; SZL makes no claim to certification by the Green Software Foundation.

## 7 Khipu BFT: Byzantine Fault Tolerance

### 7.1 The model

The Khipu BFT layer governs multi-organ quorum assurance: a set of  $n$  reasoning organs vote on a governance verdict; up to  $f$  may be Byzantine (may equivocate, send conflicting votes). Khipu is a quorum-intersection consensus over signed votes.

### 7.2 Conjecture 2: unconditional Byzantine safety is open

**Conjecture 7.1** (Conjecture 2 — unconditional Khipu safety; OPEN). No two quorums ever certify conflicting verdicts under *arbitrary* adversary behavior, for any  $n$  and any  $f < n/3$ .

We **never claim Conjecture 2**. It is open. The classical LSP result [15] requires  $n \geq 3f + 1$ ; below this threshold no BFT protocol can be safe. The protocol-level safety-and-liveness proof (DAG construction, certification, commit rules, adversarial timing)—analogous to the gap between a quorum lemma and full mechanized protocol proofs such as Mysticeti in Rocq—is the open work.

### 7.3 Conditional agreement: proven axiom-clean (Wave 23)

**Theorem 7.2** (Conditional Khipu agreement; [experimental, CI-green]; Lutar.Wave23.khipu\_quorum\_safety\_conditional [21]). *Under  $n \geq 3f + 1$  and honest non-equivocation (each honest organ signs at most one vote per action per round), any two certified quorums of size  $\geq 2f + 1$  share at least one honest organ and therefore cannot certify conflicting verdicts; the committed verdict is unique.*

*Proof sketch.* By quorum intersection:  $|Q_1 \cap Q_2| = |Q_1| + |Q_2| - |Q_1 \cup Q_2| \geq (2f + 1) + (2f + 1) - (3f + 1) = f + 1$ . At least  $f + 1 - f = 1$  member of  $Q_1 \cap Q_2$  is honest. Under honest non-equivocation, that honest organ cannot have signed conflicting verdicts; therefore  $Q_1$  and  $Q_2$  cannot have certified conflicting verdicts. The Lean proof extracts the witness via `Finset` inclusion–exclusion.  $\square$

Axiom ledger: `#print axioms of Lutar.Wave23.khipu_quorum_safety_conditional` yields the core set `{propxt, Classical.choice, Quot.sound}` (no project axiom; axiom-clean).

### 7.4 Conjecture 3: liveness

**Conjecture 7.3** (Conjecture 3 — Khipu liveness; OPEN). Under honest-majority assumptions and asynchrony bounds, Khipu makes progress.

Conjecture 3 is entirely open; no Lean work has been done on it. It is stated here to complete the honest picture of what the Khipu layer does and does not guarantee.

### 7.5 The checkable-antecedent pattern (Pillars P3 and P4)

Theorem 3.3 and Theorem 7.2 share an identical epistemic structure:

| Pillar         | Unconditional claim        | Status                                     | Conditional result                                         |
|----------------|----------------------------|--------------------------------------------|------------------------------------------------------------|
| P3 / $\Lambda$ | Unique A1–A5 aggregator    | FALSE<br>( <code>maxAgg_ne_Lambda</code> ) | Theorem U (slice-multiplicativity)                         |
| P4 / Khipu     | Two quorums never conflict | OPEN (Conjecture 2)                        | Thm. 7.2<br>(honest non-equivocation,<br>$n \geq 3f + 1$ ) |

The **checkable-antecedent pattern** is the conceptual core of GPD: in each pillar, the honest result is a conditional theorem whose antecedent is the *weakest auditor-checkable property*, and the unconditional statement sits at a machine-checked sharp boundary. Governing a post-deterministic system means *engineering the antecedents to hold and attesting that they held*, not proving a universal guarantee.

## 8 Application: Counter-UAS Auditable Interdiction (*killinchu*)

### 8.1 Overview

*killinchu* is the maritime / counter-UAS command body in the GPD substrate. It is a case study in applying the five-pillar GPD framework to a high-consequence, real-time, regulated domain. The repository is `szl-holdings/killinchu`; this section **describes the application but does not modify the repository**.

### 8.2 The interdiction loop

A *killinchu* interdiction event consists of four stages:

1. **Detect.** Sensor fusion identifies a candidate object and computes axis scores (range confidence, track age, IFF result, threat probability).
2. **Track.** The Chaski FIFO channel (F7-guaranteed delivery ordering) propagates the track state across organs. The F7 guarantee is operationally significant: if sensor updates were delivered out of order, a track would appear to “jump” and an incorrect kinematic model would be used for prediction.
3. **Decide.** The  $\Lambda$ -gate evaluates axis scores. A decision to interdict is authorized only when  $\Lambda_k(x) \geq \tau_{\text{killinchu}}$ . The Khipu quorum layer (Theorem 7.2, conditional) ensures that, under  $n \geq 3f + 1$  and honest non-equivocation, a quorum of organs must agree before authorization.
4. **Act.** The interdiction command is emitted. The engine emits a DSSE receipt (signed, including GSF SCI energy field) deposited in the Merkle log. The receipt records: which track triggered the decision, the  $\Lambda$  value at authorization time, the quorum signatures, and the energy cost.

### 8.3 Auditability

An auditor holding the receipt, the public quorum keys, and the Merkle log root can verify:

- **Structural integrity.** The receipt DAG is acyclic (F4); the log sequence is strictly monotone (F22). An attacker who wanted to insert a fabricated prior interdiction event would need to recompute the Merkle root— an operation that requires breaking the hash collision-resistance idealization.
- **Authorization.** The  $\Lambda$  value and axis scores are in the receipt; the auditor can recompute  $\Lambda_k(x)$  from the axis scores and verify that  $\Lambda_k(x) \geq \tau$ .
- **Quorum.** The quorum signatures are in the receipt; the auditor can verify that a threshold number of authorized organs signed the decision.
- **Energy.** The GSF SCI field is signed and in the receipt.

## 8.4 Honest status of the killinchu deployment

The killinchu artifact is SLSA Build Level 1 and Level 2 attested (run 26896047715, cosign-verified) [18]. The substrate is **not** ATO-authorized, IL5-certified, or FedRAMP-authorized; those are [ROADMAP] items. Trust is never 100%; the  $\Lambda$  weakest-link property ensures that a single sensor failure or IFF anomaly will veto authorization. The Khipu safety guarantee is conditional (Theorem 7.2); under adversarial conditions exceeding the  $n \geq 3f + 1$  threshold, the Byzantine safety guarantee does not hold. The killinchu deployment is a *demonstration* of the GPD substrate in a high-consequence setting, not a certified operational system.

# 9 Honesty Methodology

## 9.1 The honesty doctrine

The GPD substrate adheres to a binding honesty doctrine (v11 LOCKED [21]):

- **[locked]** — proven in Lean 4 with only {`propext`, `funext`, `Classical.choice`, `Quot.sound`}; sorry-free; pinned; part of the locked eight.
- **[experimental, CI-green]** — proven sorry-free with only the core axioms, CI-green at the recorded commit, in the experimental tier; **never folded into the locked eight**.
- **[axiom-gated]** — sorry-free *given* an explicitly declared idealizing axiom (e.g. hash collision-resistance), with the axiom in the `#print axioms` ledger.
- **[measured]** — an engineering measurement; outside the proven tier.
- **[Conjecture]** — a research hypothesis; never called a theorem.
- **[ROADMAP]** — a planned but not yet deployed feature; never claimed as current status.
- **SAMPLE** — example data used for illustration; not production measurements.
- **MODELED** — a simulation or model output; not empirical data.
- **UNAVAILABLE** — data that would be relevant but that has not been collected and is not claimed.

## 9.2 The half-state principle

A claim is in the *half-state* when it is neither fully proven nor honestly labeled as a conjecture: for example, labeling a machine-checked FALSE proposition as “likely true” or labeling a **sorry**-bearing Lean theorem as “proven.” The half-state is the **only unacceptable outcome** under the doctrine: it misleads downstream users who are making trust decisions based on the claim.

The half-state principle has two corollaries:

- **Negative results are reported as positive scientific contributions.** The machine-checked falsity of  $\Lambda$  unconditional uniqueness (Conjecture 1) and the openness of Khipu unconditional safety (Conjecture 2) are reported prominently, not buried. These boundaries are what make the conditional results (Theorem U, Theorem 7.2) trustworthy: a reader who knows the boundary can trust the conditional.
- **Count discipline.** The locked count is exact and machine-certified (`locked_count_eight`). No result is folded into the locked tier until it is (a) genuinely non-vacuous, (b) sorry-free, and (c) axiom-limited to the kernel basis. The non-vacuity audit of F4 and F7 is an instance of this discipline.

## 9.3 The checkable-antecedent pattern as a governance methodology

The GPD governance methodology generalizes the checkable-antecedent pattern to *any* governance primitive of a post-deterministic system:

1. Identify the *universal* governance guarantee you would like (“the aggregator is unique,” “the quorum never splits”).
2. Machine-check whether the universal guarantee holds. If it does not, report this as a machine-checked FALSE / OPEN result.
3. Find the *weakest checkable antecedent* under which the universal guarantee becomes true.
4. Prove the conditional theorem; publish the axiom ledger.
5. Engineer the system so the antecedent holds; attest that it held.

This methodology converts governance from a promise (“we claim X”) into an attested conditional (“we prove  $X$  under  $A$ , we attest  $A$  held”). The attestation is the DSSE receipt + Merkle inclusion proof; the conditional theorem is the formal warrant.

## 9.4 Attributed classical results

GPD applies the following classical results without reclaiming them:

- **Lindblad 1976** [16]: the unique generator form of GKSL dynamics. Applied in the coherence-decay scaffolding (F11/F12); not re-derived.
- **BCP 2014** [5]: the  $\ell_1$ -norm coherence monotone. Applied in the  $\Lambda$ -v5 gate; not re-derived.
- **Kleene 1938** [13]: the iterate-supremum least-fixed-point characterization. Applied in the  $\Lambda$ -aggregator convergence (Wave25/26); not re-derived.
- **Tarski 1955** [29]: the lattice fixed-point theorem. The Lean `OrderHom.lfp` API is due to Tarski / Mathlib; the Wave25/26 convergence results build on it.



- **Aczél 1966** [2]: characterization of quasi-arithmetic means. GPD’s Theorem U is the machine-checked instance of Aczél’s characterization under declared axioms.
- **McAllester 1999** [23]: PAC-Bayes bounds. Applied in the epistemic-uncertainty framing of the trust axis scores; not re-derived.
- **Viazovska 2017** [31]: the dimension-8 sphere-packing density result. Cited for the E8 error-detection geometry application; not re-derived.

## 10 Limitations and Roadmap

### 10.1 Formal limitations

- **$\Lambda$  unconditional uniqueness is machine-checked FALSE (Conjecture 1).** Theorem U holds under slice-multiplicativity but not unconditionally. Full closure of Conjecture 1 requires the BKS  $n$ -adic functional-analysis construction, which depends on infrastructure not yet in Mathlib v4.18.0.
- **Khpu unconditional Byzantine safety is open (Conjecture 2).** Conditional agreement (Theorem 7.2) is proven axiom-clean, but the full protocol proof (adversarial timing, DAG construction, commit rules) remains open. Khpu liveness is Conjecture 3, entirely untouched.
- **$\sim 307$  open sorry obligations in the experimental tier.** Disclosed; never claimed proven. The experimental-tier baseline at the drift head is 1323 declarations / 23 axioms (22 unique) / 307 sorries; the *locked* baseline at c7c0ba17 remains 749/14/163.
- **Cryptographic binding is axiom-gated.** Tamper-evidence of the receipt chain depends on hash collision-resistance (SHA-256 + Merkle domain-separation), which is an idealization, not a proved hardness result.
- **Reed–Solomon (F18) proves only the lower-distance half of Singleton.** The upper half is open.
- **F19 (Bekenstein scaffolding) is applied, not proved.** The Bekenstein bound itself is a classical result of Bekenstein (1981); the GPD formalization is scaffolding only.
- **Theorem 9 (Merkle Functor) is experimental, not locked.** It is CI-kernel-checked but not in the locked count.
- **Known incorrect theorem statements in the experimental tier.** DPO `k1Divergence` and `pinsker` are false-as-stated (no simplex hypothesis); CF-21 is the correct companion. These are disclosed, not repaired silently.

### 10.2 Deployment limitations

- **No ATO / IL5 / FedRAMP authorization.** All [ROADMAP]. The killinChu deployment is a demonstration system, not a certified operational platform.
- **SLSA L3 is roadmap.** Current attestation: L1 + L2 where `attest-build-provenance` runs; L1-only elsewhere.

- **Public Sigstore Rekor per-receipt is roadmap.** The self-hosted Merkle log is LIVE; public Rekor integration is Phase II.
- **TEE binding is roadmap.** Trusted execution environment hardware attestation is Phase II.
- **Energy values are engineering measurements, not audited.** Third-party SCI certification is a roadmap item.
- **Trust is never 100%.** The  $\Lambda$  zero-absorption property is a design choice, not a bug: the system is designed to never claim certainty.

### 10.3 Roadmap summary

| Item                                              | Phase     | Blocker                           |
|---------------------------------------------------|-----------|-----------------------------------|
| Conjecture 1 full closure ( $\Lambda$ uniqueness) | Research  | BKS $n$ -adic in Mathlib          |
| Conjecture 2 full Khipu protocol proof            | Research  | Protocol-level Lean formalization |
| Conjecture 3 Khipu liveness                       | Research  | Not started                       |
| Public Sigstore Rekor per-receipt                 | Phase II  | Engineering                       |
| TEE binding (hardware attestation)                | Phase II  | Engineering                       |
| SLSA L3 attestation                               | Phase III | Engineering + audit               |
| ATO / FedRAMP / IL5 authorization                 | Phase III | Regulatory                        |
| Third-party SCI energy certification              | Phase III | Audit                             |

## 11 Conclusion

We have presented **Governed Post-Determinism**, a machine-checked, cryptographically-receipted substrate for verifiable AI inference. The substrate provides:

- Eight locked-proven Lean 4 formulas anchoring the structural invariants of the receipt substrate (acyclicity, FIFO ordering, emit monotonicity, replay determinism, coding guarantees, gate scaffolding). The count is itself a machine-certified theorem.
- A DSSE/ECDSA-P256 receipt pipeline with in-toto Statement v1 and self-hosted Merkle inclusion proofs, producing offline-verifiable receipts for every governed inference.
- Conditional proofs at the precise boundary of what can be guaranteed: Theorem U (axiom-free  $\Lambda$  uniqueness under slice-multiplicativity) and the conditional Khipu agreement theorem—both with machine-checked boundaries showing where the unconditional claims fail.
- An honesty methodology transferable to any AI governance substrate: epistemic labeling, the half-state principle, non-vacuity audits, and the checkable-antecedent pattern.

The key observation is that *honest negative results strengthen the credibility of positive claims*. Knowing that  $\Lambda$  unconditional uniqueness is machine-checked false makes Theorem U—which is proven under declared, checkable hypotheses—*more* credible than any uncaveated uniqueness

claim would be. Knowing that Khipu unconditional safety is open makes the conditional agreement theorem—which is proven axiom-clean—*more* credible than any unconditional BFT claim would be.

The paper’s primary contribution is not new physics or pure mathematics; it is the machine-checked formalization, the governed-inference pipeline, and the verifiable-receipt substrate—along with the honesty discipline that makes their claims checkable. Trust is never 100%; the system is designed to ensure that it never needs to be.

**Concept DOI (always-latest):** [10.5281/zenodo.19944926](https://doi.org/10.5281/zenodo.19944926) [21].

## References

- [1] János Aczél. On mean values. *Bull. Amer. Math. Soc.*, 54(4):392–400, 1948.
- [2] János Aczél. *Lectures on Functional Equations and Their Applications*. Academic Press, 1966.
- [3] Arize AI. Arize AI platform: LLM observability and evaluation. <https://arize.com>, 2024.
- [4] ARMO Security. AI agent governance. <https://www.armosec.io/blog/ai-agent-governance/>, 2025.
- [5] Tillmann Baumgratz, Marcus Cramer, and Martin B. Plenio. Quantifying coherence. *Phys. Rev. Lett.*, 113:140401, 2014.
- [6] Miles Brundage et al. Toward trustworthy AI development: Mechanisms for supporting verifiable claims, 2020.
- [7] Miguel Castro and Barbara Liskov. Practical Byzantine fault tolerance. In *Proc. USENIX OSDI*, 1999.
- [8] John H. Conway and Neil J. A. Sloane. Sphere packings, lattices and groups, 1999.
- [9] Credo AI. Credo AI: AI governance platform. <https://www.credo.ai>, 2024.
- [10] Fiddler AI. Fiddler AI observability platform. <https://www.fiddler.ai>, 2024.
- [11] Green Software Foundation. Software carbon intensity (SCI) specification v1.0. <https://sci-guide.greensoftware.foundation/>, 2022.
- [12] G. H. Hardy, J. E. Littlewood, and G. Pólya. *Inequalities*. Cambridge University Press, 1934.
- [13] Stephen C. Kleene. On notation for ordinal numbers. *J. Symb. Logic*, 3(4):150–155, 1938.
- [14] Gerwin Klein et al. seL4: Formal verification of an OS kernel. In *Proc. ACM SOSP*, 2009.
- [15] Leslie Lamport, Robert Shostak, and Marshall Pease. The Byzantine generals problem. *ACM Trans. Program. Lang. Syst.*, 4(3):382–401, 1982.
- [16] Göran Lindblad. On the generators of quantum dynamical semigroups. *Comm. Math. Phys.*, 48(2):119–130, 1976.

- [17] Jr. Lutar, Stephen P. Axiom-free conditional uniqueness:  $\Lambda$  under slice-multiplicativity (v24). <https://doi.org/10.5281/zenodo.19944926>, 2026.
- [18] Jr. Lutar, Stephen P. Governed post-determinism (GPD), Locked-Eight Edition: {F1,F4,F7,F11,F12,F18,F19,F22} kernel-verified (v26). <https://doi.org/10.5281/zenodo.19944926>, 2026.
- [19] Jr. Lutar, Stephen P. The Lutar invariant  $\Lambda$ : Closed-form aggregator for governed autonomy (v3). <https://doi.org/10.5281/zenodo.19983066>, 2026.
- [20] Jr. Lutar, Stephen P. lutar-lean: Lean 4 formalization of the SZL governed-AI kernel. <https://github.com/szl-holdings/lutar-lean>, 2026.
- [21] Jr. Lutar, Stephen P. The ouroboros thesis program (concept DOI, always-latest). <https://doi.org/10.5281/zenodo.19944926>, 2026.
- [22] Jr. Lutar, Stephen P. Verifiable multi-agent anatomy — Lutar calculus:  $\Lambda$  downgraded to Conjecture 1 (v14). <https://doi.org/10.5281/zenodo.20174600>, 2026.
- [23] David A. McAllester. PAC-Bayesian model averaging. In *Proc. 12th Annual Conf. Comput. Learning Theory (COLT)*, pages 164–170, 1999.
- [24] NIST. AI risk management framework (AI RMF 1.0). NIST AI 100-1, <https://doi.org/10.6028/NIST.AI.100-1>, 2023.
- [25] Vincent Rahli, Ivana Vukotic, Marcus Völz, and Paulo Esteves-Verissimo. Velisarios: Byzantine fault-tolerant protocols powered by Coq. In *Proc. ESOP*, 2018.
- [26] Secure Systems Lab / in-toto. Dead simple signing envelope (DSSE). <https://github.com/secure-systems-lab/dsse>, 2022.
- [27] Sigstore Project. Sigstore: Keyless signing with Fulcio and Rekor. <https://www.sigstore.dev>, 2022.
- [28] SLSA Community. Supply-chain Levels for Software Artifacts. <https://slsa.dev>, 2023.
- [29] Alfred Tarski. A lattice-theoretical fixpoint theorem and its applications. *Pacific J. Math.*, 5(2):285–309, 1955.
- [30] Santiago Torres-Arias et al. in-toto: Providing farm-to-table guarantees for bits and bytes. In *Proc. USENIX Security*, 2019.
- [31] Maryna Viazovska. The sphere packing problem in dimension 8. *Ann. of Math.*, 185(3):991–1015, 2017.
- [32] Maofan Yin, Dahlia Malkhi, Michael K. Reiter, Guy Golan Gueta, and Ittai Abraham. HotStuff: BFT consensus with linearity and responsiveness. In *Proc. ACM PODC*, 2019.

## A Lean Theorem Index

### A.1 The locked eight (c7c0ba17, 749/14/163)

| ID  | Lean fully-qualified name               | File in lutar-lean                       |
|-----|-----------------------------------------|------------------------------------------|
| F1  | Lutar.f1_replay_hash_determinism        | Lutar/Core/ReplayDeterminism.lean        |
| F4  | Lutar.f4_khipu_dag_acyclic_preserved    | Lutar/Puriq/Formulas/ProvedFormulas.lean |
| F7  | Lutar.f7_chaski_fifo_order              | Lutar/Puriq/Formulas/ProvedFormulas.lean |
| F11 | Lutar.f11_ayni_reciprocity_conservation | Lutar/Anatomy/Ayni.lean                  |
| F12 | Lutar.f12_kuramoto_additive             | Lutar/Puriq/Formulas/ProvedFormulas.lean |
| F18 | Lutar.f18_reed_solomon_parity_count     | Lutar/Coding/ReedSolomon.lean            |
| F19 | Lutar.f19_bekenstein_additive           | Lutar/Capacity/Bekenstein.lean           |
| F22 | Lutar.f22_khipu_emit_monotone           | Lutar/Puriq/Formulas/ProvedFormulas.lean |

### A.2 Count theorem

```
-- Lutar.Wave8.AxiomDisclosure
theorem locked_count_eight :
  Lutar.lockedDisclosed.length = 8 := by decide
```

### A.3 Key experimental theorems (not locked; CI-green)

| Lean theorem name                                         | Status and location                                                |
|-----------------------------------------------------------|--------------------------------------------------------------------|
| Lutar.Round13.lambda_unique_of_separable                  | Theorem U; experimental, axiom-free (§3)                           |
| Lutar.Round13.maxAgg_ne_Lambda                            | Conjecture 1 witness; experimental, Lean-core only                 |
| Lutar.Wave23.khipu_quorum_safety_conditional              | Conditional Khipu agreement (§7); experimental, axiom-clean        |
| Lutar.Lambda.AggregatorLfp.lfp_eq_iSup_iterate_of_commute | Kleene iterate-supremum under commute hypothesis (Wave25)          |
| Lutar.Lambda.AggregatorLfp.lfp_eq_iSup_iterate            | Unconditional Kleene iterate ( $\omega$ -Scott-continuity; Wave26) |
| Lutar.QuantumBio.CoherenceDecay.coh_strictAnti            | Lindblad coherence strict antitonicity; Wave24                     |

### A.4 Axiom ledger summary

```

-- Locked formulas (all eight):
-- #print axioms on any locked formula =>
--   {propext, funext, Classical.choice, Quot.sound}

-- Theorem U:
-- #print axioms Lutar.Round13.lambda_unique_of_separable =>
--   {propext, Classical.choice, Quot.sound} -- no funext, no project axiom

-- Conjecture 1 witness:
-- #print axioms Lutar.Round13.maxAgg_ne_Lambda =>
--   {propext, funext, Classical.choice, Quot.sound}

-- Khipu conditional safety:
-- #print axioms Lutar.Wave23.khipu_quorum_safety_conditional =>
--   {propext, Classical.choice, Quot.sound} -- axiom-clean

```

## B Reproducibility

### B.1 Pinned commits

| Component                       | Commit / ID        | Contents                           |
|---------------------------------|--------------------|------------------------------------|
| Locked kernel                   | c7c0ba17           | 749/14/163; locks F1–F22           |
| Experimental main (Waves 11–22) | 43bcabb7           | CUT-1 closed; CI-green             |
| Theorem U                       | on main            | Round13.lambda.unique.of_separable |
| Khipu conditional safety        | Wave 23            | Wave23/QuorumSafety.lean           |
| F4/F7/F22 proofs                | 2026-06-10         | Puriq/Formulas/ProvedFormulas.lean |
| killinchi SLSA L2               | run<br>26896047715 | cosign-verified                    |
| Concept DOI                     | —                  | 10.5281/zenodo.19944926            |

### B.2 Verification instructions

```

# 1. Clone and check out the locked kernel
git clone https://github.com/szl-holdings/lutar-lean
git checkout c7c0ba17
lake build
-- => green; all 8 locked formulas verified; count = 8

-- 2. Verify the count theorem
-- #eval Lutar.lockedDisclosed.length --> 8
-- #check (Lutar.Wave8.AxiomDisclosure.locked_count_eight :
--   Lutar.lockedDisclosed.length = 8)

-- 3. Verify the axiom ledger of Theorem U
-- #print axioms Lutar.Round13.lambda_unique_of_separable
-- => {propext, Classical.choice, Quot.sound} (no project axiom)

```

```

-- 4. Verify the Conjecture 1 refutation
-- #print axioms Lutar.Round13.maxAgg_ne_Lambda
-- => {propxext, funext, Classical.choice, Quot.sound}

-- 5. Verify Khipu conditional safety
-- #print axioms Lutar.Wave23.khipu_quorum_safety_conditional
-- => {propxext, Classical.choice, Quot.sound} (axiom-clean)

# 6. Verify SLSA L2 attestation (killinchu)
cosign verify-attestation \
  --type slsaprovenance \
  --certificate-identity-regexp="^https://github.com/szl-holdings/" \
  ghcr.io/szl-holdings/killinchu:uds-v0.2.0

```

## C DOI Lineage

| Ver.                                | Date       | Key contribution                                   | DOI                      |
|-------------------------------------|------------|----------------------------------------------------|--------------------------|
| v1                                  | 2026-04-28 | Ouroboros Loop primitive                           | <a href="#">19867281</a> |
| v3                                  | 2026-05-02 | Lutar Invariant $\Lambda$ definition               | <a href="#">19983066</a> |
| v11                                 | 2026-05-11 | Applied $\Lambda$ ; measured per-request over-head | <a href="#">20119582</a> |
| v14                                 | 2026-05-28 | $\Lambda$ downgraded to Conjecture 1               | <a href="#">20174600</a> |
| v18                                 | 2026-05-30 | Multi-track substrate expansion; 7-DOI chain       | <a href="#">20434276</a> |
| v22                                 | 2026-06-03 | A5 merge; SLSA L1+L2                               | (auto-mint pending)      |
| v24                                 | 2026-06-06 | Axiom-free Theorem U                               | <a href="#">concept</a>  |
| v25                                 | 2026-06-09 | GPD unification; Wave-23 Khipu                     | <a href="#">concept</a>  |
| v26                                 | 2026-06-10 | Locked-Eight Edition: F4/F7/F22 genuine proofs     | <a href="#">concept</a>  |
| <b>Concept DOI (always-latest):</b> |            | <a href="#">10.5281/zenodo.19944926</a> [21]       |                          |

*Doctrine footer:*  $\Lambda$  = **Conjecture 1** (machine-checked FALSE; never a theorem) · conditional  $\Lambda$  = **Theorem U**, axiom-free · Khipu BFT safety = **Conjecture 2** (Wave-23 conditional agreement only) · Khipu liveness = **Conjecture 3** (open) · locked-proven = **exactly 8** {F1,F4,F7,F11,F12,F18,F19,F22} @ c7c0ba17 (749/14/163), confirmed by `locked_count_eight` · F4/F7/F22 newly proven 2026-06-10 (kernel baseline unchanged; F4/F7 formerly vacuous, now genuine) · ~185 experimental CI-green (Waves 11–23, separate tier) · **SLSA L1+L2 attested** (killinchu, alloy) / L1 honest+L2 roadmap elsewhere · **L3 roadmap** · in-toto Statement v1 + DSSE ECDSA-P256 **LIVE** · self-hosted Merkle log **LIVE** · public Rekor per-receipt **ROADMAP** · trust never 100% · 0 runtime CDN · no ATO/IL5/FedRAMP · no AGI.