

## Small Models Struggle to Learn from Strong Reasoners

Yuetai Li/ Xiang Yue} Zhangchen Xu/ Fengqing Jiang/ Luyao Niu/

**Bill Yuchen Lin/** **Bhaskar Ramasubramanian\*** **Radha Poovendran/**

/ University of Washington } Carnegie Mellon University • Western Washington University  
{yuetai l i , zxu9, fqj i ang, l uyaoni u, byuchenl , rp3}@uw. edu,  
xyue2@andrew. cmu. edu, ramasub@www. edu

## Abstract

Large language models (LLMs) excel in complex reasoning tasks, and distilling their reasoning capabilities into smaller models has shown promise. However, we uncover an interesting phenomenon, which we term the *Small Model Learnability Gap*: small models (< 3B parameters) do not consistently benefit from long chain-of-thought (CoT) reasoning or distillation from larger models. Instead, they perform better when fine-tuned on shorter, simpler reasoning chains that better align with their intrinsic learning capacity. To address this, we propose Mix Distillation, a simple yet effective strategy that balances reasoning complexity by combining long and short CoT examples or reasoning from both larger and smaller models. Our experiments demonstrate that Mix Distillation significantly improves small model reasoning performance compared to training on either data alone. These findings highlight the limitations of direct strong model distillation and underscore the importance of adapting reasoning complexity for effective reasoning capability transfer.

## 1 Introduction

Large language models (LLMs) (Anthropic, 2023; Brown et al., 2020; OpenAI, 2023; Touvron et al., 2023a) have demonstrated remarkable performance in complex reasoning tasks, enabling

advancements in mathematical problem-solving, logical inference, and structured decision-making (Cobbe et al., 2021; Shao et al., 2024; Yang et al., 2024). A key advancement in improving LLM complex reasoning capability is the chain-of-thought (CoT) prompting. This technique decomposes complex problems into intermediate reasoning steps, enhancing both performance and interpretability. (Wei et al., 2023).

✎ 1: Small student models (  $\leq 3$ B parameters) do not consistently benefit from long CoT reasoning or distillation from large teacher models. Instead, they perform better when fine-tuned on shorter CoT reasoning or distilled from smaller teachers, which better matches their intrinsic learning capacity. We term this phenomenon the *Small Model Learnability Gap*.

However, the high computational cost of LLMs hinders their deployment on resource-constrained devices, motivating the development of smaller models that offer similar capabilities at reduced cost. A widely adopted strategy to achieve this is distillation (Agarwal et al., 2024; Hinton et

## Small Models Struggle to Learn from Strong Reasoners

Yuetai Li/ Xiang Yue<sup>3</sup> Zhangchen Xu/ Fengqing Jiang/ Luyao Niu/

**Bill Yuchen Lin** / **Bhaskar Ramasubramanian** \* **Radha Poovendran** /

/ University of Washington } Carnegie Mellon University • Western Washington University  
 {yuetai li , xzu9, fqj i ang, l uyaoni u, byuchen l , rp3}@uw. edu,  
 xyue2@andrew. cmu. edu, ramasub@wwu. edu

## Abstract

\*f J    i D E 1 GPT-Academic    • y e 1/2 ( ' i e 1/2  
< + LaTeX i e 1/2 H C R Y ‡ \    @    i e 1/2  
e 1/2 i e 1/2 e 1/2 + i e 1/2 v i e 1/2 i e 1/2 GitHub O  
@ [https://github.com/binary-husky/gpt\\_academic/](https://github.com/binary-husky/gpt_academic/) y  
e 1/2 S E O @ <https://auth.gpt-academic.top/> S M '  
i e 1/2 < : Qwen2.5-72B-Instruct S M i e 1/2 ) i e 1/2  
0.3 : † 2 b ' i e 1/2 „ , i e 1/2 c q e 1/2 • b i e 1/2  
d e 1/2 d f J  
' < i e 1/2 < L L M s ( B „ i e 1/2  
- h ° i e 1/2 f i e 1/2 i e 1/2 O f  
„ ! < - \_ > : i e 1/2 6 i e 1/2  
° † \* E „ ° a i e 1/2 ! <  
f ` i e 1/2 < ! < 3 B i e 1/2 i e 1/2  
• i e 1/2 C o T i e 1/2 ! < - e 1/2  
e 1/2 v ; i e 1/2 e 1/2 f i e 1/2 e 1/2  
f ∈ U „ i e 1/2 i e 1/2  
i e 1/2 i e 1/2 f i e 1/2 ( f ` i e 1/2  
: † e 1/2 e 1/2 i e 1/2 i e 1/2  
Mix Distillation i e 1/2 i e 1/2 H  
„ V e i e 1/2 i e 1/2 <  
i e 1/2 e 1/2 < ! < - „ e s a “  
B ' i e 1/2 U e 1/2 ( i e 1/2  
i e 1/2 i e 1/2 ÷ i e 1/2 > W e 1/2  
e 1/2 < ! < „ ' i e 1/2 e 1/2  
† i e 1/2 ! < e 1/2 @ P ' v : †  
„ B ' i e 1/2 i e 1/2 e 1/2

## 1 Introduction

' < i' < 1/2 < LLMs (Anthropic, 2023; Brown et al., 2020; OpenAI, 2023; Touvron et al.,

2023a) (B, ... i  $\frac{1}{2}$  U: t S S, ' i  $\frac{1}{2}$  t p f i  $\frac{1}{2}$   $\frac{1}{2}$   $\frac{1}{2}$  ' ... E i  $\frac{1}{2}$  i  $\frac{1}{2}$  i U (Cobbe et al., 2021; Shao et al., 2024; Yang et al., 2024) (  $\frac{1}{2}$   $\frac{1}{2}$  LM B' i  $\frac{1}{2}$  s. i U / i  $\frac{1}{2}$  i  $\frac{1}{2}$   $\frac{1}{2}$  T  $\frac{1}{2}$  i  $\frac{1}{2}$  i  $\frac{1}{2}$  i  $\frac{1}{2}$  B i  $\frac{1}{2}$   $\frac{1}{2}$  - i  $\frac{1}{2}$  e  $\frac{1}{2}$  i  $\frac{1}{2}$  t' i E  $\frac{1}{2}$   $\frac{1}{2}$   $\frac{1}{2}$  (Wei et al., 2023)

[illegible]

6   ' < i 2 < LLMs „ i 2—  
, ; • † f i 2 • × P i 2 „ i 2 i 2 i 2  
Ä • † i 2 i 2 ! < i 2 < i 2 f N „  
, i 2 { < „ Y i 2 Z ° i 2 i 2 i 2 i 2  
i 2 „ V e / „ • (Agarwal et al., 2024; Hinton  
et al., 2015; Kim et al., 2024a) v - 1 : ' Y  
! < „ CoT • ( Ž ® f 1 „ f !  
< i 2 O i 2 i 2 i 2 i 2 i 2 „ •  
i 2 „ CoT • i 2 i 2 i 2 ! < „ B "

Our experiments demonstrate that *Mix Distillation* consistently improves small model reasoning performance compared to standard distillation.

Throughout this work, we use the term **short CoT**, to describe concise reasoning paths to arrive at solutions (Min et al., 2024; Yeo et al., 2025) and **long CoT** to describe an extended reasoning sequence that is not only longer but also demonstrates more complex reflective thoughts (Qwen, 2024b; Yeo et al., 2025). Additionally, we use the term **large teacher CoT** to refer to the reasoning trace generated by a larger teacher model, and the term **small teacher CoT** for the reasoning steps produced by a smaller teacher model. Please see Appendix D for more examples.

[illegible]

### 3.1 Experiment Setup

2.2 Supervised Fine-Tuning (SFT)

Supervised fine-tuning (SFT) is widely adopted to enhance reasoning capabilities of LLMs on a dataset  $D = \{ (x^i, y^i) \}_{i=1}^N$ , where  $y^i$  can be short CoT, long CoT, strong model CoT or weak model CoT sequences. The SFT process updates the parameters of a language model by minimizing the negative log-likelihood loss over the instruction dataset  $D$ .

3 Small Model Learnability Gap

In this section, we fine-tune student models using different CoT data. We then reveal the small model learnability gap given the performance of fine-tuned models.

3.1 Experiment Setup

**Datasets.** We use the 7,500 prompt set of MATH (Hendrycks et al., 2021). This dataset encompasses seven math topics such as advanced calculus, geometry, and linear algebra.

**Student models.** Our study considers ten student models from the Qwen (Qwen, 2024a) and Llama (Meta, 2024a,b) model families of varying sizes. These models include the Instruct version of Qwen2.5-0.5B, Qwen2.5-1.5B, Qwen2.5-3B, Qwen2.5-7B, Qwen2.5-14B, and Qwen2.5-32B, and the Instruct version of Llama3.2-1B, Llama3.2-3B, Llama3.1-8B, and Llama3.3-70B. A comprehensive overview of the student models is presented in Table 4 of Appendix A.

**Teacher models.** To compare long CoT with short CoT, we use QwQ-32B-Preview (Qwen, 2024b) to generate long CoT sequences and Qwen2.5-32B-Instruct as the response generator for short CoT. Within each model family, we designate the larger scale model as the large teacher and the smaller scale model as the small teacher. This includes Qwen2.5-72B-Instruct

vs Qwen2.5-3B-Instruct, Llama3.1-70B-Instruct vs Llama3.1-8B-Instruct, and Gemma2-27B-it vs Gemma2-9B-it.

**Evaluation Benchmarks.** We evaluate the reasoning capability of fine-tuned student models on a set of commonly used benchmarks, including MATH (Hendrycks et al., 2021), GSM8K (Cobbe et al., 2021), AMC 2023, AIME 2024, and the English math subset of OlympiadBench (He et al., 2024). These benchmarks span a wide range of challenge levels, from elementary mathematics to advanced competition problems. We define the student model performance as the average score on five benchmarks. Unless otherwise specified, all fine-tuned models are evaluated in a zero-shot setting using greedy decoding. We set the maximum generation tokens as 16k. Please see Appendix A for detailed experimental setup.

We define the following performance scores:

- $P_{Long}$ : Performance score of a student model fine-tuned on long CoT data.
- $P_{Short}$ : Performance score of a student model fine-tuned on short CoT data.
- $P_{Large}$ : Performance score of a student model fine-tuned on CoT from a larger teacher.
- $P_{Small}$ : Performance score of a student model fine-tuned on CoT from a smaller teacher.

**Training Setup.** Teacher models generate responses by rejection sampling (Dong et al., 2023; Gulcehre et al., 2023; Tong et al., 2024; Yuan et al., 2023; Yue et al., 2023; Zelikman et al., 2022) By default, teacher models employ greedy decoding. By combining the math problem instructions with corresponding solutions generated by teacher models, we construct problem-solution pairs to fine-tune student models. We train the models using the

$$P_{Long} = \frac{1}{N} \sum_{i=1}^N \mathbb{1}_{\{y_i \in \mathcal{Y}_{Long}\}} \quad P_{Short} = \frac{1}{N} \sum_{i=1}^N \mathbb{1}_{\{y_i \in \mathcal{Y}_{Short}\}}$$

$$P_{Large} = \frac{1}{N} \sum_{i=1}^N \mathbb{1}_{\{y_i \in \mathcal{Y}_{Large}\}} \quad P_{Small} = \frac{1}{N} \sum_{i=1}^N \mathbb{1}_{\{y_i \in \mathcal{Y}_{Small}\}}$$



Figure 2: Long CoT Gap ( $\Delta_{Long} = P_{Long} - P_{Short}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen to generate long CoT responses, while Qwen2.5-32B-Instruct is chosen to generate short CoT responses. Negative (Positive)  $\Delta_{Long}$  indicates that long CoT is worse (better) than short CoT. Our results demonstrate that short CoT is better for smaller student models (indicated by  $\Delta_{Long} < 0$ ), while long CoT is better for larger student models (indicated by  $\Delta_{Long} > 0$ ).

Figure 3: Large model CoT Gap ( $\Delta_{Large} = P_{Large} - P_{Small}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen as the large teacher to generate responses, while Qwen2.5-32B-Instruct is chosen as the small teacher to generate responses. Negative (positive)  $\Delta_{Large}$  indicates that large teacher CoT is worse (better) than small teacher CoT. Our results demonstrate that small teacher CoT is better for smaller student models (indicated by  $\Delta_{Large} < 0$ ), while large model CoT is better for larger student models (indicated by  $\Delta_{Large} > 0$ ).

LLaMA-Factory framework (Zheng et al., 2024). For student models of scale less than 14B, we use full-parameter SFT and implement a cosine learning rate schedule with a maximum learning rate of  $10^{-5}$  to fine-tune student models for two epochs (Touvron et al., 2023b). For student models larger than 14B, we adopt LoRA fine-tuning with a learning rate of  $10^{-4}$  for two epochs. Detailed hyperparameters and information about the experimental platform are provided in Appendix A.

### 3.2 Long CoT Gap

This section evaluates the reasoning capabilities of student models fine-tuned over long CoT data and short CoT data. We quantify the performance difference between long and short CoT data using *long CoT gap*  $\Delta_{Long}$ , defined as:

$$\Delta_{Long} = P_{Long} - P_{Short}$$

Figure 2 provides a comprehensive overview of the long CoT gap  $\Delta_{Long}$  across different student

Figure 3: Large model CoT Gap ( $\Delta_{Large} = P_{Large} - P_{Small}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen as the large teacher to generate responses, while Qwen2.5-32B-Instruct is chosen as the small teacher to generate responses. Negative (positive)  $\Delta_{Large}$  indicates that large teacher CoT is worse (better) than small teacher CoT. Our results demonstrate that small teacher CoT is better for smaller student models (indicated by  $\Delta_{Large} < 0$ ), while large model CoT is better for larger student models (indicated by  $\Delta_{Large} > 0$ ).

### 3.2 Long CoT Gap

Figure 4: Long CoT Gap ( $\Delta_{Long} = P_{Long} - P_{Short}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen to generate long CoT responses, while Qwen2.5-32B-Instruct is chosen to generate short CoT responses. Negative (Positive)  $\Delta_{Long}$  indicates that long CoT is worse (better) than short CoT. Our results demonstrate that short CoT is better for smaller student models (indicated by  $\Delta_{Long} < 0$ ), while long CoT is better for larger student models (indicated by  $\Delta_{Long} > 0$ ).

Figure 5: Large model CoT Gap ( $\Delta_{Large} = P_{Large} - P_{Small}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen as the large teacher to generate responses, while Qwen2.5-32B-Instruct is chosen as the small teacher to generate responses. Negative (positive)  $\Delta_{Large}$  indicates that large teacher CoT is worse (better) than small teacher CoT. Our results demonstrate that small teacher CoT is better for smaller student models (indicated by  $\Delta_{Large} < 0$ ), while large model CoT is better for larger student models (indicated by  $\Delta_{Large} > 0$ ).

Figure 6: Long CoT Gap ( $\Delta_{Long} = P_{Long} - P_{Short}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen to generate long CoT responses, while Qwen2.5-32B-Instruct is chosen to generate short CoT responses. Negative (Positive)  $\Delta_{Long}$  indicates that long CoT is worse (better) than short CoT. Our results demonstrate that short CoT is better for smaller student models (indicated by  $\Delta_{Long} < 0$ ), while long CoT is better for larger student models (indicated by  $\Delta_{Long} > 0$ ).

Figure 7: Large model CoT Gap ( $\Delta_{Large} = P_{Large} - P_{Small}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen as the large teacher to generate responses, while Qwen2.5-32B-Instruct is chosen as the small teacher to generate responses. Negative (positive)  $\Delta_{Large}$  indicates that large teacher CoT is worse (better) than small teacher CoT. Our results demonstrate that small teacher CoT is better for smaller student models (indicated by  $\Delta_{Large} < 0$ ), while large model CoT is better for larger student models (indicated by  $\Delta_{Large} > 0$ ).

Student Model	$P_{Long}$	$P_{Short}$	$\Delta_{Long}$	Better?
Qwen2.5-0.5B	14.8	19.5	-4.7	Short
Qwen2.5-1.5B	27.0	34.2	-7.1	Short
Qwen2.5-3B	40.3	43.4	-3.1	Short
Qwen2.5-7B	48.9	47.2	1.7	Long
Qwen2.5-14B	59.2	54.3	4.9	Long
Qwen2.5-32B	73.0	59.3	13.7	Long
Llama-3.2-1B	15.8	19.5	-3.7	Short
Llama-3.2-3B	32.5	33.1	-0.6	Short
Llama-3.1-8B	35.2	31.5	3.7	Long
Llama-3.3-70B	58.2	54.3	3.8	Long

Figure 8: Long CoT Gap ( $\Delta_{Long} = P_{Long} - P_{Short}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen to generate long CoT responses, while Qwen2.5-32B-Instruct is chosen to generate short CoT responses. Negative (Positive)  $\Delta_{Long}$  indicates that long CoT is worse (better) than short CoT. Our results demonstrate that short CoT is better for smaller student models (indicated by  $\Delta_{Long} < 0$ ), while long CoT is better for larger student models (indicated by  $\Delta_{Long} > 0$ ).

### 3.3 Large Teacher CoT Gap

Figure 9: Large Teacher CoT Gap ( $\Delta_{Large} = P_{Large} - P_{Small}$ ) of student models with different models sizes for (a) Qwen family (b) Llama family. For teacher models, Qwen2.5-72B-Instruct is chosen as the large teacher to generate responses, while Qwen2.5-32B-Instruct is chosen as the small teacher to generate responses. Negative (positive)  $\Delta_{Large}$  indicates that large teacher CoT is worse (better) than small teacher CoT. Our results demonstrate that small teacher CoT is better for smaller student models (indicated by  $\Delta_{Large} < 0$ ), while large model CoT is better for larger student models (indicated by  $\Delta_{Large} > 0$ ).

models. The detailed benchmark scores on MATH, GSM8K, AIME, AMC, and OlympiadBench are deferred to Table 7 in Appendix B. We report the following key takeaways.

## Takeaway 1: Long CoT Gap

Small student models tend to benefit more from short CoT, while large student models gain greater advantages from long CoT.

We observe that long CoT is more effective for larger models, consistently leading to improved performance across most math benchmarks. For example, the student model Qwen2.5-32B-Instruct improves about 15 points across all math metrics on average.

However, long CoT data is not effective for smaller models, yielding significantly less improvement compared to short CoT. On the MATH and AMC benchmarks, student model Qwen2.5-1.5B-Instruct performs over 10 points lower when fine-tuned with long CoT data. This shows that smaller models may not be able to effectively learn and utilize the long CoT paradigm. Please see more attribution analysis in Section 3.4.

Student Model	$P_{Long}$	$P_{Short}$	$Long$	Better?
Qwen2.5-0.5B	14.8	19.5	-4.7	Short
Qwen2.5-1.5B	27.0	34.2	-7.1	Short
Qwen2.5-3B	40.3	43.4	-3.1	Short
Qwen2.5-7B	48.9	47.2	1.7	Long
Qwen2.5-14B	59.2	54.3	4.9	Long
Qwen2.5-32B	73.0	59.3	13.7	Long
Llama-3.2-1B	15.8	19.5	-3.7	Short
Llama-3.2-3B	32.5	33.1	-0.6	Short
Llama-3.1-8B	35.2	31.5	3.7	Long
Llama-3.3-70B	58.2	54.3	3.8	Long

h 1: Comparison of the average performance between fine-tuning with long CoT ( $P_{Long}$ ) and short CoT ( $P_{Short}$ ). We find that small student models may struggle to learn from long CoT data.

Student Model	$P_{Large}$	$P_{Small}$	$Large$	Better?
Qwen2.5-0.5B	16.9	20.4	-3.5	Weak
Qwen2.5-1.5B	32.2	33.0	-0.8	Weak
Qwen2.5-3B	39.7	39.4	0.3	Strong
Qwen2.5-7B	48.9	42.3	6.6	Strong
Qwen2.5-14B	52.9	49.9	3.0	Strong
Qwen2.5-32B	59.5	53.0	6.5	Strong
Llama-3.2-1B	16.5	18.5	-1.9	Weak
Llama-3.2-3B	32.8	31.2	1.6	Strong
Llama-3.2-8B	25.6	25.1	0.5	Strong
Llama-3.2-70B	57.6	53.3	4.3	Strong

h 2: Comparison of average performance between fine-tuning with large teacher CoT ( $P_{Long}$ ) and small teacher CoT ( $P_{Small}$ ). We find that small student models may struggle to learn from large teacher CoT data.

### 3.3 Large Teacher CoT Gap

We investigate how effective small models may learn from large teacher and small teachers. We define a *large teacher CoT gap* as:

$$Large = P_{Large} \quad P_{Small}:$$

Figure 3 provides a comprehensive comparison of the  $\mathcal{L}_{Large}$  incurred by all student models. The detailed benchmark scores of MATH, GSM8K, AIME, AMC and OlympiadBench are deferred to Table 8 in Appendix B. More experimental results of different teacher models, including LI ama3.1-70B vs LI ama3.1-8B and Gemma2-27B vs Gemma2-9B are in Table 9 of Appendix B.

We observe that larger student models learn effectively from large teacher CoT. For example, Qwen2.5-7B-Instruct and Qwen2.5-32B-Instruct student models improve over 5 points on average, with Qwen2.5-32B-Instruct achieving more than a 15 point increase on the AIMC benchmark. However, smaller models do not learn effectively from large teacher models such as Qwen2.5-72B-Instruct. Instead, small teacher models such as Qwen2.5-3B-Instruct may serve as better teacher models for small stu-

Student Model	$P_{Large}$	$P_{Small}$	$Large$	Better?
Qwen2.5-0.5B	16.9	20.4	-3.5	Weak
Qwen2.5-1.5B	32.2	33.0	-0.8	Weak
Qwen2.5-3B	39.7	39.4	0.3	Strong
Qwen2.5-7B	48.9	42.3	6.6	Strong
Qwen2.5-14B	52.9	49.9	3.0	Strong
Qwen2.5-32B	59.5	53.0	6.5	Strong
Llama-3.2-1B	16.5	18.5	-1.9	Weak
Llama-3.2-3B	32.8	31.2	1.6	Strong
Llama-3.2-8B	25.6	25.1	0.5	Strong
Llama-3.2-70B	57.6	53.3	4.3	Strong

[illegible]

$CoTi_{1/2}V_{1/2}$ :

$$Large = P_{Large} \quad P_{Small}:$$

i 8 i 2 i 2 † @ f ! < @ • × „ Large  
„ h b i 2 MATH GSM8K AIME AMC  
CE OlympiadBench „ i i 2 i 2 i 2 i 2 « ” i O D  
U B „ h 8 - Y ! < „ i i 2 E i  
œ i 2 l ama3.1-70B Li ama3.1-8B i i  
Gemma2-27B Gemma2-9B „ i 2 i 2 U B  
„ h 9

[illegible]

•  $\xi_{1/2} / \text{HM}_n \vee (\text{Kim et al. 2024b})$  —  $h$  —  $\xi_{1/2} < \xi / \xi_{1/2}$   
 $Y : \dagger \xi_{1/2} \quad h \in Y \quad \xi_{1/2} \xi_{1/2}$   
 $\xi_{1/2} \xi_{1/2} \quad K \quad (\xi_{1/2} \xi_{1/2} \xi_{1/2}) \cdot R$   
 $\xi_{1/2} \xi_{1/2} < \xi_{1/2}$

- $\frac{1}{2} 2: 1 \quad Y \quad \text{CoTi} \quad \frac{1}{2} 2:$

$$\begin{aligned} & \text{" } f \text{ ! } < > \text{ } \ddot{Z} \ddot{i} \text{ } \mathcal{F} \frac{1}{2} \text{" } Y \text{ ! } < \\ & - f \text{ ` } - \ddot{i} \text{ } \mathcal{J} \frac{1}{2} \text{ ' } < f \text{ ! } < \text{ } \ddot{i} \text{ } \mathcal{C} \frac{1}{2} \\ & < Y \text{ ! } < - \times \ddot{i} \text{ } \ddot{J} \frac{1}{2} \frac{1}{2} \end{aligned}$$

### 3.4 Analysis of Small Model Learnability Gap

† i ½ ½ ½ ½ ½ ½ ' ½ ½ i ½  
 i ½ = j p f ¶ ! < „ ! < ½ ½ f  
 F ( i ½ - ( ! < i ½ ½ f  
 i ½ CoT æ ' < Y CoT p n „  
 i ½ ' i ½ ½ ½ w S e i ½ i ½  
 f † f ! < Qwen2.5-Math-1.5B-Instruct  
 æ Qwen2.5-1.5B-Instruct K i ½ ½ f ' ½  
 i ½ ½ i ½ v i ½ ½ p f  
 ¶ ! < „ • CoT i ½ ½ Ž ( !  
 < d S • ( ' < Y CoT i ½ ½  
 i ½ Qwen2.5-Math-1.5B „ ' i ½ ½ ... i ½  
 Qwen2.5-1.5B i ½ p f ¶ ! < i ½ ½ Y  
 ½ CoT - x i ½ ½ i ½ ½ i ½ ½ <  
 ½ f ½ ' i ½ ½ \* s . i ½ f ! <  
 ( † ½ „ ½ ½ P i ½ ½ ½ ½ ½ ½  
 æ , @ i ½

- $\frac{1}{2} \cdot 3 = 1 \frac{1}{2}$   $\frac{1}{2} \cdot \frac{1}{2} = \frac{1}{4}$   $\frac{1}{2} \cdot \frac{1}{2} = \frac{1}{4}$

[illegible]

- $\frac{1}{2} 4: \ddot{\text{I}} @ \frac{1}{2} <$  VS  $\ddot{\text{I}} \frac{1}{2}$

$$\langle i | @_{V_2} \langle j | \frac{1}{2} i | \frac{1}{2} j | \frac{1}{2} k | V_2 | W \rangle$$
$$f^{\sim} i | \frac{1}{2} V_2 V_2 | \frac{1}{2}$$
[illegible]



✎ 4: Math expert models usually have a less significant Learnability Gap than the general models. A positive Gap means long CoT or large teacher CoT is better while negative means worse. This indicates that the math expert model could more easily learn from long CoT data or large teacher CoT.

ability gap is the *limited in-domain knowledge of small student models*. We summarize this observation in the following takeaway.

### Takeaway 3: Effect of Domain Knowledge

Limited domain knowledge of small models may hinder their learning from strong reasoning teachers.

**Base models exhibit a more significant learnability gap.** We observe that base models generally exhibit a more significant learnability gap than Instruct models in Figure 5. This suggests that it is more challenging for small base models to effectively learn from long CoT data or large teacher CoT.

## Takeaway 4: Base vs Instruct

Small base models experience more significant learnability gap than Instruct models.

**Speaking styles shift.** We adopt the method from (Lin et al., 2023) to evaluate the rank shift of each token before and after fine-tuning on long CoT and Large teacher CoT data. This allows us to compare the token distribution shifts induced by the fine-tuning process. We then annotate the tokens that exhibit the largest rank shifts as the most shifted tokens. Our analysis reveals that these to-

kens are predominantly associated with expressive and stylistic elements, such as `wait` , `But` , and `Let` . Please see [Appendix C](#) for more details.

## Takeaway 5: Speaking Styles Shift

Long CoT and large teacher CoT primarily shift the student model’s distribution of tokens associated with speaking styles.

#### 4 Mix Distillation: Bridge Small Model Learnability Gap

This section presents our Mix Distillation approach to bridge the small model learnability gap.

### 4.1 Mix Distillation

We propose *Mix Distillation* to address the learnability gap observed in small models. This approach blends easier-to-learn data with more challenging data for small models, thereby leveraging the strengths of both.

Our insight is that small models tend to perform better on data that closely matches their inherent distribution (such as short CoT or small teacher CoT), while they struggle with data that exhibits greater distribution shifts. The token distribution of the mixed long CoT and large teacher CoT data may become closer to that of small models’ inherent distribution, thereby enabling them to learn

[illegible]

#### 4 Mix Distillation: Bridge Small Model Learnability Gap

[illegible]

### 4.1 Mix Distillation

[illegible]

## 4.2 Experiment Results

Qwen2.5-3B-Instruct \ : f CoT 1/2 " s G' i 1/2 i 1/2 1/2  
! < v • ( MATH (7.5k) \ : - i 1/2 Qwen2.5-3B-Instruct \ : f ! < v i 1/2  
i 1/2 i 1/2 " Y ! < i 1/2 1/2 C 1/2 : 0.2 i 1/2 1/2 Mix-Long E Mix-Large \$  
\ : i 1/2 f i 1/2 Qwen2.5-72B • CoT i 1/2 1/2 ( " \* i 1/2 1/2 G i 1/2 1/2  
Qwen2.5-32B j CoT Qwen2.5-72B ' Y s G' i 1/2

CoT    Qwen2.5-3B    Y    CoT    1 2 1/2

Deepseek-R1-32B (DeepSeek-AI, 2025) \ :

$\gamma = \frac{1}{2}$ ,  $p_{\text{mix}} = 0.2$

ž Ći ġh Mix-Long Ć Mix-Large(

p ĩ 0½ ĩ ĩ ½ ĩ ½ ĩ ½ ĩ ½  
 ½ ĩ ĩ ½ • „ f ! < ( U  
 p n ĩ ĩ ½ ĩ ĩ ½ ĩ ½ ĩ ½ ĩ ½ ĩ ½ ĩ ½  
 , Qwen2.5-3B-Instruct( MATHCEAMC  
 ½ ( Mix-Long ĩ ½ ĩ ½ • CoTp n ĩ ĩ ½  
 ĩ ½ ĩ ½ ĩ ½ ĩ ½ ĩ ½ ( ' Y CoTp n  
 ½ ĩ ĩ ½ ĩ ½ Qwen2.5-3B-Instruct ĩ Mix  
 Large( MATH AIMECEAMC \_\_>: ĩ ĩ ½  
 ĩ ½ ĩ ½ ĩ ½ ĩ ½ „ f ! < ĩ ½ ĩ ½  
 ÷ • „ p n ĩ ĩ ½ ĩ ½ ĩ ½ ĩ ½

•  $\frac{1}{2} 6: \div$       •  $\% \text{ i } \frac{1}{2} \mathcal{L}$

[illegible]







Figure 7: Case Study of Mix-Long. Models fine-tuned on long CoT tended to overthink, while those trained on short CoT produced incorrect answers. In contrast, Mix-Long, incorporating branching elements (e.g., `Alternatively`), achieved a balanced reasoning process and arrived at the correct answer.

Interestingly, we find that after mixing long CoT and short CoT data, the small student model’s output incorporates characteristics of long CoT, such as a branching process, while maintaining a reduced token length and avoiding overly elaborate thinking. This is illustrated in Figure 7. We observed that the small student model fine-tuned on long CoT data becomes overwhelmed by repeated thoughts and fails to stop, whereas the model fine-tuned on short CoT data produces incorrect answers. In contrast, our proposed Mix-Long, which incorporates branching elements (e.g., the use of “Alternatively”), delivers the correct answer. Additionally, the average token lengths of responses generated by long CoT, short CoT, and Mix-Long are 3384.7, 575.7, and 1248.9, respectively. We

### 5.1 Chain-of-Thought

## 5.2 Synthetic Reasoning Data

Although human-crafted reasoning datasets have been used to enhance LLM reasoning capabilities (Hendrycks et al., 2021; LI et al., 2024), their development is both time-consuming and labor-intensive. Recent advancements have streamlined this process by generating instructions or responses directly from LLMs (Hui et al., 2024; Toshniwal et al., 2024; Xu et al., 2024; Yue et al., 2023; Zhang et al., 2025) or extracting data directly from web (Paster et al., 2023; Yue et al., 2024), yielding more detailed and diverse chain-of-thought reasoning pathways. Recent study has investigated the impact

 $4, \frac{1}{2}$ [illegible]

, ‡ Œ Ž ĩ ž ½€ / ĩ Øœž : <  
ĩ ž ½< „ ĩ ĩ ž ½ ĩ ™ žē- • ( „ p  
nĩ œ½ž ž½ž / ½ ĩ ™ ½ ĩ ž ½ĩ ž ž½ž  
„ Pĩ Ŭ½ž ž½ž \$ ĩ ž žž ž₂ „ " ( , ‡  
%oĩ ž žž ĩ ž ½

Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos, Matthieu Geist, and Olivier Bachem. 2024. **On-policy distillation of language models: Learning from self-generated mistakes**. *Preprint*, arXiv:2306.13649.

Anthropic. 2023. [Introducing claude](#).

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. [Language models are few-shot learners](#). *Preprint*, arXiv:2005.14165.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. [Training verifiers to solve math word problems](#). *Preprint*, arXiv:2110.14168.

DeepSeek-AI. 2025. [Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning](#). *Preprint*, arXiv:2501.12948.

, i 2 i 2 1/2 z > i 2 1/2 v ž i 2  
 (AFOSR) 9nD©O® FA9550-23-1-0208 w  
 > v ž i 2 (ONR) 9nD©O® N0014-23-  
 1-2386 i 2 1/2 1/2 1/2 1/2 1/2 (NSF) A i 2 1/2 1/2  
 „ Qi 2 1/2 1/2 1/2 \ v @ (ACTION) 9  
 nD©O® IIS 2229876 /  
 , i 2 i 2 1/2 1/2 1/2 1/2 i 2 1/2 h  
 i 2 1/2 1/2 1/2 „ D 1/2 , P™- h i 2 1/2  
 i 2 1/2 1/2 i 2 1/2 1/2 1/2 1/2 1/2 ^ ž \ v  
 š i 2 1/2 NSF v T | : „ CE L \

of various response generators (Kim et al., 2024b), suggesting that in the domains of instruction following and reasoning, responses from stronger teacher models do not necessarily produce the most effective learning effects for student models. However, these investigations have not recognized student model size as a critical factor influencing this phenomenon, nor have they performed the more attribution and mitigation analyses as in this paper.

## 6 Conclusion and Future Work

In this paper, we show that long CoT data and large model responses were not uniformly beneficial for small student models. We found that small models may perform better when fine-tuned with short CoT and small model CoT. We termed this challenge as the Small Model Learnability Gap. The reason behind it may be that small student models excel on data that closely match their inherent distribution but struggle with significant distribution shifts. To bridge the gap, we introduced Mix Distillation, including Mix-Long, which combined long CoT and short CoT data in a ratio, and Mix-Large, which integrated large and small teacher CoT. Experimental results showed that both Mix-Long and Mix-Large outperform baselines across most evaluation metrics, which implied mix distillation outperforms training on a single data distribution. This paper provided practical insights for optimizing post-training strategies to enhance small language model reasoning capability.

We will explore several promising directions as future work. First, we will refine mix distillation by optimally combining diverse data sources and proposing more fine-grained mixing algorithms to boost reasoning capabilities. Second, we propose to study how strong reasoning teachers can generate data that is better suited for tuning small student models, thereby facilitating more effective knowledge transfer. Third, we will conduct further

theoretical and model interpolability studies on the small model learnability gap. Lastly, we will investigate which SFT methods yield the best initial policies for subsequent RL procedure, ultimately enhancing overall model performance.

## Acknowledgment

This work is partially supported by the Air Force Office of Scientific Research (AFOSR) under grant FA9550-23-1-0208, the Office of Naval Research (ONR) under grant N0014-23-1-2386, and the National Science Foundation (NSF) AI Institute for Agent-based Cyber Threat Intelligence and Operation (ACTION) under grant IIS 2229876.

This work is supported in part by funds provided by the National Science Foundation, Department of Homeland Security, and IBM. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the NSF or its federal agency and industry partners.

## Limitations

While our study provides valuable insights into the understanding of small model learnability gap in math reasoning, we acknowledge that our research primarily focuses on this specific domain and does not evaluate other crucial skills such as instruction following, code generation, or multimodal understanding. We also did not investigate the impact of fine-grained variations in pre-training data composition on the small model learnability gap. A more detailed analysis of how different pre-training data sources and their proportions affect learning outcomes could offer valuable insights into optimizing data selection strategies for mitigating this gap.

DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, and et al. 2024. [Deepseek-v3 technical report](#). *Preprint*, arXiv:2412.19437.

Hanze Dong, Wei Xiong, Deepanshu Goyal, Yihan Zhang, Winnie Chow, Rui Pan, Shizhe Diao, Jipeng Zhang, Kashun Shum, and Tong Zhang. 2023. [Raft: Reward ranked finetuning for generative foundation model alignment](#). *Preprint*, arXiv:2304.06767.

Caglar Gulcehre, Tom Le Paine, Srivatsan Srinivasan, Ksenia Konyushkova, Lotte Weerts, Abhishek Sharma, Aditya Siddhant, Alex Ahern, Miaosen Wang, Chenjie Gu, Wolfgang Macherey, Arnaud Doucet, Orhan Firat, and Nando de Freitas. 2023. [Reinforced self-training \(rest\) for language modeling](#). *Preprint*, arXiv:2308.08998.

Chaoqun He, Renjie Luo, Yuzhuo Bai, Shengding Hu, Zhen Leng Thai, Junhao Shen, Jinyi Hu, Xu Han, Yujie Huang, Yuxiang Zhang, Jie Liu, Lei Qi, Zhiyuan Liu, and Maosong Sun. 2024. [Olympiad-bench: A challenging benchmark for promoting agi with olympiad-level bilingual multimodal scientific problems](#). *Preprint*, arXiv:2402.14008.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. [Measuring mathematical problem solving with the math dataset](#). *Preprint*, arXiv:2103.03874.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. [Distilling the knowledge in a neural network](#). *Preprint*, arXiv:1503.02531.

Zhenyu Hou, Xin Lv, Rui Lu, Jiajie Zhang, Yujiang Li, Zijun Yao, Juanzi Li, Jie Tang, and Yuxiao Dong. 2025. [Advancing language model reasoning through reinforcement learning and inference scaling](#). *Preprint*, arXiv:2501.11651.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. [Lora: Low-rank adaptation of large language models](#). *Preprint*, arXiv:2106.09685.

Tingfeng Hui, Lulu Zhao, Guanting Dong, Yaqi Zhang, Hua Zhou, and Sen Su. 2024. [Smaller language models are better instruction evolvers](#). *Preprint*, arXiv:2412.11231.

Gyeongman Kim, Doohyuk Jang, and Eunho Yang. 2024a. [Promptkd: Distilling student-friendly knowledge for generative language models via prompt tuning](#). *Preprint*, arXiv:2402.12842.

Seungone Kim, Juyoung Suk, Xiang Yue, Vijay Viswanathan, Seongyun Lee, Yizhong Wang, Kiril Gashteovski, Carolin Lawrence, Sean Welleck, and Graham Neubig. 2024b. [Evaluating language models as synthetic data generators](#). *Preprint*, arXiv:2412.03679.

Kimi Team. 2025. [Kimi k1.5: Scaling reinforcement learning with llms](#). *Preprint*, arXiv:2501.12599.

Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, Lester James V. Miranda, Alisa Liu, Nouha Dziri, Shane Lyu, Yuling Gu, Saumya Malik, Victoria Graf, Jena D. Hwang, Jiangjiang Yang, Ronan Le Bras, Oyvind Tafjord, Chris Wilhelm, Luca Soldaini, Noah A. Smith, Yizhong Wang, Pradeep Dasigi, and Hannaneh Hajishirzi. 2025. [Tulu 3: Pushing frontiers in open language model post-training](#). *Preprint*, arXiv:2411.15124.

Jia LI, Edward Beeching, Lewis Tunstall, Ben Lipkin, Roman Soletskyi, Shengyi Costa Huang, Kashif Rasul, Longhui Yu, Albert Jiang, Ziju Shen, Zihan Qin, Bin Dong, Li Zhou, Yann Fleureau, Guillaume Lample, and Stanislas Polu. 2024. [Numinamath. \[https://github.com/project-numina/ai-mo-progress-prize\]\(https://github.com/project-numina/ai-mo-progress-prize\)](#) ([https://github.com/project-numina/ai-mo-progress-prize/blob/main/report/numina\\_dataset.pdf](https://github.com/project-numina/ai-mo-progress-prize/blob/main/report/numina_dataset.pdf)).

Bill Yuchen Lin, Abhilasha Ravichander, Ximing Lu, Nouha Dziri, Melanie Sclar, Khyathi Chandu, Chandra Bhagavatula, and Yejin Choi. 2023. [The unlocking spell on base llms: Rethinking alignment via in-context learning](#). *Preprint*, arXiv:2312.01552.

Shayne Longpre, Le Hou, Tu Vu, Albert Webson, Hyung Won Chung, Yi Tay, Denny Zhou, Quoc V. Le, Barret Zoph, Jason Wei, and Adam Roberts. 2023. [The flan collection: Designing data and methods for effective instruction tuning](#). *Preprint*, arXiv:2301.13688.

Meta. 2024a. Llama-3.2-3b. <https://huggingface.co/meta-llama/Llama-3.2-3B>.

Meta. 2024b. Meet llama 3.1. <https://llama.meta.com>.

Yingqian Min, Zhipeng Chen, Jinhao Jiang, Jie Chen, Jia Deng, Yiwen Hu, Yiru Tang, Jiapeng Wang, Xiaoxue Cheng, Huatong Song, Wayne Xin Zhao, Zheng Liu, Zhongyuan Wang, and Ji-Rong Wen. 2024. [Imitate, explore, and self-improve: A reproduction report on slow-thinking reasoning systems](#). *Preprint*, arXiv:2412.09413.

NovaSky. 2025. [Sky-T1: Train your own o1 preview model within \\$450](#). Accessed: 2025-01-09.

OpenAI. 2023. [Gpt-4 technical report](#).

OpenAI. 2024. [Learning to reason with llms](#).

Jiayi Pan, Junjie Zhang, Xingyao Wang, Lifan Yuan, Hao Peng, and Alane Suhr. 2025. [Tinyzero](#). <https://github.com/Jiayi-Pan/TinyZero>. Accessed: 2025-01-24.



## Ethical Statement

This paper focuses on the evaluation and enhancement of reasoning capabilities in small language models through distillation techniques. The dataset and benchmarks used in our experiments are publicly available. We do not introduce or endorse any applications that could cause harm or be misused. This paper does not present any ethical concerns.

## References

- Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos, Matthieu Geist, and Olivier Bachem. 2024. [On-policy distillation of language models: Learning from self-generated mistakes](#). *Preprint*, arXiv:2306.13649.
- Anthropic. 2023. [Introducing claude](#).
- Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. [Language models are few-shot learners](#). *Preprint*, arXiv:2005.14165.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. [Training verifiers to solve math word problems](#). *Preprint*, arXiv:2110.14168.
- DeepSeek-AI. 2025. [Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning](#). *Preprint*, arXiv:2501.12948.
- DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, and et al. 2024. [Deepseek-v3 technical report](#). *Preprint*, arXiv:2412.19437.
- Hanze Dong, Wei Xiong, Deepanshu Goyal, Yihan Zhang, Winnie Chow, Rui Pan, Shizhe Diao, Jipeng Zhang, Kashun Shum, and Tong Zhang. 2023. [Raft: Reward ranked finetuning for generative foundation model alignment](#). *Preprint*, arXiv:2304.06767.
- Caglar Gulcehre, Tom Le Paine, Srivatsan Srinivasan, Ksenia Konyushkova, Lotte Weerts, Abhishek Sharma, Aditya Siddhant, Alex Ahern, Miaosen Wang, Chenjie Gu, Wolfgang Macherey, Arnaud Doucet, Orhan Firat, and Nando de Freitas. 2023. [Reinforced self-training \(rest\) for language modeling](#). *Preprint*, arXiv:2308.08998.
- Chaoqun He, Renjie Luo, Yuzhuo Bai, Shengding Hu, Zhen Leng Thai, Junhao Shen, Jinyi Hu, Xu Han, Yujie Huang, Yuxiang Zhang, Jie Liu, Lei Qi, Zhiyuan Liu, and Maosong Sun. 2024. [Olympiad-bench: A challenging benchmark for promoting agi with olympiad-level bilingual multimodal scientific problems](#). *Preprint*, arXiv:2402.14008.
- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. [Measuring mathematical problem solving with the math dataset](#). *Preprint*, arXiv:2103.03874.
- Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. [Distilling the knowledge in a neural network](#). *Preprint*, arXiv:1503.02531.
- Zhenyu Hou, Xin Lv, Rui Lu, Jiajie Zhang, Yujiang Li, Zijun Yao, Juanzi Li, Jie Tang, and Yuxiao Dong. 2025. [Advancing language model reasoning through reinforcement learning and inference scaling](#). *Preprint*, arXiv:2501.11651.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. [Lora: Low-rank adaptation of large language models](#). *Preprint*, arXiv:2106.09685.
- Tingfeng Hui, Lulu Zhao, Guanting Dong, Yaqi Zhang, Hua Zhou, and Sen Su. 2024. [Smaller language models are better instruction evolvers](#). *Preprint*, arXiv:2412.11231.
- Gyeongman Kim, Doohyuk Jang, and Eunho Yang. 2024a. [Promptkd: Distilling student-friendly knowledge for generative language models via prompt tuning](#). *Preprint*, arXiv:2402.12842.
- Seungone Kim, Juyoung Suk, Xiang Yue, Vijay Viswanathan, Seongyun Lee, Yizhong Wang, Kiril Gashteovski, Carolin Lawrence, Sean Welleck, and Graham Neubig. 2024b. [Evaluating language models as synthetic data generators](#). *Preprint*, arXiv:2412.03679.
- Kimi Team. 2025. [Kimi k1.5: Scaling reinforcement learning with llms](#). *Preprint*, arXiv:2501.12599.
- Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, Lester James V. Miranda, Alisa Liu, Nouha Dziri, Shane Lyu, Yuling Gu, Saumya Malik, Victoria Graf, Jena D. Hwang, Jiangjiang Yang, Ronan Le Bras, Oyvind Tafjord, Chris Wilhelm, Luca Soldaini, Noah A. Smith, Yizhong Wang, Pradeep Dasigi, and Hannaneh Hajishirzi. 2025. [Tulu 3: Pushing frontiers in open language model post-training](#). *Preprint*, arXiv:2411.15124.
- Keiran Paster, Marco Dos Santos, Zhangir Azerbayev, and Jimmy Ba. 2023. [Openwebmath: An open dataset of high-quality mathematical web text](#). *Preprint*, arXiv:2310.06786.
- Qwen. 2024a. [Qwen2.5: A party of foundation models](#).
- Qwen. 2024b. [Qwq: Reflect deeply on the boundaries of the unknown](#). 2024b.
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. [Deepseekmath: Pushing the limits of mathematical reasoning in open language models](#). *Preprint*, arXiv:2402.03300.
- Avi Singh, John D. Co-Reyes, Rishabh Agarwal, Ankesh Anand, Piyush Patil, Xavier Garcia, Peter J. Liu, James Harrison, Jaehoon Lee, Kelvin Xu, Aaron Parisi, Abhishek Kumar, Alex Alemi, Alex Rizkowsky, Azade Nova, Ben Adlam, Bernd Bohnet, Gamaleldin Elsayed, Hanie Sedghi, Igor Mordatch, Isabelle Simpson, Izzeddin Gur, Jasper Snoek, Jeffrey Pennington, Jiri Hron, Kathleen Keane, Kevin Swersky, Kshiteej Mahajan, Laura Culp, Lechao Xiao, Maxwell L. Bileschi, Noah Constant, Roman Novak, Rosanne Liu, Tris Warkentin, Yundi Qian, Yamini Bansal, Ethan Dyer, Behnam Neyshabur, Jascha Sohl-Dickstein, and Noah Fiedel. 2024. [Beyond human data: Scaling self-training for problem-solving with language models](#). *Preprint*, arXiv:2312.06585.
- Yuxuan Tong, Xiwen Zhang, Rui Wang, Ruidong Wu, and Junxian He. 2024. [Dart-math: Difficulty-aware rejection tuning for mathematical problem-solving](#). *Preprint*, arXiv:2407.13690.
- Shubham Toshniwal, Wei Du, Ivan Moshkov, Branislav Kisanin, Alexan Ayrapetyan, and Igor Gitman. 2024. [Openmathinstruct-2: Accelerating ai for math with massive open-source instruction data](#). *Preprint*, arXiv:2410.01560.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023a. [Llama: Open and efficient foundation language models](#). *Preprint*, arXiv:2302.13971.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajwal Bhargava, Shruti Bhosale, et al. 2023b. [Llama 2: Open foundation and fine-tuned chat models](#). *arXiv preprint arXiv:2307.09288*.
- Lewis Tunstall, Edward Beeching, Nathan Lambert, Nazneen Rajani, Kashif Rasul, Younes Belkada, Shengyi Huang, Leandro von Werra, Clémentine Fourrier, Nathan Habib, Nathan Sarrazin, Omar Sanseviero, Alexander M. Rush, and Thomas Wolf. 2023. [Zephyr: Direct distillation of lm alignment](#). *Preprint*, arXiv:2310.16944.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. 2023. [Chain-of-thought prompting elicits reasoning in large language models](#). *Preprint*, arXiv:2201.11903.
- Zhangchen Xu, Fengqing Jiang, Luyao Niu, Yuntian Deng, Radha Poovendran, Yejin Choi, and Bill Yuchen Lin. 2024. [Magpie: Alignment data synthesis from scratch by prompting aligned llms with nothing](#). *Preprint*, arXiv:2406.08464.
- An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, Keming Lu, Mingfeng Xue, Runji Lin, Tianyu Liu, Xingzhang Ren, and Zhenru Zhang. 2024. [Qwen2.5-math technical report: Toward mathematical expert model via self-improvement](#). *Preprint*, arXiv:2409.12122.
- Edward Yeo, Yuxuan Tong, Morry Niu, Graham Neubig, and Xiang Yue. 2025. [Demystifying long chain-of-thought reasoning in llms](#). *Preprint*, arXiv:2502.03373.
- Longhui Yu, Weisen Jiang, Han Shi, Jincheng Yu, Zhengying Liu, Yu Zhang, James T. Kwok, Zhenguo Li, Adrian Weller, and Weiyang Liu. 2024. [Metamath: Bootstrap your own mathematical questions for large language models](#). *Preprint*, arXiv:2309.12284.
- Zheng Yuan, Hongyi Yuan, Chengpeng Li, Guanting Dong, Keming Lu, Chuanqi Tan, Chang Zhou, and Jingren Zhou. 2023. [Scaling relationship on learning mathematical reasoning with large language models](#). *Preprint*, arXiv:2308.01825.
- Xiang Yue, Xingwei Qu, Ge Zhang, Yao Fu, Weihao Huang, Huan Sun, Yu Su, and Wenhui Chen. 2023. [Mammoth: Building math generalist models through hybrid instruction tuning](#). *Preprint*, arXiv:2309.05653.
- Xiang Yue, Toney Zheng, Ge Zhang, and Wenhui Chen. 2024. [Mammoth2: Scaling instructions from the web](#). *Preprint*, arXiv:2405.03548.
- Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah D. Goodman. 2022. [Star: Bootstrapping reasoning with reasoning](#). *Preprint*, arXiv:2203.14465.
- Weihao Zeng, Yuzhen Huang, Wei Liu, Keqing He, Qian Liu, Zejun Ma, and Junxian He. 2025. [7b model and 8k examples: Emerging reasoning with reinforcement learning is both effective and efficient](#). <https://hkust-nlp.notion.site/simplerl-reason>. Notion Blog.
- Dylan Zhang, Qirun Dai, and Hao Peng. 2025. [The best instruction-tuning data are those that fit](#). *Preprint*, arXiv:2502.04194.



- Jia LI, Edward Beeching, Lewis Tunstall, Ben Lipkin, Roman Soletskyi, Shengyi Costa Huang, Kashif Rasul, Longhui Yu, Albert Jiang, Ziju Shen, Zihan Qin, Bin Dong, Li Zhou, Yann Fleureau, Guillaume Lample, and Stanislas Polu. 2024. Numinamath. [<https://github.com/project-numina/ai-mo-progress-prize>] ([https://github.com/project-numina/ai-mo-progress-prize/blob/main/report/numina\\_dataset.pdf](https://github.com/project-numina/ai-mo-progress-prize/blob/main/report/numina_dataset.pdf)).
- Bill Yuchen Lin, Abhilasha Ravichander, Ximing Lu, Nouha Dziri, Melanie Sclar, Khyathi Chandu, Chandra Bhagavatula, and Yejin Choi. 2023. The unlocking spell on base llms: Rethinking alignment via in-context learning. *Preprint*, arXiv:2312.01552.
- Shayne Longpre, Le Hou, Tu Vu, Albert Webson, Hyung Won Chung, Yi Tay, Denny Zhou, Quoc V. Le, Barret Zoph, Jason Wei, and Adam Roberts. 2023. The flan collection: Designing data and methods for effective instruction tuning. *Preprint*, arXiv:2301.13688.
- Meta. 2024a. Llama-3.2-3b. <https://huggingface.co/meta-Llama/Llama-3.2-3B>.
- Meta. 2024b. Meet Llama 3.1. <https://llama.meta.com>.
- Yingqian Min, Zhipeng Chen, Jinhao Jiang, Jie Chen, Jia Deng, Yiwen Hu, Yiru Tang, Jiapeng Wang, Xiaoxue Cheng, Huatong Song, Wayne Xin Zhao, Zheng Liu, Zhongyuan Wang, and Ji-Rong Wen. 2024. Imitate, explore, and self-improve: A reproduction report on slow-thinking reasoning systems. *Preprint*, arXiv:2412.09413.
- NovaSky. 2025. Sky-T1: Train your own o1 preview model within \$450. Accessed: 2025-01-09.
- OpenAI. 2023. Gpt-4 technical report.
- OpenAI. 2024. Learning to reason with llms.
- Jiayi Pan, Junjie Zhang, Xingyao Wang, Lifan Yuan, Hao Peng, and Alane Suhr. 2025. Tinyzero. <https://github.com/Jiayi-Pan/TinyZero>. Accessed: 2025-01-24.
- Keiran Paster, Marco Dos Santos, Zhangir Azerbayev, and Jimmy Ba. 2023. Openwebmath: An open dataset of high-quality mathematical web text. *Preprint*, arXiv:2310.06786.
- Qwen. 2024a. Qwen2.5: A party of foundation models.
- Qwen. 2024b. Qwq: Reflect deeply on the boundaries of the unknown. 2024b.
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *Preprint*, arXiv:2402.03300.
- Avi Singh, John D. Co-Reyes, Rishabh Agarwal, Ankesh Anand, Piyush Patil, Xavier Garcia, Peter J. Liu, James Harrison, Jaehoon Lee, Kelvin Xu, Aaron Parisi, Abhishek Kumar, Alex Alemi, Alex Rizkowsky, Azade Nova, Ben Adlam, Bernd Bohnet, Gamaleldin Elsayed, Hanie Sedghi, Igor Mordatch, Isabelle Simpson, Izzeddin Gur, Jasper Snoek, Jeffrey Pennington, Jiri Hron, Kathleen Keane, Kevin Swersky, Kshiteej Mahajan, Laura Culp, Lechao Xiao, Maxwell L. Bileschi, Noah Constant, Roman Novak, Rosanne Liu, Tris Warkentin, Yundi Qian, Yamini Bansal, Ethan Dyer, Behnam Neyshabur, Jascha Sohl-Dickstein, and Noah Fiedel. 2024. Beyond human data: Scaling self-training for problem-solving with language models. *Preprint*, arXiv:2312.06585.
- Yuxuan Tong, Xiwen Zhang, Rui Wang, Ruidong Wu, and Junxian He. 2024. Dart-math: Difficulty-aware rejection tuning for mathematical problem-solving. *Preprint*, arXiv:2407.13690.
- Shubham Toshniwal, Wei Du, Ivan Moshkov, Branislav Kisanin, Alexan Ayrapetyan, and Igor Gitman. 2024. Openmathinstruct-2: Accelerating ai for math with massive open-source instruction data. *Preprint*, arXiv:2410.01560.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023a. Llama: Open and efficient foundation language models. *Preprint*, arXiv:2302.13971.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023b. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.
- Lewis Tunstall, Edward Beeching, Nathan Lambert, Nazneen Rajani, Kashif Rasul, Younes Belkada, Shengyi Huang, Leandro von Werra, Clémentine Fourrier, Nathan Habib, Nathan Sarrazin, Omar Sanseviero, Alexander M. Rush, and Thomas Wolf. 2023. Zephyr: Direct distillation of lm alignment. *Preprint*, arXiv:2310.16944.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. 2023. Chain-of-thought prompting elicits reasoning in large language models. *Preprint*, arXiv:2201.11903.
- Zhangchen Xu, Fengqing Jiang, Luyao Niu, Yuntian Deng, Radha Poovendran, Yejin Choi, and Bill Yuchen Lin. 2024. Magpie: Alignment data synthesis from scratch by prompting aligned llms with nothing. *Preprint*, arXiv:2406.08464.
- An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, Keming Lu,
- Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, Zheyang Luo, Zhangchi Feng, and Yongqiang Ma. 2024. Llamafactory: Unified efficient fine-tuning of 100+ language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, Bangkok, Thailand. Association for Computational Linguistics.

Mingfeng Xue, Runji Lin, Tianyu Liu, Xingzhang Ren, and Zhenru Zhang. 2024. [Qwen2.5-math technical report: Toward mathematical expert model via self-improvement](#). *Preprint*, arXiv:2409.12122.

Edward Yeo, Yuxuan Tong, Morry Niu, Graham Neubig, and Xiang Yue. 2025. [Demystifying long chain-of-thought reasoning in llms](#). *Preprint*, arXiv:2502.03373.

Longhui Yu, Weisen Jiang, Han Shi, Jincheng Yu, Zhengying Liu, Yu Zhang, James T. Kwok, Zhengguo Li, Adrian Weller, and Weiyang Liu. 2024. [Metamath: Bootstrap your own mathematical questions for large language models](#). *Preprint*, arXiv:2309.12284.

Zheng Yuan, Hongyi Yuan, Chengpeng Li, Guanting Dong, Keming Lu, Chuanqi Tan, Chang Zhou, and Jingren Zhou. 2023. [Scaling relationship on learning mathematical reasoning with large language models](#). *Preprint*, arXiv:2308.01825.

Xiang Yue, Xingwei Qu, Ge Zhang, Yao Fu, Wenhao Huang, Huan Sun, Yu Su, and Wenhua Chen. 2023. [Mammoth: Building math generalist models through hybrid instruction tuning](#). *Preprint*, arXiv:2309.05653.

Xiang Yue, Tuney Zheng, Ge Zhang, and Wenhua Chen. 2024. [Mammoth2: Scaling instructions from the web](#). *Preprint*, arXiv:2405.03548.

Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah D. Goodman. 2022. [Star: Bootstrapping reasoning with reasoning](#). *Preprint*, arXiv:2203.14465.

Weihao Zeng, Yuzhen Huang, Wei Liu, Keqing He, Qian Liu, Zejun Ma, and Junxian He. 2025. 7b model and 8k examples: Emerging reasoning with reinforcement learning is both effective and efficient. <https://hkust-nlp.notion.site/simplified-reason>. Notion Blog.

Dylan Zhang, Qirun Dai, and Hao Peng. 2025. [The best instruction-tuning data are those that fit](#). *Preprint*, arXiv:2502.04194.

Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, Zheyang Luo, Zhangchi Feng, and Yongqiang Ma. 2024. [Llamafactory: Unified efficient fine-tuning of 100+ language models](#). In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, Bangkok, Thailand. Association for Computational Linguistics.

## A Detailed Experimental Setups

Category	Models
Teacher Models	
Long CoT vs ShortCoT	QwQ-32B-Preview vs Qwen2.5-32B-Instruct
Large Teacher vs Small Teacher	
Qwen Family	Qwen2.5-72B-Instruct vs Qwen2.5-3B-Instruct
Llama Family	Llama3.1-70B-Instruct vs Llama3.1-8B-Instruct
Gemma Family	Gemma2-27B-it vs Gemma2-9B-it
Student Models	
Qwen Family	Qwen2.5-0.5B-Instruct, Qwen2.5-1.5B-Instruct, Qwen2.5-3B-Instruct, Qwen2.5-7B-Instruct, Qwen2.5-14B-Instruct, Qwen2.5-32B-Instruct
Llama Family	Llama3.2-1B-Instruct, Llama3.2-3B-Instruct, Llama3.1-8B-Instruct, Llama3.3-70B-Instruct

h 4: Overview of Teacher and Student Models

### A.1 Models

h 4: Overview of Teacher and Student Models

### A.2 Training Setup

h 4: Overview of Teacher and Student Models

Hyper-parameter	Value
Learning Rate	$1 \times 10^{-5}$
Number of Epochs	2
Number of Devices	4
Per-device Batch Size	2
Optimizer	Adamw
Learning Rate Scheduler	cosine
Max Sequence Length	16384

h 5: dh>: tEt i p , ...i p 1/2

Hyper-parameter	Value
Learning Rate	$1 \times 10^{-4}$
Number of Epochs	2
Number of Devices	4
Per-device Batch Size	1
Lora Target	full
Learning Rate Scheduler	cosine
Warmup Ratio	0.03
Max Sequence Length	16384

h 6: dh>: t LoRA® , ...i p 1/2

2023; Dong et al., 2023) 1/2 1/2Y ! < 1/2\* j 1/2 i 1/2 f i 1/2 i 1/2 ! < „ i 1/2 1/2 1/2 we i 1/2 1/2 t i 1/2 1/2 1/2 1/2 f ! < i 1/2 1/2 Y ! < „ 1/2 1/2 1/2 1/2 1/2 v [ i 1/2 ! < i 1/2 „ OL-1/2 1/2 1/2 i 1/2 f ! <

### A.3 Evaluation Setup

i 1/2 < - i 1/2 t LLaMA-Factory (Zheng et al., 2024) ( i 1/2 t NVIDIA A100-SXM4-80GB GPU \* AMD EPYC 7763 648 h 512 GB...X„ i h i 1/2 i 1/2 Ž i 1/2 Ž 14B„ f ! < i 1/2 h i 1/2 p® Sf ! < „ i 1/2 Ž 14B i 1/2 i 1/2 LoRA® (Hu et al., 2021) h 5 h 6 + i 1/2 i 1/2 LoRA® „ ...i p 1/2 Y ! < i 1/2 1/2 1/2 1/2 (Zelikman et al., 2022; Tong et al., 2024; Yue et al., 2023; Singh et al., 2024; Gulcehre et al., 2023; Yuan et al., 2023; Dong et al., 2023) 1/2 1/2Y ! < 1/2\* j 1/2 i 1/2 f i 1/2 i 1/2 ! < „ i 1/2 1/2 1/2 1/2 we i 1/2 1/2 t i 1/2 1/2 1/2 1/2 f ! < i 1/2 1/2 Y ! < „ 1/2 1/2 1/2 1/2 1/2 v [ i 1/2 ! < i 1/2 „ OL-1/2 1/2 1/2 i 1/2 f ! <





2021), GSM8K (Cobbe et al., 2021), AMC 2023, AIME 2024, and the English math subset of OlympiadBench (He et al., 2024).

Unless otherwise specified, all fine-tuned models are evaluated in a zero-shot setting using greedy decoding. We set the maximum generation tokens as 16k. The evaluation prompt is shown below.

Prompt

Solve the following math problem and present the final answer in the format: Final Answer: fyour answerg  
Problem: {problem}  
Answer:

After extracting the final answer of the evaluated model, we first employ exact matching to determine the correctness of the answer. If the answer is incorrect, we use Qwen-32B-Instruct as a judge to compare the extracted final answers against that of the ground truth. The prompt is shown below.

Prompt

Given a math problem, its correct final answer, and the model’s generated final answer, determine if the model’s answer is correct. Respond with ‘True’ if the it is correct and ‘False’ if it is incorrect.  
Problem: {problem}  
Correct Final Answer: {ground truth}  
Model’s Generated Final Answer: {resp answer}  
Your Judgement:

B More Experiments Results

In this section we present additional experiment results of long CoT gap and large teacher CoT gap.

B.1 Long CoT Gap: Additional Results

Table 7 shows the detailed performance scores and gap of each benchmark for different student models fine-tuned on long CoT and short CoT. QwQ-32B-Preview is chosen to generate long CoT and awhile Qwen-2.5-32B-Instruct is chosen to generate short CoT. We observe that small student models tend to benefit more from short CoT, while large student models gain greater advantages from long CoT.

B.2 Large Teacher CoT Gap: Additional Results

Table 8 shows the detailed performance scores and gap of each benchmark for different student models distilled from large teacher and small teacher. We summarize the performance of 10 student models from the Llama and Qwen families across various model sizes. Qwen-2.5-72B-Instruct is chosen as the large teacher while Qwen-2.5-3B-Instruct is chosen as the small teacher. The results are shown in Table 8. Our findings indicate that small student models may experience degraded performance when distilled from a large teacher compared to a small teacher, whereas larger student models benefit more from distilling a large teacher.

Table 9 shows more experiment results for teacher models in different model families, including Gemma-27B-it vs Gemma-9B-it and Llama3.1-72B-Instruct vs Llama3.1-8B-Instruct.

C Examples of Speaking Style Shift

We adopt the method from (Lin et al., 2023) to evaluate the most shifted tokens after fine-tuning on long CoT and Large teacher CoT data. Figure 8 shows the calculation process. This allows us to compare the token distribution shifts induced by the fine-tuning process. We annotate the tokens that

Model	MATH			GSM8K			AIME			AMC			Olympiad			Average	
	P <sub>Long</sub>	P <sub>Short</sub>	Long	P <sub>Long</sub>	P <sub>Short</sub>	Long	P <sub>Long</sub>	P <sub>Short</sub>	Long	P <sub>Long</sub>	P <sub>Short</sub>	Long	P <sub>Long</sub>	P <sub>Short</sub>	Long	Long	
Llama-3.2-1B	28.6	33.4	-4.78	42.3	49.2	-6.90	0.00	0.00	0.00	2.50	7.50	-5.00	5.48	7.40	-1.92	-3.72	
Llama-3.2-3B	48.7	50.9	-2.14	75.1	77.5	-2.42	3.33	3.33	0.00	17.5	15.0	2.50	17.6	18.7	-1.04	-0.619	
Llama-3.1-8B	50.0	44.6	5.36	81.4	75.5	5.84	0.00	0.00	0.00	27.5	22.5	5.00	17.3	14.8	2.52	3.74	
Llama-3.3-70B	75.3	74.9	0.340	92.7	91.2	1.44	26.7	13.3	13.3	55.0	52.5	2.50	41.3	39.7	1.63	3.85	
Qwen2.5-0.5B	23.0	31.5	-8.44	39.5	45.3	-5.84	0.00	0.00	0.00	7.50	15.0	-7.50	4.00	5.93	-1.93	-4.74	
Qwen2.5-1.5B	41.6	52.3	-10.7	63.8	71.7	-7.89	0.00	0.00	0.00	17.5	27.5	-10.0	12.3	19.4	-7.11	-7.13	
Qwen2.5-3B	56.2	61.0	-4.84	80.0	82.0	-1.98	3.33	10.0	-6.67	37.5	37.5	0.00	24.4	26.4	-1.93	-3.08	
Qwen2.5-7B	68.2	67.8	0.460	86.2	85.7	0.560	13.3	6.67	6.67	40.0	40.0	0.00	36.6	35.7	0.889	1.72	
Qwen2.5-14B	78.3	76.2	2.04	93.3	92.5	0.760	20.0	6.67	13.3	60.0	55.0	5.00	44.4	40.9	3.56	4.94	
Qwen2.5-32B	84.8	82.3	2.44	94.9	94.3	0.610	40.0	10.0	30.0	85.0	62.5	22.5	60.4	47.3	13.2	13.7	

h 7: d h ; i t 1/2 ( • CoTCE CoTpn ® „ LlamaCEQweni 1/2 < „ ' i 1/2 i 1/2 MATH  
GSM8K AIME AMCCEOlympiadBench i 1/2 i 1/2 Q 1/2 QwQ-32B-Preview • CoT  
Qwen-2.5-32B-Instruct CoT i 1/2Q 1/2 < f ! < i 1/2 CoT- x i 1/2 1/2 ' < f !  
< i 1/2 CoT- - i 1/2 1/2

Model	MATH			GSM8k			AIME			AMC			Olympiad			Average	
	P <sub>Strong</sub>	P <sub>Weak</sub>	Strong	P <sub>Strong</sub>	P <sub>Weak</sub>	Strong	P <sub>Strong</sub>	P <sub>Weak</sub>	Strong	P <sub>Strong</sub>	P <sub>Weak</sub>	Strong	P <sub>Strong</sub>	P <sub>Weak</sub>	Strong	Strong	
Llama-3.2-1B	29.8	29.6	0.160	44.4	47.5	-3.18	0.00	0.00	0.00	2.50	7.50	-5.00	6.07	7.70	-1.63	-1.93	
Llama-3.2-3B	47.4	47.9	-0.500	71.2	74.1	-2.88	3.33	0.00	3.33	25.0	17.5	7.50	16.9	16.4	0.445	1.58	
Llama-3.2-8B	37.6	37.6	-0.040	67.0	69.2	-2.20	6.67	0.00	6.67	7.50	7.50	0.00	9.19	11.0	-1.78	0.530	
Llama-3.2-70B	74.5	72.2	2.28	92.0	92.2	-0.152	16.7	16.7	0.00	67.5	50.0	17.5	37.3	35.7	1.63	4.25	
Qwen2.5-0.5B	30.0	31.0	-0.920	43.1	45.4	-2.35	0.00	0.00	0.00	5.00	17.5	-12.5	6.52	8.30	-1.78	-3.51	
Qwen2.5-1.5B	50.3	50.7	-0.440	70.6	71.0	-0.455	0.00	3.33	-3.33	22.5	20.0	2.50	17.8	20.0	-2.22	-0.790	
Qwen2.5-3B	57.5	60.3	-2.82	79.9	79.5	0.379	0.00	3.33	-3.33	35.0	27.5	7.50	25.9	26.4	-0.444	0.256	
Qwen2.5-7B	71.3	63.6	7.66	87.8	84.1	3.72	6.67	0.00	6.67	40.0	35.0	5.00	38.8	29.0	9.78	6.56	
Qwen2.5-14B	76.4	72.8	3.66	93.1	89.6	3.49	6.67	3.33	3.33	47.5	45.0	2.50	41.0	39.0	2.07	3.01	
Qwen2.5-32B	80.5	76.8	3.72	92.2	92.7	-0.531	20.0	3.33	16.7	57.5	50.0	7.50	47.4	42.4	5.04	6.48	

h 8: d h ; i t 1/2 MATH GSM8K AIME AMCCEOlympiadBench i 1/2 LlamaCEQweni 1/2  
< ( • ( ' < Y CoTCE < Y CoT® „ ' i 1/2 i 1/2 Qwen-2.5-72B-Instruct \ : ' < Y  
Qwen-2.5-3B-Instruct \ : < Y i 1/2Q 1/2 i 1/2Y • i 1/2 < f ! < i 1/2 1/2Y  
• i 1/2 1/2 1/2 1/2 i 1/2 f' „ f ! < i 1/2 1/2Y • - x i 1/2 1/2

Model	Gemma2-9B vs Gemma2-27B						Llama3.1-8B vs Llama3.1-70B					
	MATH	AMC	Olympiad	AIME	GSM8k	Average	MATH	AMC	Olympiad	AIME	GSM8k	Average
Llama3.2-1B	-1.42	-7.50	0.00	0.00	-0.227	-1.83	-1.42	-5.00	-0.296	3.33	0.152	-0.646
Llama3.2-3B	2.08	-7.50	-0.888	0.00	1.67	-0.928	-0.14	10.0	-0.593	3.33	1.06	2.73
Llama3.1-8B	0.56	0.00	0.078	0.00	-0.516	0.0243	-2.18	7.50	2.67	0.00	-1.29	1.34
Llama3.1-70B	0.02	7.50	-0.741	10.0	0.152	3.39	2.72	17.5	5.48	6.67	0.986	6.67
Qwen2.5-0.5B	-4.56	0.00	0.741	0.00	0.592	-0.645	-1.88	0.00	0.185	0.00	-1.74	-0.688
Qwen2.5-1.5B	-1.20	2.50	-1.19	0.00	-0.986	-0.174	-1.48	5.00	-0.148	3.33	-1.14	1.11
Qwen2.5-3B	0.44	5.00	1.78	0.00	-0.758	1.29	-1.26	5.00	-0.741	-3.33	-1.29	-0.325
Qwen2.5-7B	0.22	5.00	1.04	-3.33	3.94	1.37	3.68	20.0	4.15	3.33	2.81	6.79
Qwen2.5-14B	1.32	2.50	-0.148	0.00	-0.986	0.537	2.18	0.00	0.445	3.33	-0.303	1.13
Qwen2.5-32B	0.10	2.50	1.48	3.44	1.36	1.78	2.72	-2.50	5.63	3.33	0.834	2.00

h 9: d h U: t i 1/2Y ! < „ • i 1/2 1/2 ! < „ ' i 1/2 i 1/2 Gemma-27B-it Gemma-9B-it i 1/2 1/2  
Llama3.1-72B-Instruct Llama3.1-8B-Instruct i 1/2Q 1/2Si 1/2Y ! < „ • i 1/2 < f  
! < „ ' i 1/2 1/2 1/2M ' < f ! < i 1/2 1/2Y ! < - • i 1/2 1/2

Model	MATH			GSM8K			AIME			AMC			Olympiad			Average
	$P_{\text{Long}}$	$P_{\text{Short}}$	Long	$P_{\text{Long}}$	$P_{\text{Short}}$	Long	$P_{\text{Long}}$	$P_{\text{Short}}$	Long	$P_{\text{Long}}$	$P_{\text{Short}}$	Long	$P_{\text{Long}}$	$P_{\text{Short}}$	Long	Long
Llama-3.2-1B	28.6	33.4	-4.78	42.3	49.2	-6.90	0.00	0.00	0.00	2.50	7.50	-5.00	5.48	7.40	-1.92	-3.72
Llama-3.2-3B	48.7	50.9	-2.14	75.1	77.5	-2.42	3.33	3.33	0.00	17.5	15.0	2.50	17.6	18.7	-1.04	-0.619
Llama-3.1-8B	50.0	44.6	5.36	81.4	75.5	5.84	0.00	0.00	0.00	27.5	22.5	5.00	17.3	14.8	2.52	3.74
Llama-3.3-70B	75.3	74.9	0.340	92.7	91.2	1.44	26.7	13.3	13.3	55.0	52.5	2.50	41.3	39.7	1.63	3.85
Qwen2.5-0.5B	23.0	31.5	-8.44	39.5	45.3	-5.84	0.00	0.00	0.00	7.50	15.0	-7.50	4.00	5.93	-1.93	-4.74
Qwen2.5-1.5B	41.6	52.3	-10.7	63.8	71.7	-7.89	0.00	0.00	0.00	17.5	27.5	-10.0	12.3	19.4	-7.11	-7.13
Qwen2.5-3B	56.2	61.0	-4.84	80.0	82.0	-1.98	3.33	10.0	-6.67	37.5	37.5	0.00	24.4	26.4	-1.93	-3.08
Qwen2.5-7B	68.2	67.8	0.460	86.2	85.7	0.560	13.3	6.67	6.67	40.0	40.0	0.00	36.6	35.7	0.889	1.72
Qwen2.5-14B	78.3	76.2	2.04	93.3	92.5	0.760	20.0	6.67	13.3	60.0	55.0	5.00	44.4	40.9	3.56	4.94
Qwen2.5-32B	84.8	82.3	2.44	94.9	94.3	0.610	40.0	10.0	30.0	85.0	62.5	22.5	60.4	47.3	13.2	13.7

Figure 7: This table summarizes the performance of models in Llama and Qwen families fine-tuned with long CoT and short CoT data. They are evaluated on MATH, GSM8K, AIME, AMC, and OlympiadBench. Qwen2-32B-Preview is chosen to generate long CoT and while Qwen2-5-32B-Instruct is chosen to generate short CoT. We observe that small student models tend to benefit more from short CoT, while large student models gain greater advantages from long CoT.

Figure 8: This table summarizes the performance of models in Llama and Qwen families fine-tuned with large teacher CoT and small teacher CoT when evaluated on MATH, GSM8K, AIME, AMC, and OlympiadBench. Qwen2-5-72B-Instruct is chosen as the large teacher while Qwen2-5-3B-Instruct is chosen as the small teacher. We observe that small student models may experience degraded performance when distilled from a large teacher compared to a small teacher, whereas larger student models benefit more from the distilling a large teacher.

Model	MATH			GSM8k			AIME			AMC			Olympiad			Average
	$P_{\text{Strong}}$	$P_{\text{Weak}}$	Strong	$P_{\text{Strong}}$	$P_{\text{Weak}}$	Strong	$P_{\text{Strong}}$	$P_{\text{Weak}}$	Strong	$P_{\text{Strong}}$	$P_{\text{Weak}}$	Strong	$P_{\text{Strong}}$	$P_{\text{Weak}}$	Strong	Strong
Llama-3.2-1B	29.8	29.6	0.160	44.4	47.5	-3.18	0.00	0.00	0.00	2.50	7.50	-5.00	6.07	7.70	-1.63	-1.93
Llama-3.2-3B	47.4	47.9	-0.500	71.2	74.1	-2.88	3.33	0.00	3.33	25.0	17.5	7.50	16.9	16.4	0.445	1.58
Llama-3.2-8B	37.6	37.6	-0.040	67.0	69.2	-2.20	6.67	0.00	6.67	7.50	7.50	0.00	9.19	11.0	-1.78	0.530
Llama-3.2-70B	74.5	72.2	2.28	92.0	92.2	-0.152	16.7	16.7	0.00	67.5	50.0	17.5	37.3	35.7	1.63	4.25
Qwen2.5-0.5B	30.0	31.0	-0.920	43.1	45.4	-2.35	0.00	0.00	0.00	5.00	17.5	-12.5	6.52	8.30	-1.78	-3.51
Qwen2.5-1.5B	50.3	50.7	-0.440	70.6	71.0	-0.455	0.00	3.33	-3.33	22.5	20.0	2.50	17.8	20.0	-2.22	-0.790
Qwen2.5-3B	57.5	60.3	-2.82	79.9	79.5	0.379	0.00	3.33	-3.33	35.0	27.5	7.50	25.9	26.4	-0.444	0.256
Qwen2.5-7B	71.3	63.6	7.66	87.8	84.1	3.72	6.67	0.00	6.67	40.0	35.0	5.00	38.8	29.0	9.78	6.56
Qwen2.5-14B	76.4	72.8	3.66	93.1	89.6	3.49	6.67	3.33	3.33	47.5	45.0	2.50	41.0	39.0	2.07	3.01
Qwen2.5-32B	80.5	76.8	3.72	92.2	92.7	-0.531	20.0	3.33	16.7	57.5	50.0	7.50	47.4	42.4	5.04	6.48

Figure 8: This table summarizes the performance of models in Llama and Qwen families fine-tuned with large teacher CoT and small teacher CoT when evaluated on MATH, GSM8K, AIME, AMC, and OlympiadBench. Qwen2-5-72B-Instruct is chosen as the large teacher while Qwen2-5-3B-Instruct is chosen as the small teacher. We observe that small student models may experience degraded performance when distilled from a large teacher compared to a small teacher, whereas larger student models benefit more from the distilling a large teacher.

Problem

Let  $(x, y)$  be an ordered pair of real numbers that satisfies the equation  $x^2 + y^2 = 14x + 48y$ . What is the maximum value of  $y$ ?

Model	Gemma2-9B vs Gemma2-27B						Llama3.1-8B vs Llama3.1-70B					
	MATH	AMC	Olympiad	AIME	GSM8k	Average	MATH	AMC	Olympiad	AIME	GSM8k	Average
Llama3.2-1B	-1.42	-7.50	0.00	0.00	-0.227	-1.83	-1.42	-5.00	-0.296	3.33	0.152	-0.646
Llama3.2-3B	2.08	-7.50	-0.888	0.00	1.67	-0.928	-0.14	10.0	-0.593	3.33	1.06	2.73
Llama3.1-8B	0.56	0.00	0.078	0.00	-0.516	0.0243	-2.18	7.50	2.67	0.00	-1.29	1.34
Llama3.1-70B	0.02	7.50	-0.741	10.0	0.152	3.39	2.72	17.5	5.48	6.67	0.986	6.67
Qwen2.5-0.5B	-4.56	0.00	0.741	0.00	0.592	-0.645	-1.88	0.00	0.185	0.00	-1.74	-0.688
Qwen2.5-1.5B	-1.20	2.50	-1.19	0.00	-0.986	-0.174	-1.48	5.00	-0.148	3.33	-1.14	1.11
Qwen2.5-3B	0.44	5.00	1.78	0.00	-0.758	1.29	-1.26	5.00	-0.741	-3.33	-1.29	-0.325
Qwen2.5-7B	0.22	5.00	1.04	-3.33	3.94	1.37	3.68	20.0	4.15	3.33	2.81	6.79
Qwen2.5-14B	1.32	2.50	-0.148	0.00	-0.986	0.537	2.18	0.00	0.445	3.33	-0.303	1.13
Qwen2.5-32B	0.10	2.50	1.48	3.44	1.36	1.78	2.72	-2.50	5.63	3.33	0.834	2.00

Figure 9: This table presents the performance of student models distilled from different teacher models, including Gemma-27B-Instruct vs Gemma-9B-Instruct and Llama3.1-70B-Instruct vs Llama3.1-8B-Instruct. We observe that small student models may experience degraded performance when distilled from a large teacher compared to a small teacher, whereas larger student models benefit more from the distilling a large teacher.

exhibit the largest rank shifts as the most shifted tokens. We choose Qwen2.5-3B-Instruct as the student model. We put the results of most shifted tokens after fine-tuning on long CoT data in Figure 9 and 10. The results of most shifted tokens after fine-tuning on large teacher CoT data are shown in Figure 11. Our analysis reveals that these tokens are predominantly associated with expressive and stylistic elements, such as “wait”, “But”, and “Let”.

## D Examples of Various CoT Data

This section demonstrates examples of different CoT data including long CoT, short CoT, large teacher CoT and small teacher CoT. See the following examples.

### Example of most shifted tokens after fine-tuning on long CoT data. (1/2)

So I’ve got this math problem here. It says: “Let  $(x, y)$  be an ordered pair of real numbers that satisfies the equation  $x^2 + y^2 = 14x + 48y$ . What is the maximum value of  $y$ ? Okay, let’s see how to approach this.

First, I need to understand what the equation is telling me. It’s an equation involving  $x$  and  $y$ , and it’s set equal to zero:

$$x^2 + y^2 - 14x - 48y = 0:$$

I need to find the maximum value of  $y$  for real numbers  $x$  and  $y$  that satisfy this equation.

Hmm, maybe I can rearrange this equation to make it easier to work with. Let’s see:

$$x^2 - 14x + y^2 - 48y = 0:$$

I can complete the square for both  $x$  and  $y$  terms.

For  $x$ :  $x^2 - 14x$ , to complete the square, I take half of  $-14$ , which is  $-7$ , and square it to get  $49$ . So,  $x^2 - 14x$  becomes  $(x - 7)^2 - 49$ .

For  $y$ :  $y^2 - 48y$ , half of  $-48$  is  $-24$ , squared is  $576$ . So,  $y^2 - 48y$  becomes  $(y - 24)^2 - 576$ .

Now, plugging these back into the equation:

$$(x - 7)^2 - 49 + (y - 24)^2 - 576 = 0:$$

Simplify:

$$(x - 7)^2 + (y - 24)^2 - 625 = 0;$$

$$\text{So, } (x - 7)^2 + (y - 24)^2 = 625:$$

This looks like the equation of a circle with center at  $(7, 24)$  and radius  $25$ .

Wait, but the problem is asking for the maximum value of  $y$ , and I have a circle equation. So, the maximum  $y$  would be the  $y$ -coordinate of the highest point on the circle, which is the center plus the radius.

Wait, but the center is at  $(7, 24)$ , and the radius is  $25$ , so the highest point would be at  $(7, 24 + 25) = (7, 49)$ .

But, let me double-check if this makes sense. The equation is

$$x^2 + y^2 = 14x + 48y;$$

and I’ve transformed it into

$$(x - 7)^2 + (y - 24)^2 = 625;$$

which is indeed a circle with center  $(7, 24)$  and radius  $25$ .

So, the maximum  $y$  would be  $24 + 25 = 49$ .

But, wait, the problem says “the maximum value of  $y$ ,” and I’ve found that to be  $49$ . But let me consider if there are any other constraints or if I’ve missed something.

Let me think about the original equation:

$$x^2 + y^2 = 14x + 48y;$$

17

I can rearrange it to:

$$x^2 - 14x + y^2 - 48y = 0:$$



Figure 8: The process of calculating most shifted tokens. We decode each token generated by the fine-tuned LLM in the student model before fine-tuning. Then we calculate the rank shift in the student model for each token generated by the fine-tuned model. We annotate the tokens that exhibit the largest rank shifts as the most shifted tokens. We found that these tokens are predominantly associated with expressive and stylistic elements, such as `But` and `Let`.

Problem

Let  $(x, y)$  be an ordered pair of real numbers that satisfies the equation  $x^2 + y^2 = 14x + 48y$ . What is the maximum value of  $y$ ?

Example of **most shifted tokens** after fine-tuning on long CoT data (2/2)

**Then**, completing the square:

$$(x - 7)^2 - 49 + (y - 24)^2 - 576 = 0;$$

$$(x - 7)^2 + (y - 24)^2 = 625;$$

Yes, that's a circle with center  $(7, 24)$  and radius 25.

**So**, the maximum  $y$  is indeed  $24 + 25 = 49$ .

**But**, just to be thorough, let's consider if there are any points on the circle where  $y$  is greater than 49. The center is at  $(7, 24)$ , and the radius is 25, so the highest point is at  $(7, 49)$ , and the lowest point would be at  $(7, -1)$ .

**But**, the problem is asking for the maximum value of  $y$ , and I've found that to be 49.

Therefore, the final answer is 49.

**Final Answer:**

49

Figure 10: Example of most shifted tokens after fine-tuning on long CoT data (2/2)

Example of **most shifted tokens** after fine-tuning on long CoT data. (1/2)

So I've got this math problem here. It says: "Let  $(x, y)$  be an ordered pair of real numbers that satisfies the equation  $x^2 + y^2 = 14x + 48y$ . What is the maximum value of  $y$ ? Okay, let's see how to approach this.

First, I need to understand what the equation is telling me. It's an equation involving  $x$  and  $y$ , and it's set equal to zero:

$$x^2 + y^2 - 14x - 48y = 0:$$

I need to find the maximum value of  $y$  for real numbers  $x$  and  $y$  that satisfy this equation.

Hmm, maybe I can rearrange this equation to make it easier to work with. Let's see:

$$x^2 - 14x + y^2 - 48y = 0:$$

I can complete the square for both  $x$  and  $y$  terms.

For  $x$ :  $x^2 - 14x$ , to complete the square, I take half of  $-14$ , which is  $-7$ , and square it to get  $49$ .

So,  $x^2 - 14x$  becomes  $(x - 7)^2 - 49$ .

For  $y$ :  $y^2 - 48y$ , half of  $-48$  is  $-24$ , squared is  $576$ . So,  $y^2 - 48y$  becomes  $(y - 24)^2 - 576$ .

Now, plugging these back into the equation:

$$(x - 7)^2 - 49 + (y - 24)^2 - 576 = 0:$$

Simplify:

$$(x - 7)^2 + (y - 24)^2 - 625 = 0;$$

$$\text{So, } (x - 7)^2 + (y - 24)^2 = 625:$$

This looks like the equation of a circle with center at  $(7, 24)$  and radius  $25$ .

Wait, but the problem is asking for the maximum value of  $y$ , and I have a circle equation. So, the maximum  $y$  would be the  $y$ -coordinate of the highest point on the circle, which is the center plus the radius.

Wait, but the center is at  $(7, 24)$ , and the radius is  $25$ , so the highest point would be at  $(7, 24 + 25) = (7, 49)$ .

But, let me double-check if this makes sense. The equation is

$$x^2 + y^2 = 14x + 48y;$$

and I've transformed it into

$$(x - 7)^2 + (y - 24)^2 = 625;$$

which is indeed a circle with center  $(7, 24)$  and radius  $25$ .

So, the maximum  $y$  would be  $24 + 25 = 49$ .

But, wait, the problem says "the maximum value of  $y$ ," and I've found that to be  $49$ . But let me consider if there are any other constraints or if I've missed something.

Let me think about the original equation:

$$x^2 + y^2 = 14x + 48y;$$

19

I can rearrange it to:

$$x^2 - 14x + y^2 - 48y = 0:$$

Example of **Most Shifted Tokens** after fine-tuning on large model CoT

To solve the problem, we start with the given equation:

$$x^2 + y^2 = 14x + 48y$$

First, we rearrange the equation to bring all terms to one side:

$$x^2 - 14x + y^2 - 48y = 0$$

Next, we complete the square for both  $x$  and  $y$ .

For  $x$ :

$$x^2 - 14x$$

To complete the square, we add and subtract  $\frac{14}{2}^2 = 49$ :

$$x^2 - 14x + 49 - 49$$

$$(x - 7)^2 - 49$$

For  $y$ :

$$y^2 - 48y$$

To complete the square, we add and subtract  $\frac{48}{2}^2 = 576$ :

$$y^2 - 48y + 576 - 576$$

$$(y - 24)^2 - 576$$

Now, substitute these completed squares back into the equation:

$$(x - 7)^2 - 49 + (y - 24)^2 - 576 = 0$$

$$(x - 7)^2 + (y - 24)^2 - 625 = 0$$

$$(x - 7)^2 + (y - 24)^2 = 625$$

This is the equation of a circle with center  $(7, 24)$  and radius  $25$ .

To find the maximum value of  $y$ , we need to find the highest point on the circle. The highest point on the circle is directly above the center, which is at  $y = 24 + 25 = 49$ .

Thus, the maximum value of  $y$  is:

$$y = 49$$

Final Answer: 49

11 1/2 ( ' < Y CoT ® Oi 1/2 ° " : < @ Oi 1/2 ° G : Fr

Example of **most shifted tokens** after fine-tuning on long CoT data (2/2)

Then, completing the square:

$$(x - 7)^2 - 49 + (y - 24)^2 - 576 = 0;$$

$$(x - 7)^2 + (y - 24)^2 = 625;$$

Yes, that's a circle with center  $(7; 24)$  and radius 25.

So, the maximum  $y$  is indeed  $24 + 25 = 49$ .

But, just to be thorough, let's consider if there are any points on the circle where  $y$  is greater than 49. The center is at  $(7; 24)$ , and the radius is 25, so the highest point is at  $(7; 49)$ , and the lowest point would be at  $(7; -1)$ .

But, the problem is asking for the maximum value of  $y$ , and I've found that to be 49. Therefore, the final answer is 49.

**Final Answer:**

49

Problem

What is the sum of the positive odd divisors of 60?

10: **Most shifted tokens** after fine-tuning on long CoT data (2/2). All the most shifted tokens are labeled as red.



### Example of Most Shifted Tokens after fine-tuning on large model CoT

To solve the problem, we start with the given equation:

$$x^2 + y^2 = 14x + 48y$$

First, we rearrange the equation to bring all terms to one side:

$$x^2 - 14x + y^2 - 48y = 0$$

Next, we complete the square for both  $x$  and  $y$ .

For  $x$ :

$$x^2 - 14x$$

To complete the square, we add and subtract  $\left(\frac{14}{2}\right)^2 = 49$ :

$$x^2 - 14x + 49 - 49$$

$$(x - 7)^2 - 49$$

For  $y$ :

$$y^2 - 48y$$

To complete the square, we add and subtract  $\left(\frac{48}{2}\right)^2 = 576$ :

$$y^2 - 48y + 576 - 576$$

$$(y - 24)^2 - 576$$

Now, substitute these completed squares back into the equation:

$$(x - 7)^2 - 49 + (y - 24)^2 - 576 = 0$$

$$(x - 7)^2 + (y - 24)^2 - 625 = 0$$

$$(x - 7)^2 + (y - 24)^2 = 625$$

This is the equation of a circle with center  $(7; 24)$  and radius 25.

To find the maximum value of  $y$ , we need to find the highest point on the circle. The highest point on the circle is directly above the center, which is at  $y = 24 + 25 = 49$ .

Thus, the maximum value of  $y$  is:

$$y = 49$$

Final Answer: 49

1/2 11: Example of most shifted tokens after fine-tuning on large teacher CoT. All the most shifted tokens are labeled as red.

### Long CoT Example

To find the sum of the positive odd divisors of 60, I first need to understand what the divisors of 60 are and then identify which of those are odd.

First, let's find all the positive divisors of 60. To do this, I can start by factoring 60 into its prime factors.

$$60 = 2^2 \cdot 3^1 \cdot 5^1$$

Now, to find all the positive divisors, I can take all possible products of these prime factors raised to their possible exponents. For 2, the exponents can be 0; 1; or 2; for 3, 0 or 1; and for 5, 0 or 1. Listing them out:

$$1 = 2^0 \cdot 3^0 \cdot 5^0;$$

$$2 = 2^1 \cdot 3^0 \cdot 5^0;$$

$$4 = 2^2 \cdot 3^0 \cdot 5^0;$$

$$3 = 2^0 \cdot 3^1 \cdot 5^0;$$

$$6 = 2^1 \cdot 3^1 \cdot 5^0;$$

$$12 = 2^2 \cdot 3^1 \cdot 5^0;$$

$$5 = 2^0 \cdot 3^0 \cdot 5^1;$$

$$10 = 2^1 \cdot 3^0 \cdot 5^1;$$

$$20 = 2^2 \cdot 3^0 \cdot 5^1;$$

$$15 = 2^0 \cdot 3^1 \cdot 5^1;$$

$$30 = 2^1 \cdot 3^1 \cdot 5^1;$$

$$60 = 2^2 \cdot 3^1 \cdot 5^1;$$

So, the positive divisors of 60 are:

$$1; 2; 3; 4; 5; 6; 10; 12; 15; 20; 30; 60;$$

Now, I need to identify which of these are odd. Odd numbers are not divisible by 2, so I can eliminate any divisors that are even.

The odd divisors are:

$$1; 3; 5; 15;$$

Now, I need to find the sum of these odd divisors:  $1 + 3 + 5 + 15 = 24$ . Alternatively, using the prime factorization approach: Since the odd divisors are those that do not include the factor 2, I can ignore the 2's in the prime factorization. The remaining odd part is:

$$3^1 \cdot 5^1;$$

The sum of the divisors of this odd part is:

$$(1 + 3)(1 + 5) = 4 \cdot 6 = 24;$$

This matches the previous result.

Therefore, for  $60 = 2^2 \cdot 3^1 \cdot 5^1$ , the sum of the odd divisors is:

Problem

What is the sum of the positive odd divisors of 60?

Short CoT Example

To find the sum of the positive odd divisors of 60, we first need to factorize 60 into its prime factors. The prime factorization of 60 is:

$$60 = 2^2 \cdot 3 \cdot 5$$

Since we are only interested in the odd divisors, we can ignore the factor of 2. Therefore, we only consider the factors 3 and 5. The odd divisors of 60 are the divisors of  $3 \cdot 5 = 15$ . The divisors of 15 are 1; 3; 5; and 15.

Next, we sum these divisors:

$$1 + 3 + 5 + 15 = 24$$

Therefore, the sum of the positive odd divisors of 60 is:

$$\boxed{24}$$

13/2 Short CoT example

Problem

Find the greatest  $a$  such that

$$\frac{7^p \cdot \sqrt{(2a)^2 + (1)^2} \cdot 4a^2 \cdot 1}{1 + 4a^2 + 3} = 2:$$

### Long CoT Example

To find the sum of the positive odd divisors of 60, I first need to understand what the divisors of 60 are and then identify which of those are odd.

First, let's find all the positive divisors of 60. To do this, I can start by factoring 60 into its prime factors.

$$60 = 2^2 \cdot 3^1 \cdot 5^1$$

Now, to find all the positive divisors, I can take all possible products of these prime factors raised to their possible exponents. For 2, the exponents can be 0; 1; or 2; for 3, 0 or 1; and for 5, 0 or 1. Listing them out:

$$1 = 2^0 \cdot 3^0 \cdot 5^0;$$

$$2 = 2^1 \cdot 3^0 \cdot 5^0;$$

$$4 = 2^2 \cdot 3^0 \cdot 5^0;$$

$$3 = 2^0 \cdot 3^1 \cdot 5^0;$$

$$6 = 2^1 \cdot 3^1 \cdot 5^0;$$

$$12 = 2^2 \cdot 3^1 \cdot 5^0;$$

$$5 = 2^0 \cdot 3^0 \cdot 5^1;$$

$$10 = 2^1 \cdot 3^0 \cdot 5^1;$$

$$20 = 2^2 \cdot 3^0 \cdot 5^1;$$

$$15 = 2^0 \cdot 3^1 \cdot 5^1;$$

$$30 = 2^1 \cdot 3^1 \cdot 5^1;$$

$$60 = 2^2 \cdot 3^1 \cdot 5^1;$$

So, the positive divisors of 60 are:

$$1; 2; 3; 4; 5; 6; 10; 12; 15; 20; 30; 60;$$

Now, I need to identify which of these are odd. Odd numbers are not divisible by 2, so I can eliminate any divisors that are even.

The odd divisors are:

$$1; 3; 5; 15;$$

Now, I need to find the sum of these odd divisors:  $1 + 3 + 5 + 15 = 24$ . Alternatively, using the prime factorization approach: Since the odd divisors are those that do not include the factor 2, I can ignore the 2's in the prime factorization. The remaining odd part is:

$$3^1 \cdot 5^1;$$

The sum of the divisors of this odd part is:

$$(1 + 3)(1 + 5) = 4 \cdot 6 = 24;$$

This matches the previous result.

Therefore, for  $60 = 2^2 \cdot 3^1 \cdot 5^1$ , the sum of the odd divisors is:

### Large Teacher CoT Example (1/2)

To solve the equation  $\frac{\sqrt{(2a)^2 + 12} - 4a^2 - 1}{1 + 4a^2 + 3} = 2$ , we start by simplifying the expression inside the square root in the numerator. The equation becomes:

$$\frac{\sqrt{4a^2 + 12} - 4a^2 - 1}{1 + 4a^2 + 3} = 2$$

Let's denote  $x = \sqrt{1 + 4a^2}$ . Then the equation transforms into:

$$\frac{7x - 4a^2 - 1}{x + 3} = 2$$

Next, we clear the fraction by multiplying both sides by  $x + 3$ :

$$7x - 4a^2 - 1 = 2(x + 3)$$

Expanding and simplifying the right side, we get:

$$7x - 4a^2 - 1 = 2x + 6$$

Rearranging terms to isolate  $x$  and  $a^2$ , we have:

$$7x - 2x - 4a^2 - 1 - 6 = 0 \Rightarrow 5x - 4a^2 - 7 = 0 \Rightarrow 5x = 4a^2 + 7 \Rightarrow x = \frac{4a^2 + 7}{5}$$

Recall that  $x = \sqrt{1 + 4a^2}$ . Therefore, we have:

$$\sqrt{1 + 4a^2} = \frac{4a^2 + 7}{5}$$

To eliminate the square root, we square both sides:

$$1 + 4a^2 = \left(\frac{4a^2 + 7}{5}\right)^2$$

Expanding the right side, we get:

$$1 + 4a^2 = \frac{(4a^2 + 7)^2}{25} = \frac{16a^4 + 56a^2 + 49}{25}$$

Multiplying both sides by 25 to clear the denominator, we obtain:

$$25 + 100a^2 = 16a^4 + 56a^2 + 49$$



Short CoT Example

To find the sum of the positive odd divisors of 60, we first need to factorize 60 into its prime factors. The prime factorization of 60 is:

$$60 = 2^2 \cdot 3 \cdot 5$$

Since we are only interested in the odd divisors, we can ignore the factor of 2. Therefore, we only consider the factors 3 and 5. The odd divisors of 60 are the divisors of  $3 \cdot 5 = 15$ . The divisors of 15 are 1, 3, 5, and 15.

Next, we sum these divisors:

$$1 + 3 + 5 + 15 = 24$$

Therefore, the sum of the positive odd divisors of 60 is:

24

1/2 13: Short CoT example

Problem

Find the greatest  $a$  such that

$$\frac{7 \sqrt{(2a)^2 + (1)^2} - 4a^2 - 1}{1 + 4a^2 + 3} = 2:$$

Large Teacher CoT Example (2/2)

Rearranging all terms to one side, we get a standard polynomial equation:

$$16a^4 + 56a^2 + 49 - 100a^2 - 25 = 0 \Rightarrow 16a^4 - 44a^2 + 24 = 0$$

Let  $y = a^2$ . Then the equation becomes a quadratic in  $y$ :

$$16y^2 - 44y + 24 = 0$$

We solve this quadratic equation using the quadratic formula  $y = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ , where  $a = 16$ ,  $b = -44$ , and  $c = 24$ :

$$y = \frac{44 \pm \sqrt{(-44)^2 - 4 \cdot 16 \cdot 24}}{2 \cdot 16} = \frac{44 \pm \sqrt{1936 - 1536}}{32} = \frac{44 \pm \sqrt{400}}{32} = \frac{44 \pm 20}{32}$$

This gives us two solutions for  $y$ :

$$y = \frac{64}{32} = 2 \quad \text{and} \quad y = \frac{24}{32} = \frac{3}{4}$$

Since  $y = a^2$ , we have  $a^2 = 2$  or  $a^2 = \frac{3}{4}$ . The corresponding values for  $a$  are  $a = \sqrt{2}$  and  $a = \frac{\sqrt{3}}{2}$ . The greatest value of  $a$  is  $\sqrt{2}$ .

Thus, the greatest  $a$  that satisfies the equation is:

$\sqrt{2}$

### Large Teacher CoT Example (1/2)

To solve the equation  $\sqrt{\frac{7(2a)^2+1^2}{1+4a^2+3}} = 2$ , we start by simplifying the expression inside the square root in the numerator. The equation becomes:

$$\sqrt{\frac{7(4a^2+1)}{1+4a^2+3}} = 2$$

Let's denote  $x = \sqrt{1+4a^2}$ . Then the equation transforms into:

$$\frac{7x}{x+3} = 2$$

Next, we clear the fraction by multiplying both sides by  $x+3$ :

$$7x - 4a^2 - 1 = 2(x+3)$$

Expanding and simplifying the right side, we get:

$$7x - 4a^2 - 1 = 2x + 6$$

Rearranging terms to isolate  $x$  and  $a^2$ , we have:

$$7x - 2x - 4a^2 - 1 - 6 = 0 \Rightarrow 5x - 4a^2 - 7 = 0 \Rightarrow 5x = 4a^2 + 7 \Rightarrow x = \frac{4a^2 + 7}{5}$$

Recall that  $x = \sqrt{1+4a^2}$ . Therefore, we have:

$$\sqrt{1+4a^2} = \frac{4a^2 + 7}{5}$$

To eliminate the square root, we square both sides:

$$1 + 4a^2 = \left(\frac{4a^2 + 7}{5}\right)^2$$

Expanding the right side, we get:

$$1 + 4a^2 = \frac{(4a^2 + 7)^2}{25} = \frac{16a^4 + 56a^2 + 49}{25}$$

Multiplying both sides by 25 to clear the denominator, we obtain:

$$25 + 100a^2 = 16a^4 + 56a^2 + 49$$

### Small Teacher CoT Example (1/2)

To solve the equation  $\sqrt{\frac{7(2a)^2+(1)^2}{1+4a^2+3}} = 2$ , we start by simplifying the expression inside the square root and the equation itself.

First, simplify the expression under the square root in the numerator:

$$(2a)^2 + 1^2 = 4a^2 + 1$$

So the equation becomes:

$$\sqrt{\frac{7(4a^2+1)}{4a^2+1+3}} = 2$$

Next, let  $x = \sqrt{4a^2+1}$ . Then the equation transforms into:

$$\frac{7x}{x+3} = 2$$

Since  $x = \sqrt{4a^2+1}$ , we can express  $4a^2$  in terms of  $x$ :

$$4a^2 = x^2 - 1$$

Substitute  $4a^2 = x^2 - 1$  into the equation:

$$\frac{7x}{x+3} = 2$$

Simplify the numerator:

$$7x - x^2 + 1 = 2(x+3)$$

So the equation becomes:

$$\frac{7x - x^2}{x+3} = 2$$

Multiply both sides by  $x+3$  to clear the denominator:

$$7x - x^2 = 2(x+3)$$

Expand and simplify:

$$7x - x^2 = 2x + 6$$

Rearrange all terms to one side:

$$x^2 + 7x - 2x - 6 = 0$$

$$x^2 + 5x - 6 = 0$$

Multiply through by -1 to make the leading coefficient positive:

$$x^2 - 5x + 6 = 0$$

Large Teacher CoT Example (2/2)

Rearranging all terms to one side, we get a standard polynomial equation:

$$16a^4 + 56a^2 + 49 - 100a^2 - 25 = 0 \Rightarrow 16a^4 - 44a^2 + 24 = 0$$

Let  $y = a^2$ . Then the equation becomes a quadratic in  $y$ :

$$16y^2 - 44y + 24 = 0$$

We solve this quadratic equation using the quadratic formula  $y = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ , where  $a = 16$ ,  $b = -44$ , and  $c = 24$ :

$$y = \frac{44 \pm \sqrt{(-44)^2 - 4 \cdot 16 \cdot 24}}{2 \cdot 16} = \frac{44 \pm \sqrt{1936 - 1536}}{32} = \frac{44 \pm \sqrt{400}}{32} = \frac{44 \pm 20}{32}$$

This gives us two solutions for  $y$ :

$$y = \frac{64}{32} = 2 \quad \text{and} \quad y = \frac{24}{32} = \frac{3}{4}$$

Since  $y = a^2$ , we have  $a^2 = 2$  or  $a^2 = \frac{3}{4}$ . The corresponding values for  $a$  are  $a = \sqrt{2}$  and  $a = \frac{\sqrt{3}}{2}$ . The greatest value of  $a$  is  $\sqrt{2}$ .

Thus, the greatest  $a$  that satisfies the equation is:

$$\boxed{\sqrt{2}}$$

Small Teacher CoT Example (2/2)

Factor the quadratic equation:

$$(x - 2)(x - 3) = 0$$

So, the solutions are:

$$x = 2 \quad \text{or} \quad x = 3$$

Recall that  $x = \sqrt{4a^2 + 1}$ . We need to check both solutions:

1. For  $x = 2$ :

$$\sqrt{4a^2 + 1} = 2$$

Square both sides:

$$4a^2 + 1 = 4$$

$$4a^2 = 3$$

$$a^2 = \frac{3}{4}$$

$$a = \frac{\sqrt{3}}{2}$$

2. For  $x = 3$ :

$$\sqrt{4a^2 + 1} = 3$$

Square both sides:

$$4a^2 + 1 = 9$$

$$4a^2 = 8$$

$$a^2 = 2$$

$$a = \sqrt{2}$$

The greatest value of  $a$  among the solutions is  $\sqrt{2}$ .

Thus, the final answer is:

$$\boxed{\sqrt{2}}$$

Problem

What is the greatest common divisor of 128, 144 and 480?



### Small Teacher CoT Example (1/2)

To solve the equation  $\sqrt{\frac{(2a)^2 + (1)^2}{1 + 4a^2 + 3}} = 2$ , we start by simplifying the expression inside the square root and the equation itself.

First, simplify the expression under the square root in the numerator:

$$(2a)^2 + 1^2 = 4a^2 + 1$$

So the equation becomes:

$$\sqrt{\frac{4a^2 + 1}{4a^2 + 1 + 3}} = 2$$

Next, let  $x = \sqrt{4a^2 + 1}$ . Then the equation transforms into:

$$\frac{7x}{x + 3} = 2$$

Since  $x = \sqrt{4a^2 + 1}$ , we can express  $4a^2$  in terms of  $x$ :

$$4a^2 = x^2 - 1$$

Substitute  $4a^2 = x^2 - 1$  into the equation:

$$\frac{7x}{x + 3} = 2$$

Simplify the numerator:

$$7x - x^2 + 1 = 7x - x^2$$

So the equation becomes:

$$\frac{7x - x^2}{x + 3} = 2$$

Multiply both sides by  $x + 3$  to clear the denominator:

$$7x - x^2 = 2(x + 3)$$

Expand and simplify:

$$7x - x^2 = 2x + 6$$

Rearrange all terms to one side:

$$x^2 + 7x - 2x - 6 = 0$$

$$x^2 + 5x - 6 = 0$$

Multiply through by -1 to make the leading coefficient positive:

$$x^2 - 5x + 6 = 0$$

### Large Teacher CoT Example

To find the greatest common divisor (GCD) of 128, 144, and 480, we can use the prime factorization method.

#### 1. Prime Factorization:

$$128 = 2^7;$$

$$144 = 2^4 \cdot 3^2;$$

$$480 = 2^5 \cdot 3 \cdot 5;$$

#### 2. Identify the common prime factors:

The common prime factor among 128, 144, and 480 is 2.

#### 3. Determine the lowest power of the common prime factor:

The lowest power of 2 in the factorizations is  $2^4$ .

#### 4. Calculate the GCD:

The GCD is:

$$2^4 = 16;$$

Therefore, the greatest common divisor of 128, 144, and 480 is:

$$\boxed{16}$$

### Small Teacher CoT Example (2/2)

Factor the quadratic equation:

$$(x - 2)(x - 3) = 0$$

So, the solutions are:

$$x = 2 \quad \text{or} \quad x = 3$$

Recall that  $x = \sqrt{4a^2 + 1}$ . We need to check both solutions:

1. For  $x = 2$ :

$$\sqrt{4a^2 + 1} = 2$$

Square both sides:

$$4a^2 + 1 = 4$$

$$4a^2 = 3$$

$$a^2 = \frac{3}{4}$$

$$a = \frac{\sqrt{3}}{2}$$

2. For  $x = 3$ :

$$\sqrt{4a^2 + 1} = 3$$

Square both sides:

$$4a^2 + 1 = 9$$

$$4a^2 = 8$$

$$a^2 = 2$$

$$a = \sqrt{2}$$

The greatest value of  $a$  among the solutions is  $\sqrt{2}$ .

Thus, the final answer is:

$$\boxed{\sqrt{2}}$$

### Small Teacher CoT Example

To find the greatest common divisor (GCD) of 128, 144, and 480, we start by finding the prime factorization of each number.

The prime factorization of 128 is:

$$128 \div 2 = 64$$

$$64 \div 2 = 32$$

$$32 \div 2 = 16$$

$$16 \div 2 = 8$$

$$8 \div 2 = 4$$

$$4 \div 2 = 2$$

$$2 \div 2 = 1$$

Thus,

$$128 = 2^7$$

The prime factorization of 144 is:

$$144 \div 2 = 72$$

$$72 \div 2 = 36$$

$$36 \div 2 = 18$$

$$18 \div 2 = 9$$

$$9 \div 3 = 3$$

$$3 \div 3 = 1$$

Thus,

$$144 = 2^4 \cdot 3^2$$

The prime factorization of 480 is:

$$480 \div 2 = 240$$

$$240 \div 2 = 120$$

$$120 \div 2 = 60$$

$$60 \div 2 = 30$$

$$30 \div 2 = 15$$

$$15 \div 3 = 5$$

$$5 \div 5 = 1$$

Thus,

$$480 = 2^5 \cdot 3 \cdot 5$$

Now, we identify the common prime factors. The factorizations are:

$$128 = 2^7; \quad 144 = 2^4 \cdot 3^2; \quad 480 = 2^5 \cdot 3 \cdot 5$$

The only common prime factor among all three numbers is 2.

Next, we determine the smallest power of the common prime factor. The lowest power of 2 among these factorizations is  $2^4$ .

Therefore, the GCD of 128, 144, and 480 is:

### Problem

What is the greatest common divisor of 128, 144 and 480?

Large Teacher CoT Example

To find the greatest common divisor (GCD) of 128, 144, and 480, we can use the prime factorization method.

1. Prime Factorization:

$$128 = 2^7;$$

$$144 = 2^4 \cdot 3^2;$$

$$480 = 2^5 \cdot 3 \cdot 5;$$

2. Identify the common prime factors:

The common prime factor among 128, 144, and 480 is 2.

3. Determine the lowest power of the common prime factor:

The lowest power of 2 in the factorizations is  $2^4$ .

4. Calculate the GCD:

The GCD is:

$$2^4 = 16;$$

Therefore, the greatest common divisor of 128, 144, and 480 is:

$$\boxed{16}$$

Problem

Rounded to 2 decimal places, what is  $\frac{7}{9}$ ?

Large Teacher CoT Example

To solve the problem, we need to divide 7 by 9 and then round the result to two decimal places.

$$\frac{7}{9} = 0.777 \dots$$

Rounded to two decimal places, this becomes 0.78.

Final Answer:  $\boxed{0.78}$

Small Teacher CoT Example

To solve the problem of finding the value of  $\frac{7}{9}$  rounded to 2 decimal places, we can follow these steps:

1. **Perform the division:** Calculate  $\frac{7}{9}$ .

2. **Convert to decimal:** Perform the division to get the decimal equivalent.

3. **Round to 2 decimal places:** Round the decimal to 2 decimal places.

Let's start with the division:

$$\frac{7}{9} = 0.777 \dots$$

Next, we need to round this decimal to 2 decimal places. The digit in the third decimal place is 7, which is greater than or equal to 5. Therefore, we round the second decimal place up from 7 to 8.

So,  $0.7777 \dots$  rounded to 2 decimal places is 0.78.

The final answer is:

$$\boxed{0.78}$$



Small Teacher CoT Example

To find the greatest common divisor (GCD) of 128, 144, and 480, we start by finding the prime factorization of each number.

The prime factorization of 128 is:

$$\begin{array}{l} 128 \div 2 = 64 \\ 64 \div 2 = 32 \\ 32 \div 2 = 16 \\ 16 \div 2 = 8 \\ 8 \div 2 = 4 \\ 4 \div 2 = 2 \\ 2 \div 2 = 1 \end{array}$$

Thus,

$$128 = 2^7$$

The prime factorization of 144 is:

$$\begin{array}{l} 144 \div 2 = 72 \\ 72 \div 2 = 36 \\ 36 \div 2 = 18 \\ 18 \div 2 = 9 \\ 9 \div 3 = 3 \\ 3 \div 3 = 1 \end{array}$$

Thus,

$$144 = 2^4 \cdot 3^2$$

The prime factorization of 480 is:

$$\begin{array}{l} 480 \div 2 = 240 \\ 240 \div 2 = 120 \\ 120 \div 2 = 60 \\ 60 \div 2 = 30 \\ 30 \div 2 = 15 \\ 15 \div 3 = 5 \\ 5 \div 5 = 1 \end{array}$$

Thus,

$$480 = 2^5 \cdot 3 \cdot 5$$

Now, we identify the common prime factors. The factorizations are:

$$128 = 2^7; \quad 144 = 2^4 \cdot 3^2; \quad 480 = 2^5 \cdot 3 \cdot 5$$

The only common prime factor among all three numbers is 2.

Next, we determine the smallest power of the common prime factor. The lowest power of 2 among these factorizations is  $2^4$ .

Therefore, the GCD of 128, 144, and 480 is:

Problem

Rounded to 2 decimal places, what is  $\frac{7}{9}$ ?

Large Teacher CoT Example

To solve the problem, we need to divide 7 by 9 and then round the result to two decimal places.

$$\frac{7}{9} = 0.777 \dots$$

Rounded to two decimal places, this becomes 0.78.

Final Answer: 0.78

Small Teacher CoT Example

To solve the problem of finding the value of  $\frac{7}{9}$  rounded to 2 decimal places, we can follow these steps:

1. **Perform the division:** Calculate  $\frac{7}{9}$ .
2. **Convert to decimal:** Perform the division to get the decimal equivalent.
3. **Round to 2 decimal places:** Round the decimal to 2 decimal places.

Let's start with the division:

$$\frac{7}{9} = 0.7777 \dots$$

Next, we need to round this decimal to 2 decimal places. The digit in the third decimal place is 7, which is greater than or equal to 5. Therefore, we round the second decimal place up from 7 to 8.

So,  $0.7777 \dots$  rounded to 2 decimal places is 0.78.

The final answer is:

0.78