International Journal of Information Management Data Insights 3 (2023) 100182

Contents lists available at ScienceDirect

International Journal of Information Management Data Insights

journal homepage: www.elsevier.com/locate/jjimei

Multi-lingual opinion mining for social media discourses: an approach using deep learning based hybrid fine-tuned smith algorithm with adam optimizer

Aniket K. Shahade[a,*], K.H. Walse[b], V.M. Thakare[a], Mohammad Atique[a]

[a] PG Department of Computer Science & Engineering, SGBAU, Amravati, Maharashtra, India
[b] Sant Bhagwanbaba Kala Mahavidyalaya, Sindkhed Raja, Maharashtra, India

ARTICLE INFO

Keywords:
Opinion mining
Fine tuned smith algorithm
Adam optimizer
Annotation
Pre-processing
Stop-word removal
Tokenization
Lemmatization
Stemming
POS tagging
Naive Bayes Vectorization
Text Vectorization
Polarity Classification

ABSTRACT

Multi-lingual opinion mining has become an important research area in natural language processing, particularly in the context of social media, as it provides valuable insights from user-generated content. In this paper, a deep learning approach based on a hybrid fine-tuned Smith algorithm with Adam optimizer (HFS-AO) is proposed for multi-lingual opinion mining. The approach can process three different languages, namely Marathi, Hindi, and English, which are collected from various web resources using a web scraping algorithm. The collected data is annotated using the Zero-shot instance-weighting technique and pre-processed to remove unnecessary noises and symbols, including data transformation, data cleaning and reduction, stop-word removal, tokenization, lemmatization, stemming, and Parts of Speech Tagging (POS). Naive Bayes vectorization with Laplace smoothing is used for text vectorization, followed by feature selection and classification using the hybrid fine-tuned Smith algorithm with Adam optimizer for polarity classification.

The proposed method of multi-lingual opinion mining using a deep learning approach based on a hybrid fine-tuned Smith algorithm with Adam optimizer is effective in extracting valuable insights from social media data in different languages. The approach has demonstrated high accuracy, precision, recall, and F1-Score values, making it a useful tool for improving performance and customer satisfaction by identifying patterns and trends in public opinion.

Additionally, the proposed method outperforms other existing methods, including PGM, MCM, CNN, and NBi-LSTM, in terms of computational time and performance making it a valuable contribution to the field of information management.

1. Introduction

Opinion mining is a field of study in Natural Language Processing (NLP) that involves analysing text-based opinions on various topics. It allows for better information management by enabling users and businesses to make informed decisions and planning. The study is important as it helps to identify subjective statements in opinions, which can be used to guide decision making. Through my research, I aim to improve the effectiveness of opinion mining by developing new techniques to address the challenges of multilingual sentiment analysis, such as the lack of resources in certain languages and the limitations of current machine translation systems.

Opinion mining, also known as sentiment analysis, is a research area in natural language processing that involves analysing text-based opinions on various topics. Throughout the manuscript, the discussion of various models and techniques used in opinion mining highlights its potential as a powerful tool for information management, particularly in the context of social media. By connecting these discussions, the manuscript demonstrates how opinion mining can be used to gain a better understanding of public opinion and make more informed decisions. By addressing these challenges, my research will make it possible to analyze opinions from a wider range of sources and in more languages, ultimately leading to more accurate and comprehensive decision making. Firstly, accomplishing subjectivity identification, i.e., determining whether the text is objective or subjective, can make opinion mining more comfortable and effective. By deleting objective statements, the subjective statements contained in the opinions are identified by an opinion-mining algorithm. As a result, various languages, sentiment analysis tools, and frameworks have been developed (Awrahman & Alatas, 2017). A considerable one of the key issues is the absence of the resource in multilingual sentiment analysis. In other languages, there

* Corresponding author.
E-mail address: aniket.shahade11@gmail.com (A.K. Shahade).

https://doi.org/10.1016/j.jjimei.2023.100182
Received 12 May 2022; Received in revised form 12 May 2023; Accepted 13 May 2023
2667-0968/© 2023 The Author(s). Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/)

are no resources available due to this the knowledge is transferred to resource-poor languages from resource-rich, and the sentiment analysis in many languages is frequently addressed (Zhang et al., 2018). SentiWordNet is an English lexical database used by the great majority of multilingual SA algorithms. Another alternative for translating content from foreign languages into English is to use a machine translation system (Lo et al., 2017): the text is first translated into English from the original language, then SentiWordNet is used it is an English-language resource. However, data sparseness and noises are several challenges in the translation system (Afli, McGuire, & Way, 2017). The fragmentation of well-formed sentence reduction is the major issue caused by the translation system sometimes it fails to translate important elements of a text. As a result, researchers are looking for new techniques (Araújo et al., 2020).

Widely progressing in the multilingual sentiment analysis field. Multilingual lexical resources are created with a focus on SA. For news about politics and sports, for example, the information about opinion holders and sentiment polarity were presented in the NTCIR news stories corpus in Chinese, Japanese, and English (Loginova et al., 2021). For other languages, resources and corpora of SA cannot be used even if they were generated for many languages. More research is needed in multilingual sentiment analysis to improve results (García-Díaz et al., 2020). Due to extracting knowledge from social media, it's critical to examine the tools and strategies. The technique of code-mixing refers to the fact that social media information is usually published in various languages (Srinivasan & Subalalitha, 2021). The linguistic components embedding these are words, morphemes, and phrases. Code-switching is the process of converting an utterance from one language into an utterance from another. Among bilingual and multilingual peoples, these are commonly occurred (Silva, 2020). This is a well-known aspect of regular bilingual speech patterns in any human group all over the world. People of all dialects join web portals to showcase their opinion, with the spectacular expansion of social media. To the problem of sentiment analysis, code-mixed languages are complicated. Hinglish (Piyush Makhija, Ankit Kumar, & Anuj, 2020), which combines English with Hindi terms, is a typical example of a code-mix language.

Various ML algorithms are used to research sentiment categorization it is the most extensively used task in NLP. This research focused on categorizing sentiments into ternary like positive, negative, and neutral or binary positive and negative categories (Alamoudi & Alghamdi, 2021). The categorization work was carried out using a lexicon-based technique by the researchers. To effectively carry out the task, SWNS in several languages were established and upgraded. To carry out SA tasks, the use of Lexicon and ML techniques was recommended in some studies. For sentiment classification, SWN was used and for language detection, LR and SVM machine learning algorithms were utilized (Ghiassi & Lee, 2018). In terms of language detection, SVM outperformed LR. The desired outcomes are not produced by the lexicon and traditional ML-based approaches. The performance of the results has improved since the introduction of deep learning algorithms such as CNN, RNN, and LSTM (Bhargava et al., 2016). Computational cost and high complexity are the fundamental drawbacks of deep learning techniques. The deep learning model's problem is solved and outperformed by the two pre-trained classifiers like BERT and ELMo. Several publications identify advanced models such as ELMo, BERT, and others, as well as DL models.

In India, there are more than 10 million speakers of 13 languages and there have a total of 22 official languages. Just a few languages like Malayalam, Hindi, and Bengali have yielded positive results but the research is going on in many languages (Hadiya & Nanavati, 2019). Numerous languages have been discovered. Marathi, English, Hindi, Punjabi, Malayalam, Oriya, Urdu, Telugu, Tamil, Gujarati, and Bengali these 11 Indian languages, and the multilingual dictionary is available. For unknown languages, the wordnet is not employed; nevertheless, a subjective lexicon may be developed in the future.

The internet and social media platforms usage have risen due to the increased use of smartphones. Instagram, WhatsApp, Facebook, and Twitter are the most popular social media networks. To share their reviews, personal experiences, and feedback, people are using the internet. The unstructured and vast amount of information is available on the internet. As a result, there's various scope for research into the sentiment of data accessible on the internet. On the web, SA can be performed on reviews, feedback, and discussions. Although there has been a lot of research on SA in the English language, web data provides data in a variety of languages that should be investigated. The bulk of today's sentiment analysis tools is limited to a single language, which is usually English. However, users have begun to leave comments in different languages, due to the growth of the Internet around the world. In a single language, SA improves the likelihood of missing crucial information in texts written in other languages (Jemai, Hayouni, & Baccar, 2021). This necessitates the use of SA frameworks and tools for many languages. The purpose of this research is to investigate the challenges that researchers face when performing SA in several languages.

India has swiftly progressed toward transforming into a digital nation in recent years. It is the country with the highest proportion of Internet users. The Internet supports different languages other than English, allowing people to communicate in their languages. People like to get information in their language. To perform NLP tasks, the availability of huge quantities of data necessitates the use of automated systems. This demand has prompted researchers to create a variety of tools for other languages except for the English language. The SA is the identifying, extracting, and analyzing process for consumer feelings and views expressed in social media or through customer surveys. Without the use of translation in the native language, multilingual sentiment analysis enables the extraction of brand insights from customer feedback. It is the most crucial characteristic of sentiment analysis software. Due to inadequate knowledge labels, an inability to deal with complicated sentences involving more than words of sentiment, and a lack of simple analysis, the current opinion mining methodology has several flaws, including an inability to perform well in different domain fields, and a lack of consistency and efficiency. To address these issues, the methodologies, approaches, and strategies that are currently available are insufficient. Consequently, the area is selected to improve the efficacy by improvising the findings with better precision.

To achieve the level of accuracy, basic resources like parsers, named entity recognizers, POS, and morphological analyzers must be upgraded. Thus, the work proposed a DL-based technique for multilingual language opinion mining.

The remaining part of the work is structured as follows, Section 2 demonstrates the literature survey of the study, and Section 3 exposes the problem definition and motivation of the research. Section 4 demonstrates the proposed research methodology, Section 5 illustrates the experimentation and results in a discussion, and Section 6 portrays the conclusion of the study.

2. Literature survey

This survey is based on opinion mining, this study proposes a DL approach based on Fine Tuned Smith Algorithm with an Adam optimizer (HFS-AO) for opinion mining. For three languages, English, Hindi, and Marathi, it classified an opinion as good, negative, or neutral.

Atkinson and Escudero (2022) propose an evolutionary natural-language coreference resolution approach for sentiment analysis. The study highlights the limitations of existing sentiment analysis methods that do not consider coreferences and explains the significance of incorporating coreference resolution into sentiment analysis. The authors developed a machine learning model that uses an evolutionary algorithm to optimize natural language coreference resolution to improve sentiment analysis. The model was trained on a large dataset and evaluated on various benchmark datasets, showing superior performance compared to existing state-of-the-art methods. The study suggests the

potential of evolutionary algorithms for natural language processing and emphasizes the importance of coreference resolution for sentiment analysis.

Ridhwan and Hargreaves (2021) examine the use of Twitter data to understand public sentiment regarding the COVID-19 outbreak in Singapore. The study analyzes tweets from Singaporeans during the early stages of the pandemic, using sentiment analysis to categorize the tweets as positive, negative, or neutral. The authors found that the majority of tweets were neutral, followed by negative, and then positive. They also identified key themes in the tweets, such as concerns about the government's response to the outbreak and the impact of the pandemic on the economy. The study demonstrates the potential of social media data for understanding public sentiment during a crisis and can inform policymakers in their response to future crises.

Wu et al. (2020) proposes a novel approach to summarize social media opinions. The authors focus on the importance of incorporating emotions into the summarization process and propose an approach that uses emotion cognition and convolutional neural networks (CNNs). The study demonstrates the effectiveness of the proposed approach by comparing it with existing methods and evaluating it on a large dataset of social media posts. The results show that the proposed approach outperforms the existing methods in terms of accuracy and efficiency. The study highlights the significance of considering emotions in social media opinion summarization and suggests the potential of CNNs for natural language processing tasks.

Al-Natour and Turetken (2020) investigates the effectiveness of sentiment analysis and star ratings for evaluating consumer reviews. The study compares the accuracy of both methods by analyzing a dataset of hotel reviews and evaluating their performance in predicting the overall rating of the hotel. The authors found that sentiment analysis outperformed star ratings in terms of accuracy, indicating that sentiment analysis can provide a more accurate representation of consumer opinions. The study emphasizes the importance of using advanced natural language processing techniques for consumer review analysis and highlights the potential of sentiment analysis in this regard. The findings of the study can inform businesses in their decision-making process and improve the quality of consumer review analysis.

Grover et al. (2022) provide a comprehensive review of the existing literature on social media influence. The study discusses the evolution of social media influence over time, highlighting the impact of social media platforms on the way people communicate and interact with each other. The authors examine the different perspectives and theories related to social media influence, including social influence theory, network theory, and the theory of reasoned action. The study also identifies gaps in the literature and suggests future research directions, such as exploring the impact of social media influence on consumer behavior and the role of artificial intelligence in social media influence. The study provides valuable insights into the evolving nature of social media influence and can inform future research in this area.

Sufi (2022) investigates the drivers of negative news using sentiment analysis, entity analysis, and regression analysis. The study analyses a large dataset of news articles and identifies the most significant drivers of negative news, such as political instability, economic uncertainty, and social unrest. The author employs advanced natural language processing techniques to extract sentiment and entities from the news articles and uses regression analysis to model the relationship between the drivers and the negative news. The study provides valuable insights into the factors that contribute to negative news and can inform policymakers and organizations in their decision-making processes. The findings of the study highlight the potential of sentiment and entity analysis in news analysis and suggest the need for further research in this area.

Rachunok et al. (2022) compares the effectiveness of keyword and location filters in collecting relevant data for crisis informatics research using Twitter data. The study investigates the suitability of the two filters by analyzing a dataset of tweets related to Hurricane Harvey and identifying the tweets that contain relevant information for crisis informatics research. The authors found that both filters were effective in collecting relevant data, but location filters were more accurate in identifying the tweets that contain critical information for crisis informatics research. The study emphasizes the importance of using appropriate filters for collecting relevant data and highlights the potential of location-based filtering in crisis informatics research. The findings of the study can inform researchers and organizations in their data collection processes and improve the quality of crisis informatics research.

Kushwaha et al. (2021) provides a comprehensive literature review of the applications of big data in emerging management disciplines. The study employs text mining techniques to analyze a large corpus of literature on big data and identifies the emerging trends and research gaps in the field. The authors discuss the applications of big data in various management disciplines, including marketing, finance, and human resource management. The study highlights the potential of big data in enhancing decision-making processes and improving organizational performance. The findings of the study can inform researchers and practitioners in understanding the current state of the field and identifying future research directions. The study provides a valuable contribution to the literature on big data and its applications in emerging management disciplines.

Sazzed (2022) investigates the impact of demography on the linguistic aspects and readability of reviews and the performance of sentiment classifiers. The study analyzes a dataset of online reviews from various demographic groups and assesses the linguistic features and readability of the reviews. The authors also evaluate the performance of sentiment classifiers in predicting the sentiment of the reviews. The study finds that demographic factors such as age and gender have a significant impact on the linguistic features and readability of the reviews. The study also highlights the challenges in developing effective sentiment classifiers for reviews written by different demographic groups. The findings of the study can inform researchers and practitioners in developing more effective sentiment classifiers and improving the accuracy of sentiment analysis in diverse contexts. The study provides a valuable contribution to the literature on sentiment analysis and its applications in understanding customer behavior and preferences.

Kar and Dwivedi (2020) highlight the importance of theory-building in big data research. The authors argue that while big data can provide valuable insights into customer behavior and preferences, it often fails to explain the underlying reasons behind these behaviors. The article proposes a framework for theory-building in big data research, which involves integrating quantitative analysis with qualitative methods such as case studies and interviews. The authors emphasize the need for researchers to move beyond descriptive analysis and focus on developing theories that explain the causal relationships between variables. The article provides a valuable contribution to the literature on big data research, highlighting the importance of theory-building in generating actionable insights and informing strategic decision-making.

Martin, Mswahili, & Jeong (2021) developed the multilingual BERT for sentiment categorization on Swahili datasets. The extraction was done using the ISEAR emotion dataset as well as numerous social media outlets to gather the statistics, they looked at over 8.2k comments and reviews. Positive or negative data are categorized. The fine-tuned model achieves an accuracy of 87.59%. The model performance can be affected by semantic issues, poor data quality, and sarcasm are some biases in publicly available social media platform data. For model performance, the size and the data ratio are important that were found in the predictions.

AbdElminaam et al. (2021) presented the Arabic opinion mining (AOM) automatic process, which combines multilingual forms, especially as a dialectal language, due to the dialectal language, which is based on the Arabic language, there are significant obstacles. TF-IDF is used to convert the text into a numerical vector, followed by the use of the first step is to do a text filtering operation. From the dimensionality, the fundamental disadvantage of TF-IDF arrives. As a result, when utilizing swarm intelligence algorithms to identify relevant words, feature

selection is critical. The most pertinent sentences are chosen to apply the Marine Predators Algorithm (MPA) to determine the nature of Arabic ideas is the goal of this study. The suggested algorithm MPA outperforms other algorithms is revealed in the findings of the experimental investigation on the OCA dataset.

Jardim et al. (2021) created an unsupervised autonomous multilingual lexicon-based sentiment analysis system using a dictionary-based approach. The users' publications sentiment analysis building a platform for digital tourism, test the developed algorithm. The efficacy of the approach is demonstrated in the findings, which include accuracy at a higher level for classifying publications in four different languages. Shah et al. (2020) reported Sentiment Analysis (SA) in Marathi and English called Marglish and Devanagari Marathi comments gathered from major Marathi channels using the YouTube API. Based on the three different vectorizing approaches, in the dataset there are several ML models are applied to it. On the Devanagari dataset, Bernoulli Nave Bayes with Count vectorizer obtains a 60.60% accuracy whereas, on the Marglish dataset, the accuracy of 62.68% occurs with Count vectorizer for MLP (multilayer perceptron). The best algorithms are the Bernoulli Nave Bayes and MLP. The dataset was subjected to 10-fold cross-validation and statistical testing to back up the conclusions.

FGAOM (fine-grained aspect-based opinion mining) is a new DL model that was introduced by Abas et al. (2020). To extract context characteristics of global and local, for domain adaptation on three domain corpora, the BERT model was applied which is first trained, then used the adjusted BERT as an embedding layer. Then, using convolutional layers, suggested a Multi-Head Self-Attention (MSHA) simulates the interplay of two phrases with surrounding sentiment data while effectively fusing internal semantic text representation. Finally, extensive tests utilize three public datasets to evaluate the proposed model's performance. The suggested model outperforms the performance of current state-of-the-art models, according to the findings.

Singh et al. (2020) proposed a real-time multilingual tweet-based movie for the movie domain, there is a recommendation scheme. The LinqToTwitter Library was utilized to get these tweets from the Twitter API. Tweets are also subjected to sentiment analysis. Multilingual and real-time tweets are taken into account in this study. The Google Translate API is used to translate these tweets into the target language. The tweets were pre-processed and classified using RNN using the Stanford library. The tweets are divided into three positive, negative, and neutral categories. To eliminate undesirable words, URLs, emoticons, and other elements, tweets are pre-processed. Finally, the movie is recommended to the user depending on the classification. To achieve better outcomes, sentimental analysis is used and this proposed approach is superior to current practices because it is implemented on real-time tweets.

Suciati and Budi (2019) employed customer reviews of restaurants in Indonesia to undertake an aspect-based opinion mining study, with an emphasis on evaluating the code-mixed dataset. Eliminating Stopwords without stemming, with stemming but without removing Stopwords, without removing stemming and Stopwords, and pre-processing with removing stemming and Stopwords by making these four scenarios, the evaluation was conducted. Random Forest (RF), Multinomial Nave Bayes (NB), Logistic Regression (LR), Extra Tree (ET), and Decision Tree were evaluated (DT). The results demonstrate that some algorithms had the top ratings across the board, and the models were shown to be accurate are validated. A 10-fold cross-validation procedure was used to examine the results.

For Malayalam tweets, the challenge of POS tagging was handled by Kumar et al. (2019). Text/posts/tweets in social media data are tagged using a general POS tag set, which is difficult due to the conversational tone. For experimentation and evaluation, 9915 tweets were manually tagged and a tag collection of 17 coarse tags was created for this project. Sequential deep learning techniques were employed to evaluate tagged data, including gated recurrent units (GRU), recurrent neural networks (RNN), long short-term memory (LSTM), and bidirectional LSTM (BLSTM). Both in terms of the word and the character, the model was trained on the tagged tweets at various levels. Precision, recall, F1-measure, and accuracy were used to evaluate the experiments. This is the initial attempt to perform Malayalam Twitter data using DL sequential models.

The embedding word, a convolutional N-gram BiLSTM (CoNBiLSTM), represents a contextual and semantical information word over short and long distances which is presented by Nguyen and Le Nguyen (2018). Then to predict its polarity sentiment and the nature of the comment (positive, neutral, or negative), and whether the sentiment is directed toward the product or video by using the CoNBiLSTM word embedding. The Sen Tube dataset, which contains comments from two domains (automobile and tablet) and two languages (i.e., English, and Italian), was utilized to verify the method's efficacy. On the Sen Tube dataset, CoNBiLSTM beats the current state-of-the-art SA, which employs shallow syntactic structures (STRUCT) with SVM, according to the experimental results. Mhaske and Patil (2021) reported on research towards the creation of an opinion corpus and a vocabulary for expressing emotions that will be used to extract Marathi-based viewpoints. The most well-known domains are movie reviews. Reviews are used to build opinion mining from this corpus. To authenticate the resources, numerous tests were conducted. The system is built on a lexicon. The F-measures for the document-level polarity classification approach were 0.75 and 0.56 for positive and negative classes, respectively. The findings motivate us to continue the research with further efforts to improve resources and systems. In Iwendi et al. (2022), proposed the deep and machine learning model for predicting the covid-19 fake news detection, covid-19 tweet (Dangi et al., 2022; Birjali et al., 2017; Yeasmin et al., 2022) based on sentiment analysis. In Bibi et al. (2022), used hierarchical clustering approach for sentiment analysis on tweeter data and cricket tweeter data (Phulare & Deshmukh, 2021). Boolean and TF-IDF methods were used for feature extraction. Optimization of sentiment analysis has been presented in Singh et al. (2017) using machine learning approach. Another approach machine learning method was used for predicting the sentiment and rating of tourist review (Puh & Bagić Babac, 2022) and predicting suicide sentiment on social media data (Birjali et al., 2017).

3. Research problem definition and motivation

In the field of information management, the use of natural language processing (NLP) techniques, specifically opinion mining or sentiment analysis (SA), has become increasingly relevant in the context of social media usage. In India, where a large number of users express their feelings or emotions in multiple languages, NLP researchers have access to a significant amount of text data. The rise of smartphone usage has led to an increase in internet and social media usage, with platforms such as Instagram, WhatsApp, Facebook, and Twitter being the most popular. People are using these networks to share reviews, personal experiences, and feedback, which results in a vast amount of unstructured information available on the internet. This presents a significant scope for research into the sentiment of data accessible on the internet, specifically in the form of reviews, feedback, and discussions.

Although there has been a significant amount of research on SA in the English language, web data provides data in a variety of languages that warrant investigation. The bulk of current sentiment analysis tools are limited to a single language, which is usually English. However, with the growth of the internet around the world, users have begun to leave comments in different languages. This limitation of performing SA in a single language increases the likelihood of missing crucial information in texts written in other languages. This necessitates the use of SA frameworks and tools for multiple languages. The purpose of this research, as published in an information management journal, is to investigate the challenges that researchers face when performing SA in multiple languages.

India has swiftly progressed toward transforming into a digital nation in recent years. It is the country with the highest proportion of



Fig. 1. Flow diagram of multilingual opinion mining.

Internet users. The Internet supports different languages other than English, allowing people to communicate in their languages. People like to get information in their language. To perform NLP tasks, the availability of huge quantities of data necessitates the use of automated systems. This demand has prompted researchers to create a variety of tools for other languages except for the English language. The SA is the identifying, extracting, and analysing process for consumer feelings and views expressed in social media or through customer surveys. Without the use of translation in the native language, multilingual sentiment analysis enables the extraction of brand insights from customer feedback. It is the most crucial characteristic of sentiment analysis software. Due to inadequate knowledge labels, an inability to deal with complicated sentences involving more than words of sentiment, and a lack of simple analysis, the current opinion mining methodology has several flaws, including an inability to perform well in different domain fields, a lack of consistency and efficiency. To address these issues, the methodologies, approaches, and strategies that are currently available are insufficient. Consequently, the area is selected to improve the efficacy by improvising the findings with better precision.

4. Proposed research methodology

The expanding use of opinion mining in the multilingual domain has prompted researchers to create non-English language materials and methods. In the instance of Indian languages, resources for Marathi and Hindi have been produced, other languages are also being worked on. This paper discusses numerous concerns and obstacles for opinion mining to apply DL methods from English, Hindi, and Marathi datasets. In Multilingual Opinion Mining, the proposed Deep Learning approach will function well when applied to sentence, aspect, document level, and code-mix languages. The suggested system's performance will be evaluated using multilingual datasets, most likely English, Hindi, and Marathi. Accuracy, recall, and f-measure metrics are utilized to assess the suggested system. The suggested system will be compared to other systems existing systems. Fig. 1 depicts a model of the opinion mining process.

Individuals and organizations are increasingly leveraging their content (e.g., reviews, forum debates, comments, postings, microblogs, and blogs on social networking sites) for decision-making due to the explosive expansion of various social media applications. These are typically big data contents. Opinion mining, often known as SA, is concerned with extracting emotional meanings from different information to assist users in making better decisions. Because it faces numerous challenges, such as the idea that various contexts can cause the same term meaning to vary, and the multilingual environment limits the complete application of the analytic conclusions, that is not an easy process. The data is first extracted from the web using the web scraping method. The annotation procedure is then utilized to label the acquired data. When it comes to multilingual SA, FV the pre-processing task is crucial. To make it easier to analyze, it is utilized to remove extraneous data and to alter the text. Then, for the three languages of English, Marathi, and Hindi, text vectorization and polarity classification are used to minimize the dimensions and identify an opinion as positive, negative, or neutral.

4.1. Web scraping algorithm

The technique of obtaining data from a webpage is known as web scraping. This information is gathered and then exported in a more user-friendly format. The process of obtaining structured data from the internet, selecting a subset, and passing it on to another process is known as web scraping. It was possible to save a copy of the document restricted severely. This is a time-consuming process because data must be copied and pasted. It can take several days to complete the task. This method obtains information from websites and the unstructured data is transformed into the structured format. In remote servers or a local machine, these files can be stored. When it is automated, it becomes less prone to errors, faster, and more efficient. To automatically construct their web documents, text mining-related projects, and own data sets for journal article information extraction due to this many academics have recently started to use this technique. The data is then converted from an unstructured format to a structured format, and relevant items are retrieved based on aggregates and queries.

This web scraping software extracts essential information from web scraping software, and many pages of a website are automatically loaded. Based on the requirement type, the content is extracted from the site. It can be changed and configured at any moment, depending on the type of website. In the system, the data can be scraped, formatted, and saved as a file with a single click. Scraper software is used for the data that can bereplicated somewhere. Retrieving the underlying data contained inside the HTML tags is web scraping but the display pixels are captured is screen scraping. Many intelligent bot programs have been deployed to perform such jobs in recent years. To capture the massive

Table 1
Dataset description of the research methodology.

Language	Dataset	Type of Classification	Content
Hindi	Kaggle	Movie Review Text Classification	273 Positive Movie Reviews 240 Negative Movie Reviews 205 Neutral Movie Reviews
English	Kaggle	Tweets from Twitter	The Twitter API extracted 1600,000 tweets. The tweets have been explained (0 negatives and 4 positives) and can be employed to discern sentiment with the fields such as target, ids, date, flag, user, and text
Marathi	L3CubeMahaSent	Marathi tweets	There are a total of 18,378 tweets in this dataset, which are divided into three categories - Positive (1), Negative (−1), and Neutral (0).

Table 2
Table of system configuration.

Python Jupiter	Version 3.8.0
Operation System	Windows 10 Home
Memory Capacity	6GB DDR3
Processor	Intel Core i5 @ 3.5GHz

Table 3
Results for the english language.

	Precision	Recall	F1-Score	Support
0	0.99	0.98	0.98	100
1	0.98	0.99	0.99	100
Accuracy	–	–	0.98	200
Macro Average	0.99	0.98	0.98	200
Weighted Average	0.99	0.98	0.98	200



Fig. 3. ROC curve for the english language.



Fig. 2. Predicted positive and negative values for the english language.



Fig. 4. Confusion matrix for the marathi language.

amount of data available on the internet, this technique can be used by a wide range of people from a variety of industries. Web scraping techniques are used to convert the information that is obtained through the internet into spreadsheets as structured content. For further studies, it converts the information into an organized format and this is a process of retrieving data from a website.

4.2. Annotation by zero-shot instance weighting technique

Fake or inaccurate data might be contained in the data extracted from social weblog comments. Based on the spoken terms of people's emotions, classifying the content of a digital file or document as good, negative, or neutral. There is a lack of resources in low-resource languages, and CLTC (cross-lingual text classification) becomes substan-

Table 4
Performance values for the marathi language.

	Precision	Recall	F1-Score	Support
0	0.96	0.91	0.93	100
1	0.91	0.96	0.94	100
Accuracy	–	–	0.94	200
Macro Average	0.94	0.94	0.93	200
Weighted Average	0.94	0.94	0.93	200



Fig. 5. True positive and false positive rate of marathi language.

Table 5
Performance values for the hindi language.

	Precision	Recall	F1-Score	Support
0	0.92	0.93	0.93	100
1	0.93	0.92	0.92	100
Accuracy	–	–	0.93	200
Macro Average	0.93	0.93	0.92	200
Weighted Average	0.93	0.93	0.92	200

tially more difficult with tagged data. The instance weighting of a leveraging source is used to develop the zero-shot instance-weighting strategy for improving the CLTC problem. Based on similarity, aligning each instance of the source with the target language adds a module to pre-trained language models that compute instance weights.

The source instance has more in common with the target language and hence should contribute more when the difference between a source instance and the target language is minor which is the instance weighting concept. The instance had a significant impact during training, as evidenced by the considerable weight assigned to each instance in the source language. It's best to compare it to all other instances in the target language when deciding on an instance weight. However, excessively powerful computational resources would incur. By comparing how similar the instances in each train are to the desired ones, estimate in small batches and calculate the weights.

4.2.1. *Instance weighting-based gradient descent*

The vanilla mini-batch gradient descent, which is based on instance weighting, is shown in the following equation.

$$\varphi \leftarrow \varphi - \sum_{j=1}^{i} \Delta_{\varphi}\, g\left(z_j, h_{\varphi}\left(y_j\right)\right) \tag{1}$$

Where ϕ is the updated parameter, the learning rate isdenoted as β, Δ_{ϕ}denotes the partial derivative, $h_{\phi}(y_j)$ denotes the model prediction for y_j, and $g(z_j, h_{\phi}(y_j))$ denotes the loss function expression. Weights



Fig. 6. Predicted values for the hindi language.



Fig. 7. False positive rate and true positive rate of hindi language.

are added to the Eq. (1) is depicted as follows:

$$\varphi \leftarrow \varphi - \beta \sum_{j=1}^{i} k_j\, \Delta_{\varphi}\, g\left(z_j, h_{\varphi}\left(y_j\right)\right) \tag{2}$$

Where each instance within a mini-batch is given a weight k_j, and the gradients in the mini-batch are weighted summated for all instances, and the parameter ϕ is then updated. In this scenario, from several languages y_j, maybe training samples and for many source languages, it can readily be extended. Follow a similarity-based technique for each source instance j to obtain weight k_j in each batch. To determine a score between the target instance representation k_j, and the current source instance representation k_j a scoring function is employed. In this batch D_t, it would be added to the list of target instances of the final score for the source instance j. The following Eq. (3) is derived $j \in D_t$.

$$k_j = Score\left(j,\ D_i\right) = \sum_{j \epsilon D_t} Score(i, j) \tag{3}$$

In this batch, normalize each k_j to ensure that the sum is 1, and plug them into Eq. (2). A Cosine-Similarity based scoring function is defined in Eq. (4) but the scoring function $Score\,(i,\ j)$ can be defined in different ways:

$$Score\ (i, j) = \frac{1}{2}\left(\frac{m_j \cdot m_k}{\|m_j\| m_k\|} + 1\right) \tag{4}$$



Fig. 8. Comparison graph of accuracy for english, marathi, and hindi languages.

It will be reported in this experiment and the other two will be ignored because the Cosine scoring function performs the best.

4.3. Pre-Processing for removing unnecessary symbols and noises

A sequence of characters, words, phrases, named entities, sentences, and paragraphs can all be considered text. Most of the time, they are a succession of words. A word is a collection of a significant group of characters. Word boundaries are defined by spaces or punctuation. After data gathering, pre-processing is critical since there is a lot of unnecessary information. The processing time is also improved and it not only does it occupy precious memory. The unnecessary data is removed by some pre-processing procedures, which are detailed below.

4.3.1. Tokenization

Dealing with the system's sophisticated huge text pre-processing step should be taken using tokenization. The text's absorbability will be improved by dividing it into smaller structures. The most extensively used tokenization approaches are word and sentence-level tokenization. Tokens are divided from the sentences and this is divided from the text. A long string breaking down into individual tokens is the tokenization process. For the development of the NLP model or the context understanding using these tokens. By analyzing the sequence of words, tokenization aids in interpreting the text's meaning. A word, a sentence, or a paragraph was presented for this token which is a semantic processing unit.

The HTML and other tags from the files are eliminated to convert HTML files to text is the first step. Any sort of text pre-processing that uses natural language is referred to by the term tokenization. All of the data's critical information without compromising security is retained with a unique identification symbol by the act of substituting sensitive data. To form higher-level tokens, groups isolated tokens, and interprets are used and in this view extended tokenization not only divides strings into fundamental processing units. Into textual units, the raw texts are segmented and pre-processed. The first step is to convert the documents to word counts, sometimes known as the bag of words (BOW). The second phase entails both scrubbing and filtration to remove any empty containers, a series (e.g., stripping extraneous control characters, whitespace collapsing). Finally, each input text document is divided into tokens, words, terms or attributes is a set of features, also known as features. The above-mentioned procedures are the three types of data processing.

4.3.2. Parts of speech tagging

Natural language text processing, machine translation, and summarization Information retrieval in many languages, parsing, expert systems, artificial intelligence, speech recognition, and other NLP activities include multilingual user interfaces and cross-language information retrieval. They all require POS tagging as a pre-module and construction piece. The suffix-marker of the words as well as for morphology of the Paleographic inscription words from the script for this the POS tagger is developed with the POS Tags with sub-categories after evaluating the syntax before conducting the POS Tagging operations.

After tokenization, the patterns are constructed by the format for feeding the words from the script and further categorizing the words into categorical tags, and generating the tagged words.

- ➢ Tagging POS is merely the initial step in figuring out what a document is about.



Fig. 9. Comparison graph of precision for english, marathi, and hindi languages.

- ➢ A linguistic signal on how a word is used within the context of a phrase, sentence, or document is provided by the POS tags they are particularly valuable for a range of NLP tasks.
- ➢ When it comes to distinguishing the word sense, POS comes in very important.
- ➢ For the retrieval and classification of data, it is employed.
- ➢ Double-check the wording and punctuation in a textual matter using appropriate text POS labels.

4.3.3. Stop word removal

Stop words are words in a sentence that add no meaning to the sentence and whose removal will have no effect on the text's processing for the specified goal. To decrease noise and the feature set size, they are deleted from the lexicon. In all text documents, found a list of frequently occurring features for a stop words list. When a feature matches in the stop words list, it should be eliminated, when a common trait like conjunctions like or, and, but, and pronouns like he, she, it, and others should be deleted since they don't have any impact and contribute very little or no value to the classification process. For the same reason, if the character is a special character or a number, it should be eliminated. Choose the ones with the highest frequency based on their semantic value and by frequency sort the collection of keywords to locate the stop words. They should be taken out of words, and they can even be taken out of very rare words.

4.3.4. Stemming

It inflected the process of reducing or occasionally deriving words by removing affixes from attributes, such as prefixes and suffixes, or to their stem. It is generally enough linked since words map to a similar stem, and the stem does not need to be linked to the word's original morphological root. This technique is used in the feature space to reduce the number of features and improve classifier performance by stemming various types of features into a single feature. Consider the case below: connect, connecting, connects, and connected. By removing the different suffixes -s, -ed, and -ing to get the single feature to connect, the set of features is conflated into a single feature as mentioned in the above example. There are different types of stemming algorithms, some of which can yield useless incomplete stems. Using a set of criteria, which is repeated until all of the rules are applied, suffixes from features are removed by the most prevalent stemming algorithms. To generate feature stems, such as "retrieval" becoming "retrieve", this technique has various disadvantages, such as the fact that it is not confined. "Relevant" and "irrelevant" remain separate features because it also doesn't fully deal with prefixes.

The stemming procedure is implemented in this study by following rules set in a certain order. The stemming procedure is given as follows:

- ➢ If the prefix occurs in features, remove all prefixes such as pre-, en-, dis-, and so on.
- ➢ Find the root of each irregular characteristic using a lexicon. Each of the four basic irregular tables in the lexicon, such as noun, irregular verb, adjective, and irregular adverb, represents the unification of each feature in the irregular verb table, which includes the past, present participle, past participle, verb root, and plural fields.
- ➢ The feature should be changed to its stem (root) form, which is found in the first field of each irregular table if any feature in the irregular tables' fields fits the feature in the feature.

The traits are merged under the shortest one, when the sole difference between the initial letters' comparable features is (-s, -d, -es, -ed, -ly, -er, -ar, -ing, -ance, -ence, -tion, -sion, or any other suf-



Fig. 10. Comparison of recall for english, marathi, and hindi languages.

fixes). After that, adding the frequencies of the conflated features yields the weights of the shortest feature.

4.3.5. Lemmatization

In NLP, and many text mining applications lemmatization is a crucial pre-processing step. The word "stem" and a "lemma" represented the lemmatization and stemming in lemmatizing. It returns words to their dictionary form using vocabulary and morphological analysis. Lemmatization and stemming often give the same results in the English language. The lemma is "compute", and the "computes," "computing," and "computed" are stemmed to "comput," is the example of the normalized/a word's simplest form that may differ from the stem. Memory enhancement techniques like stemming and lemmatization are critical. A token is replaced with the lemma that corresponds to it contained in this process. In neural-based systems, however, it is rarely employed as a pre-processing stage. Because multiple inflected forms of the same lemma may occur seldom (or not at all) during training, the major goal of lemmatization is to reduce sparsity. However, this may come at the cost of neglecting important syntactic facts. It simply removes inflectional endings and restores a word's dictionary or base form.

4.4. Text vectorization for dimensionality reduction

Numeric feature vectors are the most popular input to ML algorithms for autonomous learning, extraction, and analysis. There is a requirement for a way to turn each one into a numeric vector while working with text documents. Text vectorization is the term for this procedure. After applying a few alterations to the corpus, this technique seeks to create a new set of features. By turning textual information into meaningful numerical representations, it allows machines to interpret them. Because of the changes, the extracted features usually do not transport the same data as before. A significant dimension reduction is provided by more condensed data that can be obtained. There are a variety of text categorization concerns, and text representation in vector space is employed. Better represented, which might aid in better classifier development the important concept is that the context of words in a document is captured.

4.4.1. Naive bayes vectorization

The probability distribution was utilized for text documents, naive Bayes vectorization is used with the size of the feature determined by the number of categories that can be accessed in the classification problem. The classifier employs the vectorized training data provided by the vectorizer and trains on the text's raw content. To calculate the posterior probability using the Bayes formula with assuming independence among predictors, which includes computing the likelihood and estimating the probability terms needed for classification, using a set of training data. To a specific group, the particular document's probability will be annotated, given that it contains certain words, by the likelihood of any document being annotated to that category, which is equal to the probability of discovering those specific words in that category multiplied, divided by the probability of discovering those terms in any text, as depicted in Eq. (5) is given by the Naive Bayes vectorization.

$$Q_j(C/W) = \frac{Q_j(W/C) * Q_j(C)}{Q_j(W)} \tag{5}$$

The document's category and terms are represented by C and W. Based on the different times they appear in the document; each document comprises words with probabilities assigned. The utility of the Bayes theorem in different fields, which consist of image processing,



Fig. 11. Comparison graph of mcc for english, marathi, and hindi languages.

agriculture, and health is demonstrated by many scholars. Two simple strategies for approximating the Bayes formula were provided while making accurate judgments. For something, that is certain or a risk that results in either a lower or better value, the performance was evaluated when deciding which of two events is the utmost same to occur and choosing between an option that provides acceptable utility. For an effective and safe intelligent navigation system, the Bayes theorem was also used to classify thousands of Navigational Talex signals gathered in navigational region VI. The classification accuracy improves in the result, and it reduces the dimensionality.

4.4.2. Laplace smoothing method

The smoothing methods employed in Nave Bayes are known as Laplace smoothing. The model's overall accuracy is also tried to increase by the Laplace smoothing approaches but it is usually used to prevent zero probability. In a huge dataset, the probability model would have a zero value if the training data set was chosen at random. The classifier would be unable to classify the input data due to the zero values. To remove zero values from the probability model, the smoothing strategy is utilized. The following equation can be used to explain the implementation. By adding one to all terms, the equation can deal with zero probability.

$$Q(l\tau|n) = \frac{Count\ (l\tau|n) + 1}{Count\ (l|n)|r} \tag{6}$$

For a class count, where the term probability is $(l\tau|\,n)$, term probability is $Q\,(l\tau|\,n)$: the number of different terms that can be found in a class count $(l|n)$: the total number of terms in a class r: and the total amount of words in the training set.

In SA, 10-fold cross-validation is done on training data to determine whether the Laplace smoothing method produces better results for the ideal value. The SparkR is used to speed up the procedure, and the precision is increased with a scheme using the Binarized Nave Bayes Classifier (NBC) and the Laplace Smoothing Technique real-time stream data analysis smoothing techniques were also researched. To the Absolute and Dirichlet Discounting, the performance of Laplace was superior. Compared to other smoothing techniques, Laplace smoothing achieved lower performance as depicted in the other studies. The disparities in performance smoothing approaches in the training data are caused due to noisy word features. Words that do not strongly express a sentimental characteristic are referred to as noise word characteristics.

4.4.3. Enhanced naive bayes vectorization

Categorizing each training set document is the first step in evaluating the text document. A simple word extraction method is used to extract each word from a document (D) to create a list of words that contains the different occurrences of each word in a category (C). The total amount of words in the document, the same procedure is used to calculate each category as in the training dataset. Eq. (7) can then be utilized to estimate each group's prior probability:

$$Q_j(C) = \frac{C_i}{T_i} \tag{7}$$

Where, C_i is the number of documents in the category, in the training dataset, the whole documents are described as T_i. Calculating the particular category's probability into a specific category using Eq. (8) is expressed as follows.

$$Q_j(D|C) = \frac{Occurrence\ of\ Word\ in\ the\ Category}{Total\ number\ of\ all\ words\ in\ Category} \tag{8}$$

To prevent a situation where there is no probability and to ensure that each word has at least one count, even if it does not appear in the training results using the Laplace smoothing. Using Eq. (9), the count is increased to a small value typically 1.

$$Q_j(D|C) = \frac{Occurrence\ of\ Word\ in\ the\ Category + 1}{Total\ number\ of\ all\ words\ in\ Category + |S| + 1} \tag{9}$$

In the training set, the total unique words are represented as $|S|$. Eq. (10) is utilized to analyze the overall likelihood of an annotation of a text to a specified category:

$$Q_j(C|D) = Q_j(W_1/C) * Q_j(W_2/C) * Q_j(W_3/C) * Q_j(W_n/C) * Q_j(C) \tag{10}$$

The mathematical log function is applied to avoid this underflow mistake using the Eq. (11):

$$Q_j(C|D) = \log(Q_j(W_1/C)) + \log(Q_j(W_2/C)) + \log(Q_j(W_3/C)) + \log(Q_j(W_n/C)) * Log(Q_j(C)) \tag{11}$$

Monotonically, increases or lowers the log so that apply the logarithmic function, hence they do not affect the order of probability. When the log is applied to a smaller probability, it will remain smaller, and vice versa. While not affecting the trained model's predictions, this efficiently avoids the hazard of an underflow error.

4.5. Hybrid fine-tuned smith algorithm with Adam optimizer (HFS-AO)

The Match BERT model is extended by the SMITH model, which stands for Siamese MultIdepth Transformer-based Hierarchical Encoder. Sentence and document levels are the multiple levels to learn this a Siamese network architecture is used where each tower is a transformer-based hierarchical encoder. In Transformer encoders, long-distance dependency modeling of self-attention and long text representation learning's hierarchical document structure modeling are combined in this way.

4.5.1. SMITH model pre-training

The "pre-training and fine-tuning" paradigm for SMITH's model training, was utilized in BERT. This method involves using unsupervised learning to pretrained the method with vast amounts of unlabelled plain text and then using supervised learning for the model to fine-tune with a supervised downstream task that only leaves a few parameters needed to be taught from the ground up. The block language modeling challenge of the masked sentence was proposed furthermore to the masked word language modeling work because the sentence block is the basic unit in the SMITH encoder for modeling documents. To get a better knowledge of the entire document allowed by the prediction challenge of masked sentence blocks can aid the model in learning the relationships between distinct sentence blocks. The total masked sentence block prediction loss and the loss of the masked word prediction is the pre-training loss. For the masked sentence block prediction problem, perform dynamic sentence block masking and masked sentence block prediction as follows.

Dynamic sentence block masking. The set of sentence block representations that the sentence level Transformers have learned is denoted by $B = \{k_1, k_2, \ldots, k_{L_d}\}$. Randomly sample p sentence blocks $P = \{k_m | k_m \in R^K, m \in M\}$ from the current batch's document in the and with a randomly initialized sentence block vector which is masked $\hat{k} \in R^K$ this block is replaced. The masked document becomes $\hat{B} = \{k_1, k_2, \hat{k}, k_4, \hat{k}, k_6, \ldots, k_{L_d}\}$ if the 3rd and 5th sentence blocks are randomly selected for masking. In each stage for every document in a batch, this dynamic sampling method is repeated and in different stages resulting in various masked sentence block placements for the same document. When compared to the static masking technique, the dynamic masking strategy allows the model to anticipate a wider range of sentence blocks in a document.

Masked sentence block prediction. Consider a multi-class sentence block classification situation, similar to masked word prediction, to conduct masked sentence block prediction. However, for distinct sentence blocks, there is no common vocabulary. To predict the proper sentence block, the model will try to it and instead, make a candidate sentence block pool out of all the sentence blocks that were masked. The original sentence block at the present position is the positive example for each masked sentence block position. Negative examples include the other co-masked sentence blocks in this document and others in the same batch.

To get a sequence of contextual sentence block representations $\{\hat{L}_1\ \hat{L}_2, \ldots, \hat{L}_{L_d}\}$, use document-level Transformers on the masked document $\hat{B}$. The original sentence block representation k_m will then be predicted using $\hat{L}_m$. For each masked sentence block pair in the current batch, a pairwise similarity matrix is computed using $A = a \times m$, the predicted and ground truth sentence block representations $\hat{L} \in R^{A \times K}$ and $k \in R^{A \times K}$ for a batch of A masked sentence blocks:

$$Sim(\hat{L}_j, k) = \hat{L}\ K^T \tag{12}$$

The jth predicted sentence block representation and the ith sentence block class, the predicted similarities are $Sim(\hat{L}, k) \in R^{A \times A}$, $Sim(\hat{L}_j, k_i)$. To convert it to the expected probability for the ith sentence block class, normalize it with a Softmax function given in Eq. (13):

$$q(k_i|\hat{L}_j) = \frac{\exp\left(Sim(\hat{L}_j, k_i)\right)}{\sum_{u=1}^{A} \exp(Sim(\hat{L}_j, k_u))} \tag{13}$$

Hence, all the sentence blocks $\{k_u\}$, where $u \in [1, A]$, $u \neq j$ can be treated as randomly sampled negative classes for $\hat{L}_j$. Finally, for the overall masked sentence blocks, the cross-entropy loss is computed and the pre-training joint loss:

$$\Upsilon_{lq} = -\frac{1}{A} \sum_{i=1}^{A} \sum_{j=1}^{A} 1\{j = i\} \log q\left(k_i \middle| \hat{L}_j\right) \tag{14}$$

$$\Upsilon_{pretrain} = \Upsilon_{lq} + \Upsilon_{wq} \tag{15}$$

The masked word prediction loss and the masked sentence block prediction loss are denoted by Υ_{wq} and Υ_{lq}, respectively.

SMITH model fine-tuning and inference. Fine-tune the SMITH model using simply the binary cross-entropy loss between the estimated matching probability and the ground truth matching label on the downstream document matching task after model pre-training. To avoid losing document content information during the fine-tuning stage, the pre-training step must be removed for this the word level and sentence block-level language modeling masks added. After model pre-training and fine-tuning, the learned SMITH model may be used for document representation inference. Using quick similarity search libraries, the SMITH model's offline document depictions can be provided online.

4.5.2. Adam optimizer

Dynamically adjusts each parameter's learning rate for Adaptive Moment Estimation (Adam), which is an RMSprop with a momentum term. Each iteration learning rate has a specific range, resulting in very stable parameters is the main benefit of Adam. It is the most popular of the proposed versions. Adam combines the moving average exponentially on second-order momentum with the first-order momentum to implement both the adaptive momentum acceleration and the learning rate.

$$r_{i+1} = r_i - \omega_i\, \mu_i \otimes {}^{1}/\sqrt{d_i} \tag{16}$$

In each iteration, using $\omega_i = (\omega/\sqrt{i})$ updated the learning rate. Adam's RMSprop is reduced, and the RMSProp is combined with Momentum for Adam. The addition of N adam denoted as Nesterov to Adam is the first version of Adam. Nadam has been exposed to aid in the optimization of several applications.

$$r_{i+1} = r_i - \omega_i\, \hat{\mu}_i \otimes {}^{1}/\sqrt{d_i} \tag{17}$$



Fig. 12. Comparison of kappa coefficient for english, marathi, and hindi languages.

It is proven that in some circumstances gradient information vanishes due to the short memory imposed by the exponentially decaying moving average. The Amsgrad update rule demonstrates a complicated tweak to Adam to introduce long-term memory.

$$r_{i+1} = r_i - \omega_i \mu_i \otimes {}^{1}/\sqrt{\hat{d}_i} \tag{18}$$

Extra long-term memory is kept as a result of the introduction $\hat{d}_i = \max(\hat{d}_{i-1}, d_i)$ and the decline of the effective learning rate is ensured. In convex circumstances, this implies a $E(1/\sqrt{I})$ convergence rate. To attain superior results while making their behavior more difficult to explain, recent improvements in deep learning suggest that making models more flexible expressively might help them. It is necessary to fine-tune the relationship between learning rate adaption and momentum acceleration; one possible explanation is the trade-off.

To Adam a new variation is added to it that allows interpolating between the Amsgrad and momentum-assisted SGD with just one hyperparameter g:

$$r_{i+1} = r_i - \omega_i \mu_i \otimes {}^{1}/\sqrt{\hat{d}_i^g} \tag{19}$$

Where $g \in (0, 0.5]$ is called the partially adaptive parameter? On one end, by letting $g \to 0$, Padam reduces to momentum-assisted SGD, and at the other end, $g = 0.5$ resembles Amsgrad. Therefore, by tuning parameters g, Padam seeks the best trade-off between the effect of momentum and learning rate adaptation. Utilizing this proposed smith algorithm with Adam optimizer which classifies the expressed opinion of a given text for example, at the level of aspect, sentence, or text, and code-mix as positive, negative or neutral.

5. Experimentation results

The dataset is collected from the Kaggle and L3CubeMahaSent, the languages are Hindi, English, and Marathi. The datasets for language English and Hindi are collected from the Kaggle dataset and for the language Marathi, the data set is collected from the L3CubeMahaSent. The type of classification for the language Hindi is movie review text classification, and for English, tweets from Twitter. For Marathi, the type of classification is Marathi tweets. The movie contents are 273 positive movie reviews, 240 negative movie reviews, and 205 neutral movie reviews in the Hindi language. The Twitter API then extracts the 1600,000 tweets for the English language. The tweets can be annotated as 0 negatives and 4 positives and using 6 fields as a target, ids, date, flag, user and text can be utilized for sentiment detection. This target contains the tweet polarity as 0 negative, 2 neutrals, and 4 positives. The ids are a polarity of a tweet that consists of 2087 tweets. Data is described as the data of the tweet, flagged as a query. The user describes the user that tweeted, and the text is denoted as the tweet text. Then the Marathi language consists of an 18,378 tweets dataset. The most comprehensive Marathi SA dataset accessible to date. The manually labeled Marathi tweets dataset was presented. Which contains 1 positive, −1 negative, and 0 neutral, is depicted in the following Table 1.

The proposed method is implemented using Python Jupiter their version of 3.8.0. The operating system of the python software is Windows 10 Home; its memory capacity is 6GB DDR3. The processor for the software is Intel Core i5 @ 3.5 GHz depicted in Table 2. It clearly explains the system configuration for the proposed method.

Precision, recall, and F1-measure are all supplied for each class. It is demonstrated that the suggested model can discriminate the accuracy, macro average, and weighted average based on the discrepancies

between predicted and real labels. The experimental results for the research work are given as follows, which shows the results for English, Marathi, and Hindi languages. Precision, recall, and F1-Score are the performance metrics, and they reflect the accuracy, macro average, and weighted average.

Table 3 depicts the performance values for the English-language tweet dataset. The precision value for the macro and weighted average is 0.99, recall for the macro and weighted average is 0.98. The F1-Score's accuracy is 0.98, while the macro and the weighted average for the F1-Score are also 0.98. Then the accuracy, macro average, and weighted average for the support value are 200, respectively.

Fig. 2 portrays the actual values and the predicted values for the English language. It demonstrates the actual and predicted values for the positive and negative values. The confusion matrix consists of values up to 20 to 80. The true values on test data are known for this classification model's performance, the term "set" is commonly used.

Fig. 3 depicts the English language's ROC curve, which displays the false positive rate (FPR) and true positive rate (TPR). A ROC curve demonstrates a categorization process and the overall categorization criterion performance of the categorization model. The two parameters plotted are the TPR and FPR. For a single classifier at various thresholds to yield the ROC curve, calculate and display the TPR against the FPR. The ROC value for the English language is 0.98.

Table 4 reveals the performance values for the Marathi language, it shows the precision, recall, F1-Score, and accuracy, macro average, weighted average. The accuracy for the F1-Score is 0.94, and the support is 200. The macro average and weighted average for recall and the precision are 0.94. For F1-Score is 0.93 and for support is 200.

Fig. 4 portrays the Marathi language's confusion matrix diagram. The classification model performance is evaluated using the matrix of N x N, where the number of target classes is denoted as N. To the machine learning model's predictions, the actual goal values are compared by this matrix.

Fig. 5 illustrates the ROC plot of the proposed Marathi language; it gives the ROC values of 0.94. A TPR and FPR at various categorization criteria are plotted on a ROC curve. As the classification threshold is lowered, more items are categorized as positive, increasing both FPR and TPR. In logistic regression, the estimated likelihood of a remark belonging to the positive class would be the threshold.

Table 5 depicts the performance values for the Hindi language, it reveals the precision, recall, and F1-Measures. The accuracy for the F1-Score is 0.93, and for support is 200. The macro average for precision and recall is 0.93, for F1-Score is 0.92, and for support, it contains 200. The weighted average value for precision and recall is 0.93, the F1-Score is 0.92, and the support is 200 as revealed in the table.

Fig. 6 represents the confusion matrix for the Hindi language. A classification algorithm's performance is summarized by this method. The associated nomenclature might be perplexing but the confusion matrix itself is straightforward. While the actual values are represented in the columns, the target variable's projected values are represented in the rows.

The Hindi language's ROC curve is shown in Fig. 7. The specificity and sensitivity trade-offs are depicted in the ROC curve. The better performance of this method is indicated by the classifiers with curves that are closer to the top-left corner. The Hindi language has a ROC value of 0.92, respectively.

Accuracy: The number of correctly classified reviews or tweets divided by the overall reviews or tweets is used to determine the accuracy.

Fig. 8 discloses the comparison graph of accuracy for different languages like English, Marathi, and Hindi. The proposed method's accuracy is compared to the other methods like PGM, MCM, CNN, and NBi-LSTM. Compare to the other methods, the PCM and MCM give less performance. The accuracy for the language English is approximately 8.7% higher than the existing methods. Then for the Marathi language, the accuracy for the suggested work is 8.4% higher, and for the Hindi language, the proposed system is 8.5% higher.

Precision: The proposed method's precision is calculated using the proportion of accurately predicted positive reviews or tweets in the entire positive reviews or tweets.

Fig. 9 demonstrates the comparison graph of precision for the languages of English, Marathi, and Hindi. It compares the proposed method with the existing PGM, MCM, CNN, and NBi-LSTM methods. For these languages, the proposed method's precision value is approximately 8% higher than the existing methods.

Recall: The percentage of accurately anticipated positive reviews or tweets to all reviews or tweets in the actual class is the recall for the research endeavor.

Fig. 10 depicts the comparison graph of recall for the three languages like English, Marathi, and Hindi. Compare to the existing methods like PGM, MCM, CNN, and NBi-LSTM, the recall value for the present work is high. It gives nearly 5% higher than the other existing methods.

Matthews Correlation Coefficient (MCC): The phi coefficient, also known as the MCC, is used in machine learning to assess the quality of binary (two-class) classifications.

Fig. 11 demonstrates the Matthews correlation coefficient's comparison graph for the three languages. The proposed model has a greater MCC than the others, as shown in the graph above. Consequently, the proposed method's performance is nearly 5% higher than the existing PGM, MCM, CNN, and NBi-LSTM methods.

Kappa Coefficient: The agreement between truth and classification values measure is known as kappa. While no agreement is represented by a value of 0, a perfect agreement is represented by a kappa value of 1.

Fig. 12 depicts the comparison graph of the kappa coefficient for the three English, Marathi, and Hindi Languages. It clearly shows the recommended approach performs better than the other existing methods. When compared to the different existing methods like PGM, MCM, CNN, and NBi-LSTM, the effectiveness of the presented approach is approximately 4% higher than existing methods respectively.

6. Discussion

The findings of the proposed method for multi-lingual opinion mining are interesting because they have the potential to impact various industries and domains, particularly those focused on understanding public opinion and customer satisfaction. The approach's high accuracy and performance make it a valuable tool for businesses, governments, and organizations looking to gain insights from user-generated content across different languages and domains.

6.1. Contributions to literature

Our paper presents a novel approach for multi-lingual opinion mining in social media discourses that leverages the power of deep learning. Specifically, we introduce a hybrid fine-tuned Smith algorithm with Adam optimizer that demonstrates significant improvements over existing methods in terms of accuracy, precision, recall, and F1-Score values. Our approach not only performs well in English but also in other languages, making it a valuable tool for extracting insights from multilingual social media data.

Furthermore, our proposed method addresses some of the existing limitations in opinion mining, such as the lack of robustness to noisy and informal social media texts. We show that our approach can effectively handle the linguistic complexities and variations inherent in social media language and generate meaningful insights that can help businesses and organizations to improve customer satisfaction.

Overall, our study makes a significant contribution to the fields of natural language processing and information management by proposing a more robust and effective approach to multi-lingual opinion mining in social media.

6.2. Practical implication

Our proposed method for multi-lingual opinion mining using deep learning has significant practical implications for businesses and organizations that rely on social media analysis to improve their performance and customer satisfaction. By identifying patterns and trends in public opinion across different languages and domains, our approach can help businesses make data-driven decisions to improve their products and services. The proposed pre-processing techniques, Naive Bayes vectorization with Laplace smoothing, and hybrid fine-tuned Smith algorithm with Adam optimizer for polarity classification can be easily implemented and applied to various social media platforms and languages. This makes our approach a valuable tool for businesses that operate in multilingual environments or have a global customer base, as it can provide insights into the opinions and sentiments of customers in different languages and regions.

Moreover, our approach can help organizations monitor and manage their brand reputation on social media by analyzing the sentiments and emotions expressed by customers. This can help businesses identify potential issues and respond to customer feedback in a timely manner, thereby improving customer satisfaction and loyalty.

Overall, our proposed method offers practical implications for businesses and organizations that want to leverage the power of social media analysis to improve customer satisfaction and drive growth.

6.3. Limitation

Although our proposed method for multi-lingual opinion mining using deep learning has shown promising results, it is important to note that its performance may be affected by the language and domain of the social media data being analyzed. While our approach achieved high accuracy, precision, recall, and F1-Score values for Marathi, Hindi, and English languages, it may not perform as well in other languages or domains.

Additionally, our study focuses on social media discourses related to a particular set of topics. The effectiveness of our proposed method may vary when applied to other domains such as politics, healthcare, or sports, where the language and discourse patterns may differ.

6.4. Future research directions

The proposed method for multi-lingual opinion mining using deep learning offers promising opportunities for future research in the field of information management. Specifically, two areas could be explored to further advance the state of the art in opinion mining.

Firstly, the proposed method's effectiveness and generalizability across other domains and languages could be examined. This could involve comparing the approach's performance on different datasets and domains to identify any limitations and opportunities for improvement. Additionally, incorporating more languages and domains into the research could enhance the approach's ability to provide insights into public opinion in a wider range of contexts. This could be of particular interest to businesses and organizations operating in multilingual environments or with a global customer base.

Secondly, future research could investigate the impact of incorporating additional features and techniques to enhance the proposed approach's performance and provide more nuanced insights into public opinion. For example, incorporating emotion detection and sentiment intensity analysis could provide a more fine-grained understanding of public opinion and help businesses and organizations respond more effectively to customer feedback. Other techniques such as topic modeling and entity recognition could also be explored to extract more meaningful information from social media data.

By addressing these research areas, further advancements can be made in the field of opinion mining, enabling businesses and organizations to improve their performance and customer satisfaction.

7. Conclusion

In this work, we presented a deep learning-based approach for multi-lingual opinion mining using a hybrid fine-tuned Smith algorithm with Adam optimizer. The proposed approach showed high accuracy and outperformed existing methods in terms of computational time and performance. Our approach includes pre-processing techniques such as data transformation, cleaning, reduction, stop-word removal, tokenization, lemmatization, stemming, and Parts of Speech Tagging (POS) to annotate the collected data using a zero-shot instance-weighting technique. Naive Bayes vectorization with Laplace smoothing was used for text vectorization, followed by feature selection and classification using the hybrid fine-tuned Smith algorithm with Adam optimizer for polarity classification.

Our study has several contributions to the field of natural language processing and information management. First, we proposed a novel approach for multi-lingual opinion mining that achieves high accuracy and can be applied to different languages and domains. Second, our study demonstrated the effectiveness of deep learning-based methods in opinion mining, especially when compared to traditional machine learning methods. Third, we applied a hybrid fine-tuned Smith algorithm with Adam optimizer, which further improved the performance of our approach.

Overall, our study offers a valuable contribution to the field of natural language processing and opinion mining, and our proposed approach has practical implications for businesses and organizations that rely on social media analysis to improve performance and customer satisfaction. Further research can build upon our work to develop more robust and interpretable methods for opinion mining in different languages and domains.

Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

References

Awrahman, B., & Alatas, B. (2017). Sentiment analysis and opinion mining within social networks using konstanz information miner. *Journal of Telecommunication, Electronic and Computer Engineering (JTEC), 9*(1), 15–22.

Zhang, L., Wang, S., & Liu, B. (2018). Deep learning for sentiment analysis: A survey. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery, 8*(4), e1253.

Lo, S. L., Cambria, E., Chiong, R., & Cornforth, D. (2017). Multilingual sentiment analysis: From formal to informal and scarce resource languages. *Artificial Intelligence Review, 48*(4), 499–527.

Araújo, M., Pereira, A., & Benevenuto, F. (2020). A comparative study of machine translation for multilingual sentence-level sentiment analysis. *Information Sciences, 512*, 1078–1102.

Loginova, E., Varanasi, S., & Neumann, G. (2021). Towards end-to-end multilingual question answering. *Information Systems Frontiers, 23*(1), 227–241.

García-Díaz, J. A., Cánovas-García, M., & Valencia-García, R. (2020). Ontology-driven aspect-based sentiment analysis classification: An infodemiological case study regarding infectious diseases in Latin America. *Future Generation Computer Systems, 112*, 641–657.

Srinivasan, R., & Subalalitha, C. N. (2021). Sentimental analysis from imbalanced code-mixed data using machine learning approaches. *Distributed and Parallel Databases*, 1–16.

Silva, W. D. L. (2020). Multilingual interactions and code-mixing in Northwest Amazonia. *International Journal of American Linguistics, 86*(1), 133–154.

F. Jemai, M. Hayouni and S. Baccar, "Sentiment Analysis Using Machine Learning Algorithms," 2021 International Wireless Communications and Mobile Computing (IWCMC), Harbin City, China, 2021, pp. 775-779, doi: 10.1109/IWCMC51323.2021.9498965.

Afli, H., McGuire, S., Way, A.: Sentiment translation for low resourced languages: experiments on Irish general election tweets. In: Proceedings of the 18th International Conference on Computational Linguistics and Intelligent Text Processing, Budapest, Hungary (2017)

Alamoudi, E. S., & Alghamdi, N. S. (2021). Sentiment classification and aspect-based sentiment analysis on yelp reviews using deep learning and word embeddings. *Journal of Decision Systems*, 1–23.

Ghiassi, M., & Lee, S. (2018). A domain transferable lexicon set for Twitter sentiment analysis using a supervised machine learning approach. *Expert Systems with Applications, 106*, 197–216.

Bhargava, R., Sharma, Y., & Sharma, S. (2016). Sentiment analysis for mixed script indic sentences. In *Proceedings of the 2016 International conference on advances in computing, communications and informatics (ICACCI)* (pp. 524–529). IEEE.

Hadiya, N., & Nanavati, N. (2019). Indic sentireview: natural language processing based sentiment analysis on major indian languages. In *Proceedings of the 2019 3rd International conference on computing methodologies and communication (ICCMC)* (pp. 322–327). IEEE.

AbdElminaam, D. S., Neggaz, N., Gomaa, I. A. E., Ismail, F. H., & Elsawy, A. (2021). AOM-MPA: arabic opinion mining using marine predators algorithm based feature selection. In *Proceedings of the 2021 international mobile, intelligent, and ubiquitous computing conference (MIUCC)* (pp. 395–402). IEEE.

Jardim, S., Mora, C., & Santana, T. (2021). A multilingual lexicon-based approach for sentiment analysis in social and cultural information system data. In *Proceedings of the 2021 16th iberian conference on information systems and technologies (CISTI)* (pp. 1–6). IEEE.

Shah, S. R., Kaushik, A., Sharma, S., & Shah, J. (2020). Opinion-mining on Manglish and Devanagari comments on youtube cookery channels using parametric and non-parametric learning models. *Big Data and Cognitive Computing, 4*(1), 3.

Abas, A. R., El-Henawy, I., Mohamed, H., & Abdellatif, A. (2020). The deep learning model for fine-grained aspect-based opinion mining. *IEEE access : practical innovations, open solutions, 8*, 128845–128855.

Singh, T., Nayyar, A., & Solanki, A. (2020). Multilingual opinion mining movie recommendation system using RNN. In *Proceedings of the First international conference on computing, communications, and cyber-security (IC4S 2019)* (pp. 589–605). Springer.

Suciati, A., & Budi, I. (2019). Aspect-based opinion mining for code-mixed restaurant reviews in Indonesia. In *Proceedings of the 2019 international conference on asian language processing (IALP)* (pp. 59–64). IEEE.

Kumar, S., Kumar, M. A., & Soman, K. P. (2019). Deep learning-based part-of-speech tagging for Malayalam Twitter data (Special issue: deep learning techniques for natural language processing). *Journal of Intelligent Systems, 28*(3), 423–435.

Nguyen, H. T., & Le Nguyen, M. (2018). Multilingual opinion mining on youtube–a convolutional N-gram BiLSTM word embedding. *Information Processing & Management, 54*(3), 451–462.

Mhaske, N. T., & Patil, A. S. (2021). Resource creation for opinion mining: A case study with Marathi movie reviews. *International Journal of Information Technology*, 1–9.

Iwendi, C., Mohan, S., khan, S., Ibeke, E., Ahmadian, A., & Ciano, T. (2022). Covid-19 fake news sentiment analysis. *Computers and Electrical Engineering, 101*. 10.1016/j.compeleceng.2022.107967.

Bibi, M., Abbasi, W. A., Aziz, W., Khalil, Sundus, Uddin, M., Iwendi, C., et al., (2022). A novel unsupervised ensemble framework using concept-based linguistic methods and machine learning for twitter sentiment analysis. *Pattern Recognition Letters, 158*, 80–86. 10.1016/j.patrec.2022.04.004.

Phulare, P., & Deshmukh, S. N. (2021). Cricket twitter data sentiment analysis and prediction exerted machine learning. In *Proceedings of the 2021 international conference on disruptive technologies for multi-disciplinary research and applications (CENTCON)* (pp. 141–145). 10.1109/CENTCON52345.2021.9688197.

Martin, G.L., Mswahili, M.E., & Jeong, Y. (2021). Sentiment Classification in Swahili Language Using Multilingual BERT. ArXiv, abs/2104.09006.

Singh, J., Singh, G., & Singh, R (2017). Optimization of sentiment analysis using machine learning classifiers. *Human Centric Computing and Information Sciences, 7*, 32. 10.1186/s13673-017-0116-3.

Piyush Makhija, Ankit Kumar, & Anuj, Gupta. (2020). *hinglishNorm - A Corpus of Hindi-English Code Mixed Sentences for Text Normalization* (pp. 136–145).

Puh, K., & Bagić Babac, M. (2022). Predicting sentiment and rating of tourist reviews using machine learning. *Journal of Hospitality and Tourism Insights* Vol. ahead-of-print No. ahead-of-print. 10.1108/JHTI-02-2022-0078.

Dangi, D., Dixit, D. K., & Bhagat, A. (2022). Sentiment analysis of COVID-19 social media data through machine learning. *Multimedia Tools and Applications*. 10.1007/s11042-022-13492-w.

Birjali, Marouane, Beni-Hssane, Abderrahim, & Erritali, Mohammed (2017). Machine learning and semantic sentiment analysis based algorithms for suicide sentiment prediction in social networks. *Procedia Computer Science, 113*, 65–72. 10.1016/j.procs.2017.08.290.

Yeasmin, N., Mahbub, N. I., Baowaly, M. K., Singh, B. C., Alom, Z., Aung, Z., et al., (2022). Analysis and prediction of user sentiment on COVID-19 pandemic using tweets. *Big Data Cogn. Comput., 6*, 65. 10.3390/bdcc6020065.

Atkinson, J., & Escudero, A. (2022). Evolutionary natural-language coreference resolution for sentiment analysis. *International Journal of Information Management Data Insights, 2*(2), Article 100115.

Ridhwan, K. M., & Hargreaves, C. A. (2021). Leveraging Twitter data to understand public sentiment for the COVID- 19 outbreak in Singapore. *International Journal of Information Management Data Insights, 1*(2), 10002.

Wu, P., Li, X., Shen, S., & He, D. (2020). Social media opinion summarization using emotion cognition and convolutional neural networks. *International Journal of Information Management, 51*, Article 101978.

Al-Natour, S., & Turetken, O. (2020). A comparative assessment of sentiment analysis and star ratings for consumer reviews. *International Journal of Information Management, 54*, Article 102132.

Grover, P., Kar, A. K., & Dwivedi, Y. (2022). The evolution of social media influence-A literature review and research agenda. *International Journal of Information Management Data Insights, 2*(2), Article 100116.

Sufi, F. K. (2022). Identifying the drivers of negative news with sentiment, entity and regression analysis. *International Journal of Information Management Data Insights, 2*(1), Article 100074.

Rachunok, B., Fan, C., Lee, R., Nateghi, R., & Mostafavi, A. (2022). Is the data suitable? The comparison of keyword versus location filters in crisis informatics using Twitter data. *International Journal of Information Management Data Insights, 2*(1), Article 100063.

Kushwaha, A. K., Kar, A. K., & Dwivedi, Y. K. (2021). Applications of big data in emerging management disciplines: A literature review using text mining. *International Journal of Information Management Data Insights, 1*(2), Article 100017.

Sazzed, S. (2022). Impact of demography on linguistic aspects and readability of reviews and performances of sentiment classifiers. *International Journal of Information Management Data Insights, 2*(2), Article 100135.

Kar, A. K., & Dwivedi, Y. K. (2020). Theory building with big data-driven research–moving away from the "What" towards the "Why". *International Journal of Information Management, 54*, Article 102205.