



U.S. Department
of Transportation


Research and
Special Programs
Administration

400 Seventh Street, S.W.
Washington, D.C. 20590

DOT-E 10253 (EXTENSION)
FIRST REVISION April 5, 1991

In accordance with 49 CFR 107.105 of the Department of Transportation (DOT) Hazardous Materials Regulations DOT-E 10253 is hereby extended for the party(ies) listed below by changing the expiration date in paragraph 10 to August 31, 1996. This change is effective from the issue date of this extension. All other terms of the exemption remain unchanged.

This extension applies only to party(ies) listed below based on the application(s) received in accordance with 49 CFR 107.105. This extension constitutes a necessary part of this exemption and must be attached to it.


Alan I. Roberts
Associate Administrator
for Hazardous Materials Safety

SEP 15 1994

(DATE)

Dist: FHWA

EXEMPTION HOLDER

APPLICATION DATE

Drew Industrial Division (Ashland Chemical Co.)
Columbus, OH

August 8, 1994

ADVISORY

IF YOU ARE A HOLDER OF AN EXEMPTION THAT AUTHORIZES THE USE OF A PACKAGING WITH A MAXIMUM CAPACITY LESS THAN 450 L (119 GALLONS) OR A MAXIMUM NET MASS LESS THAN 400 KG (882 POUNDS), PLEASE BE ADVISED THAT YOUR EXEMPTION MAY NOT BE RENEWED BEYOND SEPTEMBER 30, 1996. IN ADDITION, NO NEW CONSTRUCTION OF PACKAGINGS WHICH FALL WITHIN THE NON-BULK CAPACITIES LISTED ABOVE ARE AUTHORIZED AFTER SEPTEMBER 30, 1994. THIS IS CONSISTENT WITH THE IMPLEMENTATION OF THE NEW PACKAGING REQUIREMENTS ADOPTED UNDER DOCKET HM-181. ANY APPLICATION SUBMITTED TO THIS OFFICE TO RENEW AN EXEMPTION BEYOND THE SEPTEMBER 30, 1996 DATE WILL BE DENIED UNLESS THE APPLICATION CONTAINS SUPPORTING INFORMATION TO JUSTIFY THE CONTINUATION OF THE EXEMPTION.



U.S. Department
of Transportation

Research and
Special Programs
Administration

400 Seventh Street, S.W.
Washington, D.C. 20590

APR 5 1991

DOT-E 10253
(FIRST REVISION)

1. Drew Industrial Division, Ashland Chemical Company, Boonton, New Jersey, is hereby granted an exemption from certain provisions of this Department's Hazardous Materials Regulations to offer the packaging described in paragraph 7 below for use in the transportation in commerce of flammable liquids or corrosive liquids described in paragraph 3 below, subject to the requirements specified herein. This exemption authorizes the use of a non-DOT specification rotationally molded, cross-linked polyethylene portable tank enclosed within a protective steel frame for the shipment of certain flammable liquids or corrosive liquids, and provides no relief from any regulation other than as specifically stated.

2. BASIS. This exemption is based on Poly Processing Company's application on behalf of Drew Industrial Division, Ashland Chemical Company dated November 9, 1989, submitted in accordance with 49 CFR 107.105 and the public proceeding thereon, and supplemental letter dated February 7, 1991.

3. HAZARDOUS MATERIALS (Descriptor and class).

a. Corrosive liquids for which a DOT-34 reusable polyethylene drum is prescribed in 49 CFR Part 173, and which have no secondary hazards and a vapor pressure of no greater than 14.7 psia at 130°F., classed as corrosive material.

b. Flammable liquids compatible with polyethylene which have no secondary hazards and have a flash point of 73°F or higher.

4. PROPER SHIPPING NAME (49 CFR 172.101). Specific chemical name or generic description, as appropriate.

5. REGULATION AFFECTED. 49 CFR Part 173, Subparts D and F, 178.19, 178.253.

6. MODES OF TRANSPORTATION AUTHORIZED. Motor vehicle.

APR 5 1991

Continuation of 1st Rev. DOT-E 10253

Page 2

7. SAFETY CONTROL MEASURES.

a. Packaging prescribed is a non-DOT specification rotationally molded polyethylene portable tank having a nominal water capacity of 300 gallons or 400 gallons, set in a foam filled polyethylene pallet and enclosed within a steel frame. Packaging is as shown on or represented by Poly Processing Company's drawing numbers PPC091589-1 dated September 15, 1989, PPC042485-3 dated April 24, 1989, and PPC100186-3 dated October 1, 1986; and Pioneer Plastics & Services drawing number 2002 (Sheets 1 through 5), on file with the Office of Hazardous Materials Exemptions and Approvals (OHMEA).

b. Each portable tank must be made from high density cross-linkable polyethylene which has been specifically identified and is acceptable to the OHMEA. In addition, each portable tank must be in compliance with the provisions of 49 CFR 178.19 except as follows:

i. 178.19-3 - Does not apply.

ii. 178.19-4 - Does not apply.

iii. 178.19-6(a) - Does not apply. Instead, each portable tank must be permanently marked by embossment or with a metal certification plate permanently affixed to the tank. The markings must be in letters and numbers at least 1/4-inch high located on the side of the tank. The markings shall be understood to certify that the portable tank complies with all requirements of this exemption and must contain at least the following information:

DOT-E 10253 portable tank.

Tank manufacturer _____

Test pressure 15 psig. _____

Serial number _____

Date of manufacture (month and year) _____

Tare weight _____ lbs.

Rated gross weight _____ lbs.

Capacity _____ U.S. Gal.

iv. 178.19-7(a)(3) - Changed to read: Each portable tank shall be tested by retaining for 5 minutes, hydrostatic pressure of at least 15 psig at equilibrium without leakage or pressure drop.

APR 5 1991

v. 178.19-7(c)(2) - Does not apply.

c. Each tank must be fitted with a pressure relief device that will limit the pressure in the tank to 15 psig and is in accordance with 49 CFR 178.253-4 except as follows:

i. 178.253-4(a)

- Frangible devices are not authorized.

ii. 178.253-4(c)(1)

- The pressure relief device must open at not less than 10 psig and not over 15 psig.

- The minimum venting capacity for pressure activated vents must be 6,000 SCFH at not more than 15 psig.

iii. 178.253-4(c)(3)

- A fusible device that will function at a temperature no greater than 250°F may be used provided the vapor pressure in the tank at 250°F does not exceed 15 psig.

d. Portable tanks must be capable of satisfactorily withstanding the drop test and hydrostatic pressure test prescribed in 49 CFR 178.19-7(a), the stacking test prescribed in 49 CFR 178.251-5(a)(2), and the vibration test prescribed in 49 CFR 178.253-5(a)(1).

e. The nominal thickness of the portable tank is 0.3125 inch for the 300-gallon container and 0.375 inch for the 400-gallon container. The minimum thickness of the portable tank, measured at any point, is 0.200 inch for the 300-gallon container and 0.250 inch for the 400-gallon container. Other details of the shipping container must be as depicted on Poly Processing Company drawing numbers PPC091589-1, PPC042485-3, and PPC100186-3, included in the petitioner's application; and Pioneer Plastics & Services drawing number 2002 (Sheets 1 through 5), on file with the OHMEA.

f. Additionally, each portable tank must possess the chemical and physical properties as reported to the OHMEA by the petitioner's letter dated September 15, 1989.

APR 5 1991

Continuation of 1st Rev. DOT-E 10253

Page 4

g. Any changes in design, resin, or process methods must be approved by the OHMEA. Prototype test results for the drop, hydrostatic, and vibration tests required in paragraph 7.d. of this exemption must accompany any request for changes in design, resin, or process method.

Additionally, prototype test results for the stacking test required in paragraph 7.d. of this exemption must accompany any request for changes in design or construction of the steel frame.

h. Reuse of any portable tank must be in accordance with the applicable requirements of 49 CFR 173.28 and 173.32(f) as modified herein. Each portable tank must be hydrostatically retested in accordance with 49 CFR 173.32(f) as applicable to DOT Specification 57 portable tanks, at a test pressure of 15 psig for 5 minutes without a drop in pressure or leakage. Any tank that fails must be rejected and may not be used again for the transportation of hazardous materials. The date of the most recent periodic retest must be marked on the tank near the tank identification markings required in paragraph 7.b.iii. of this exemption. The owner of the tank or his authorized agent must retain a written record indicating the date and results of all required tests and the name and address of the tester, until the next retest has been satisfactorily completed and recorded.

i. Portable tanks with repaired bodies are not authorized.

j. Commodities must be compatible with the polyethylene (PE) portable tank, and may not permeate the PE to an extent that a hazardous condition could be caused during transportation and handling.

k. Any fitting must be protected in accordance with 49 CFR 178.253-3.

l. The sides of each portable tank must be marked "KEEP THIS END UP" in two places, 180° apart, with an arrow pointing to the tank top.

m. Tanks must always be filled and shipped on the foam filled polyethylene pallet and enclosed within the protective steel frame, as described in the petitioner's application.


8. SPECIAL PROVISIONS.

- a. Shippers may use the packaging covered by this exemption pursuant to 49 CFR 173.22a.
- b. Each portable tank must be plainly marked on both sides near the middle, in letters at least two inches high on a contrasting background, "DOT-E 10253."
- c. A copy of this exemption, in its current status, must be maintained at each manufacturing facility at which this packaging is manufactured and must be made available to a DOT representative upon request.
- d. Each packaging manufactured in accordance with the requirements of this exemption must be marked in a manner which identifies the physical location (city and state) of the facility at which it is manufactured.

9. REPORTING REQUIREMENTS: Any incident involving loss of packaging contents or packaging failure must be reported to the Associate Administrator for Hazardous Materials Safety as soon as practicable.

10. EXPIRATION DATE. February 28, 1992.

Issued at Washington, D.C.


Alan I. Roberts

Associate Administrator
for Hazardous Materials Safety

APR 5 1991

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, U.S. Department of Transportation, Washington, D.C. 20590.
Attention: Exemptions Branch.

Dist: FHWA.