



U.S. Department
of Transportation

**Pipeline and Hazardous
Materials Safety
Administration**

May 05, 2025

1200 New Jersey Avenue, SE
Washington, DC 20590

DOT-SP 13336
(SIXTH REVISION)

EXPIRATION DATE: 2029-04-30

(FOR RENEWAL, SEE 49 CFR 107.109)

1. GRANTEE: Sharpsville Container Corporation
Sharpsville, PA
2. PURPOSE AND LIMITATIONS:
 - a. This special permit authorizes the manufacture, mark, sale and use of a non-DOT specification cylinder conforming with all regulations applicable to a DOT Specification 3E cylinder, except as specified herein, for the transportation in commerce of the hazardous materials authorized by this special permit. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce. The safety analyses did not consider the hazards and risks associated with consumer use, use as a component of a transport vehicle or other device, or other uses not associated with transportation in commerce.
 - c. In accordance with 49 CFR 107.107(a), party status may not be granted to a manufacturing special permit. These packagings may be used in accordance with 49 CFR 173.22a.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.302a(a)(1), and § 173.304a in that non-DOT specification cylinders are not authorized, except as specified herein.
5. BASIS: This special permit is based on the application of Sharpsville Container Corporation, dated March 18, 2025, submitted in accordance with § 107.109.

Tracking Number: 2025034726

6. HAZARDOUS MATERIALS (49 CFR 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
1-Chloro-1,2,2,2-tetrafluoroethane <i>or</i> Refrigerant gas R 124	2.2	UN1021	N/A
1-Chloro-2,2,2-trifluoroethane <i>or</i> Refrigerant gas R 133a	2.2	UN1983	N/A
Chlorodifluorobromomethane <i>or</i> Refrigerant gas R 12B1	2.2	UN1974	N/A
Chlorodifluoromethane <i>or</i> Refrigerant gas R 22	2.2	UN1018	N/A
Chlorotrifluoromethane <i>or</i> Refrigerant gas R 13	2.2	UN1022	N/A
1,1-Difluoroethane <i>or</i> Refrigerant gas R 152a	2.1	UN1030	N/A
1,1-Difluoroethylene <i>or</i> Refrigerant gas R 1132a	2.1	UN1959	N/A
1,2-Dichloro-1,1,2,2-Tetrafluoroethane <i>or</i> Refrigerant gas R 114	2.2	UN1958	N/A
Air, compressed	2.2	UN1002	N/A
Bromotrifluoromethane <i>or</i> Refrigerant gas R 13B1	2.2	UN1009	N/A
Chlorodifluoromethane and chloropentafluoroethane mixture <i>or</i> Refrigerant gas R 502 <i>with fixed boiling point, with approximately 49 percent chlorodifluoromethane</i>	2.2	UN1973	N/A
Chloropentafluoroethane <i>or</i> Refrigerant gas R 115	2.2	UN1020	N/A

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Dichlorodifluoromethane and difluoroethane azeotropic mixture <i>or</i> Refrigerant gas R 500 <i>with approximately 74 percent dichlorodifluoromethane</i>	2.2	UN2602	N/A
Dichlorodifluoromethane <i>or</i> Refrigerant gas R 12	2.2	UN1028	N/A
Dichlorofluoromethane <i>or</i> Refrigerant gas R 21	2.2	UN1029	N/A
Ethylene	2.1	UN1962	N/A
Hexafluoroethane <i>or</i> Refrigerant gas R 116	2.2	UN2193	N/A
Nitrogen, compressed	2.2	UN1066	N/A
Oxygen, compressed	2.2	UN1072	N/A
Refrigerant gases, n.o.s.	2.2	UN1078	N/A
Refrigerant gases, n.o.s <i>or</i> Dispersant gases, n.o.s.	2.1	NA1954	N/A
Tetrafluoromethane <i>or</i> Refrigerant gas R 14	2.2	UN1982	N/A

7. SAFETY CONTROL MEASURES:

a. PACKAGING: Prescribed packaging is a non-DOT specification steel cylinder made in conformance with drawings on file with the Office of Hazardous Materials Safety (OHMS), § 178.35 and DOT Specification 3E (§ 178.42) except as follows:

§ 178.35(f) Markings. All markings required except that “DOT-SP 13336-1800” must replace “DOT 3E1800”.

§ 178.35(g) Inspector’s report. Applicable inspection reports required are:

- (1) Inspector’s certification.

- (2) Record of chemical analysis.
- (3) Flattening test.

§ 178.42(a) Type, size, and service pressure. Seamless tubing partially closed in at either end with closure on either end by circumferentially welded end caps. Cylinder is not over 90 cubic inch water capacity. Longitudinal seams and welded tubing are prohibited. The service pressure must be 1800 psig.

§ 178.42(b) Steel.

- (1) Aluminum killed 1010 seamless tubing of uniform quality. Content percent may not exceed the following: Carbon 0.12, manganese 0.50, phosphorous 0.04, and sulfur 0.05 (ladle analysis); or
- (2) Cold drawn seamless type 4130 alloy tubing. Content percent may not exceed the following: carbon (0.25-0.35), manganese (0.40-0.90), phosphorus (0.04), sulfur (0.05), silicon (0.15-0.35), chromium (0.80-1.10), molybdenum (0.15-0.25).
- (3) Seamless stainless steel type 304 ASTM A-269. Content percent may not exceed the following: carbon (0.08), manganese (2.00), phosphorus (0.045), sulfur (0.030), silicon (1.0), chromium (18.0 – 20.0) and nickel (8.0 – 11.0).

§ 178.42(d) Manufacture. The last sentence is deleted.

§ 178.42(f) Hydrostatic test.

- (1) * * *
- (2) The cylinder referred to in paragraph (f)(1) of this section must burst at a pressure higher than 6,000 psi without fragmenting or otherwise showing lack of ductility, and one additional cylinder in the same lot of 500 must be subjected to a 3000 psi test and subsequently to a flattening test between knife edges with the circumferential joint at a right angle to the plates. The knife edges must be 60° wedge shaped rounded to 1/2 inch radius. Flattening to six times the thickness of the seam joint without cracking is required. The last sentence is deleted.
- (3) Other cylinders must be examined under hydrostatic pressure of at least 3000 psig and show no defect. The pressure must be maintained for at least 30 seconds and sufficiently longer to insure complete examination.

§ 178.42(g) Leakage test. All cylinders must be tested for leakage by internal air or gas at 1,800 psig following the hydrostatic test. Leakers must be rejected.

b. OPERATIONAL CONTROLS: Cylinders must be shipped in strong outside packagings in conformance with § 173.301(a)(9). Each cylinder must be secured against rotational movement within the outside packaging.

8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this special permit for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this special permit.

b. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modification or change is made to the package and it is offered for transportation in conformance with this special permit and the HMR.

c. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this special permit must be marked with a registration symbol designated by the Office of Hazardous Materials Safety for a specific manufacturing facility.

e. A current copy of this special permit must be maintained at each facility where the package is manufactured under this special permit. It must be made available to a DOT representative upon request.

f. Charging of cylinders with liquefied gases must conform to the requirements in § 173.304a.

g. Ethylene is forbidden for shipment by passenger-carrying aircraft.

h. Transportation of oxygen is only authorized by aircraft when in accordance with § 175.501.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel, cargo aircraft only, and passenger-carrying aircraft (See restrictions in paragraphs 8.g. and 8.h. of this special permit).

10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel or aircraft used to transport packages covered by this special permit. The shipper must furnish a current copy of this special permit to the air carrier before or at the time the shipment is tendered.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
 - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, Parts 171-180.
 - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when applicable.

Each “Hazmat employee”, as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)—“The Hazardous Materials Safety and Security Reauthorization Act of 2005” (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term “exemption” to “special permit” and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this

special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for William Schoonover
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, U.S. Department of Transportation, East Building PHH-13, 1200 New Jersey Avenue, Southeast, Washington, D.C. 20590.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at <https://www.phmsa.dot.gov/approvals-and-permits/hazmat/special-permits-search>. Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: Casey Chambers