



U.S. Department
of Transportation

Research and
Special Programs
Administration

400 Seventh Street, S.W.
Washington, D.C. 20590

DOT-E 8518 (EXTENSION)
SECOND REVISION May 19, 1987

In accordance with 49 CFR 107.105 of the Department of Transportation (DOT) Hazardous Materials Regulations DOT-E 8518 is hereby extended for the party(ies) listed below by changing the expiration date in paragraph 10 to September 30, 1994. This change is effective from the issue date of this extension. All other terms of the exemption remain unchanged.

This extension applies only to party(ies) listed below based on the application(s) received in accordance with 49 CFR 107.105. This extension constitutes a necessary part of this exemption and must be attached to it.

Alan I. Roberts
Alan I. Roberts
Associate Administrator
for Hazardous Materials Safety

JUN 16 1993

(DATE)

Dist: FHWA

EXEMPTION HOLDER

APPLICATION DATE

Hayter Trucking, Inc.
Taft, CA

January 22, 1993

Barnett Trucking, Inc.
Fillmore, CA

April 20, 1993

Speed's Oil Tool Service, Inc.
Santa Maria, CA

April 21, 1993

NOT Active

Denial 6-13-97



U.S. Department
of Transportation

Research and
Special Programs
Administration

DOT-E 8518
(SECOND REVISION)

400 Seventh Street, S.W.
Washington, D.C. 20590

MAY 19 1987

1. Crosby & Overton, Inc., Long Beach, California is hereby granted an exemption from those provisions of this Department's Hazardous Materials Regulations specified in paragraph 5 below to offer packages prescribed herein for use in the transportation of the hazardous materials described in paragraph 3 below in commerce subject to the requirements specified herein. This exemption authorizes use of a non-DOT specification cargo tank, and provides no relief from any regulation other than specifically stated. Each of the following is hereby granted the status of a party to this exemption:

Buck Does It, Inc., Pomona, CA - PTE-1.
Petrolane Lomita Gasoline Co., Long Beach, CA - PTE-2.
Ecology Control Industries, Ventura, CA - PTE-3.
Universal Engineering, Inc., Benicia, CA - PTE-4.

2. BASIS. This exemption is based on Pacific Tank and Manufacturing's applications dated October 23, 1980 and January 10, 1985, submitted in accordance with 49 CFR 107.103 and 107.105 and the public proceeding thereon and supplemental letter dated January 5, 1987, submitted by Crosby & Overton, Inc. The granting of party status is based on applications submitted in accordance with 107.111:

Buck Does It, Inc.'s application dated November 26, 1986.
Petrolane Lomita Gasoline Co.'s application dated March 4, 1987.
Ecology Control Industries application dated April 20, 1987.
Universal Engineering, Inc.'s application dated May 11, 1987.

3. HAZARDOUS MATERIALS (Descriptor and class). Liquid and semi-solid waste material, including mixtures, compatible with the packaging, containing flammable liquids or corrosives or poison B materials, or combinations thereof, classed as flammable liquid, corrosive material or poison B as appropriate.

4. PROPER SHIPPING NAME (49 CFR 172.101). Specific commodity name, or generic description, as appropriate.

5. REGULATION AFFECTED. 49 CFR 173.119(a) and (m), 173.245(a), 173.346(a), 178.340-7, 178.342-5, 178.343-5.

6. MODES OF TRANSPORTATION AUTHORIZED. Motor vehicle.

7. SAFETY CONTROL MEASURES. Packaging prescribed is a non-DOT specification cargo tank designed and constructed in full compliance with DOT Specification MC-307 or MC-312 (49 CFR 178.340, 178.342, 178.343) except as follows:

a. The cargo tank must be designed, built and certified in accordance with Section VIII of the ASME Code to a minimum design pressure as follows and must be stamped for both internal and external pressure ratings:

<u>Basic Cargo Tank Specification</u>	<u>Design Pressure (psig)</u>		<u>Minimum Test Pressure (psig)</u>
	<u>Internal (See Note 1)</u>	<u>External (See Note 2)</u>	
MC 307	25	15	37.5
MC 312	25	15	37.5

Note 1: The design pressure must be at least equal to the maximum pressure used for unloading.

Note 2: Vacuum tanks must have an external design pressure of at least 15 psi.

b. Circumferential reinforcement must comply with 49 CFR 178.340-7 except the maximum unreinforced portion of the shell may exceed 60-inches provided thickness and tensile strength of the shell material in combination with the frame and circumferential reinforcement produces structural integrity at least equal to that prescribed in 49 CFR 178.340-4(b).

c. In place of internal valves prescribed in 49 CFR 178.342-5(a) and 178.343-5(b), each tank may be equipped with one 6-inch maximum diameter bottom outlet with gate, plug or butterfly valve and one optional 4-inch maximum diameter bottom inlet with gate, plug or butterfly valve located near the rear of tank in accordance with Drawing PT1001 dated October 1980 on file with the Office of Hazardous Materials Transportation (OHMT). Each bottom outlet and each bottom inlet must be equipped with an additional shut-off valve, or a blank flange or a sealing cap.

d. The metal identification plate and the manufacturer's certificate must not be marked to indicate compliance with DOT MC-307 or MC-312 specifications but instead must bear reference to DOT-E 8518.

e. Tanks that are to be used in transporting flammable waste materials must be equipped with a spring loaded relief valve.

8. SPECIAL PROVISIONS.

a. A copy of this exemption must be carried aboard each motor vehicle used to transport packages covered by this exemption.

b. Each cargo tank must be reinspected and retested once every two years in accordance with 49 CFR 177.824 as prescribed for DOT Specification MC-307 or MC 312 cargo tanks, as appropriate, at one and one-half times the design pressure.

c. Each cargo tank must be plainly marked on the right side near the front, in letters at least two inches high on a contrasting background, "DOT-E 8518."

d. The Manufacturer's Data Report for the first cargo tank fabricated must be submitted to the OHMT prior to initial shipment.

9. REPORTING REQUIREMENTS. Any incident involving loss of contents of the package or cargo tank rollover must be reported to the OHMT as soon as practicable.

10. EXPIRATION DATE. March 15, 1989.

Issued at Washington, D.C.:

sn/ *Suzanne Hedgepeth*
Alan I. Roberts
Director

Office of Hazardous Materials Transportation

MAY 19 1987

(DATE)

Address all inquiries to: Director, Office of Hazardous Materials Transportation,
Research and Special Programs Administration, U.S. Department of Transportation,
Washington, D.C. 20590. Attention: Exemptions Branch.

Dist: FHWA.