



U.S. Department
of Transportation

Research and
Special Programs
Administration

JUL 3- 1997

400 Seventh Street, S.W.
Washington, D.C. 20590

DOT-E 10468
(SIXTH REVISION)

EXPIRATION DATE: September 30, 1998

(FOR RENEWAL, SEE 49 CFR 107.109)

1. **GRANTEE:** Clawson Tank Company
Clarkson, Michigan
2. **PURPOSE AND LIMITATIONS:**

This exemption authorizes the continued use of a reusable, non-DOT specification rotationally molded, linear low density, high density, or linear medium density polyethylene, portable tank (intermediate bulk container), manufactured prior to October 1, 1996, enclosed within a protective wire frame for the transportation in commerce of the Class 3, 8, and Division 5.1 materials identified in paragraph 6 below. This exemption provides no relief from any regulation other than as specifically stated herein.
3. **REGULATORY SYSTEM AFFECTED:** 49 CFR Parts 106, 107 and 171-180.
4. **REGULATIONS FROM WHICH EXEMPTED:** 49 CFR Part 173 Subpart F, 178 Subparts N and O in that non-DOT specification packagings are authorized.
5. **BASIS:** This exemption is based on the application of Clawson Tank Company dated June 17, 1996 submitted in accordance with 49 CFR 107.105 and supplemental information dated September 5, 1996 and May 20, 1997.

NO RENEWAL

NOT ACTIVE

JUL 3 - 1997

Continuation of DOT-E 10468 (6th Rev)

Page 2

6. HAZARDOUS MATERIALS (49 CFR 172.101):

Hazardous materials description -- proper shipping name	Hazard Class/ Division	Identi- fication Number	Packing Group
Class 8 liquid for which UN 1H1 plastic drums are authorized in 49 CFR 173, and which have no secondary hazards and a vapor pressure not greater than 14.7 psia at 130° F.	8	Various	II & III
Hydrogen peroxide, aqueous solutions	5.1	UN2014 or UN2984	II & III
Isopropanol	3	UN1219	II & III
Ethanol	3	UN1170	II & III
Methanol	3	UN1230	II & III
Class 3 materials compatible with polyethylene which have no secondary hazards and a flash point greater than 73°F.			

and other hazardous materials which have been specifically identified to, and acknowledged in writing by, the Office of Hazardous Materials Exemptions and Approvals (OHMEA) prior to the first shipment.

7. SAFETY CONTROL MEASURES.

a. Packagings prescribed are non-DOT/UN standard rotationally molded polyethylene intermediate bulk containers of up to 550-gallon capacity, enclosed within a protective wire frame, as shown on or represented by Clawson Tank drawings No. 27090-1 and 27090-2 dated 6/20/90, 049590-1 dated 11/25/91, 04950-2 dated 11/25/91, 051890 dated 11/25/91 and 058390 dated 11/25/91. Each tank must be made of linear low density polyethylene, high density polyethylene or linear medium density polyethylene which has been specifically identified to and is acceptable to the OHMEA. No new construction authorized.

JUL 3 - 1997

- i. Each portable tank must be permanently marked by embossment or with a metal certificate plate is marked by embossment on the polyethylene unit, the serial number and date of manufacture may be etched or stamped into the polyethylene. Where stamping or etching is performed, the marked area thickness may not be reduced below the minimum reduced thickness prescribed herein. The markings must be in letters and number at least 1/4-inch high located on the side of the tank. The markings shall be understood to certify that the portable tank complies with all requirements of this exemption and must contain at least the following information:

DOT-E 10468 portable tank

Tank manufacturer _____

Test pressure 15 psig.

Serial number _____

Date of manufacture (month and year) _____

Tare weight _____ lbs.

Rated gross weight _____ lbs.

Capacity _____ U.S. gallons

- ii. The minimum polyethylene thickness at any point for these tanks must be 0.250 inches.

b. TESTING - Reuse of any packaging under this exemption must be in accordance with the applicable requirements of 49 CFR 173.28 and 173.32(e) as modified herein. Each packaging must be hydrostatically retested in accordance with 49 CFR 173.32(e) as applicable to DOT Specification 57 tanks, at a test pressure of 15 psig for 5 minutes without a drop in pressure or leakage. Any tank that fails must be rejected and may not be used again for the transportation of hazardous materials. The date of the most recent periodic retest must be marked on the tank near the tank identification markings required in paragraph 7.a. of this exemption. The owner of the tank or his authorized agent must retain a written record indicating the date and results of all required tests and the name and address of the tester, until the next retest has been satisfactorily completed and recorded.

JUL 3 - 1997

c. OPERATIONAL CONTROLS -

- i. Portable tanks with repaired bodies are not authorized.
- ii. Commodities must be compatible with the polyethylene portable tank, and may not permeate the polyethylene to an extent that a hazardous condition could be caused during transportation and handling.
- iii. Portable tanks for hydrogen peroxide must have a vented closure to prevent accumulation of internal pressure.
- iv. Portable tanks must always be filled and shipped while enclosed within the protective wire frame as shown in the petitioner's application.

8. SPECIAL PROVISIONS:

- a. Offerors for transportation of the hazardous materials specified in this exemption may use the packaging described in this exemption for the transportation of such hazardous materials provided no modifications or changes are made to the packages, all terms of this exemption are complied with, and a copy of the current exemption is maintained at each facility from which such offering occurs.
- b. Each packaging manufactured under the authority of this exemption must be either (1) marked with the name of the manufacturer and location (city and state) of the facility at which it is manufactured or (2) marked with a registration symbol designated by OHMEA for a specific manufacturing facility.
- c. A copy of this exemption, in its current status, must be maintained at each manufacturing facility at which this packaging is manufactured and must be made available to a DOT representative upon request.
- d. Shippers using the packaging covered by this exemption must comply with all provisions of this exemption, and all other applicable requirements contained in 49 CFR Parts 171-180.

JUL 3 - 1997

Continuation of DOT-E 10468 (6th Rev)

Page 5

e. MARKING - Each packaging must be plainly marked on both sides near the middle, in letters at least two inches high on a contrasting background, "DOT-E 10468". Additionally, the sides of each portable tank must be marked "KEEP THIS END UP" in two places, 180° apart, with an arrow pointing to the tank top.

f. Each packaging manufactured under the authority of this exemption must be either (1) marked with the name of the manufacturer and location (city and state) of the facility at which it is manufactured or (2) marked with a registration symbol designated by OHMEA for a specific manufacturing facility.

g. Consistent with the regulations adopted under Docket HM-181E for intermediate bulk containers (IBCs), exemptions for IBCs of the type covered by those regulations will not allow new construction after September 30, 1996. Existing IBCs may be continued in service, provided renewal provisions under Section 107.109 are met, until September 30, 1998 under the conditions specified in the exemption that applies for their use. After September 30, 1998, each IBC must conform to, and be certified as meeting, a UN IBC standard set forth in Subparts N and O of Part 178 of the Hazardous Materials Regulations (HMR; 49 CFR).

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel.

10. MODAL REQUIREMENTS:

a. A copy of this exemption must be carried aboard each cargo vessel, or motor vehicle used to transport packages covered by this exemption.

b. Shipments by rail must be in compliance with the requirements of 49 CFR 174.63 and may not be transported on flatcars or on flat trailers, except under conditions approved by the Federal Railroad Administration.

11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. Section 5101 et seq:


o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 171-180.

- o Registration required by 49 CFR 107.601 et seq., when applicable.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. **REPORTING REQUIREMENTS:** The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (49 CFR 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must also inform the AAHMS, in writing, as soon as practicable of any incidents involving the package and shipments made under this exemption.

Issued at Washington, D.C.


Alan I. Roberts
Associate Administrator
for Hazardous Materials Safety

JUL 3 - 1997

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.
Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Dist: FHWA, FRA, USCG
PO: JSH