



U.S. Department
of Transportation

Research and
Special Programs
Administration

JUN 17 1996

400 Seventh Street, S.W.
Washington, D.C. 20590

DOT-E 10740

EXPIRATION DATE: April 30, 1998

(FOR RENEWAL, SEE 49 CFR SECTION 107.105.)

1. **GRANTEE:** CSX Transportation/Bulk Intermodal Distribution Services
Philadelphia, Pennsylvania
2. **PURPOSE AND LIMITATION:** This exemption authorizes tank cars, containing hazardous materials identified in paragraph 6, to remain standing with unloading connections attached when no product is being transferred, provided that a minimal level of monitoring, as specified in this exemption is maintained, and provides no relief from any regulations other than as specifically stated.
3. **REGULATORY SYSTEM AFFECTED:** 49 CFR Parts 106, 107 AND 171-180.
4. **REGULATIONS FROM WHICH EXEMPTED:** 49 CFR 174.67 (i) and (j); 172.302(c) and Appendix B to Subpart B of Part 107.
5. **BASIS.** This exemption is based on CSX Transportation/Bulk Intermodal Distribution Service's application of December 11, 1991, submitted in accordance with 49 CFR 107.103, and the public proceeding thereon.
6. **HAZARDOUS MATERIALS (49 CFR 172.101):**

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/Division	Identification number	Packing Group
Isopropanol or isopropyl alcohol	3	UN 1219	II

Hazardous Materials Description (Cont.)			
Proper Shipping Name	Hazard Class/Division	Identification number	Packing Group
Hydrogen Peroxide, aqueous solutions <i>with more than 40 percent but not more than 60 percent hydrogen peroxide (stabilized as necessary)</i>	5.1	UN 2014	II
Hydrogen Peroxide, aqueous solutions <i>with more than 20 percent but not more than 40 percent hydrogen peroxide (stabilized as necessary)</i>	5.1	UN 2014	II
Fluorosilicic Acid	8	UN 1777	I
Ferric Chloride solution	8	UN 2582	III
Butyl acrylate	3	UN 2348	III
Aluminum chloride solution	8	UN 2581	III
Corrosive Liquid, n.o.s. (ferric sulfate)	8	UN 1760	II

7. PACKAGING(S) and SAFETY CONTROL MEASURES:

- a. Packagings prescribed are DOT specification tank cars authorized for the material specified meeting all DOT specification requirements.
- b. Any manually operated switch, under the proprietary control of the exemption holder, providing access to the track on which the equipment is located must be lined against movement to that track and locked with an effective locking device operable only by a representative of the facility.

c. The facility operator shall install a bi-directional derail in an effective location (at least 50 feet when possible) from the end of the equipment to be protected by the caution sign. The person performing the unloading operation shall lock the device in the derailing position with an effective locking device operable only by a representative of the facility.

d. When a signalling system is used (including a monitoring system or a sensing device), the system must be capable of alerting the designated employee in the event of an emergency and providing immediate notification of any monitoring system malfunction. If the monitoring system does not have self-monitoring capability, the designated employee shall check the monitoring system hourly for proper operation. (For recommendations on the selection, installation and maintenance of signalling systems see NFPA 72 - Installation, Maintenance and Use of Protective Signalling Systems.)

e. In the absence of the unloader:

- (i) the tank car and facility shutoff valves must be secured in the closed position;
- (ii) no product may be transferred;
- (iii) the requirements of 49 CFR 174.67(a)(2) and (3) apply; and
- (iv) the facility operator shall designate an employee responsible for on-site monitoring of the transfer facility. This employee must be made familiar with the nature and properties of the product contained in the tank car, procedures to be followed in the event of an emergency; and, in the event of an emergency, have the ability and authority to take responsive actions

f. The transfer facility shutoff valve shall be located as close as practicable to the point of connection between the transfer system and the tank car and in a manner that will minimize the release of product in the event of hose rupture or separation. The facility operator must take appropriate steps to prevent rupture of transfer hoses due to product expansion (i.e. liquid expansion chambers or hoses with an increased minimum burst pressure rating.)

8. SPECIAL PROVISIONS.

a. The facility operator shall have written safety procedures on file at each location that uses this exemption. The facility operator shall instruct each employee performing any function under this exemption on the contents of these procedures and ensure compliance with them. The written procedures must contain at least the following:

- (i) A physical description of the facility including the address and hours of operation.
- (ii) A drawing of the transfer facility showing *natural and manmade barriers*, locations of protective equipment (i.e. derail and caution sign), locations of emergency equipment and locations of signalling equipment.
- (iii) Procedures for monitoring the transfer facility [see paragraphs 7(a) and (b)].
- (iv) Information on the contents of the tank car including:
 - (a) *chemical or common name of the product*
 - (b) health and physical hazards involved in handling the product
 - (c) emergency and first aid procedures
- (v) Procedures for securing the transfer facility and protective equipment including derail, switch locks, tank car brakes, caution sign and wheel blocks.
- (vi) Equipment available for employee safety and procedures for using the equipment.
- (vii) Procedures and limitations for movement of tank cars in the vicinity of the transfer facility.
- (viii) Testing and maintenance of system components including signalling systems.
- (ix) Training requirements for designated employees responsible for *monitoring the transfer facility*.

- (x) Procedural steps in the event of an emergency, including names and phone numbers of key personnel and public agencies to contact.
 - (xi) Procedures for reviewing incidents to determine whether the written procedures require revision or modification to prevent future occurrences and amending those procedures when the review necessitates changes.
- b. The facility operator must establish and maintain liaison with fire, police and other appropriate public officials to learn the responsibilities and resources of each governmental agency that may be called upon to respond to an emergency involving the tank car and transfer facility and acquaint the officials with the facility's capabilities and procedures in the event of an emergency.
- c. The marking requirements of Appendix B to Subpart B of part 107 and 172.302(c) are waived.
9. MODES OF TRANSPORTATION AUTHORIZED. Rail freight.
10. MODAL REQUIREMENTS: None as a requirement of this exemption.
11. COMPLIANCE. Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by Federal hazardous materials transportation law, 49 U.S.C. 5101 *et seq.*
- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Registration required by 49 CFR 107.601 *et seq.*, when applicable.
- No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect unless a regulation has been amended making the exemption no longer necessary.
12. REPORTING REQUIREMENTS. The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety as soon as practicable. (49 CFR 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.)

Continuation of DOT-E 10740

Page 6

Issued at Washington, D.C.:

Alan I. Roberts
Alan I. Roberts
Associate Administrator
for Hazardous Materials Safety

6/17/96
(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety,
Research and Special Programs Administration, Department of Transportation,
Washington, D.C. 20590. Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions
and legible reductions of this exemption are permitted. Any alteration of this
exemption is prohibited.

Dist: FRA