

February 7, 2007



U.S. Department
of Transportation

400 Seventh Street, S.W.
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

DOT-SP 13215
(SECOND REVISION)

EXPIRATION DATE: January 31, 2011

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Coil Tubing Services LLC
Broussard, LA
2. PURPOSE AND LIMITATIONS:
 - a. This special permit authorizes the transportation in commerce of certain Division 2.2 materials in non-DOT specification insulated portable tanks conforming with all regulations applicable to a DOT Specification MC-338 insulated cargo tank, except as specified herein. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
 - c. No party status will be granted to this special permit.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.318 and 176.76(g)(1) in that a non-DOT specification portable tank is authorized as specified herein.
5. BASIS: This special permit is based on the application of Coil Tubing Services LLC dated January 31, 2007, submitted in accordance with § 107.109.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Material Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Nitrogen, refrigerated liquid	2.2	UN1977	N/A

7. SAFETY CONTROL MEASURES:a. PACKAGING -

(1) Packaging authorized is an insulated non-DOT specification portable tank designed and constructed in accordance with DOT Specification MC-338 cargo tank motor vehicle, except as modified herein. The portable tank is enclosed in an ISO type frame and is vacuum-insulated. Design pressure is in the range of 75 to 100 PSIG for the internal tank. Design temperature is -320°F for the inner tank and any part, valve or fitting that may come in contact with the lading. Tank material is SA 240 Type 304 for the inner tank and 43D 2540 carbon steel for the outer jacket. Water capacity may not exceed 2150 US gallons.

(2) Tanks must conform with one of the following three Wessington Cryogenics Ltd drawings:

DRG C/2506 dated 10/03/02

DRG C/2228 dated 28/06/02

DRG C/2529 dated 28/06/02

All tanks must conform with calculations, specifications and drawings on file with the Office of Hazardous Materials Special Permits and Approvals (OHMSPA) and with § 178.338, except as follows:

(i) § 178.338-10 does not apply.

(ii) The portable tank need not conform with § 178.338-13(b) or (c). Lifting lugs, framework and any anchoring to the inner tank or the tank jacket must conform with § 178.338-13(a).

(iii) Portable tanks that meet the definition of "container" must meet the requirements of 49 CFR parts 450 thru 453, and each design must be qualified in accordance with § 178.270-13(c), even if used in domestic service.

(iv) Special permit number "DOT-SP 13215" must replace the mark "MC-338" on the nameplate specified in § 178.338-18(a).

b. TESTING - Each portable tank must be reinspected and retested once every five years in accordance with the procedure prescribed in § 180.605 for DOT Specification 51 portable tanks. The test pressure for the inner tank must be determined from the following formulas:

If there is no vacuum in the outer jacket during test: $P_T = 1.25 \times [P_d + H_s + 14.7]$

If vacuum exists in the outer jacket during test:

$$P_T = 1.25 \times [P_d + H_s + 14.7] - 14.7$$

Where:

P_T = Test pressure, psig

P_d = Design pressure (the sum of the maximum allowable working pressure, liquid head and 14.7 psi)

H_s = Static head of liquid in inner tank, psi

c. OPERATIONAL CONTROLS -

(1) Each portable tank must be prepared and shipped as required in § 173.318, as applicable for the lading.

(2) Shipments by cargo vessel must conform with 49 CFR 176.76(g). The portable tank must be stowed on deck and may not be overstowed with other containers or freight. Any lading road relief valve set at a pressure lower than that prescribed for the (safety) pressure relief valve must be closed during transportation by cargo vessel.

(3) No person may transport or offer for transport a portable tank containing liquid nitrogen unless the

tank has a readable vacuum, at the gauge tube, of 200 microns or less.

(4) Each offeror must determine the actual vacuum level for each tank prior to shipment of the tank. If it is determined that the vacuum level of the tank is over 200 microns, with the vessel at cryogenic temperature, or the offeror can not obtain an accurate micron reading for any reason, the tank may not be refilled until the tank vacuum has been restored and the vacuum level is able to be read at the gauge tube, at a level of 200 microns or below.

8. SPECIAL PROVISIONS:

a. A person who is not a holder of this special permit, but receives a package covered by this special permit, may reoffer it for transportation provided no modification or change is made to the package or its contents and it is offered for transportation in conformance with this special permit and the HMR.

b. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

c. New construction of a portable tank under this special permit is not authorized.

d. Packages permanently marked 'DOT-E 13215', prior to October 1, 2007 may continue to be used under this special permit for the remaining service life of the packaging or until the special permit is no longer valid. Packages marked on or after October 1, 2007 must be marked 'DOT-SP 13215'.

e. Shipping papers displaying 'DOT-E 13215' may continue to be used until October 1, 2007, provided the special permit remains valid.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle and cargo vessel.

10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel or motor vehicle used to transport packages covered by this special permit.

11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:

- o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, Parts 171-180.
- o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
- o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)—"The Hazardous Materials Safety and Security Reauthorization Act of 2005" (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR 171.15 - Immediate notice of certain hazardous materials

incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.



Diane LaValle

for Bob Richard
Deputy Associate Administrator
for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: AM