


4 3 2 1
Phoenix 8 In 8 Out CODEC Cover Page

CONFIDENTIAL INFORMATION. COPYRIGHT SANEWAVE, INC. 2003, ALL RIGHTS RESERVED. USAGE SUBJECT TO TERMS OF AGREEMENT DATED 6/16/2003. SCHEMATIC FOR USE IN DXB MANUFACTURING ONLY.


Title	Phoenix CODEC - Cover Page
Size	Document Number
C	<Doc>

Rev A0
Date: Wednesday, January 21, 2004 Sheet 1 of 9


Phoenix - 8 in/8 out Backplane



Line Inputs 1-4



Line Inputs 5-8




Allow for 20dBu of headroom for +4dBu mode (18Vpp).
Allow for 20dBv of headroom for -10dBv mode (4.5Vpp).
Input circuit will accept +24.5dBu input for +4dBu mode
and +10dBv input for -10dBv. 0dBFS for each of these maximum inputs.

Note: Gain calculations include ADC input impedance of 13k typical at 48kHz.


CODEC - Line Inputs 5-8	
Size	Document Number
C	<Doc>
Rev A0	Date: Wednesday, January 21, 2004 Sheet 4 of 9



Line Outs 1-2



Line Outs 3-4




Title **CODEC - Line Out 3-4**

Size **C** Document Number **<Doc>**


Rev **A0**

Date: **Wednesday, January 21, 2004** Sheet **6** of **9**

Line Outs 5-6



Line Outs 7-8



Line In/Out Connectors

