Cheatsheet Java

Comments

Single-line Comment:

```
String txt = "Hello!";
//this is a Comment
System.out.println(txt);

```

Multi-line Comment:

```
String txt = "Hello!";
/*Comments will not be
executed */
System.out.println(txt);
```

Control structures

```
if(condition1){
  /*if condition1 true,
  execute*/
}
else if(condition2){
  /*if condition1 false and
  condition2 true, execute */
}
else{
  //if everything false, execute
}
```

Loops

```
for(int i=0; i<10; i++){
  //execute 10 times
}
while(condition){
  //execute as long as condition
}
do{
  //execute at least once
}while(condition);
```

Switch

```
switch(expression){
  case 1:
    //execute if expression==1
    break;
  case 2:
    //execute if expression==2
    break;
  default:
    /*execute if expression is
     not 1 or 2 */
    break;
}
```

Types

Primitive data types:

Type	Size	Type	Size
byte	8 bit	float	32 bit
short	16 bit	double	64 bit
int	32 bit	Type	Value
long	64 bit	char	'a', 'G'
		boolean	true, false
		void	-

Typecasting: $byte \rightarrow short \rightarrow char \rightarrow int \rightarrow long \rightarrow float \rightarrow double$

Non-Primitive data types:

Type	Value
String	"Hello World!"
Array	int[] myNum = {10, 20, 30, 40};

Declaration, Initialisation

Declaration: int a; String txt;

<Type>< Name>;

Initialisation: int b = 50; int b = a;

<Type><Name>=<Literal/Variable>;

Assignment: a = b; txt = "abc";

Operations

Arithmetic:

Operation	Example
+	3 + 5 == 8
-	7 - 2 == 5
*	4 * 2 == 8
/	7 / 2 == 3
% (Modulo)	72 % 10 == 2

Comparison:

Operator	Math	Example
>	$>$	5 > 2
>=	$\geq$	5 >= 2
<	$<$	10 < 21
<=	$\leq$	5 <= 5
==	$=$	5 == 5
!=	$\neq$	-32 != 32

Functions

```
//Delaration and Implementation
<ret-type> <func-name>(<para-type>
      <para-name>, ...){
    // function body
    //execute
    return <expression>;
}
//Function call
<func-name>(<argument>, ...);
```

Official Documentation: https://docs.oracle.com/en/java/javase/18/docs/api/index.html
Educational: https://www.w3schools.com/java/