

Detecting State Changes of Indoor Everyday Objects using Wi-Fi Channel State Information

Sep. 12th, 2017

Kazuya Ohara*, Takuya Maekawa, and Yasuyuki Matsushita

Osaka University, Japan


Background

2

Detecting State Changes of Indoor Everyday Objects
(e.g. Open/Close door or window)

Application

- Home automation (adaptive HVAC control)
- Monitoring an independently living elderly person



Background


Detecting State Changes of Indoor Everyday Objects
(e.g. Open/Close door or window)

Application

- Home automation (adaptive HVAC control)
- Monitoring an independently living elderly person

—Usual Method—

- ✓ Attach sensors to each object
 - ◆ High deployment and maintenance costs
- ✓ Use camera images
 - ◆ Invasion of privacy



Background

4


Detecting State Changes of Indoor Everyday Objects
(e.g. Open/Close door or window)

Application

- Home automation (adaptive HVAC control)
- Monitoring an independently living elderly person

—Usual Method—

- ✓ Attach sensors to each object
 - ◆ High deployment and maintenance costs
- ✓ Use camera images
 - ◆ Invasion of privacy



Wi-Fi signal



- The path of Wi-Fi signal is greatly affected by state changes of the indoor everyday objects.
- Wi-Fi communications are used widely in indoor environments.

Purpose

Purpose

- Estimate states of indoor everyday objects from propagation information of Wi-Fi signals based on machine learning techniques.

♦ open }
 ♦ close } event
 ♦ opened }
 ♦ closed } state




Propagation Information


- Channel State Information (CSI)
 - including the various effects such as reflection and path loss of signals
 - high dimensional complex matrix



Channel State Information




- **MIMO (Multiple Input Multiple Output)**
using multiple antennas for transmitting and receiving signals
- **OFDM (Orthogonal Frequency Division Multiplexing)**
using subcarriers whose frequencies are different from each other



Channel State Information

7




h : complex value


$\|h\|$: amplitude change

$\angle h$: phase change

$$h = \|h\|e^{j\angle h}$$



h is obtained at each antenna and subcarrier



N_T : # of transmit antennas

N_R : # of receive antennas

N_S : # of subcarriers


Problem

- ◆ Wi-Fi signals are very noisy → Noise reduction
- ◆ CSI is complex information including reflection → Difficult to design feature

Existing approach

Noise reduction: Aggregate CSI data and reduce the dimensionality using PCA

Feature design: Researchers design manually (waveform, frequency of data)



Problem


9

- ◆ Wi-Fi signals are very noisy → Noise reduction
- ◆ CSI is complex information including reflection → Difficult to design feature

Existing approach

Noise reduction: Aggregate CSI data and reduce the dimensionality using PCA
Feature design: Researchers design manually (waveform, frequency of data)

Activity of one person
(e.g. walking, falling)



Problem

10

- ◆ Wi-Fi signals are very noisy → Noise reduction
- ◆ CSI is complex information including reflection → Difficult to design feature

Existing approach


Noise reduction: Aggregate CSI data and reduce the dimensionality using PCA

Feature design: Researchers design manually (waveform, frequency of data)

States of multiple indoor objects

Mixed effects by objects

separate effects caused by objects



Approach


11

- Noise reduction & Separation: Independent Component Analysis (ICA)

- Feature design: extracted automatically using Convolutional Neural Network (CNN)

Approach

- Noise reduction & Separation: Independent Component Analysis (ICA)
Blind source separation




- Feature design: extracted automatically using Convolutional Neural Network (CNN)

Approach

13

- Noise reduction & Separation: Independent Component Analysis (ICA)

Signals reflected by objects are independently




- Feature design: extracted automatically using Convolutional Neural Network (CNN)

Approach



14

- Noise reduction & Separation: Independent Component Analysis (ICA)

Signals reflected by objects are independently




- Feature design: extracted automatically using Convolutional Neural Network (CNN)




Overview of Proposed Method

15



Overview of Proposed Method

16




ICA


17

ICA decomposes amplitude and phase of CSI for each subcarrier.

The number of Tx-Rx antenna pairs




Can not find apparent changes in the signals when events occurred




First component captures signal changes when events occurred

ICA

18




Overview of Proposed Method




DNN

20




DNN

21




Overview of Proposed Method




HMM

23




HMM



Evaluation dataset


25

- Each event of object occurred in an arbitrary order \times 150 sessions (train: 90%, test: 10%)
- Dimension of CSI: $N_T \times N_R \times N_S = 2 \times 3 \times 30$, CSI was obtained at the rate of 1000Hz.
- We estimate states of objects every 0.1 sec.





Evaluation dataset


- Each event of object occurred in an
- Dimension of CSI: $N_T \times N_R \times N_S =$
- We estimate states of objects every



Result for each objects




Result for each event/*state*




Result for each event/*state*

29




Result for each event/*state*





Comparison with Baselines

- Proposed: our proposed method
- w/o ICA: don't use decomposed amplitude and decomposed phase
- w/o knowledge: don't use knowledge of objects
- w/o HMM: estimate states of objects by DNN
- RF: estimate states by Random Forests using CSI denoised by PCA





Result of Long-term experiment

- Collect data for 10 days in environment 2 (20 sessions/day)
- train: first 3 days (60 sessions), test: last 7 days (140 sessions)
- Fine-tuning DNN by recognized result as pseudo ground truth for each day



Amount of training data

- Change amount of training data from 1 day to 3 days
i.e. train: 20 sessions, 40 sessions, 60 sessions



future task: method that does not require vast training data

Conclusion

34

- We proposed a method for detecting events and states of indoor everyday objects such as doors and windows using Wi-Fi CSI
- We designed a novel processing pipeline based on ICA, DNN, and HMM with a grammar based on knowledge of an object.
- We investigated the effectiveness of our method using real data. And we confirmed that our approach significantly outperformed a classic machine learning-based approach.
- However, because our method relies on deep learning, much training data results in poor recognition accuracy.
- Cope with this problem is one of our important future tasks.