🛡️ AI THREAT DEETCTION

AI-Powered Real-Time Safety & Threat Monitoring Platform

VoidDeckSafety is a full-stack, real-time threat detection system that leverages multi-provider AI vision models (OpenAI GPT-4.1, Anthropic Claude, Google Gemini) to analyze video streams, webcam feeds, and images for safety threats. It supports both **physical surveillance** (violence, weapons, medical emergencies) and **online safety** (grooming, abuse, coercion) use cases — scoring, escalating, and alerting in real time.

TypeScript 5.x
React 19
Express 4.x
PostgreSQL 16
Socket.IO 4.x
TailwindCSS 4.x

📑 Table of Contents

- Overview
- Architecture
- Features
- Tech Stack
- Prerequisites
- Project Structure
- Setup & Installation
- Environment Variables
- Running the Application
- Default Credentials

- API Reference
- Real-Time Events (WebSocket)
- External Ingestion API
- AI Providers
- Threat Scoring & Escalation
- Alert System
- Screenshots

Overview

VoidDeckSafety provides a unified platform for monitoring physical and digital environments for safety threats. The system processes media inputs through a multi-stage AI pipeline:

1. **Ingest** — Upload videos/images, stream from webcam/screen capture, or push via external API
2. **Process** — Videos are split into chunks and converted to GIFs; images are sent directly
3. **Analyze** — AI vision models analyze each frame/chunk with structured JSON output
4. **Score** — Configurable weighted scoring with per-source or global thresholds
5. **Escalate** — Pattern-based escalation rules detect sustained or recurring threats
6. **Alert** — Real-time notifications via WebSocket, webhooks (HMAC-signed), and browser push

---

Architecture

```
┌──────────────────────────────────────────────────────────────────────┐
│                        Frontend (React + Vite)                        │
│  ┌──────────┐  ┌──────────┐  ┌──────────┐  ┌──────────────────┐  │
│  | Monitor  | | Dashboard | | Analytics | | Settings/Alerts  | |
│  |  Page    | |   Page    | |   Page    | |     Pages        | |
```

```
│  └──────┘  └──────┘  └──────┘  └──────────┘ │
│      │            │           │             │
│      └────────────┴───────────┴─────────────┘
│                        │ REST API + Socket.IO
└────────────────────────┴──────────────────────┘
                         │
┌────────────────────────┴──────────────────────┐
│                Backend (Express + Socket.IO)
│                        │
│  ┌─────────────────────┴────────────────────┐
│  │                Route Layer                │
│  │  /api/auth  /api/sources  /api/jobs  /api/alerts
│  │  /api/dashboard  /api/ingest  /api/health
│  └──────────────────────────────────────────┘
│                        │
│  ┌──────────────────────────────────────────┐
│  │               Service Layer              │
│  │  jobQueue → videoProcessor → aiAnalyzer/aiProviders
│  │  → threatScorer → contextMemory → escalation
│  │  → alertService → streamProcessor
│  └──────────────────────────────────────────┘
│                        │
│  ┌──────────────────────────────────────────┐
│  │          Database Layer (Drizzle ORM)    │
│  └──────────────────────────────────────────┘
└──────────────────────────────────────────────┘
                         │
              ┌──────────┴──────────┐
              │  PostgreSQL 16      │
              │  (Docker Container) │
              └─────────────────────┘
```

Features

🔍 Dual-Mode Threat Detection

- **Physical Mode** — Analyzes video/webcam feeds for: violence, weapons, fire/smoke, medical emergencies, nudity/indecency, public disturbance, suspicious behavior, vandalism, trespassing
- **Online Mode** — Analyzes screenshots/images for: grooming, sexual content, abuse/bullying, coercion/threats, manipulation, self-harm, drug references, hate speech, personal info exposure

🤖 Multi-Provider AI Engine

- **OpenAI** GPT-4.1-mini (default) with structured JSON schema enforcement
- **Anthropic** Claude via direct HTTP API with automatic fallback
- **Google** Gemini via direct HTTP API with automatic fallback
- Hot-swappable provider selection from the UI (admin only)
- 3-attempt retry per provider with exponential backoff, plus cross-provider fallback

🎥 Video Processing Pipeline

- Automatic video splitting into configurable-length chunks (default: 5 seconds) via ffmpeg
- Chunk-to-GIF conversion (5 fps, 512px width) optimized for AI vision model input
- Concurrent job processing with configurable parallelism (`MAX_CONCURRENT_JOBS`)
- Supports `.mp4` , `.avi` , `.mkv` , `.mov` , `.webm` , `.gif` , `.png` , `.jpg` , `.jpeg` , `.webp`

📡 Real-Time Live Streaming

- **Webcam capture** — Browser `getUserMedia` → frame extraction every 3s → Socket.IO transport
- **Screen capture** — Browser `getDisplayMedia` → same pipeline
- **HLS/DASH streams** — URL-based ingestion via ffmpeg child process with configurable frame interval
- Live video preview in the browser with frame count tracking

📊 Configurable Threat Scoring

- Per-category weights stored in the database — fully editable from the UI
- Score calculation: sum of triggered category weights, capped at 100
- Four severity levels: **Safe** (0–39), **Low** (40–59), **Medium** (60–79), **High** (80–100)
- Per-source threshold overrides for fine-tuned sensitivity

🧠 Context Memory

- Sliding-window persistent context per source stored in PostgreSQL
- Configurable window size (default: 10 for video, 20 for images)
- Previous analysis summaries are injected into AI prompts, enabling the model to detect escalating patterns across consecutive frames/uploads

⚡ Escalation Engine

Three rule types for automatic escalation:

Rule Type	Description
Consecutive	Triggers when N consecutive analyses exceed a threshold score
Average	Triggers when the rolling average of recent scores exceeds a threshold
Category Repeat	Triggers when a specific threat category appears N times in M analyses

Rules can be **global** or **per-source**, and are togglable from the Settings page.

📈 Analytics Dashboard

- **Overview dashboard** with live stats: active sources, high-risk alerts, 5-min event count, avg latency
- **Threat trend chart** — time-series line chart (avg + max) with selectable time ranges (6h–7d)
- **Category breakdown** — bar chart showing frequency of each threat category
- **Per-source analytics** — table with source-level stats (event count, avg/max score,

last event)

- **Latency stats** — processing time metrics including p95 percentile
- All charts powered by Recharts

🔔 Alert System

- **Webhooks** — HMAC-SHA256 signed HTTP POST payloads to user-configured URLs
- **Browser Push Notifications** — Web Push (VAPID) integration
- **Socket.IO** — Real-time in-app alerts for connected clients
- Full delivery logging with status tracking (pending/sent/failed)
- Webhook test endpoint for verification

🔐 Authentication & RBAC

- JWT-based authentication with access + refresh token pairs
- Three roles with different permissions:

Role	Capabilities
Admin	Full access — manage users, change AI provider, all config
Operator	Create/manage sources, upload media, manage webhooks
Viewer	Read-only dashboard and analytics access

- Secure password hashing (bcrypt, 12 rounds)
- Session management with revocation support

📝 Audit Trail

- All configuration changes are logged with old/new values, user ID, and timestamp
- Accessible via the config audit log API

🔌 External Ingestion API

- Bearer-token authenticated endpoint (`POST /api/ingest`) for programmatic

integration

- Each source generates a unique ingestion token on creation
- Compatible with cURL, scripts, IoT devices, and third-party systems

---

Tech Stack

Backend

Technology	Purpose
Node.js + Express	HTTP server & REST API
Socket.IO	Real-time WebSocket communication
TypeScript	Type safety across the entire backend
Drizzle ORM	Type-safe PostgreSQL query builder
PostgreSQL 16	Primary database
OpenAI SDK	GPT-4.1-mini vision analysis
ffmpeg (fluent-ffmpeg)	Video splitting, GIF conversion, HLS frame extraction
jsonwebtoken	JWT authentication
bcryptjs	Password hashing
web-push	Browser push notifications (VAPID)
Zod	Environment variable validation
multer	File upload handling

Frontend

Technology	Purpose
React 19	UI framework
Vite 6	Build tool & dev server
TypeScript	Type safety
Tailwind CSS 4	Styling
Recharts	Charts & data visualization
Socket.IO Client	Real-time updates
Lucide React	Icon library

Infrastructure

Technology	Purpose
Docker Compose	PostgreSQL container management
ffmpeg	Video/stream processing (must be installed on host)

Prerequisites

Before setting up VoidDeckSafety, ensure you have the following installed:

- **Node.js** ≥ 18.x (download)
- **npm** ≥ 9.x (comes with Node.js)
- **Docker** & **Docker Compose** (download)
- **ffmpeg** — required for video processing

Installing ffmpeg

macOS:

```
brew install ffmpeg
```

Ubuntu/Debian:

```
sudo apt update && sudo apt install ffmpeg
```

Windows:

```
# Using Chocolatey
choco install ffmpeg

# Or download from https://ffmpeg.org/download.html
```

Verify installation:

```
ffmpeg -version
```

Project Structure

```
voiddecksafety/
├── docker-compose.yml          # PostgreSQL container definition
├── main.py                     # Standalone OpenAI vision test script
├── .env                        # Environment variables (create this)
|
├── backend/
|   ├── package.json
|   ├── tsconfig.json
|   ├── drizzle.config.ts
|   └── src/
|       ├── index.ts            # Express app entry point
|       ├── config/
|       |   └── env.ts          # Zod-validated environment config
|       ├── db/
|       |   ├── index.ts        # Drizzle ORM + pg pool setup
|       |   ├── schema.ts       # All 14 table definitions
```

```
|       |   └── seed.ts         # DB seeding (tables + defaults)
|       ├── middleware/
|       |   ├── auth.ts         # JWT auth + RBAC middleware
|       |   ├── errorHandler.ts # Global error handler
|       |   └── upload.ts       # Multer file upload config
|       ├── routes/
|       |   ├── alerts.ts       # Webhook & push subscription CRUD
|       |   ├── auth.ts         # Login, register, refresh, logout
|       |   ├── dashboard.ts    # Dashboard stats, config, analytics
|       |   ├── ingest.ts       # External API ingestion endpoint
|       |   ├── jobs.ts         # Job listing & detail
|       |   └── sources.ts      # Source CRUD + file upload
|       ├── services/
|       |   ├── aiAnalyzer.ts   # OpenAI vision analysis
|       |   ├── aiProviders.ts  # Multi-provider AI abstraction
|       |   ├── alertService.ts # Webhook + push dispatch
|       |   ├── auth.ts         # JWT + session management
|       |   ├── contextMemory.ts# Sliding-window context per source
|       |   ├── escalation.ts   # Escalation rule engine
|       |   ├── jobQueue.ts     # Concurrent job processing queue
|       |   ├── streamProcessor.ts # Live stream management
|       |   ├── threatScorer.ts # Weighted threat scoring
|       |   └── videoProcessor.ts  # ffmpeg video processing
|       ├── socket/
|       |   └── index.ts        # Socket.IO server + event handlers
|       └── types/
|           └── index.ts        # Shared TypeScript types
|
├── frontend/
|   ├── package.json
|   ├── vite.config.ts
|   ├── index.html
|   └── src/
|       ├── App.tsx             # Root component with navigation
|       ├── main.tsx            # React entry point
|       ├── index.css           # Tailwind imports
```

```
|       ├── components/
|       |   ├── PipelineCard.tsx      # Per-source monitoring card
|       |   ├── PipelineEditModal.tsx # Source config modal
|       |   ├── SourceCard.tsx        # Alternative source display
|       |   ├── StatusBadge.tsx       # Status/severity badge
|       |   ├── StreamCapture.tsx     # Live stream capture UI
|       |   ├── ThreatGauge.tsx       # SVG circular threat gauge
|       |   └── UploadPanel.tsx       # New source creation form
|       ├── hooks/
|       |   ├── useAuth.tsx     # Auth context provider + hook
|       |   └── useSocket.ts    # Socket.IO connection hook
|       ├── pages/
|       |   ├── AlertsPage.tsx  # Webhook & alert management
|       |   ├── AnalyticsPage.tsx # Deep analytics & charts
|       |   ├── DashboardPage.tsx # Overview dashboard
|       |   ├── LoginPage.tsx   # Login/register page
|       |   └── SettingsPage.tsx# Global settings page
|       ├── services/
|       |   └── api.ts          # HTTP client with auto token refresh
|       └── types/
|           └── index.ts        # Frontend TypeScript types
|
└── data/                       # Generated data directory
    ├── chunks/                 # Video chunks (temp)
    ├── frames/                 # Stream frames
    ├── gifs/                   # Generated GIFs for AI analysis
    ├── hls/                    # HLS stream data
    └── uploads/                # Uploaded media files
```

Setup & Installation

1. Clone the Repository

```
git clone https://github.com/t-sibiraj/dlweek-brainfresh-threatdetection.git
cd dlweek-brainfresh-threatdetection
```

2. Start PostgreSQL

```
docker-compose up -d
```

This starts a PostgreSQL 16 container with:

- **User:** `voiddecksafety`
- **Password:** `voiddecksafety`
- **Database:** `voiddecksafety`
- **Port:** `5432`
- Persistent volume for data durability

Verify it's running:

```
docker-compose ps
```

3. Configure Environment Variables

Create a `.env` file in the **project root**:

```
cp .env.example .env   # or create manually
```

```
# ─── Required ──────────────────────────────────────────
OPENAI_API_KEY=sk-your-openai-api-key-here

# ─── Database (default works with docker-compose) ──────
DATABASE_URL=postgresql://voiddecksafety:voiddecksafety@localhost:5432/voiddecksafety
```

```
# ─── Server ──────────────────────────────────────────────
PORT=4000
NODE_ENV=development

# ─── Video Processing ────────────────────────────────────
VIDEO_CHUNK_SECONDS=5
MAX_CONCURRENT_JOBS=2

# ─── AI Context ──────────────────────────────────────────
MAX_VIDEO_CONTEXT=10
MAX_IMAGE_CONTEXT=20
MODEL_NAME=gpt-4.1-mini

# ─── Threat Thresholds ───────────────────────────────────
THREAT_THRESHOLD_HIGH=70
THREAT_THRESHOLD_MEDIUM=40

# ─── Authentication ──────────────────────────────────────
JWT_SECRET=your-secret-key-change-in-production
JWT_ACCESS_EXPIRES=15m
JWT_REFRESH_EXPIRES=7d

# ─── Multi-Provider AI (Optional) ────────────────────────
AI_PROVIDER=openai
ANTHROPIC_API_KEY=
GOOGLE_AI_KEY=

# ─── Web Push (Optional) ─────────────────────────────────
VAPID_PUBLIC_KEY=
VAPID_PRIVATE_KEY=
VAPID_EMAIL=mailto:admin@voiddecksafety.local
```

> **Note:** Only `OPENAI_API_KEY` is strictly required. All other values have sensible defaults.

4. Install Backend Dependencies

```
cd backend
npm install
```

5. Install Frontend Dependencies

```
cd ../frontend
npm install
```

Running the Application

Start Everything (3 terminals)

Terminal 1 — Database:

```
docker-compose up -d
```

Terminal 2 — Backend:

```
cd backend
npm run dev
```

The backend will:

- Connect to PostgreSQL
- Create all tables automatically (idempotent)
- Seed default data (weights, escalation rules, admin user)
- Start the Express server on `http://localhost:4000`
- Initialize Socket.IO for real-time connections

Terminal 3 — Frontend:

```
cd frontend
npm run dev
```

The frontend dev server starts on `http://localhost:5173`.

Access the Application

Open **http://localhost:5173** in your browser.

Default Credentials

The database seeder creates a default admin account:

Field	Value
Email	`admin@voiddecksafety.local`
Password	`admin123`
Role	`admin`

> ⚠️ **Change these credentials in production!**

Environment Variables

Variable	Required	Default	Description
`OPENAI_API_KEY`	✅	—	OpenAI API key for GPT-4.1-mini vision
`DATABASE_URL`	❌	`postgresql://voiddecksafety:voiddecksafety@localhost:5432/voiddecksafety`	PostgreSQL connection string
`PORT`	❌	`4000`	Backend

			server port
`NODE_ENV`	❌	`development`	Environment mode
`VIDEO_CHUNK_SECONDS`	❌	`5`	Duration of each video chunk (seconds)
`MAX_CONCURRENT_JOBS`	❌	`2`	Max parallel AI analysis jobs
`MAX_VIDEO_CONTEXT`	❌	`10`	Context memory window for video sources
`MAX_IMAGE_CONTEXT`	❌	`20`	Context memory window for image sources
`MODEL_NAME`	❌	`gpt-4.1-mini`	OpenAI model name
`THREAT_THRESHOLD_HIGH`	❌	`70`	Score threshold for "high" severity
`THREAT_THRESHOLD_MEDIUM`	❌	`40`	Score threshold for "medium" severity
`JWT_SECRET`	❌	dev default	Secret for signing JWT tokens
`JWT_ACCESS_EXPIRES`	❌	`15m`	Access token expiration

`JWT_REFRESH_EXPIRES`	❌	`7d`	Refresh token expiration
`AI_PROVIDER`	❌	`openai`	Active AI provider (`openai`, `anthropic`, `google`)
`ANTHROPIC_API_KEY`	❌	—	Anthropic API key (enables Claude)
`GOOGLE_AI_KEY`	❌	—	Google AI key (enables Gemini)
`VAPID_PUBLIC_KEY`	❌	—	VAPID public key for Web Push
`VAPID_PRIVATE_KEY`	❌	—	VAPID private key for Web Push
`VAPID_EMAIL`	❌	`mailto:admin@voiddecksafety.local`	VAPID contact email

API Reference

Authentication

Method	Endpoint	Auth	Description
`POST`	`/api/auth/register`	—	Register a new user
`POST`	`/api/auth/login`	—	Login and receive token pair
`POST`	`/api/auth/refresh`	—	Refresh access token
`POST`	`/api/auth/logout`	🔒	Revoke refresh token

Sources

Method	Endpoint	Auth	Description
`GET`	`/api/sources`	🔒	List all sources
`POST`	`/api/sources`	🔒	Create a new source
`GET`	`/api/sources/:id`	🔒	Get source details + status
`PATCH`	`/api/sources/:id`	🔒	Update source settings
`DELETE`	`/api/sources/:id`	🔒	Delete a source
`POST`	`/api/sources/:id/upload`	🔒	Upload media file for analysis

Jobs

Method	Endpoint	Auth	Description
`GET`	`/api/jobs`	🔒	List jobs (filterable by `?source=id`)
`GET`	`/api/jobs/:id`	🔒	Get job detail with threat event

Dashboard & Analytics

Method	Endpoint	Auth	Description
`GET`	`/api/dashboard`	🔒	Dashboard summary stats
`GET`	`/api/threats`	🔒	Recent threat events
`GET`	`/api/analytics/trend`	🔒	Threat score trend over time
`GET`	`/api/analytics/sources`	🔒	Per-source analytics breakdown
`GET`	`/api/analytics/categories`	🔒	Category frequency breakdown
`GET`	`/api/analytics/latency`	🔒	Processing latency stats (avg/min/max/p95)

Configuration

Method	Endpoint	Auth	Description
`GET`	`/api/config/weights`	🔒	Get threat weights
`PUT`	`/api/config/weights`	🔒 Admin	Update threat weights
`GET`	`/api/config/thresholds`	🔒	Get severity thresholds
`PUT`	`/api/config/thresholds`	🔒 Admin	Update thresholds
`GET`	`/api/config/system`	🔒	Get system configuration
`PUT`	`/api/config/system`	🔒 Admin	Update system config
`GET`	`/api/config/escalation`	🔒	Get escalation rules
`PUT`	`/api/config/escalation`	🔒 Admin	Update escalation rules
`GET`	`/api/config/ai-provider`	🔒	Get AI provider status
`PUT`	`/api/config/ai-provider`	🔒 Admin	Switch AI provider

Alerts

Method	Endpoint	Auth	Description
`GET`	`/api/alerts/webhooks`	🔒	List user's webhooks
`POST`	`/api/alerts/webhooks`	🔒 Operator+	Create webhook endpoint
`PATCH`	`/api/alerts/webhooks/:id`	🔒	Update webhook
`DELETE`	`/api/alerts/webhooks/:id`	🔒	Delete webhook
`POST`	`/api/alerts/webhooks/:id/test`	🔒 Operator+	Send test webhook
`GET`	`/api/alerts/push/vapid-key`	—	Get VAPID public key
`POST`	`/api/alerts/push/subscribe`	🔒	Subscribe to push notifications
`DELETE`	`/api/alerts/push/subscribe/:id`	🔒	Unsubscribe from push
`GET`	`/api/alerts/log`	🔒	Alert delivery log

External Ingestion

Method	Endpoint	Auth	Description
`POST`	`/api/ingest`	Bearer Token	Upload media via external API

Health

Method	Endpoint	Auth	Description
`GET`	`/api/health`	—	Health check

Real-Time Events (WebSocket)

VoidDeckSafety uses Socket.IO for real-time bidirectional communication.

Client → Server Events

Event	Payload	Description
`join_source`	`{ source_id }`	Subscribe to source-specific updates
`leave_source`	`{ source_id }`	Unsubscribe from a source
`stream:start`	`{ source_id, type }`	Start live stream (webcam/screen/hls)
`stream:frame`	`{ source_id, frame }`	Send a video frame (base64)
`stream:stop`	`{ source_id }`	Stop live stream

Server → Client Events

Event	Payload	Description
`job_queued`	`JobEvent`	New analysis job queued
`job_processing`	`JobEvent`	Job started processing
`job_completed`	`JobEvent`	Job completed with results
`job_error`	`JobEvent`	Job failed
`threat_alert`	`ThreatAlertEvent`	Escalation triggered
`stream_started`	`{ source_id }`	Stream started confirmation
`stream_stopped`	`{ source_id }`	Stream stopped confirmation
`stream:frame_ack`	`{ frameCount }`	Frame received acknowledgment

External Ingestion API

For programmatic integration (IoT devices, scripts, third-party systems):

```
# Upload an image for analysis
curl -X POST http://localhost:4000/api/ingest \
  -H "Authorization: Bearer YOUR_INGESTION_TOKEN" \
  -F "source_id=YOUR_SOURCE_ID" \
  -F "file=@/path/to/image.jpg"

# Upload a video for analysis
curl -X POST http://localhost:4000/api/ingest \
  -H "Authorization: Bearer YOUR_INGESTION_TOKEN" \
  -F "source_id=YOUR_SOURCE_ID" \
  -F "file=@/path/to/video.mp4"
```

The ingestion token is generated when a source is created and is displayed in the source's Pipeline Card.

AI Providers

VoidDeckSafety supports three AI vision providers:

Provider	Model	Config Key
OpenAI (default)	GPT-4.1-mini	`OPENAI_API_KEY`
Anthropic	Claude	`ANTHROPIC_API_KEY`
Google	Gemini	`GOOGLE_AI_KEY`

- The active provider can be switched at runtime from the Analytics page (admin only)
- If the active provider fails after 3 retries, the system automatically falls back to OpenAI
- Provider availability is auto-detected based on configured API keys

---

Threat Scoring & Escalation

Scoring

Each AI analysis returns a set of triggered threat categories. The final threat score is calculated as:

```
Score = min(100, Σ weight[category] for each triggered category)
```

Default weights are seeded for both physical and online modes and are fully configurable from the Settings page.

Severity Levels

Level	Default Score Range	Color
Safe	0 – 39	Gray
Low	40 – 59	Light
Medium	60 – 79	Medium
High	80 – 100	White/Bright

Thresholds are configurable globally and per-source.

Escalation Rules

Rule	Parameters	Trigger
Consecutive	`count`, `threshold`	N consecutive scores above threshold
Average	`window`, `threshold`	Rolling average over N analyses exceeds threshold
Category Repeat	`category`, `count`, `window`	Same category appears N times in M analyses

When escalation triggers, a `threat_alert` event is emitted via Socket.IO and dispatched to all configured webhook and push notification endpoints.

Alert System

Webhooks

- Create webhook endpoints from the Alerts page
- Payloads are signed with **HMAC-SHA256** using a per-webhook secret
- Signature is sent in the `X-VoidDeck-Signature` header as `sha256=<hex>`
- Event type is sent in the `X-VoidDeck-Event` header
- Test webhooks with the built-in test button

Browser Push Notifications

- Requires VAPID key pair (generate with `npx web-push generate-vapid-keys`)
- Subscribe from the Alerts page
- Notifications are sent for threat alerts and escalation events

---

Scripts

Backend

```
npm run dev          # Start dev server with hot reload (tsx watch)
npm run build        # Build for production (tsup)
npm run start        # Run production build
npm run typecheck    # Run TypeScript type checking
npm run db:generate  # Generate Drizzle migrations
npm run db:migrate   # Run Drizzle migrations
npm run db:push      # Push schema to database
```

Frontend

```
npm run dev      # Start Vite dev server
npm run build    # Build for production
npm run preview  # Preview production build
npm run lint     # Run ESLint
```

License

This project was built for the DL Week hackathon by **Team BrainFresh**.