


# An Observable OCaml

## Compiling OCaml into C


Tianlin Zhang

5th February, 2018


# Structure of the project




# Structure of the project



# Structure of the project



# Structure of the project



# Completed work so far

Core project (a subset of OCaml containing the most commonly used features) is complete, including:

# Completed work so far

Core project (a subset of OCaml containing the most commonly used features) is complete, including:

- obtaining types from the Lambda IR
- writing a representation of a subset of C in OCaml

# Completed work so far

Core project (a subset of OCaml containing the most commonly used features) is complete, including:

- obtaining types from the Lambda IR
- writing a representation of a subset of C in OCaml
- translation of commonly used language constructs. such as `let`, `let rec`, `if`, `for`, `while`, `ref`, pattern matching etc.
- design of algebraic data structure representation and implementation
- design of closure representation, closure conversion, and function and data structure polymorphism




# Completed work so far


Core project (a subset of OCaml containing the most commonly used features) is complete, including:

- obtaining types from the Lambda IR
- writing a representation of a subset of C in OCaml
- translation of commonly used language constructs. such as `let`, `let rec`, `if`, `for`, `while`, `ref`, pattern matching etc.
- design of algebraic data structure representation and implementation
- design of closure representation, closure conversion, and function and data structure polymorphism
- library of toy OCaml programs for testing and benchmarking
- some evaluation into performance and observability of compiled output


# Benchmarks



# Benchmarks



# Benchmarks



# Observability Demo

(gdb)

# Observability Demo

(gdb) 1

# Observability Demo

```
(gdb) 1
1      let sum xs =
2          let rec go acc = function
3              | x :: xs -> go (acc + x) xs
4              | [] -> acc
5          in go 0 xs
6
7      let a = sum [3]
(gdb)
```

# Observability Demo

```
(gdb) 1
1      let sum xs =
2          let rec go acc = function
3              | x :: xs -> go (acc + x) xs
4              | [] -> acc
5          in go 0 xs
6
7      let a = sum [3]
(gdb) tb 2
```



# Observability Demo

(gdb) 1

```
1      let sum xs =  
2          let rec go acc = function  
3              | x :: xs -> go (acc + x) xs  
4              | [] -> acc  
5          in go 0 xs  
6  
7      let a = sum [3]
```

(gdb) tb 2

Temporary breakpoint 1 at 0x400690: tests/observability/sum.ml:2. (2 locations)

(gdb)

# Observability Demo

(gdb) l

```
1      let sum xs =  
2          let rec go acc = function  
3              | x :: xs -> go (acc + x) xs  
4              | [] -> acc  
5          in go 0 xs  
6  
7      let a = sum [3]
```

(gdb) tb 2

Temporary breakpoint 1 at 0x400690: tests/observability/sum.ml:2. (2 locations)

(gdb) r

# Observability Demo

(gdb) 1

```
1      let sum xs =  
2          let rec go acc = function  
3              | x :: xs -> go (acc + x) xs  
4              | [] -> acc  
5          in go 0 xs  
6  
7      let a = sum [3]
```

(gdb) tb 2

Temporary breakpoint 1 at 0x400690: tests/observability/sum.ml:2. (2 locations)

(gdb) r

Starting program: tests/observability/sum

Temporary breakpoint 1, func\_1233 (xs\_1205=...) at tests/observability/sum.ml:

```
2      let rec go acc = function
```

(gdb)

# Observability Demo

(gdb) l

```
1      let sum xs =  
2          let rec go acc = function  
3              | x :: xs -> go (acc + x) xs  
4              | [] -> acc  
5          in go 0 xs  
6  
7      let a = sum [3]
```

(gdb) tb 2

Temporary breakpoint 1 at 0x400690: tests/observability/sum.ml:2. (2 locations)

(gdb) r

Starting program: tests/observability/sum

Temporary breakpoint 1, func\_1233 (xs\_1205=...) at tests/observability/sum.ml:

```
2      let rec go acc = function
```

(gdb) s

# Observability Demo

(gdb) l

```
1      let sum xs =  
2      let rec go acc = function  
3      | x :: xs -> go (acc + x) xs  
4      | [] -> acc  
5      in go 0 xs  
6  
7      let a = sum [3]
```

(gdb) tb 2

Temporary breakpoint 1 at 0x400690: tests/observability/sum.ml:2. (2 locations)

(gdb) r

Starting program: tests/observability/sum

Temporary breakpoint 1, func\_1233 (xs\_1205=...) at tests/observability/sum.ml:

```
2      let rec go acc = function
```

(gdb) s

```
5      in go 0 xs
```

(gdb)

# Observability Demo

(gdb) l

```
1      let sum xs =
2          let rec go acc = function
3              | x :: xs -> go (acc + x) xs
4              | [] -> acc
5          in go 0 xs
6
7      let a = sum [3]
```

(gdb) tb 2

Temporary breakpoint 1 at 0x400690: tests/observability/sum.ml:2. (2 locations)

(gdb) r

Starting program: tests/observability/sum

Temporary breakpoint 1, func\_1233 (xs\_1205=...) at tests/observability/sum.ml:

```
2      let rec go acc = function
```

(gdb) s

```
5          in go 0 xs
```

(gdb)

local\_func\_1215 (acc\_1207=0, param\_1210=..., closure\_obj\_1214=0x602050) at tes

```
2      let rec go acc = function
```

# Observability Demo

(gdb)

# Observability Demo

(gdb)

3 | x :: xs -> go (acc + x) xs

(gdb)



# Observability Demo

(gdb)

```
3          | x :: xs -> go (acc + x) xs
```

(gdb) p x\_1208

# Observability Demo

```
(gdb)
3          | x :: xs -> go (acc + x) xs
(gdb) p x_1208
$1 = 3
(gdb)
```

# Observability Demo

```
(gdb)
3          | x :: xs -> go (acc + x) xs
(gdb) p x_1208
$1 = 3
(gdb) p acc_1207
```

# Observability Demo

```
(gdb)
3          | x :: xs -> go (acc + x) xs
(gdb) p x_1208
$1 = 3
(gdb) p acc_1207
$2 = 0
(gdb)
```

# Observability Demo

```
(gdb)
3          | x :: xs -> go (acc + x) xs
(gdb) p x_1208
$1 = 3
(gdb) p acc_1207
$2 = 0
(gdb) p xs_1209
```

# Observability Demo

```
(gdb)
3          | x :: xs -> go (acc + x) xs
(gdb) p x_1208
$1 = 3
(gdb) p acc_1207
$2 = 0
(gdb) p xs_1209
$3 = {i = 1, block = 0x1}
(gdb)
```

# Observability Demo

```
(gdb)
3          | x :: xs -> go (acc + x) xs
(gdb) p x_1208
$1 = 3
(gdb) p acc_1207
$2 = 0
(gdb) p xs_1209
$3 = {i = 1, block = 0x1}
(gdb) s
```

# Observability Demo

(gdb)

```
3           | x :: xs -> go (acc + x) xs
```

(gdb) p x\_1208

\$1 = 3

(gdb) p acc\_1207

\$2 = 0

(gdb) p xs\_1209

\$3 = {i = 1, block = 0x1}

(gdb) s

local\_func\_1215 (acc\_1207=3, param\_1210=..., closure\_obj\_1214=0x602050) at test

```
2           let rec go acc = function
```

(gdb)



# Observability Demo

(gdb)

```
3           | x :: xs -> go (acc + x) xs
```

(gdb) p x\_1208

\$1 = 3

(gdb) p acc\_1207

\$2 = 0

(gdb) p xs\_1209

\$3 = {i = 1, block = 0x1}

(gdb) s

local\_func\_1215 (acc\_1207=3, param\_1210=..., closure\_obj\_1214=0x602050) at test

```
2           let rec go acc = function
```

(gdb)

```
4           | [] -> acc
```

(gdb)

# Observability Demo

(gdb)

```
3           | x :: xs -> go (acc + x) xs
```

(gdb) p x\_1208

\$1 = 3

(gdb) p acc\_1207

\$2 = 0

(gdb) p xs\_1209

\$3 = {i = 1, block = 0x1}

(gdb) s

local\_func\_1215 (acc\_1207=3, param\_1210=..., closure\_obj\_1214=0x602050) at test

```
2           let rec go acc = function
```

(gdb)

```
4           | [] -> acc
```

(gdb) finish

# Observability Demo

```
(gdb)
```

```
3           | x :: xs -> go (acc + x) xs
```

```
(gdb) p x_1208
```

```
$1 = 3
```

```
(gdb) p acc_1207
```

```
$2 = 0
```

```
(gdb) p xs_1209
```

```
$3 = {i = 1, block = 0x1}
```

```
(gdb) s
```

```
local_func_1215 (acc_1207=3, param_1210=..., closure_obj_1214=0x602050) at test
```

```
2           let rec go acc = function
```

```
(gdb)
```

```
4           | [] -> acc
```

```
(gdb) finish
```

```
Run till exit from #0  local_func_1215 (acc_1207=3, param_1210=..., closure_obj_1214=0x602050) at test:0x0000000000400740 in local_func_1215 (acc_1207=0, param_1210=..., closure_obj_1214=0x602050)
```

```
0x0000000000400740 in local_func_1215 (acc_1207=0, param_1210=..., closure_obj_1214=0x602050)
```

```
3           | x :: xs -> go (acc + x) xs
```

```
Value returned is $4 = 3
```

```
(gdb)
```

## Further work

The project is roughly on schedule, within 1–2 weeks of the timetable.

Further work on the project would include:

## Further work

The project is roughly on schedule, within 1–2 weeks of the timetable.

Further work on the project would include:

- Using `liballocs` and `gdb` scripts to improve ‘observability’ and user experience while debugging

## Further work

The project is roughly on schedule, within 1–2 weeks of the timetable.

Further work on the project would include:

- Using `liballocs` and `gdb` scripts to improve ‘observability’ and user experience while debugging
- Further evaluation tasks into performance and observability

## Further work

The project is roughly on schedule, within 1–2 weeks of the timetable.

Further work on the project would include:

- Using `liballocs` and `gdb` scripts to improve ‘observability’ and user experience while debugging
- Further evaluation tasks into performance and observability

Extension tasks:

## Further work

The project is roughly on schedule, within 1–2 weeks of the timetable.

Further work on the project would include:

- Using `liballocs` and `gdb` scripts to improve ‘observability’ and user experience while debugging
- Further evaluation tasks into performance and observability

Extension tasks:

- improving closure creation performance



## Further work

The project is roughly on schedule, within 1–2 weeks of the timetable.

Further work on the project would include:

- Using `liballocs` and `gdb` scripts to improve ‘observability’ and user experience while debugging
- Further evaluation tasks into performance and observability

Extension tasks:

- improving closure creation performance
- compilation of modules, functors and exceptions

## Further work

The project is roughly on schedule, within 1–2 weeks of the timetable.

Further work on the project would include:

- Using `liballocs` and `gdb` scripts to improve ‘observability’ and user experience while debugging
- Further evaluation tasks into performance and observability

Extension tasks:

- improving closure creation performance
- compilation of modules, functors and exceptions
- compilation of standard library modules

## Some example C code

```
#line 2 "tests/observability/sum.ml"
```

```
intptr_t local_func_1215(intptr_t acc_1207,value_type param_1210,  
    closure_t closure_obj_1214){closure_t go_1206;go_1206=  
    TO_CLOSURE(closure_obj_1214[(TO_INT(*(closure_obj_1214))-1]));
```

```
#line 2 "tests/observability/sum.ml"
```

```
intptr_t ifelse_return_1216;if (UNBOX_INT(param_1210)){variable_type  
    field_access_1217;field_access_1217=UNBOX_BLOCK(param_1210)  
    [2];intptr_t let_return_1218;{{value_type xs_1209;xs_1209=  
    TO_VALUE(field_access_1217);variable_type field_access_1219;  
    field_access_1219=UNBOX_BLOCK(param_1210)[1];intptr_t  
    let_return_1220;{{intptr_t x_1208;x_1208=TO_INT(  
    field_access_1219);
```

```
#line 3 "tests/observability/sum.ml"
```

```
#line 3 "tests/observability/sum.ml"
```

```
intptr_t binop_result_1221;binop_result_1221=(acc_1207+x_1208);  
    intptr_t temp_1222;temp_1222=binop_result_1221;value_type  
    temp_1223;temp_1223=xs_1209;intptr_t apply_result_1224;  
    apply_result_1224=((intptr_t(*) (intptr_t,value_type,closure_t))  
    ((intptr_t(*) (intptr_t,value_type,closure_t))TO_FUNC(go_1206[
```