

Lecture 05 Assignments

1. What is a *semaphore*? Complete the semaphore solution of the **bounded buffer producer-consumer** problem by filling the blanks of the given *producer* and *consumer* structures:

A **bounded buffer** with *n* locations;

Semaphore **mutex** initialized to the value 1;

Semaphore **full** initialized to the value 0;

Semaphore **empty** initialized to the value *n*;

Producer process

```
do {      produce an Item;

    1.1 -----

    1.2 -----

        add item to the buffer; //Critical Section

    1.3 -----

        signal (full); // signal to consumer that the buffer is full

} while (TRUE);
```

Consumer process

```
do {

    1.4 -----

    1.5 -----

        remove an item from the buffer; //Critical Section

        signal (mutex); // signal to producer that the mutex is free

    1.6 -----

} while (TRUE);
```

- 2). Complete the semaphore solution of *Readers priority situation* of **Readers-Writers** synchronization problem by filling in the blanks of the structure of the *Readers process* based on the following data:

- i. Dataset
- ii. Semaphore **rw_mutex** initialized to 1
- iii. Semaphore **mutex** initialized to 1
- iv. Integer **read_count** initialized to 0

Readers process

```
do {

    //first finding readers using mutex

2.1 -----
    read_count++; // find readers

    if (read_count == 1) //if at least one reader

        wait(rw_mutex); // then a writer should wait

2.2 -----

    /* reading is performed */

2.3 -----

    read_count--; // reading by readers
    if (read_count == 0) // if no more readers

2.4 -----

    signal(mutex); // signal 'mutex' to synchronized writers

} while (TRUE);
```

- 3). What is a Critical Section (CS)? How would the *semaphore* solve the issue(s) of the CS in a process synchronization problem?
- 4). How does an OS recognize the user-level threads for its execution? Describe the importance of **Light Weight Processes (LWPs)** in this scenario.
- 5). What are the two Inter-Process Communication (IPC) models? What are the strengths and weaknesses of the two approaches?

6). Identify the nature of the process structure, including its IPC model, which is shown below:

```
while (true)
{
    if (counter == BUFFER_SIZE)
        /* do nothing */

    Buffer[i] = next_item;

    in = (in + 1) % BUFFER_SIZE;

    counter++; }
```

7). The execution sequence of producer and consumer processes in a multiprogramming system is shown in the **Figure** below (where the counter is a shared variable for both the producer and consumer processes). Based on the figure, answer the following:

7.1) Check whether any **race condition** occurs in the interleaved execution of processes. Describe its reason(s).

7.2) Is this a process synchronization problem? Why?

Time	Process	Register-counter Status	Value
T ₀	producer	<i>register</i> ₁ = counter	<i>register</i> ₁ = 5
T ₁	producer	<i>register</i> ₁ += 1	<i>register</i> ₁ = 6
T ₂	producer	counter = <i>register</i> ₁	counter = 6
T ₃	consumer	<i>register</i> ₂ = counter	<i>register</i> ₂ = 6
T ₄	consumer	<i>register</i> ₂ -= 1	<i>register</i> ₂ = 5
T ₅	consumer	counter = <i>register</i> ₂	counter = 5
T ₆	producer	<i>register</i> ₁ = counter	counter = 5

8). What is the meaning of the term **busy waiting**? What other kinds of waiting are there in an OS? Can busy waiting be avoided altogether? Explain your answer.

9). Show that if the **wait()** and **signal()** semaphore operations are not executed atomically, then mutual exclusion may be violated.

10). The implementation of **mutex locks** suffers from **busy waiting**. Describe what changes would be necessary so that a process waiting to acquire a **mutex lock** would be blocked and placed into a waiting queue until the lock became available.