

Class 17 Plots

Trinity Lee A16639698

November 28, 2023

```
file_path <- "mm-second.x.zebrafish.tsv"
```

```
# Read the TSV file into a data frame
```

```
data <- read.table(file_path, header = TRUE, sep = "\t")
```

```
## Warning in scan(file = file, what = what, sep = sep, quote = quote, dec = dec,  
## : number of items read is not a multiple of the number of columns
```

```
# Display the first few rows of the data
```

```
head(data)
```

```
##      NP_598866.1 XP_009294521.1 X46.154 X273 X130 X6 X4 X267 X420 X684 X1.70e.63  
## 1 NP_598866.1 NP_001313634.1 46.154 273 130 6 4 267 476 740 4.51e-63  
## 2 NP_598866.1 XP_009294513.1 46.154 273 130 6 4 267 475 739 4.69e-63  
## 3 NP_598866.1 NP_001186666.1 33.071 127 76 5 4 126 338 459 5.19e-12  
## 4 NP_598866.1 NP_001003517.1 30.400 125 82 4 4 126 344 465 2.67e-11  
## 5 NP_598866.1 NP_001003517.1 30.645 62 41 2 53 113 43 103 4.40e-01  
## 6 NP_598866.1 NP_956073.2 34.444 90 56 3 40 126 527 616 1.70e-10  
##      X214  
## 1 214.0  
## 2 214.0  
## 3 67.8  
## 4 65.5  
## 5 33.9  
## 6 63.2
```

```
colnames(data) <- c("qseqid", "sseqid", "pident", "length", "mismatch", "gapopen", "qstart", "qend", "sstart", "send", "eval", "bitscore")
```

```
# Display the first few rows of the data
```

```
head(data)
```


```
##      qseqid      sseqid pident length mismatch gapopen qstart qend sstart  
## 1 NP_598866.1 NP_001313634.1 46.154 273 130 6 4 267 476  
## 2 NP_598866.1 XP_009294513.1 46.154 273 130 6 4 267 475  
## 3 NP_598866.1 NP_001186666.1 33.071 127 76 5 4 126 338  
## 4 NP_598866.1 NP_001003517.1 30.400 125 82 4 4 126 344  
## 5 NP_598866.1 NP_001003517.1 30.645 62 41 2 53 113 43  
## 6 NP_598866.1 NP_956073.2 34.444 90 56 3 40 126 527  
##      send      eval bitscore  
## 1 740 4.51e-63 214.0  
## 2 739 4.69e-63 214.0  
## 3 459 5.19e-12 67.8  
## 4 465 2.67e-11 65.5  
## 5 103 4.40e-01 33.9
```

```
## 6 616 1.70e-10 63.2
```


```
bitscore_values <- data$bitscore
```

```
# Create a histogram with breaks=30
```

```
hist(bitscore_values, breaks = 30, col = "skyblue", main = "Histogram of bitscore values",  
      xlab = "Bitscore", ylab = "Frequency")
```




```
plot(data$pident * (data$qend - data$qstart), data$bitscore)
```



```
library(ggplot2)
ggplot(data, aes(pident, bitscore)) + geom_point(alpha=0.1)
```

```
## Warning: Removed 1 rows containing missing values (`geom_point()`).
```



```
ggplot(data, aes((data$pident * (data$qend - data$qstart)), bitscore)) + geom_point(alpha=0.1) + geom_s
```

```
## Warning: Use of `data$pident` is discouraged.
## i Use `pident` instead.

## Warning: Use of `data$qend` is discouraged.
## i Use `qend` instead.

## Warning: Use of `data$qstart` is discouraged.
## i Use `qstart` instead.

## Warning: Use of `data$pident` is discouraged.
## i Use `pident` instead.

## Warning: Use of `data$qend` is discouraged.
## i Use `qend` instead.

## Warning: Use of `data$qstart` is discouraged.
## i Use `qstart` instead.

## `geom_smooth()` using method = 'gam' and formula = 'y ~ s(x, bs = "cs")'
## Warning: Removed 1 rows containing non-finite values (`stat_smooth()`).
## Warning: Removed 1 rows containing missing values (`geom_point()`).
```

