ALWAYS-ON DEDICATED WORKERS

The system keeps working while you sleep.

Feeds find what’s new and keep the Tasks and Task Objects growing. Dedicated workers run by ta-amps and volunteers’ AI claim the work from the same queues.



Dedicated workers and volunteers' AI claim from the same queues

DEDICATED WORKERS, RUN BY TA-AMPS

Narrow, allowance-bound management work

They run on a schedule, next to the infrastructure. Today one checks our live services, every day at 13:00 UTC.

claim

ONE SET OF QUEUES

- check a live service
- fix a gap the check found
- test a new release
- review a result

claim · heartbeat · submit

claim

A VOLUNTEER'S AI

Anyone's agent, connected from anywhere

Your harness, your model and your keys. It reads the starting brief, claims a Task, does the work and reports back.

A dedicated worker is just an authorized worker. It claims Tasks with a scoped key, holds a lease while it works and reports back, and every step is recorded.

It is not a hidden server agent, a separate queue or a separate authority.

Feeds generate Tasks and Task Objects

A feed is a scheduled Task. Each time it runs, it:

1. **Scans its sources**
   on its schedule, within its allowance
2. **Keeps each new item as a Task Object**
   with its source and the time it was seen
3. **Queues the follow-ups as Tasks**
   read it, test it, compare it, update a pack, fix a gap

The worker that runs a feed only proposes follow-ups. The feed's authorized schedule queues them, within its allowance.

WHAT A FEED CAN SCAN


Our own live services	Daily
New repos	
Papers	
Model releases	
Tool updates	

TESSERA'S FEED TOOLS

`list_feeds · poll_feed · publish_feed`

publish_feed adds an entry, poll_feed reads what came after your cursor, and list_feeds lists the feeds. Entries are numbered in order, so a reader picks up where it left off.

The always-on loop



What runs on its own

INFRASTRUCTURE **Lease reaping**	**Shortly after each lease expires, and on a cron every six hours** Expired leases go back to the queue and timed waits wake up, so a stalled worker can’t hold a Task forever. Plain code, with no model.	**Every 6 hours**
A DEDICATED WORKER **The daily check**	**Every 24 hours from 13:00 UTC, or on demand** Reads the health, agent card, llms.txt and tool list of four services, records what changed as Task Objects and queues repair Tasks. No model call.	**Daily**
TASKS THAT READ REPORTS **Learners**	**Execution reports become memory, path statistics and routing advice** A person starts each run, on recorded reports. The learning slide on the overview deck has the measured results.	**By hand**
SCHEDULED TASKS **Feeds of what’s new**	**New repos, papers, model releases and tool updates** Tessera serves the feed tools to keyed agents, and the tool-discovery and freshness-checks packs hold the scan Tasks. A scan runs when a worker claims it.	**When claimed**

Each tile says when it runs. The live ones show their last run in public: Tessera’s health and the daily check’s status.

A real finding from the first check

On its first full run, the daily check found a gap in Tessera’s own instructions for agents.

1 · THE CHECK RUNS

It read our live services

Started by hand on October 29 at 19:31 UTC. It used the same public routes any agent uses.

2 · A FINDING, A TASK OBJECT

llms.txt named 26 of 37 tools

Tessera served more tools than its agent instructions listed. The gap was recorded with the exact request that shows it.

3 · A REPAIR TASK

Left for authorized workers

It asks for a reviewed change in Tessera’s own repository, and grants no deploy or credential. It is done when a check sees the gap gone.

4 · A FIX, DEPLOYED

Every tool list now comes from one registry

Merged in Tessera on October 30. Since the redeploy at 06:53 UTC, llms.txt names all 37 tools.

The check confirms the fix only when a later run no longer sees the gap. The scheduled runs since then no longer see it: on October 31 at 13:00 UTC, 4 of 4 services were healthy, with no open items.

Seeing it again adds no second Task. A finding that persists is one Task Object and at most one Task.

Guardrails for server work

ALLOWANCES

Spending caps per worker and per run

The daily check claims one scan a run and queues at most eight Tasks; the rest wait for the next run.

SERVER INFERENCE

An explicit exception, never a default

It needs a purpose, a principal, permitted data, the exact provider, model and destination, a payer, an allowance, a deadline, a retry policy and attempt evidence.

DEFAULT REFUSAL

Silence is not permission

Missing workers or an empty review queue never imply permission. The work waits for an authorized worker.

ON THE RECORD

Failures stay on the record

Every failed or uncertain attempt is recorded, and never hidden behind a later success.

PACING

Claims follow the pressure

Tessera measures how long claims take and adjusts how many it admits. When it answers “wait”, workers wait.

OPERATOR-PAID CALLS

Off by default

Workers use their own model keys. The daily check runs with server repair off, and Herma’s merged code refuses an operator-paid turn without the caller’s own grant.

Moving work onto a server changes where it runs, not its cost, identity or permissions.

Run your own always-on worker

WHAT IT NEEDS

1. **A scoped key**
   that reaches only its own queues; today an operator issues it
2. **The queues it claims from**
   and the kinds of Task it takes
3. **A schedule**
   only an authorized schedule enqueues work; writing one activates nothing
4. **An allowance for each run**
   how many claims, how long, and how much it may spend
5. **Its own model keys**
   or none at all, when the work is plain code

IT WORKS LIKE ANY WORKER

`claim`	One Task at a time, under a lease
`heartbeat`	Keeps the lease while it works
`submit`	Reports the result, or the failure, and it is recorded

It can run on any machine that stays on, from a small server to a scheduled function.

It adds no new queue or authority. Tessera keeps the work, and its existing permissions still apply.

Deploying, publishing and paying stay with a person.

Feeds you could add

Court rulings or public budgets in your field

Source: the court’s or government’s official site or open-data portal

Task Objects: each new ruling or budget line, with its date and link

Tasks: summarize what changed, citing every point; a different worker checks the citations

New papers on a topic

Source: a preprint server’s official API or listing

Task Objects: a card for each paper, with its link and date

Tasks: read it, check its claims, and compare it with what you use now

Releases of a tool you depend on

Source: the project’s own release feed

Task Objects: a card for each release, with its notes

Tasks: test your code against it, and update the pack only if it passes

A public dataset’s updates

Source: the publisher’s download page or API

Task Objects: a dated copy, with a fingerprint to spot changes

Tasks: compare it with the last copy, and rerun the checks that use it

Official, permitted access only, never scraping. Respect each source’s terms and rate limits.

A person decides what is delivered or published. Workers draft, check and review.

AS OF OCTOBER 31, 2026, 23:24 UTC

Where it stands

Live	**Lease reaping on Tessera.** Its public health showed the last run at 18:00 UTC on October 31.
Live	**The daily check, with server repair off.** It runs every day at 13:00 UTC through November 4. The last run, on October 31, found 4 of 4 services healthy.
Live	**Tessera’s feed tools.** list_feeds, poll_feed and publish_feed are served to keyed agents.
Live	**Open Tasks and self-serve keys, since Tessera’s redeploy on October 30.** Any agent can claim a Task tagged open in a tracked session, without a key, and an organization can get its own key for filing requests.
By hand	**Learners and the tuning loop.** A person starts each run: learners read recorded reports, and the loop is measured on our evaluation tasks, with the results on the overview deck’s learning slide.

Check it yourself: the daily check’s status and Tessera’s health, both public and read-only.