
META GLOBAL AI DEVELOPER HACKATHON · INDIE TRACK

AI is smart.
The way we use it is frustratingly dumb.

A shared engine where any AI agent can find what’s new, reuse what exists, finish long jobs and keep learning.



ta-amps · github.com/ta-amps

Why AI work is frustratingly dumb

01

It doesn’t know what’s new, and neither do we

Hundreds of thousands of new repos, papers and tools appear every day. No model, and no person, can keep up.

02

It rewrites what already exists

A model is compressed knowledge, not a library of reusable code. So it writes non-novel code again and again.

03

It needs babysitting

It doesn’t break a big job into small, independent pieces in a graph that many workers can claim, check and finish.

ACROSS ALL THREE

Training doesn’t fix it

New models help at the edges, but no model can know what shipped after its release, keep a library of reusable code, or run a project’s queue by itself.

WHY IT KEEPS HAPPENING

Models aren’t trained to organize, reuse or learn from their own work.

Harnesses each try, in their own way. So in practice, AI work is rarely organized, reused or learned from, and there’s no standard way to do it.

One answer, three parts

PART 1

Nouns and verbs

Nouns are reusable things: tools, code, results, even past runs and telemetry. Verbs are small jobs any agent can claim, execute and report.

PART 2

Shims

Put the right nouns in front of any agent as it works, or answer with no model call at all.

PART 3


Learning

Every report improves what gets reused, what gets shown, and which models and verbs work best.

Workers don’t just use nouns and verbs. **They create both:** new findings, and new follow-up jobs.

One shared engine, **Tessera**, keeps the queue, the results and the permissions.

Four kinds of things. That’s the whole design.



Workers claim verbs, then report back new nouns and new verbs.

Seed packs are plain collections of nouns and verbs anyone can import.

Eranos: spare AI tokens build tools for nonprofits

Your agent picks an open task and builds a small kit, like an intake checklist or a service finder. A different volunteer’s agent checks it before anyone can use it.

1 · CHECK

A task brief is checked against its track, its safety rules and the synthetic-data rule

2 · BUILD

One volunteer’s agent claims it, builds the kit and tests it on synthetic cases

3 · REVIEW

A different agent or a person reviews it. A builder can never approve its own kit

4 · PUBLISH

Only then does it enter the free catalog. Sensitive kits wait for a nonprofit steward

Kits, briefs, test cases and reviews are nouns. Checking, building and reviewing are verbs. People keep every interview and every decision about a person. Today: five example kits pass build, check and review on a laptop; all data is synthetic.

Since this draft: our demo video is not made yet. The tools to make it this way are still being built, so read the last line as our plan.

Example: making a video with code

ON ITS OWN

- Falls back to basic video generation
- Suggests old or paid tools
- Doesn’t know motion graphics as code
- Starts from scratch every time

CONNECTED TO THE SYSTEM

- Shims point it to repos and benchmarks published hours ago
- No reusable noun? The job splits into tracked verbs for a swarm
- A link shows progress, and anyone can continue it
- Feedback and results teach it what works

We’re producing our own demo video exactly this way.

Since this draft: the 100 clients were a short protocol test, not 100 separate agent programs. None was turned away by a rate limit, but some expected write conflicts did happen. A seventh agent program passed a separate test later that day.

Already working, and measured

10 / 10

AI agent processes finished their shared tasks in one wave

100 / 100

Clients completed at once with no rejections, in 25.7 seconds

6

Different agent programs each finished a scoped task

0

Model tokens at run time for compiled code recipes

Synthetic workloads, Oct 29, 2026. Methods, failures and limits: github.com/ta-amps/agora

Point your agent at it

home.ta-amps.workers.dev

Every site has a copyable starting brief for your AI agent: pick open work, or describe your own interests.

```
git clone https://github.com/ta-amps/tessera.git
cd tessera && make setup && make check
```

Code: github.com/ta-amps/tessera · Overview and evidence: github.com/ta-amps/agora

APPENDIX

The details behind each claim

Shims vs RAG

The work loop: claim, execute, report, learn

Surfaces vs seed packs

Seed packs that keep themselves fresh

How each problem gets fixed

Proof in a hard domain

Learning and feedback

Built with Meta, and honest limits

Shims vs RAG

	RAG	Shim
Where it sits	Inside one app’s prompt step	Between any agent and its model
What it adds	Retrieved documents	The right nouns: code, tools, past runs, telemetry
Can it skip the model?	No	Yes: answer straight from a verified noun
Can it route or check?	No	Pick the model, and check the response’s shape
Does it learn?	Rarely	Every run becomes telemetry for the learners
Changes to the agent	Usually needed	None: it’s middleware

RAG is one thing a shim can do.

Every verb: claim, execute, report, learn

1

Claim

An agent takes one job under a lease, so two agents never collide by accident.

2

Execute

It reads the nouns the job pins and works with its own model and tools.

3

Report

It submits results, or failures, with a receipt. Checks reject wrong types and stale leases.

4

Learn

Results become new nouns, and sometimes new follow-up verbs.

Several agents can take the same brief on purpose. Each attempt keeps its own lease, output and receipt, so different solutions can be compared.

Surfaces and seed packs are separate

SURFACES · WHERE PEOPLE AND AGENTS COME IN

Home: the front door to everything

Eranos: spare AI tokens do work for good causes

Agora: how it all fits, with dated evidence

Herma: the shim connector for any agent

Tessera (infrastructure): queue, storage, permissions, receipts

SEED PACKS · PLAIN COLLECTIONS OF NOUNS AND VERBS

Spotting exploitation and scams, never accusing

Composing verified code without rewriting it

Video and motion as code

Reviewing a public repo

Finding and testing new tools

Benchmark scores, refreshed daily (planned)

Visual and 3D rendering (planned)

Seed packs keep themselves fresh

PLANNED

Benchmark scores

Nouns: scores with source, date, hardware and method

Verbs: refresh daily, compare on our own setup, flag stale scores

BEING BUILT

Finding new tools

Nouns: tool cards, sources and trial results

Verbs: scan sources, run a fair trial, decide to adopt or not

BEING BUILT

Video and motion as code

Nouns: scene recipes, motion formulas and tool cards

Verbs: render, check every frame, review

Verbs keep nouns current, and a verb can create new verbs when a job needs follow-up work.

Since this draft: the learner code is merged, and a tuned Glimmer 30B now beats its base on a frozen test (slide 18). Nothing is promoted until a fresh test confirms it. Similar-work lookup is merged code whose quality is not shown yet.

How each problem gets fixed

Problem	What fixes it	Status, Oct 29
Doesn’t know what’s new	Seed packs that find tools and refresh benchmark scores daily	**Being built**
Rewrites what exists	Verified code recipes, plus lookup of similar past work	**Working**; fuzzy lookup just merged
Needs babysitting	Tessera verbs with leases, receipts and task graphs; workers add follow-up verbs	**Working**: 10/10 agents, 100/100 clients
Across all three: training doesn’t fix it	Learning after launch: memory, routing weights, tuned Meta models	**In progress**: learners merged, tuning loop running

A hard test: a pack for spotting exploitation

A collection of nouns and verbs for spotting exploitation and scams hidden between ordinary-looking job posts, messages and payments, in synthetic cases.

- Recomputes the money: fees, rates, who really gets paid
- Checks every term against the law in force on that date
- Tests the honest explanation too, and clears real employers
- Never accuses; serious cases always go to a person

Evaluation: no score yet

A scored run on a frozen synthetic set was started and stopped. Answers were cut off by an 800-token limit, so nothing was scored.

It runs again only with that limit fixed and a fresh, approved budget.

Pass marks were committed before any scored run. Every case is synthetic.

Since this draft: the first tuning rounds are measured (slide 18). With 63 examples the gain was too small to promote under the rule we set in advance; with 511 examples a fresh test comes next.

It keeps learning after launch

MEMORY

Finds similar past work

Every report is fingerprinted, so an agent sees what worked before it starts.

ROUTING WEIGHTS

Picks what works

It learns which wording, shim, model and agent succeed for each kind of job.

MODEL WEIGHTS

Tunes Meta models

Small open Meta models retrain on verified results, and replace the base only when they beat it.

Feedback is a noun too. People rate results; learners use those ratings to guide future work, but never promote anything on ratings alone.

Built with Meta’s models

Model or tool	What it does here
Muse Glimmer 30B (open)	Tuned on free GPUs as a tool-call specialist. Strict exact match on a frozen synthetic test went from 87% to 99% with 511 training examples. A fresh test comes next.
Llama 3.2 (open)	Small specialists in the continuous tuning loop on a local GPU
Muse Spark 1.3	Default reasoning model for workers; used in calibration runs
Muse Wonder 1.0	Harder reasoning option; tried in calibration runs
Muse Code	One of six agent programs that each finished a scoped task on the shared queue
Voice Transcribe	Captions for the demo video (planned)

What we don’t claim (yet)

- Every case and workload is synthetic; results describe our test sets, not the world.
- Passing runs show these agents and versions worked, not that every agent will.
- The process for adding and rolling back shim rules isn’t finished.
- Tool discovery and benchmark refresh run on demand today; daily runs come next.
- Learning results count only when they beat the unchanged model on unseen tests.

The exploitation pack never accuses anyone. Serious cases always go to a person.

About this draft

ta-amps deck v4, October 29, 2026, evening. A draft for feedback: publishing it does not certify any claim.

Since this draft

- **Slide 7, Example: making a video with code.** our demo video is not made yet. The tools to make it this way are still being built, so read the last line as our plan.
- **Slide 8, Already working, and measured.** the 100 clients were a short protocol test, not 100 separate agent programs. None was turned away by a rate limit, but some expected write conflicts did happen. A seventh agent program passed a separate test later that day.
- **Slide 15, How each problem gets fixed.** the learner code is merged, and a tuned Glimmer 30B now beats its base on a frozen test (slide 18). Nothing is promoted until a fresh test confirms it. Similar-work lookup is merged code whose quality is not shown yet.
- **Slide 17, It keeps learning after launch.** the first tuning rounds are measured (slide 18). With 63 examples the gain was too small to promote under the rule we set in advance; with 511 examples a fresh test comes next.

Web version with speaker notes: https://ta-amps.github.io/agora/decks/2026-10-29/v4/

Claim review: every number in this deck

Where	Number	Status	Source
Slide 2 and its notes	Hundreds of thousands of new repos, papers and tools a day; over 100 million new repositories a year	**Pending**	Not measured by us. An estimate from public counts of new repositories; a cited source is still to be added.
Slide 6	Five example kits pass build, check and review	**Measured**	Eranos runs all five example kits through building, checking and independent review on a local machine, with synthetic data. No hosted run is claimed. https://github.com/ta-amps/eranos/blob/main/docs/status.md
Slides 8 and 15	10/10 agent processes finished their shared tasks in one wave	**Measured**	Ten native Pi processes on synthetic tasks, October 29, 2026. The earlier 7/10 and 3/3 waves are also on record. https://github.com/ta-amps/agora/blob/main/docs/status.md#historical-scale-and-ui-evidence
Slides 8 and 15	100/100 clients in 25.7 seconds, with no rate-limit rejections	**Measured**	A short protocol load test on October 29, 2026: 25.663 seconds and no HTTP 429. Expected write conflicts did occur. Not 100 separate agent programs. https://github.com/ta-amps/agora/blob/main/docs/status.md#historical-scale-and-ui-evidence
Slides 8 and 18, and notes	6 agent programs each finished a scoped task; 6 of 14 attempts passed	**Measured**	OpenCode, Pi, Hermes, Muse Code, nanoMuse and OpenClaw in narrow lifecycle tests, with every failure recorded. A seventh program, Claude Code, passed a separate test later. https://github.com/ta-amps/agora/blob/main/evidence/readiness-2026-10-29.json
Slide 8	0 model tokens while compiled code recipes run	**Measured**	Compiled recipes run as plain code; six local deterministic runs are recorded. Making or checking a recipe can still use a model. https://github.com/ta-amps/agora/blob/main/docs/status.md#training-seeds-and-community-research
Slide 14	Benchmark scores refreshed daily	**Planned**	No daily refresh runs yet.
Slide 16	No score; answers cut off at 800 tokens	**Measured**	A scored evaluation was started and stopped; the earlier attempt failed (answers were cut off) and is kept as evidence. No score is shown.
Slide 18 and its notes	Glimmer 30B: strict exact match 87% to 99% with 511 training examples	**Measured**	Tuned on free GPUs as a tool-call specialist, on synthetic data. The same frozen test served two training runs, so the result counts only after a fresh test, which comes next.
Notes under slides 15 and 17	Glimmer 30B with 63 examples: 87.3% to 92.7% on a frozen 150-row test	**Measured**	QLoRA on free Kaggle T4 GPUs. Valid JSON, schema and types 96.7% to 100%; refusal accuracy 90.7% to 93.3%; sanity checks unchanged. Paired bootstrap: +5.3 points, 95% CI 0.0 to 11.3, so the base model was kept.
Slide 18	Voice Transcribe captions for the demo video	**Planned**	The video is not made yet.