

Section 11 - Forms

v-model Vs. Ref

If the `type='number'` of an input field is `number` then v-model automatically converts the input string to number and return it, while ref will return string as usual everything doesn't matter type of an input field.

Form Handling

Using `v-model`, we can easily handle input fields with type text, number, checkboxes (group), radios, and checkbox (single)

The screenshot displays a Vue.js development environment with three main panels: code editor, form preview, and console.

Code Editor (Left): Shows the `TheForm.vue` file. It includes a `data` object with `userName`, `userAge`, `referrer`, `interest`, `how`, and `terms`. The `interest` array contains `'news'` and `'tutorials'`. The `how` radio button has a `value` of `'videos'`. The `terms` checkbox has a `value` of `'news'`. The `formHandler` method is also defined.

Form Preview (Right): Shows the rendered form. It includes a text input for `Tabish`, a number input for `11`, a dropdown for `Word of mouth`, a group of checkboxes for `News`, `Tutorials`, and `Nothing`, a group of radio buttons for `Video Courses`, `Blogs`, and `Other`, and a checkbox for `Do you agree with terms?`. A `Save Data` button is at the bottom.

Console (Bottom Right): Shows the output of the `formHandler` method. It displays the `interest` array as `Proxy(Array) {0: 'news', 1: 'tutorials'}` and the `terms` checkbox as `true`.

Annotations:

- 1:** "Form Handling is easy with v-model attribute"
- 2:** "We use `userName` for input with type text, `userAge` for input with type number, `referrer` for input with type combobox ('newspaper' as default), `interest` for input with type checkbox (multiple) has same name and id, `how` for input with type radio (to not select any option we set null), `terms` for input with checkbox (single) as boolean"
- 3:** "VueJs provides grouped checkbox values in array, but for that default should be type array [], and it puts values inside it, same with radios it provides value"

Custom Component Controlling

Using `v-model` on our custom component means we will get `modelValue` and `update:modelValue` in our custom component. This comes handy to send value when we submit form.

```
VueLearning > Section11 > forms-01-starting-setup > src > components > RatingControl.vue > {} script > default > data
1 <template>
2 <section>
13 </ul>
14 </section>
15 </template>
16
17 <script>
18 export default {
19   props: ['modelValue'],
20
21   emits: ['update:modelValue'],
22
23   data() {
24     return {
25       activeOption: this.modelValue,
26     };
27   },
28 }

```

3 That's true, using v-model on our custom component means we get modelValue and update:modelValue as prop and emit function.

```
VueLearning > Section11 > forms-01-starting-setup > src > components > TheForm.vue > {} template > form > div > RatingControl
36 <template>
37 <form @submit.prevent="formHandler">
87 <div class="form-control">
109 <div>
115 <input type="text" v-model="how" />
116 </div>
117 <label for="how-other">Other</label>
118 </div>
119 <div>
120 <div>
121 <input type="checkbox" name="terms" id="terms" v-model="terms" />
122 <label for="terms">Do you agree with terms?</label>
123 </div>
124 <div>
125 <RatingControl v-model="rating"></RatingControl>
126 </div>
127 </div>

```

1 Just like v-if and v-for available on every component, we can also use v-model on custom component to control the component

2 As mentioned before, v-model is semantic sugar for v-bind:value and v-on:input, so this means using v-model on our custom component, we should get a custom value and custom input event

localhost:8080

How do you hear about us?

Newspaper

What are you interested in?

☐ News

☐ Tutorials

☐ Nothing

How do you learn?

☐ Video Courses

☐ Blogs

☐ Other

☐ Do you agree with terms?

Poor Average Great

Save Data

Elements Console Memory Sources Network

top Filter

Default levels 1 Issue

cjs.js?l=/node_module_e=script&lang=js:21

cjs.js?l=/node_module_e=script&lang=js:22

cjs.js?l=/node_module_e=script&lang=js:23

cjs.js?l=/node_module_e=script&lang=js:24

newspaper

Proxy(Array) {}

cjs.js?l=/node_module_e=script&lang=js:25

null

cjs.js?l=/node_module_e=script&lang=js:26

false

cjs.js?l=/node_module_e=script&lang=js:27

average

Relevant data is sent to Google