CSS Styling and Linking

Section 1: Learn

Linking a CSS Stylesheet

- The <link> tag is used to link an external CSS file to an HTML document.
- It is placed inside the <head> section of the HTML file.
- Example:

```
<link rel="stylesheet" href="styles.css">
```

Inline CSS

- CSS rules are applied directly within an HTML tag using the style attribute.
- Example:

```
<p style="color: red;">This is a red paragraph.</p>
```

Internal CSS

- Defined inside a <style> tag within the <head> section of an HTML document.
- Example:

```
<style>
 p {
   color: blue;
 }
</style>
```



Why Switch to External CSS?

- External CSS keeps the HTML clean and improves maintainability.
- Styles can be reused across multiple pages.

External CSS

- Styles are stored in a separate .css file.
- Example:

```
body {
  font-family: Arial, sans-serif;
  background-color: lightgray;
}
```

Font Styling and Sources

- **Font Families**: Arial, Verdana, Times New Roman.
- **Font Sources**: Google Fonts, System Fonts.
- Example using Google Fonts:

```
<link rel="stylesheet"
href="https://fonts.googleapis.com/css2?family=Roboto&display=swap">
```

CSS Selectors

- **Combinator Selectors**:
    - **Descendant ( )**: Selects all children inside a parent.

```
div p {
  color: blue;
}
```

    - **Child (>)**: Selects only direct children.

```
div > p {
  font-weight: bold;
}
```

- **Attribute Selectors**:
    - [attribute]: Selects elements with a specific attribute.

```
input[type="text"] {
  border: 1px solid black;
}
```

    - [attribute="value"]: Matches elements with the exact attribute value.

Section 2: Practice

Task 1: Link an External CSS File

1. Create a styles.css file.
2. Apply basic styles like font-family and background color.
3. Link it using the <link> tag in the HTML file.

Task 2: Use Different Selectors

1. Write CSS rules using combinator and attribute selectors.
2. Create different styles for headings and paragraphs.

Example:

```
<!DOCTYPE html>
<html lang="en">
<head>
   <link rel="stylesheet" href="styles.css">
</head>
```

```
<body>
    <div>
        <p>This is inside a div.</p>
    </div>
    <p>This is outside a div.</p>
</body>
</html>

div p {
    color: green;
}
p {
    font-size: 16px;
}
```

Section 3: Know More

FAQs

Q1: What is the advantage of using external CSS?

- It helps separate content from design and allows for easier maintenance.

Q2: Can we use multiple CSS files in one HTML file?

- Yes, multiple <link> tags can be used to include multiple stylesheets.

Q3: How do I change fonts in CSS?

- Use the font-family property with a system or imported font.

Q4: What is the difference between internal and inline CSS?



- Internal CSS applies to the entire document, while inline CSS applies only to a single element.

Q5: Why use attribute selectors?

- They allow styling elements based on their attributes without using classes or IDs.

Mastering CSS linking and selectors will help you build structured and maintainable websites.