

# ***Trend Setter***



**HD19**  
***Power Steering***



## SPECIFICATIONS

Model	HD 19 BS-III	HD 19 BS-IV
Engine & Displacement	SLT3 & Numeral, 3455 cc	SLT4 & Numeral, 3455 cc
Type	In Line four Cylinder Direct Injection	In Line four cylinder Common Rail Direct Injection
	Diesel Turbo Charger with Intercooler	
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm $\pm$ 50
Clutch	Single plate Diaphragm Type, Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Power Steering	
Brakes	Air Brake	
Suspension	Semi Elliptical Type Multi Leaf Spring	
Wheels & Tyres	8.25" X 16" - 16 PR	
No of Tyres	6+1	
Wheelbase (mm)	4760	
Min. Turning Circle Diameter in m	9.4	
Front Axle Weight (kg)	3370	
Rear Axle Weight (kg)	6880	
Kerb Weight (kg)	3500	
Max. Permissible GVW (kg)	10250	
Cargo Box Dimensions (LXBXH) in mm		
Variants		
Cab Highdeck Loadbody	5813 X 2080 X 570	
Cab Halfdeck Loadbody	5813 X 2080 X 1030	
Cab Semideck Loadbody	5813 X 2080 X 1695	

**NOTE :** As our policy is that of continuous improvement, above specifications may change without notice.



## SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A,  
Chandigarh - 160 135.  
Ph : 0172-2647700. Fax : 0172-2615111.  
E-mail : salesadm@smlisuzu.com  
www.smlisuzu.com

Authorised Dealer :