

The Truck Designed with Two Decades of Experience



SARTAJ
HG72

SPECIFICATIONS

Model	Sartaj HG 72 BS-III	Sartaj HG 72 BS-IV
Engine & Displacement	SLT3 & Numeral, 3455 cc	SLT4 & Numeral , 3455 cc
Type	In Line four Cylinder Direct Injection	In Line four Cylinder Common Rail Direct Injection
	Diesel Turbo Charger with Intercooler	
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm ± 50
Clutch	Single plate Diaphragm Type , Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Mechanical /Power Steering (Optional)	
Brakes	Hydraulic Vaccum assisted	
Suspension	Semi Ellipitical Type Multi Leaf Spring	
Wheels & Tyres	8.25" X 16" - 16 PR	
No of Tyres	4+1	
Wheelbase (mm)	3335	
Min. Turning Circle Diameter (m)	6.4	
Max. Permissible GVW (kg)	7200	
Front Axle Weight (kg)	3500	
Rear Axle Weight (kg)	3700	
Kerb Weight (kg)	2640	2730
Cargo Box Dimensions (LXBXH) (mm)		
Variants		
Cab Semideck Loadbody	3740 X 2080 X 1030	4260 X 2080 X 1030
Cab Highdeck Loadbody	3740 X 2080 X 1695	4260 X 2080 X 1695
Cabin Chassis	Available	Available

NOTE : As our policy is that of continuous improvement, above specifications may change without notice.

Features

- Available in BS - III & BS - IV Versions.
- Powerful Engine - Higher Pickup, Higher Torque at lower RPM, Gradeability and Fuel Efficiency.
- Heavy Duty Gear Box and Bigger Clutch - Longer Life.
- Box Type Chassis with tubular cross members - carry more load, provide better Strength and Rigidity.
- Steering with variable Gear Ratio - Less Driver Fatigue.
- Roof Ventilation, less Driver Fatigue and Better Comfort.
- Ready availability of Spares at reasonable Price.

**SML
ISUZU**



Authorised Dealer :

SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A,
Chandigarh - 160 135.
Ph : 0172-2647700. Fax : 0172-2615111.
E-mail : salesadm@smlisuzu.com,
www.smlisuzu.com