

... New thoughts, New Horizons

Legacy of High Performance Continues ...



Sartaj 5252 XM ...

Safe, dependable & perfect partner for your business



SML ISUZU

SPECIFICATIONS

Model	Sartaj 5252 XM BS-III	Sartaj 5252 XM BS-IV
Engine & Displacement	SLT HT3 & Numeral , 3455 cc	SLT4 & Numeral , 3455 cc
Туре	In Line four Cylinder Direct Injection	In Line four Cylinder Common Rail Direct Injection
	Diesel Turbo Charger with Intercooler	
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	315 Nm@1500-1750 rpm	296Nm @ 1500 rpm ± 50
Clutch	Single plate Diaphragm Type,Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Mechanical /Power Steering (Optional)	
Brakes	Hydraulic Vacuum assisted	
Suspension	Semi Elliptical Type Multi Leaf Spring	
Wheels & Tyres	7.00 " X 16" - 14 PR	
No of Tyres	4+1	
Wheelbase (mm)	2515	
Min. Turning Circle Diameter in (m)	10.15	
Max. Permissible GVW (kg)	4990	5200
Front Axle Weight (kg)	2390	2600
Rear Axle Weight (kg)	2600	2600
Kerb Weight (kg) (FSD)	2310	
Overall Length of the Truck (mm)	4489	
Cargo Box Dimensions (LXBXH) in mm		
Variants		
Cab Fixed deck Load body	2800 X 1860 X 400	
Cab Semi deck Load body	2800 X 1860 X 1030	
Cab High deck Load body	2800 X 1860 X 1695	
Cabin Chassis	Available	



Bigger Clutch Plate of 260mm Diameter, More Life



Strong Cargo Box



Large Tank of 70 Liter



Box Type Chassis, Heavy Load Capacity



Higher Gradeability



Powerful Engine of 101 HP Giving More Mileage



Very Strong Heavy Duty Axle



Oil Change on 30,000 km



Labor Free Service up to 52,000 km

Warranty

3 Years on Engine &

NOTE: As our policy is that of continuous improvement, above specifications may change without notice.

Always use SML ISUZU Genuine Spares

SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A, Chandigarh - 160 135. Ph: 0172-2647700. Fax: 0172-2615111.

E-mail: salesadm@smlisuzu.com

www.smlisuzu.com

Authorised Dealer:

