

Tremendous Power and Toughness



PRESTIGE

SPECIFICATIONS

Model	Prestige BS-III	Prestige BS-IV
Engine & Displacement	SLT3 & Numeral, 3455 cc	SLT4 & Numeral, 3455 cc
Type	In Line four Cylinder Direct Injection	In Line four Cylinder Common Rail Direct Injection
	Diesel Turbo Charger with Intercooler	
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm ± 50
Clutch	Single plate Diaphragm Type , Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Mechanical /Power Steering (Optional)	
Brakes	Hydraulic Vaccum assisted	
Suspension	Semi Elliptical Type Multi Leaf Spring	
Wheels & Tyres	7.50" X 16" - 16 PR	
No of Tyres	6+1	
Wheelbase (mm)	2815	3335
Min. Turning Circle Diameter (m)	5.5	6.4
Max. Permissible GVW (kg)	6440	6440
Front Axle Weight (kg)	2360	2360
Rear Axle Weight (kg)	4080	4080
Kerb Weight (kg)	2530	2800
Cargo Box Dimensions (LXBXH) (mm)		
Variants		
Cab Halfdeck Loadbody	3100 X 2080 X 570	3740 X 2080 X 570
Cab Semideck Loadbody	3100 X 2080 X 1030	3740 X 2080 X 1030
Cab Highdeck Loadbody	3100 X 2080 X 1695	3740 X 2080 X 1695
Cabin Chassis	Available	

NOTE : As our policy is that of continuous improvement, above specifications may change without notice.

SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A,
Chandigarh - 160 135.

Ph : 0172-2647700. Fax : 0172-2615111.

E-mail : salesadm@smlisuzu.com

www.smlisuzu.com

Authorised Dealer :



Features

- Available in BS - III & BS - IV Versions.
- Powerful Engine - Higher Pickup, Higher Torque at lower RPM, Gradeability and Fuel Efficiency.
- Heavy Duty Gear Box and Bigger Clutch - Longer Life.
- Box Type Chassis with tubular cross members - carry more load, provide better Strength and Rigidity.
- Steering with variable Gear Ratio - Less Driver Fatigue.
- Roof Ventilation, less Driver Fatigue and Better Comfort.
- Ready availability of Spares at reasonable Price.

