Sartaj 4 Tyre Truck Series Augment your Profits







MORE CARGO SPACE

POWERFUL ENGINE

FUEL EFFICIENT

LOW MAINTENANCE

MULTI PURPOSE LCVs

SPECIFICATIONS




	Sartaj HG 72	Sartaj 59 xm	Sartaj 5252 xm
Engine Description	BS-III, SLT HT3 / BS-IV, SLT4	BS-III, SLT HT3 / BS-IV, SLT4	BS-III, SLT HT3 / BS-IV, SLT4
Displacement (cc) Engine Type	3455 4-Cylinder In-line Direct Injection / Common Rail Direct Injection	3455 4-Cylinder In-line Direct Injection / Common Rail Direct Injection	3455 4-Cylinder In-line Direct Injection / Common Rail Direct Injection
	Diesel Turbo-charger with Inter-cooler	Diesel Turbo-charger with Inter-cooler	Diesel Turbo-charger with Inter-cooler
Performance			
Max. Engine Output	75 kw @ 3000 rpm / 75 kw @ 2800 rpm	75 kw @ 3000 rpm / 75 kw @ 2800 rpm	75 kw @ 3000 rpm / 75 kw @ 2800 rpm
Max. Torque	315 Nm @ 1500-1700 rpm / 296 Nm @ 1500 rpm ± 50	315 Nm @ 1500-1700 rpm / 296 Nm @ 1500 rpm ± 50	315 Nm @ 1500-1700 rpm / 296 Nm @ 1500 rpm ± 50
Transmission			
Gear Box	Synchromesh Manual 5 - Forward & 1 - Reverse	Synchromesh Manual 5 - Forward & 1 - Reverse	Synchromesh Manual 5 - Forward & 1 - Reverse
Clutch	Single Plate Diaphragm (260 mm Diameter)	Single Plate Diaphragm (260 mm Diameter)	Single Plate Diaphragm (260 mm Diameter)
Brake	Vacuum Assisted Hydraulic	Vacuum Assisted Hydraulic	Vacuum Assisted Hydraulic
Suspension	Semi-elliptical with Multi-Leaf Spring	Semi-elliptical with Multi-Leaf Spring	Semi-elliptical with Multi-Leaf Spring
Tyre / No. of Tyres	8.25' x 16' - 16 PR / 4 +1	8.25' x 16' - 16 PR / 4 +1	7' x 16' - 14 PR / 4 +1
Steering			
Mechanical/Power	Optional	Optional	Optional
Turning Circle Diameter (minimum) (m)	12.5	11	10.15
Wheel Base (mm)	3335	2815	2515
Gross Vehicle Weight (Max. Permissible) (kg)	7200	5990	4990/5200
Load Body Type	Dimensions (I x b x h) (mm)		
Cab Fixed Deck	4260 / 3740 x 2080 x 580	3510 x 1880 x 580	2800 x 1860 x 400
Cab Semi Deck	4260 / 3740 x 2080 x 1030	-	2800 x 1860 x 1030
Cab High Deck	4260 / 3740 x 2080 x 1695	3510 x 1880 x 1695	2800 x 1860 x 1695
Load Span <i>(ft.)</i>	14' / 12.25'	11.5'	9.1'
Cabin Chassis	Available	Available	Available

Note: Specifications are subject to change without any prior notification, as per the company policy of continuous improvement of products and service.

Features

- Available in BS-III & BS-IV Versions
 Powerful Engine Higher Pickup, Higher Torque at lower RPM,
 Gradeability and Fuel Efficiency
 Heavy Duty Gear Box and Bigger Clutch Longer Life
- Box Type Chassis with tubular cross members carry more load, provide better Strength and Rigidity
- Steering with variable Gear Ratio Less Driver Fatigue
 Roof Ventilation option available in Sartaj HG 72 variant for more comfort
 Ready availability of Spares at reasonable Price

CNG option available in select variants



Path-breaking performance that empowers your business






75 kw Powerful Engine for extra Mileage



Bigger Clutch Plate for More Life



Spacious Cargo Box for Voluminous Goods



Robust Box Type Chassis Ideal for all kinds of Loads



Heavy Duty Axle



Higher Gradeability



Larger Fuel Tank



Oil Change on 30,000 km




Labor Free Service up to 52,000 km

Multi Purpose LCVs

Safe, Dependable & Perfect Partner for Your Business





- Wide and Far Reaching Dealer Network
- Excellent Service Support
- Trustworthy and be assured that your vehicle is in the safe hands when it comes to service
- Easy Availability of Low Priced Spares
- Warranty: 3 Years on Engine and 2 Years on Vehicle (or upto 1.5 Lac km whichever is earlier)
- Easy Finance Available from All Leading Banks and Financial Lending Institutions



ALWAYS USE SML ISUZU GENUINE SPARES

SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A, Chandigarh - 160 135.

Ph: 0172-2647700. Fax: 0172-2615111.

E-mail: salesadm@smlisuzu.com,

For more information, please visit our website : www.smlisuzu.com

Authorised Dealer: