

Contest Duration: 2020-01-18(Sat) 19:00 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20200118T2100&p1=248>) - 2020-01-18(Sat) 21:00 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20200118T2300&p1=248>) (local time) (120 minutes)

[Back to Home \(/home\)](#)

[🏠 Top \(/contests/keyence2020\)](#)

[☰ Tasks \(/contests/keyence2020/tasks\)](#)

[❓ Clarifications \(/contests/keyence2020/clarifications\)](#)

[🚀 Submit \(/contests/keyence2020/submit?taskScreenName=keyence2020_d\)](#)

[☰ Results](#)

[🏆 Standings \(/contests/keyence2020/standings\)](#)

[🏆 Virtual Standings \(/contests/keyence2020/standings/virtual\)](#)

[🔧 Custom Test \(/contests/keyence2020/custom_test\)](#)

[📖 Editorial \(/contests/keyence2020/editorial\)](#)

[💬 Discuss \(https://codeforces.com/blog/entry/73139\)](https://codeforces.com/blog/entry/73139)



D - Swap and Flip

[Editorial \(/contests/keyence2020/tasks/keyence2020_d/editorial\)](#)



Time Limit: 2 sec / Memory Limit: 1024 MB

Score : 700 points

Problem Statement

We have N cards numbered $1, 2, \dots, N$. Card i ($1 \leq i \leq N$) has an integer A_i written in red ink on one side and an integer B_i written in blue ink on the other side. Initially, these cards are arranged from left to right in the order from Card 1 to Card N , with the red numbers facing up.

Determine whether it is possible to have a non-decreasing sequence facing up from left to right (that is, for each i ($1 \leq i \leq N - 1$), the integer facing up on the $(i + 1)$ -th card from the left is not less than the integer facing up on the i -th card from the left) by repeating the operation below. If the answer is yes, find the minimum number of operations required to achieve it.

- Choose an integer i ($1 \leq i \leq N - 1$). Swap the i -th and $(i + 1)$ -th cards from the left, then flip these two cards.

Constraints

- $1 \leq N \leq 18$
- $1 \leq A_i, B_i \leq 50$ ($1 \leq i \leq N$)
- All values in input are integers.

2020-11-20 (Fri)
16:29:33 +07:00

Input

Input is given from Standard Input in the following format:

```
 $N$   
 $A_1 \ A_2 \ \dots \ A_N$   
 $B_1 \ B_2 \ \dots \ B_N$ 
```

Output

If it is impossible to have a non-decreasing sequence, print -1. If it is possible, print the minimum number of operations required to achieve it.

Sample Input 1

[Copy](#)

```
3  
3 4 3  
3 2 3
```

[Copy](#)

Sample Output 1

[Copy](#)

```
1
```

[Copy](#)

By doing the operation once with $i = 1$, we have a sequence $[2, 3, 3]$ facing up, which is non-decreasing.

Sample Input 2

[Copy](#)

```
2  
2 1  
1 2
```

[Copy](#)

Sample Output 2

[Copy](#)

```
-1
```

[Copy](#)

After any number of operations, we have the sequence $[2, 1]$ facing up, which is not non-decreasing.

Sample Input 3

[Copy](#)

```
4
1 2 3 4
5 6 7 8
```

[Copy](#)

Sample Output 3

[Copy](#)

```
0
```

[Copy](#)

No operation may be required.

Sample Input 4

[Copy](#)

```
5
28 15 22 43 31
20 22 43 33 32
```

[Copy](#)

Sample Output 4

[Copy](#)

```
-1
```

[Copy](#)

Sample Input 5

[Copy](#)

```
5
4 46 6 38 43
33 15 18 27 37
```

[Copy](#)

Sample Output 5

[Copy](#)

```
3
```

[Copy](#)

Language

C++ (GCC 9.2.1)

Source Code

```
1
```

2020-11-20 (Fri)
16:29:33 +07:00