

Roadmap Inventory Management API Documentation

v 0.6 beta - Oct 24, 2025

Summary

This document provides high-level documentation for the Inventory management on the Roadmap system. This document, augmented with the provided OpenAPI specification, should allow operators to manage inventory on the Roadmap System.

1. [Authentication](#)
2. [Creating a new location](#)
3. [Creating a new face](#)
4. [Modifying an existing location](#)
5. [Modifying an existing face](#)

General Use Cases:

1. Create a new location with a face on it

The general flow is to create a location and attach faces to that location. Location is equivalent to the physical structure/stick on the ground. So, a location can have one or more faces associated with it.

Step 1: Create Location using [Creating a new location](#) endpoint (returns commb_location_id)

Step 2: Add a face to the location [Creating a new face](#) (returns commb_face_id)

2. Convert a static face to a digital face

Another general use case is converting a static face to a digital face. This will involve updating the product_id for the face using the [Modifying an existing face](#) endpoint for the face.

3. Add a new face to an existing location

Get the commb_location_id for the existing location and use the [Creating a new face](#) endpoint to add the face to the existing location

4. Disable face

Use the [Modifying an existing face](#) endpoint for the face and update the status to **Disabled**

1. Authentication

You must obtain a Bearer access token through the ROADMAP OAuth endpoint with the client ID and secret provided to you. The bearer token needs to be sent in **Authentication** header for all requests. The Bearer token is a machine to machine token which should be re-generated on expiry of the token.

Example request:

```
curl --location \
--request POST 'https://stage-commb.us.auth0.com/oauth/token' \
--header 'content-type: application/json' \
--data-raw
'{"client_id":"<CLIENT_ID>","client_secret":"<CLIENT_TOKEN>","audience":"https://stage-auth0.commb.com/apis","grant_type":"client_credentials"}'
```

Example response:

```
{
  "access_token": <ACCESS_TOKEN>,
  "expires_in": 86400,
  "token_type": "Bearer"
}
```

You should send the access token provided in Bearer format and your requests. The header will be excluded from the example requests.

2. Creating a new location

New locations can be created using the **POST /locations** endpoint.

Example request:

```
curl -X 'POST' \
'https://staging.roadmap.commb.ca/services/locations' \
-H 'Content-Type: application/json' \
-d '{
  "external_location_numeric": "string",
  "latitude": 0,
  "location_name": "string",
  "longitude": 0,
  "status": "Active"
}'
```

3. Creating a new face

Faces can be created using the **POST** `/face` endpoint. A `commb_location_id` must be provided.

Example request:

```
curl -X 'POST' \
  'https://staging.roadmap.commb.ca/services/face' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "address": "string",
    "commb_location_id": 0,
    "external_face_numeric": "string",
    "facing_direction": "N",
    "height": 0,
    "illumination_from": 24,
    "illumination_status": "Lit",
    "illumination_to": 24,
    "is_trio": 1,
    "latitude": 0,
    "longitude": 0,
    "num_of_spots": 0,
    "placing": "s",
    "product_id": 0,
    "spot_time": 0,
    "status": "Active",
    "unit_of_measure": "string",
    "width": 0
  }'
```

3.1 Adding a media to an existing face

This is to attach a media to an existing face, it can be done by using **POST**

`/face/{commb_face_id}/media` and the payload be a file (binary) preferably jpg or png. Keep in mind that if you call this endpoint more than once, the previous ones will be deactivated; the final one will remain accessible via a face's "media_asset_url" property.

Example request:

```
curl -X 'POST' \
  'https://staging.roadmap.commb.ca/services/face/50000756/media' \
  -H 'Accept-Encoding: gzip, deflate, br, zstd' \
  -H 'Content-Type: multipart/form-data' \
  -H 'Content-Length: xxxx' \
  --form 'file=@"/Users/francis/Desktop/example.png"'
```

Note: To get a list of products and their IDs, please use the **GET** `/product` endpoint.

4. Modifying an existing location

We can modify an already created location using the PATCH /locations/{id} request.

Example request:

```
curl -X 'PATCH' \    'https://staging.roadmap.commb.ca/services/
locations/60000504' \    -H 'accept: application/json' \
    -H 'Content-Type: application/json' \
    -d '{
        "external_location_numeric": "string",
        "latitude": 0,
        "location_name": "string",
        "longitude": 0,
        "operator_id": 0,
        "status": "Active"
    }'
```

5. Modifying an existing face

Using the PATCH /face/{id} request, we can modify a created face.

Example request:

```
curl -X 'PATCH' \  'https://staging.roadmap.commb.ca/  
services/face/50000297' \  -H 'accept: application/json' \  
-H 'Content-Type: application/json' \  
-d '{  
  "address": "string",  
  "external_face_numeric": "string",  
  "facing_direction": "N",  
  "height": 0,  
  "illumination_from": 24,  
  "illumination_status": "Lit",  
  "illumination_to": 24,  
  "is_trio": 1,  
  "latitude": 0,  
  "longitude": 0,  
  "num_of_spots": 0,  
  "placing": "s",  
  "product_id": 0,  
  "spot_time": 0,  
  "status": "Active",  
  "unit_of_measure": "string",  
  "width": 0  
}'
```