The Journal of Open Source Software

Peptacular: A ProForma 2.1 compliant Python package for amino acid sequence analysis

Patrick T. Garrett [1], **Titus Jung**[1], **and John R. Yates III** [1¶]

1 The Scripps Research Institute, United States ¶ Corresponding author

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Open Journals

Reviewers:

- @openjournals

Submitted: 01 January 1970
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

Summary

Mass spectrometry-based proteomics depends on computational methods to identify and characterize (amino acid) AA sequences. These sequences, ranging from short peptides to complete proteins, exhibit substantial chemical complexity due to PTMs, variable charge states, neutral losses, and isotopic patterns (Angel et al., 2012; Smith & Kelleher, 2013). **Peptacular** is a Python library designed to handle this complexity. The library provides functionality for modifying, calculating mass, m/z, isotopic distributions, physicochemical properties, enzymatic digestion, and fragmentation of AA sequences. Built around the standardized ProForma 2.1 notation, it supports all non-cross-linked ProForma features.

Statement of Need

Historically, the proteomics field has lacked standardization for representing AA sequences. Individual software tools have implemented proprietary notations, which has created barriers to data integration and reanalysis across platforms. ProForma notation (LeDuc et al., 2018) was developed to address this challenge by providing a unified representation system. However, adoption has remained limited, partly due to insufficient support in widely-used computational tools and libraries. Peptacular was specifically designed to accelerate ProForma adoption by offering a comprehensive and accessible API with clear documentation.

Additionally, with the continued advance of mass spectrometers, modern proteomics experiments routinely identify tens of thousands of AA sequences. These results are typically exported as tabular files and are frequently processed using Python, particularly with data manipulation libraries such as pandas (Team, 2025) and polars (Vink et al., 2025). To support this workflow, Peptacular's functional API allows you to directly manipulate these tabular data structures and automatically parallelizes operations, making large-scale sequence analysis both fast and straightforward (See example 2).

State of the Field

Several Python packages provide AA sequence analysis capabilities, though each has limitations as a general-purpose library for ProForma notation. **Pyteomics** (Goloborodko et al., 2013) recently added partial ProForma support while maintaining its legacy notation system, requiring format conversions that are not universally supported. **BioPython** (Cock et al., 2009) offers limited support for AA sequences and has no ProForma compatibility; its broad scope includes DNA and RNA sequences. **RustyMS** (Schulte et al., n.d.) delivers comprehensive ProForma parsing through its Python bindings but focuses primarily on parsing and offers limited prebuilt functionality for working with sequences. **PyOpenMS** (Röst et al., 2013) provides an extensive mass spectrometry toolkit but lacks ProForma compatibility.

Peptacular was designed to address these limitations as a general-purpose, ProForma 2.1-compliant AA sequence library. Developing Peptacular from scratch rather than extending existing tools offered three key advantages. First, ProForma notation serves as the foundation rather than a retrofitted addition, enabling complete feature coverage and a cleaner API. Second, the library targets AA sequence analysis specifically, avoiding the complexity that arises from supporting a broader scope. Third, the pure Python implementation ensures compatibility with modern Python versions, including free-threaded builds with the Global Interpreter Lock (GIL) disabled, which will become increasingly relevant as Python's parallelization capabilities continue to improve.

Software Design

Peptacular provides two primary APIs: a functional API and an object-oriented API. The object-oriented API employs a factory pattern to modify Proforma Annotation objects, enabling precise control over annotations. The functional API provides functions that operate directly on serialized sequences and annotations, with automatic parallelization for batch processing.

The built-in parallelization supports three execution backends: sequential, threaded, and process-based (default). Sequential execution provides single-threaded processing for small batches where parallelization overhead is detrimental. Thread-based parallelization currently offers limited benefits due to the GIL but will improve as free-threaded Python builds become standard (PEP 703). Process-based parallelization is the default and most widely supported method. Process and thread spawning mechanisms (fork, spawn, forkserver) are globally configurable, and worker processes are cached to eliminate startup overhead.

Three performance optimizations enable efficient large-scale processing. First, lazy evaluation keeps modifications in serialized form until required. Second, aggressive caching exploits the fact that proteomics datasets typically contain a small number of repeated modifications. Third, the specific objects used to store modifications within the annotations objects are only initialized when needed, reducing memory footprint and accelerating object creation.

Modification reference data, including masses, compositions, and identifiers from Unimod (Creasy & Cottrell, 2004), PSI-MOD (Hupo-Psi, n.d.-a), RESID (*RESID Database [PIR - Protein Information Resource]*, n.d.), XLMOD (Hupo-Psi, n.d.-b), and GNOme (Glygen-Glycan-Data, n.d.), are provided by the companion package **Tacular** (P. Garrett, 2026). This package embeds the data directly within itself as Python modules rather than storing them as external files. Only valid modifications are included in the embedded data; a modification is considered valid if it possesses at least one of the following properties: average mass, monoisotopic mass, or chemical formula. This design eliminates file I/O overhead during the parsing of supported ontologies.

The package includes full type annotations with a py.typed marker, which enables static type checking and provides IDE autocomplete, inline documentation, and compile-time error detection. Test coverage exceeds 70%, with continuous integration implemented through GitHub Actions. The only dependency is the companion package: tacular.

Research impact statement

Since its initial release, Peptacular has demonstrated measurable adoption. The package has accumulated over **33k** downloads from PyPI (as of 07 February 2026), with sustained weekly download rates exceeding 200 installations. It has been listed as one of three Python packages to support ProForma notation by the PSI group. Additionally, Peptacular was used to generate figures within a textbook chapter (P. T. Garrett et al., 2025).

Example Usage

Object-Based API

```python
import peptacular as pt

# Parse a sequence into a ProFormaAnnotation
peptide: pt.ProFormaAnnotation = pt.parse("PEM[Oxidation]TIDE")

# Calculate mass and m/z
mass: float = peptide.mass() # 849.342
mz: float = peptide.mz(charge=2) # 425.678

# Factory pattern
print(peptide.set_charge(2).set_peptide_name("Peptacular").serialize())
# (>Peptacular)PEM[Oxidation]TIDE/2
```

Functional-Based API

```python
import peptacular as pt

peptides = ['[Acetyl]-PEPTIDES', '<C13>ARE', 'SICK/2']

# Calculate mass and m/z for all peptides
masses: list[float] = pt.mass(peptides) # [928.4026, 374.1914, 451.2454]
mzs: list[float] = pt.mz(peptides, charge=2) # [465.2086, 188.103, 225.6227]
```

Pandas-Functional API

```python
import peptacular as pt
import pandas as pd

df = pd.DataFrame(
    {
        "seq": ["PEM[Oxidation]TIDE", "ACDEFGHIK", "M[Phospho]NOPQR"],
    }
)

df["mass"] = df["seq"].apply(pt.mass)
```

Mathematics

Peptacular calculates the molecular mass and isotopic patterns for AA sequences. This section presents the mathematical framework that underlies these calculations.

Base Mass

The base mass M_{base} of a AA sequence containing modifications is calculated as the sum of all constituent molecular components:

$$M_{base} = \sum_{i=1}^{n} m_{AAi} + M_N + M_C + M_S + M_I + M_R + M_U + \mathbb{1}_{\text{precursor}} \cdot M_L$$

where:

- n is the sequence length
- m_{AA_i} is the mass of amino acid at position i

DRAFT

- M_N is the total mass of N-terminal modifications
- M_C is the total mass of C-terminal modifications
- M_S is the total mass of static/fixed modifications (Applied to sequence)
- M_I is the total mass of position-specific modifications
- M_R is the total mass of modifications within defined sequence intervals
- M_U is the total mass of modifications with unknown positions
- M_L is the total mass of labile modifications
- $\mathbb{1}_{\text{precursor}}$ is an indicator function: 1 for precursor ions, 0 for fragment ions

Labile modifications are included only for precursor and neutral ion types.

Neutral Mass

The neutral mass M_{neutral} is calculated by combining the base mass with ion-type adjustments, isotope modifications, neutral deltas.

$$M_{\text{neutral}} = M_{\text{base}} + M_{\text{ion}} + M_{\text{isotope}} + M_{\text{ndelta}}$$

where:

- M_{base} is the peptide base mass from the previous section
- M_{ion} is the ion-type-specific mass offset
- M_{isotope} is the mass shift from a specific isotopic species
- M_{ndelta} is the mass change from neutral losses/gains

Mass-to-charge Ratio

The mass-to-charge (*m/z*) ratio is calculated by incorporating charge carriers and electron mass corrections to the neutral mass:

$$\frac{m}{z} = \frac{M_{\text{neutral}} + M_{\text{adduct}} - z \cdot m_e}{z}$$

where:

- M_{neutral} is the neutral fragment mass
- M_{adduct} is the total mass of charge carriers
- z is the total charge state
- $m_e = 0.0005485799$ Da (electron mass)

Isotopic Distribution

The isotopic distribution of a peptide is determined by convolving the isotopic patterns of all constituent elements. For a peptide with elemental composition$\{E_1 : n_1, E_2 : n_2, ..., E_k : n_k\}$, the isotopic distribution is:

$$P(\text{total}) = P(E_1)^{n_1} \otimes P(E_2)^{n_2} \otimes ... \otimes P(E_k)^{n_k}$$

where $P(E_i)$ is the natural isotopic distribution of element E_i, n_i is the count of that element, and $\otimes$ represents the convolution operation.

The computational complexity of isotopic distribution calculations scales with the number of isotopic peaks retained during the convolution process. To balance accuracy with computational efficiency, Peptacular implements several parameters to limit the number of isotopic peaks propagated through convolution operations.

Averagine Model

When the exact elemental composition is unknown, the averagine model provides an estimate of composition based on molecular mass using empirically-derived atomic ratios. The averagine values used in Peptacular were calculated by determining the cumulative count of all atoms

DRAFT

present in the entire human proteome (all reviewed proteins from UP000005640, downloaded from UniProt on February 2, 2026). This cumulative count was then normalized by the total monoisotopic mass of the proteome, yielding an atoms-per-dalton ratio for each element.

The composition is calculated as:

$$n_E = r_E \cdot M_{\text{neutral}} + n_{E,\text{ion}}$$

where:

- n_E is the estimated count of element E
- r_E is the averagine ratio (atoms per dalton) for element E
- M_{neutral} is the neutral peptide mass
- $n_{E,\text{ion}}$ is the elemental contribution from the ion type

The averagine ratios (atoms/Da) derived from the human proteome are:

- C: 0.044179
- H: 0.069749
- N: 0.012344
- O: 0.013352
- S: 0.000400

Figures

Table 1: Proforma 2.1 Compliance

?	Feature	Example	§ [Support]
Y	Amino acids (+UO)	`AAHCFKUOT`	6.1 [B]
Y	Unimod names	`PEM[Oxidation]AT`	6.2.1 [B]
Y	PSI-MOD names	`PEM[monohydroxylated residue]AT`	6.2.1 [B]
Y	Unimod numbers	`PEM[UNIMOD:35]AT`	6.2.2 [B]
Y	PSI-MOD numbers	`PEM[MOD:00425]AT`	6.2.2 [B]
Y	Delta masses	`PEM[+15.995]AT`	6.2.3 [B]
Y	N-terminal modifications	`[Carbamyl]-QPEPTIDE`	6.3 [B]
Y	C-terminal modifications	`PEPTIDEG-[Methyl]`	6.3 [B]
Y	Labile modifications	`{Glycan:Hex}EM[U:Oxidation]EV`	6.4 [B]
Y	Multiple modifications	`MPGNW[Oxidation][Carboxymethyl]PESQE`	6.5 [B]
Y	Information tag	`ELV[INFO:AnyString]IS`	6.6 [B]
Y	Ambiguous amino acids	`BZJX`	7.1 [2]
Y	Prefixed delta masses	`PEM[U:+15.995]AT`	7.2 [2]
Y	Mass gap	`PEX[+147.035]AT`	7.3 [2]
Y	Formulas	`PEM[Formula:O]AT`, `PEM[Formula:[17O1]]AT`	7.4 [2]
Y	Mass with interpretation	`PEM[+15.995|Oxidation]AT`	7.5 [2]
Y	Unknown mod position	`[Oxidation]?PEMAT`	7.6.1 [2]
Y	Set of positions	`PEP[Oxidation#1]M[#1]AT`	7.6.2 [2]
Y	Range of positions	`PRT(ESFRMS)[+19.0523]ISK`	7.6.3 [2]
Y	Position scores	`PEP[Oxidation#1(0.95)]M[#1(0.05)]AT`	7.6.4 [2]
Y	Range position scores	`(PEP)[Oxidation#1(0.95)]M[#1(0.05)]AT`	7.6.5 [2]
Y	Amino acid ambiguity	`(?VCH)AT`	7.7 [2]
Y	Modification prefixes	`PEPM[U:Oxidation]AS[M:O-phospho-L-serine]`	7.8 [2]
Y	RESID modifications	`EM[R:L-methionine sulfone]EM[RESID:AA0581]`	8.1 [T]
Y	Names	`(>Heavy chain)EVQLVESG`	8.2 [T]
Y	XL-MOD modifications	`EVTK[X:Aryl azide]LEK[XLMOD:00114]SEFD`	9.1 [X]

DRAFT

?	Feature	Example	§ [Support]
N	Cross-linkers (intrachain)	`EVTK[X:Aryl azide#XL1]LEK[#XL1]SEFD`	9.2.1 [X]
N	Cross-linkers (interchain)	`EVTK[X:Aryl azide#XL1]L//EK[#XL1]SEFD`	9.2.2 [X]
N	Branches	`ED[MOD:00093#BRANCH]//D[#BRANCH]ATR`	9.3 [X]
Y	GNO modifications	`NEEYN[GNO:G59626AS]K`	10.1 [G]
Y	Glycan compositions	`NEEYN[Glycan:Hex5HexNAc4NeuAc1]K`	10.2 [G]
Y	Charged formulas	`SEQUEN[Formula:Zn1:z+2]CE`	11.1 [A]
Y	Controlling placement	`PTI(MERMERME)[+32|Position:E]PTIDE`	11.2 [A]
Y	Global isotope	`<13C>CARBON`	11.3.1 [A]
Y	Fixed modifications	`<[Oxidation]@M>ATPEMILTCMGCLK`	11.3.2 [A]
Y	Chimeric spectra	`NEEYN+SEQUEN`	11.4 [A]
Y	Charges	`SEQUEN/2, SEQUEN/[Na:z+1,H:z+1]`	11.5 [A]
Y	Ion notation	`SEQUEN-[b-type-ion]`	11.6 [A]

Table 1 presents the level of ProForma support implemented in Peptacular. The package currently supports all ProForma 2.1 features for linear peptides. Cross-linked peptides (both inter- and intrachain) and branched structures are not currently supported. Ion notation is also not supported at the sequence level; however, the package provides extensive fragmentation support through either API. Support levels are designated as follows: [B] - Base ProForma support, [2] - ProForma 2, [T] - Top down, [X] - Cross linking, [G] - Glycan, [A] - Advanced.

Figure 1: Parallelization Performance - GIL Enabled vs GIL Disabled (Python 3.14t)

```
![This figure presents a parallelization performance comparison for mass calculations of
```

AI usage disclosure

Generative AI models were employed to support the development of this software package. Specifically, Claude Sonnet 4.5, Gemini 2.0 Pro, and GitHub Copilot's autocomplete extension were utilized for code generation, test development, debugging assistance, and documentation preparation. These tools were accessed through the Copilot extension in Visual Studio Code. Additionally, Type.ai was used to assist in manuscript preparation. All AI-generated content was subsequently reviewed and verified for accuracy.

Availability

Peptacular is distributed through PyPI (https://pypi.org/project/peptacular/) and available as open-source software on GitHub (https://github.com/tacular-omics/peptacular). Documentation is accessible at https://peptacular.readthedocs.io. The software is released under the MIT license.

Acknowledgements

This work was supported by the National Institutes of Health under grants R01 AG077046 (Analysis of protein interactions in neurodegenerative disease), R01 MH132570 (Brain-wide mapping of neuronal inhibition by novel inverse activity markers), R01 MH100175 (Proteogenetics of Autism Spectrum Disorders), R01 HL165168 (The CFTR Interactome), and U01 AG088679 (Understanding Gene-Environment Interactions in Brain Aging and Alzheimer's Disease (AD) and AD-Related Dementias (ADRD)).

DRAFT

Angel, T. E., Aryal, U. K., Hengel, S. M., Baker, E. S., Kelly, R. T., Robinson, E. W., & Smith, R. D. (2012). Mass spectrometry-based proteomics: existing capabilities and future directions. *Chemical Society Reviews*, *41*(10), 3912. https://doi.org/10.1039/c2cs15331a

Cock, P. J. A., Antao, T., Chang, J. T., Chapman, B. A., Cox, C. J., Dalke, A., Friedberg, I., Hamelryck, T., Kauff, F., Wilczynski, B., & De Hoon, M. J. L. (2009). Biopython: freely available Python tools for computational molecular biology and bioinformatics. *Bioinformatics*, *25*(11), 1422–1423. https://doi.org/10.1093/bioinformatics/btp163

Creasy, D. M., & Cottrell, J. S. (2004). Unimod: Protein modifications for mass spectrometry. *PROTEOMICS*, *4*(6), 1534–1536. https://doi.org/10.1002/pmic.200300744

Garrett, P. (2026). *tacular-omics/tacular: v1.0.1 - Zenodo + Docs* (Version v1.0.1). Zenodo. https://doi.org/10.5281/zenodo.18475557

Garrett, P. T., Turner, N. P., Nakorchevsky, A., Pankow, S., & Yates, J. R. (2025). *Mass spectrometry-based proteomics*. https://doi.org/10.1016/b978-0-323-99507-8.00013-5

Glygen-Glycan-Data. (n.d.). *GitHub - glygen-glycan-data/GNOme: GNOme - Glycan Naming and Subsumption Ontology*. https://github.com/glygen-glycan-data/GNOme

Goloborodko, A. A., Levitsky, L. I., Ivanov, M. V., & Gorshkov, M. V. (2013). Pyteomics—A Python framework for exploratory data analysis and rapid software prototyping in proteomics. *Journal of the American Society for Mass Spectrometry*, *24*(2), 301–304. https://doi.org/10.1007/s13361-012-0516-6

Hupo-Psi. (n.d.-a). *GitHub - HUPO-PSI/psi-ms-CV: HUPO-PSI mass spectrometry CV*. https://github.com/HUPO-PSI/psi-ms-CV

Hupo-Psi. (n.d.-b). *GitHub - HUPO-PSI/xlmod-CV: Repo for the XLMOD ontology for chemical cross linkers*. https://github.com/HUPO-PSI/xlmod-CV

LeDuc, R. D., Schwämmle, V., Shortreed, M. R., Cesnik, A. J., Solntsev, S. K., Shaw, J. B., Martin, M. J., Vizcaino, J. A., Alpi, E., Danis, P., Kelleher, N. L., Smith, L. M., Ge, Y., Agar, J. N., Chamot-Rooke, J., Loo, J. A., Pasa-Tolic, L., & Tsybin, Y. O. (2018). ProForma: a standard proteoform notation. *Journal of Proteome Research*, *17*(3), 1321–1325. https://doi.org/10.1021/acs.jproteome.7b00851

RESID Database [PIR - Protein Information Resource]. (n.d.). https://proteininformationresource.org/resid/

Röst, H. L., Schmitt, U., Aebersold, R., & Malmström, L. (2013). pyOpenMS: A Python-based interface to the OpenMS mass-spectrometry algorithm library. *PROTEOMICS*, *14*(1), 74–77. https://doi.org/10.1002/pmic.201300246

Schulte, D., Gabriels, R., & Heerdink, A. (n.d.). *mzcore* (Version 0.11.0). https://github.com/rusteomics/mzcore

Smith, L. M., & Kelleher, N. L. (2013). Proteoform: a single term describing protein complexity. *Nature Methods*, *10*(3), 186–187. https://doi.org/10.1038/nmeth.2369

Team, P. D. (2025). pandas-dev/pandas: Pandas. *Zenodo (CERN European Organization for Nuclear Research)*. https://doi.org/10.5281/zenodo.17992932

Vink, R., De Gooijer, S., Beedie, A., Burghoorn, G., Nameexhaustion, Peters, O., Gorelli, M. E., Reswqa, Van Zundert, J., Marshall, Hulselmans, G., Grinstead, C., Denecker, K., Manley, L., chielP, Turner-Trauring, I., Valtar, K., Mitchell, L., Sprenkels, A., … Magarick, J. (2025). pola-rs/polars: Python Polars 1.36.1. *Zenodo (CERN European Organization for Nuclear Research)*. https://doi.org/10.5281/zenodo.17873635

DRAFT