

Constructor™ 07

General purpose, work class hydraulic ROV system.

The system is characterised by a compact and integrated mechanical architecture, powerful and accessible hydraulic functions and a user friendly real time control system.

Power (Kw/Hp)
160/220

Depth rating (msg)
3000

Weight (kg)
4600

Payload (kg)
360

Technical Specifications

Dimensions

3220 × 1700 × 2150 mm (LxWxH)

Weight

4600 kg

Depth Rating

3000 MSW

Payload

~360 kg with Skid, Manipulators and standard sensors, cameras, lights and P&T installed

Through frame lift capacity

3000 kg (4×750 kg skid interface brackets)

Bollard Pull

800 kg vertical up, 900 kg vertical down, 900 kg fwd/aft, 850 kg lateral

Electric Motor

IKM 160 KW, 220 HP at shaft - 3phase 4150 VAC

Pump Main

200-230 Bar - 180 cc/rev - 315 L/min @60 hz

Pump Aux

200 Bar - 96 cc/rev - 160 L/min @60 hz

Thrusters

7x Sub Atlantic SA - 380

Oil type

Hydromax 36

HPU Trafo

3Phase 440 V - 3300 V, 230 KVA

Instrument Trafo

1Phase 440 V - 3300 V, 10 KVA

Standard Equipment

Cameras	2x Imenco Hammerhead F/Z 1x B/W Camera 1x T4 Camera 2x Greytip 1x Silvertip (skid) 1x Fish Eye / wide angle
Lights	6x DeepSea LED Sealite 115 VAC
Gyro Compass	Octans 3000
DVL	N/A
Sonar	Kongsberg MS 1000
Depth Sensor	Valeport Mini IPS
Altimeter	Tritech PA500
Transponder	2x cNode miniS 34-180
Manipulator Stb	Schilling T4
Manipulator port	Schilling rigmaster
Waterjet	Dynaset HPW220 (incl hose retractor)
Grinder	Saga Subsea 12” Grinder
Wire rope cutter	Webtool 40 mm
ROV Knife	Saga Subsea Knife