


# HD™45

## Compact 150hp Work Class ROV for depths down to 3000 meters.

Designed for accommodating the specific needs of the IMR and drill support markets. The HD™ system is optimized for installation onboard drilling rigs and ROV support vessels, where available deck space is limited.

Power (Kw/Hp)
112/150

Depth rating (msg)
3000

Weight (kg)
3600

Payload (kg)
250

# Technical Specifications

## Dimensions

2940 × 1695 × 2006 mm (LxWxH)

## Weight in air

3600 kg

## Depth Rating

3000 MSW

## Payload

~250 kg

## Through frame lift capacity

3000 kg

## Bollard Pull

850 kg vertical - 900 kg fwd, aft and lateral

## Electric Motor

112 KW, 150 HP at shaft - 4160 VAC - 3phase 50-60 hz

## Pump Main

276 bar max OP - 135 cc/rev - 208 L/min

## Pump Aux

207 bar max OP - 45 cc/rev - 71 L/min

## Thrusters

7x Sub Atlantic SA - 380

## Oil type

Hydromax 36

## ROV HPU Trafo

3Phase 440 V - 4300 V, 165 KVA

## ROV Instrument Trafo

1 Phase 440 V - 4160 V, 10 KVA

## TMS Instrument Trafo

1 Phase 440 V - 4160 V, 10 KVA

## Standard Equipment

| | |
|---|---|
| Cameras | 2x Imenco Hammerhead + 4x SD PAL Cameras for orientation |
| Lights | 8x DeepSea LED Sealite 115 VAC |
| Gyro Compass | Octans 3000 |
| DVL | NA |
| Sonar | Kongsberg MS1000 |
| Depth Sensor | Valeport Mini IPS |
| Altimeter | Tritech PA500 |
| Transponder | 2x cNode miniS 34-180 |
| Manipulators | T4 and Rigmaster |
| Waterjet | Dynaset HPW220 |
| Grinder | Saga Subsea 12"Grinder |
| Wire rope cutter | Webtool 40 mm |
| ROV Knife | Saga Subsea Knife |




# HD™46

## Compact 150hp Work Class ROV for depths down to 3000 meters.

Designed for accommodating the specific needs of the IMR and drill support markets. The HD™ system is optimized for installation onboard drilling rigs and ROV support vessels, where available deck space is limited.

Power (Kw/Hp)
112/150

Depth rating (msg)
3000

Weight (kg)
3600

Payload (kg)
250

# Technical Specifications

## Dimensions

2940 × 1695 × 2006 mm (LxWxH)

## Weight in air

3600 kg

## Depth Rating

3000 MSW

## Payload

~250 kg

## Through frame lift capacity

3000 kg

## Bollard Pull

850 kg vertical - 900 kg fwd, aft and lateral

## Electric Motor

112 KW, 150 HP at shaft - 4160 VAC - 3phase 50-60 hz

## Pump Main

276 bar max OP - 135 cc/rev - 208 L/min

## Pump Aux

207 bar max OP - 45 cc/rev - 71 L/min

## Thrusters

7x Sub Atlantic SA - 380

## Oil type

Hydromax 36

## ROV HPU Trafo

3Phase 440 V - 4300 V, 165 KVA

## ROV Instrument Trafo

1 Phase 440 V - 4160 V, 10 KVA

## TMS Instrument Trafo

1 Phase 440 V - 4160 V, 10 KVA

## Standard Equipment

| | |
|---|---|
| Cameras | 2x Imenco Hammerhead + 4x SD PAL Cameras for orientation |
| Lights | 8x DeepSea LED Sealite 115 VAC |
| Gyro Compass | Octans 3000 |
| DVL | NA |
| Sonar | Kongsberg MS1000 |
| Depth Sensor | Valeport Mini IPS |
| Altimeter | Tritech PA500 |
| Transponder | 2x cNode miniS 34-180 |
| Manipulators | T4 and Rigmaster |
| Waterjet | Dynaset HPW220 |
| Grinder | Saga Subsea 12"Grinder |
| Wire rope cutter | Webtool 40 mm |
| ROV Knife | Saga Subsea Knife |