

Supporter™ 07

General purpose, work class hydraulic ROV system, for intervention down to 2000 meter water depth.

The system is characterised by a compact and integrated mechanical architecture, powerful and accessible hydraulic functions and a user friendly real time control system.

Power (Kw/Hp)
95/125

Depth rating (msg)
2000

Weight (kg)
3050

Payload (kg)
200

Find out more at reachsubsea.com

REACH SUBSEA

Technical Specifications

Dimensions

2797 × 1700 × 1650 mm (LxWxH) - Excl. skid

Weight

2450 kg (3050 kg incl skid, manips & payload)

Depth Rating

2000 MSW

Payload

~200 kg with Skid, Manipulators and standard sensors, cameras, lights and P&T installed

Through frame lift capacity

3000 kg (4×750 kg skid interface brackets)

Bollard Pull

800 kg vertical - 525 kg fwd/aft, 525 kg lateral

Electric Motor

IKM 95 KW, 125 HP at shaft - 3Phase 3000 VAC -50/60 Hz

Pump Main

200 Bar - 140 cc/rev - 240 L/min @60 hz

Pump Aux

200 Bar - 45 cc/rev - 78 L/min @60 hz

Valvepack GFVP 1 & 2

20 x NG3 (2 × 10) valves (8 L/min)

Valvepack ACU

4 x NG6 valves (75 L/min)

Thrusters

7x Sub Atlantic SA - 300

Oil type

Hydromax HT ECO 36

HPU Trafo

3Phase 440 V - 3300 V, 145 KVA

Instrument Trafo

1Phase 440 V - 3300 V, 10 KVA

Standard Equipment

Cameras	6x SD cameras (2x P&T, 3x Orientation and 1x for manip)
Lights	6x DeepSea LED Sealite 115VAC + Gas floodlights
Gyro Compass	Octans 3000
DVL	N/A
Sonar	Kongsberg MS 1000
Depth Sensor	SAIV TD 303
Altimeter	Tritech PA500
Transponder	2x cNode miniS 34-180
Manipulators	T4 and Rigmaster
Waterjet	Dynaset HPW220 (incl hose retractor)
Grinder	Saga Subsea 12" Grinder
Wire rope cutter	Webtool 40 mm
ROV Knife	Saga Subsea Knife



Supporter™ 10

General purpose, work class hydraulic ROV system, for intervention down to 2000 meter water depth.

The system is characterised by a compact and integrated mechanical architecture, powerful and accessible hydraulic functions and a user friendly real time control system.

Power (Kw/Hp)
95/125

Depth rating (msg)
2000

Weight (kg)
3335

Payload (kg)
200

Find out more at reachsubsea.com

REACH SUBSEA

Technical Specifications

Dimensions

2500 × 1700 × 1650 mm (LxWxH)

Weight

3335 kg

Depth Rating

2000 MSW

Payload

280 kg

Bollard Pull

800 kg vertical - 525 kg fwd, aft and lateral

Electric Motor

IKM 95 KW, 125 HP at shaft - 3000 VAC

Pump Main

200 Bar - 140 cc/rev - 240 L/min

Pump Aux

200 Bar - 45 cc/rev - 78 L/min

Thrusters

Sub Atlantic SA - 300

Oil type

Hydromax 36

HPU Trafo

3Phase 440 V - 3300 V, 140 KVA

Instrument Trafo

3Phase 440 V - 3300 V, 10 KVA

Standard Equipment

Cameras	2x Imenco Hammerhead + 4x SD PAL Cameras for orientation
Lights	8x CT4011 Led
Gyro Compass	Sprint INS
DVL	Syrinx 600
Sonar	Gemini 720
Depth Sensor	Valeport Mini IPS
Altimeter	Tritech PA500
Transponder	2x cNode miniS 34-180
Manipulators	T4 and Rigmaster
Waterjet	Dynaset HPW220
Grinder	Saga Subsea 12" Grinder
Wire rope cutter	Webtool 40 mm
ROV Knife	Saga Subsea Knife



Supporter™ 21

General purpose, work class hydraulic ROV system, for intervention down to 2000 meter water depth.

The system is characterised by a compact and integrated mechanical architecture, powerful and accessible hydraulic functions and a user friendly real time control system.

Power (Kw/Hp)
115/150

Depth rating (msg)
2000

Weight (kg)
3050

Payload (kg)
280

Find out more at reachsubsea.com

REACH SUBSEA

Technical Specifications

Dimensions

2500 × 1700 × 1650 mm (LxWxH)

Weight

3050 kg

Depth Rating

2000 MSW

Payload

280 kg

Bollard Pull

800 kg vertical - 525 kg fwd, aft and lateral

Electric Motor

IKM 95 KW, 125 HP at shaft - 3000 VAC

Pump Main

200 Bar - 140 cc/rev - 240 L/min @60 hz

Pump Aux

200 Bar - 45 cc/rev - 78 L/min

Thrusters

Sub Atlantic SA - 300

Oil type

Hydromax 36

HPU Trafo

3Phase 440 V - 3300 V, 140 KVA

Instrument Trafo

1Phase 440 V - 3300 V, 10 KVA

Standard Equipment

Cameras	2x Imenco Hammerhead + 4x SD PAL Cameras for orientation
Lights	8x CT4011 Led
Gyro Compass	Sprint INS
DVL	Syrinx 600
Sonar	Gemini 1200ik, Impact ISS360
Depth Sensor	Impact ISD4000
Altimeter	Impact ISA500
Transponder	2x cNode miniS 34-180
Manipulators	T4 and Rigmaster
Waterjet	Dynaset HPW220
Grinder	Grumek Super Grinder 12"
Wire rope cutter	Webtool 70mm
ROV Knife	Saga Subsea Knife



Supporter™ 27

General purpose, work class hydraulic ROV system.

The system is characterised by a compact and integrated mechanical architecture, powerful and accessible hydraulic functions and a user friendly real time control system.

Power (Kw/Hp)
115/150

Depth rating (msg)
3000

Weight (kg)
3600

Payload (kg)
350

Technical Specifications

Dimensions

2745 × 1700 × 1931 mm (LxWxH)

Weight

3600 kg

Depth Rating

3000 MSW

Payload

~350 kg with Skid, Manipulators and standard sensors, cameras, lights and P&T installed

Bollard Pull

600 kg vertical - 700 kg fwd/aft, 600 kg lateral

Electric Motor

IKM 115 KW, 150 HP at shaft - 3000 VAC

Pump Main

200 Bar - 140 cc/rev - 240 L/min @60 hz

Pump Aux

200 Bar - 71 cc/rev - 120 L/min @60 hz

Thrusters

7x Sub Atlantic SA - 300

Oil type

Hydromax 36

HPU Trafo

3Phase 440 V - 3300 V/4400 V, 230 KVA

Standard Equipment

Cameras	2x Imenco Hammerhead + 4x SD PAL Cameras for orientation
Lights	8x DeepSea LED Sealite 115 VAC
Gyro Compass	Octans 3000
DVL	NA
Sonar	Kongsberg MS1000
Depth Sensor	Valeport Mini IPS
Altimeter	Tritech PA500
Transponder	2x cNode miniS 34-180
Manipulators	T4 and Rigmaster
Waterjet	Dynaset HPW220 (incl hose retractor)
Grinder	Saga Subsea 12"Grinder
Wire rope cutter	Webtool 40mm
ROV Knife	Saga Subsea