

ZEEROV

A fully electric work-class ROV with advanced power management for greater power and agility in a compact design.

The ZEEROV is designed with a high focus on reliability and flexibility which is the key success factor for achieving long term submersion and effective remote control from shore.

Depth rating (msw)
2000

Weight (kg)
3800

Payload (kg)
600

Technical Specifications

Dimensions

2750 × 1700 × 1690 mm (LxWxH) + height of skid

Weight

3800 kg

Depth Rating

2000 MSW

Payload

~600 kg

Through frame lift capacity

1500 kg

Bollard Pull

FWD	1226 kg
AFT	1218 kg
Lateral	1120 kg
Vertical UP	1169 kg
Vertical DOWN	1238 kg

Electric Motor

6.5KW - 800VDC

HPU

205 Bar - 28cc/rev - 70l/min @ 2500rpm

Thrusters

7x Kystdesign - KD300 20kW each

Oil type

Matrix Hydromax HT ECO 32

ROV Main Trafo

3Phase 600-800VDC - 4200V - 150KVA - 180Hz

Instrument Trafo

1 Phase 600-800VDC - 3300V - 20KVA - 60Hz

Standard Equipment

Cameras	2x Imenco Orca IP Camera 4x Imenco Goblin Cameras for orientation
Lights	9x LED SeaLite
Gyro / DVL	Sprint-NAV mini AAINS including 500kHz DVL
Sonar	Gemini 1200ik (720kHz / 1200kHz)
Depth Sensor	Valeport mini IPS 50
Transponder	2x cNode miniS 34-180
Manipulators	T4 and Smart Atlas
CTD	Valeport Mini CTD