

Manipulating Files and IO exceptions

Object Oriented Programming
2024 First Semester
Shin-chi Tadaki (Saga University)

- 1 File IO and exceptions
- 2 Standard input and output
- 3 Improving IO functions
- 4 Input classes
- 5 Output classes
- 6 Exceptions

Today's sample programs

- <https://github.com/oop-mc-saga/FileIOExamples>

File IO (Input and Output) in Java

- File IO functions are not included in `java.lang`
 - `java.lang` contains only standard IO functions
- A separate package `java.io` provides File IO functions.

IO exceptions

- IO exceptions are inevitable. They will happen when the specified file is not
 - readable, or writable by access controls,
 - found,
 - etc.
- General exceptions will be discussed later.
- Handling exceptions enables us to prevent applications failures.
 - If not, applications will be aborted by exceptions

Standard input and output

```
1 package java.lang;
2 import java.io.*;
3 public final class System{
4     private System(){}
5     public final static InputStream in;
6     public final static PrintStream out;
7     public final static PrintStream err;
8 }
```

- Standard input and output are aliases for `java.io.InputStream` and `java.io.PrintStream`.

Standard input: from keyboard

- Read character by character.
 - `int read()`: reads the next one byte and returns character code.
 - `int read(byte[] b)`: reads some number of bytes and returns the number of bytes.
 - Both methods will throws `IOException`

```
1  StringBuilder b = new StringBuilder();
2  int c;
3  try {
4      while((c = System.in.read()) != -1){
5          b.append((char)c);
6          //read 1byte data and append to b
7      }
8  } catch (IOException ex){
9      //Error handling
10 }
```

See `simplest/StandardInput.java`


Standard output

- `void print()`: prints a string
- `void println()`: prints a string then terminates the line
- Arguments of the methods
 - primitive data types
 - objects: converting to a string using `toString()` method

Improving IO functions

- Various sources and destinations of IOs
 - standard IO, files, network resources
- Hierarchical structure between applications and IO resources

Hierarchical structure of IOs



Buffering

- Peripherals are slower than CPU
- Buffering is necessary for sending and receiving data
- Use stream or reader/writer

Input classes

- Specify a file by File class
- FileInputStream
- InputStreamReader
- BufferedReader

Specify a file

- File class
 - `File file = new File(String filename)`
- Note: the constructor of File class does not check the existence and accessibility of the specified file.
- The File class provides functions for testing the existence and accessibility of the file.


methods	operations
<code>boolean canRead()</code>	test the file readable
<code>boolean canWrite()</code>	test the file writable
<code>boolean createNewFile()</code>	create a new file
<code>boolean exists()</code>	test the file existence

FileInputStream class

```
1 File file;  
2 FileInputStream fStream = new FileInputStream(file);
```

- `int read()`
 - Reads data one byte
 - returns -1 if end

Hierarchy of InputStream classes



Example 4.1: InputStream

```
1 static public String readFromInputStream(String filename)
2     throws IOException {
3     File file = new File(filename); //Specify file for reading
4     StringBuilder sb = new StringBuilder();
5     //Open input buffer
6     try ( BufferedInputStream in
7           = new BufferedInputStream(
8             new FileInputStream(file))) {
9         int n;
10        while ((n = in.read()) != -1) //Read byte by byte
11            char c = (char) n; //Convert byte to character
12            sb.append(c); //append to string builder
13        }
14    }
15    return sb.toString();
16 }
```

simplest/Input.java


try-with-resources

- The previous example use try clause without catch.
- It catches exceptions relating to resources.
- It also closes the used resources.

BufferedReader class

- Reading by byte is inconvenient for handling text
- Reader class provide reading string lines from stream
 - `int read()`: reads one character
 - `int read(char[])`: reads characters into the array.
 - `String readLine()`: reads one string line

Hierarchy of Reader classes



Example 4.2: BufferedReader

```
1  static List<String> readFromReader(String filename)
2      throws IOException {
3      File file = new File(filename);
4      List<String> stringList
5          = Collections.synchronizedList(new ArrayList<>());
6      try (BufferedReader in = new BufferedReader(
7          new InputStreamReader(
8              new FileInputStream(file), ENC))) {
9          String line;
10         //read line by line
11         while ((line = in.readLine()) != null) {
12             stringList.add(line);
13         }
14     }
15     return stringList;
16 }
```

simplest/Input.java

Example 4.3: Wrapping standard input

- Standard input can be wrapped into `InputStreamReader`

```
1 public static List<String> wrapping() {
2     List<String> stringList
3         = Collections.synchronizedList(new ArrayList<>());
4     BufferedReader in = new BufferedReader(
5         new InputStreamReader(System.in));
6     try {
7
8         String line;
9         while ((line = in.readLine()) != null) {
10             stringList.add(line);
11         }
12     } catch (IOException ex) {
13         System.err.println(ex);
14     }
15     return stringList;
16 }
```


Output classes

- Specify file by File class
- FileOutputStream
- PrintStream
- BufferedWriter

OutputStream class

- Write by bytes
 - `void write(byte[])`
- Flush this output stream
 - Output processes delay because of buffering.
 - Sometime we need to flush buffered data to destinations.
 - `void flush()`
- Close this stream
 - `void close()`

Hierarchy of output streams



PrintStream classNode

- Extends `FilterOutputStream`
- Add some methods to `OutputStream`
- Output strings
 - `print(Object)`
 - `println(Object)`
- Add one character
 - `append(char)`

Example 5.1: PrintStream


```
1 public static void main(String[] args)
2     throws FileNotFoundException {
3     File file = new File("PrintStreamSampleOutput.txt");
4     try (PrintStream out = new PrintStream(file)) {
5         for (int i = 0; i < 100; i++) {
6             int x = (int) (100 * Math.random());
7             out.println(x);
8         }
9     }
10 }
```

simplest/PrintStreamExample.java

BufferedWriter class

- Put characters and strings into the stream
 - `void write(char)`
 - `void write(String)`
 - `void newLine()`

Hierarchy of writers



Example 5.2: BufferedWriter

```
1 public static void main(String[] args) throws IOException {  
2     File file = new File("WriterSampleOutput.txt");  
3     try (BufferedWriter out = new BufferedWriter(  
4         new OutputStreamWriter(  
5             new FileOutputStream(file)))) {  
6         for (int i = 0; i < 100; i++) {  
7             int x = (int) (100 * Math.random());  
8             out.write(String.valueOf(x));  
9             out.newLine();  
10        }  
11    }  
12 }
```

simplest/WriterExample.java

Example 5.3: Wrapping standard output

```
1 public static void wrapping() {  
2     BufferedWriter out = new BufferedWriter(  
3         new OutputStreamWriter(System.out));  
4     try {  
5         out.write("Something");  
6         out.newLine();  
7     } catch (IOException ex) {  
8         System.err.println(ex);  
9     }  
10 }
```

Other IO examples

- Copy text file by line
 - `fileCopy/FileCopy.java`
- Copy binary file by byte
 - `fileCopy/BinaryFileCopy.java`

Note: line break codes


- Line break codes depend on OS.
 - UNIX, Linux, MacOS(> 9): LF (0x0a)
 - Windows: CR+LF (0x0d0a)
- Write OS independent code by Java

```
String nl = System.getProperty("line.separator");
```


Exceptions

- Exceptions are inevitable in IO operations
- Applications should handle exceptions for preventing applications from being aborted
- Java defines exceptions as class
- Exception classes provide consistent methods for handling exceptions

Hierarchy of exception classes



General ways for handling exceptions

- Inside method

```
1  try{  
2      //Something will throw exceptions  
3  } catch (Exception ex){  
4      //Error Handling  
5  }
```

- Notify exception to caller

```
1  public void method() throws Exception{  
2      //Something will throw exceptions  
3  }
```

Example 6.1: Generating exceptions

```
1 public void method() throws Exception{  
2     if(something){  
3         String message="error message";  
4         throw new Exception(message);  
5     }  
6 }
```

Other exceptions

- `ArithmeticException`: exceptional arithmetic conditions
- `ArrayIndexOutOfBoundsException`: an array has been accessed with an illegal index
- `IllegalArgumentException`: a method has been passed an illegal or inappropriate argument
- `NumberFormatException`: the string does not have the appropriate format for expressing numbers.

Examples

- The application tries to read numerics from a file, which contains non-numeric strings
 - `Exception/ExceptionExample.java`
- The method receives inappropriate Arguments
 - `Exception/NewtonMethod.java`

How to see source files of jdk libraries

- in Netbeans
 - select class name by double-click
 - mouse right button: navigate → go to source

Exercise

Implement `copyData()` method in `BinaryFileCopy.java`.