# ~~Evidence of fault zone transport of road-salt contaminated groundwater from highways to streams~~Do fault zones route road-salt-contaminated groundwater to streams? A Hudson Valley, NY Case Study

~~Tadd Bindas~~ Tadd Bindas
Marist University
Poughkeepsie, NY
taddbindas@gmail.com

~~Zion Klos~~ Zion Klos
Marist University
Poughkeepsie, NY
zion.klos@marist.edu

## Abstract

~~Many streams in~~ Road salt applied to highways has salinized streams across the northeastern United States~~have grown saltier over recent decades, a trend tied to the widespread use of salt as a road deicer and now recognized as one facet of a broader freshwater salinization syndrome. These rising salt concentrations degrade water quality and stress freshwater ecosystems. Rather than declining in summer, when little salt is applied, stream salinity often rises during these low-flow periods, when groundwater supplies most of the streamflow. This pattern reflects a legacy of road salt stored in and slowly released from groundwater , and it raises the question of what controls where that~~ , and much of that salt is stored in groundwater and released to streams over years to decades. High-angle faults are one candidate control on where this stored salt re-emerges~~. We hypothesized that high-angle geologic fault zones act as preferential conduits that rapidly route~~ , as their fractured damage zones can channel groundwater and road salt has been traced into fractured-bedrock wells. Nevertheless, it remains unclear whether faults deliver road-salt-contaminated groundwater ~~from highways to streams, potentially over kilometers and beneath topographic divides, a linkage previously inferred only from groundwater wells. We tested this with dense longitudinal surveys of~~ to streams. In this work, we surveyed specific conductance, ~~together with a targeted chloride transect~~a proxy for salinity, along three reaches of Wappinger Creek in ~~Dutchess County~~the Hudson Valley, New York, ~~where mapped faults cross the channel. Of the three fault crossings not confounded by a coincident tributary, two showed statistically significant increases in specific conductance across the fault ($\alpha$ = 0.05), and an independent chloride transect reproduced the strongest of these steps at the same mapped fault~~compared zones upstream and downstream of field-interpreted fault positions and tributary junctions within single survey days, applied change-point analysis, and measured one chloride transect. Of three fault contrasts, only one showed a significant increase, but it was small (4.3 $\mu$S/cm), was surveyed at high flow, and was part of a gradual rise beginning about 1.6 km upstream of the channel bend where we placed the fault, beside two private wastewater plants whose contribution we could not test. The other two fault contrasts, surveyed at baseflow, showed no significant increase, and no conductance breakpoint coincided with a fault contrast boundary. Conductance fell at the Site 3 tributary junction, in the direction mixing predicts, although with only three downstream points this is a weak check. We also found that zones could only be compared within a single survey day, because pooling two days created an apparent 18 $\mu$S/cm step at one fault that was a non-significant 1.6 $\mu$S/cm within a day. Hence, we do not claim that this low-cost survey shows fault-routed transport, and we regard the hypothesis as plausible but unresolved. Future work combining single-day surveys, discharge measurements, chloride-to-bromide ratios and age tracers could test it, as a step at a field-located fault that persists at baseflow and carries a deicing-salt signature would support the hypothesis, while its absence would set it aside for faults of this kind.

From this case study we find spatially explicit evidence that fault zones can concentrate the delivery of road-salt-contaminated groundwater to streams. Because comparable faults are already mapped throughout the region, we argue that known fault locations should be incorporated into both roadway and water-quality management planning.

***Keywords*** water quality · fault lines · salinity · de-icing · roadway management

## 1 Introduction

Introduced in the early 1940s as a road Road salt has been used as a de-icing agent in North America and Europe, road salt's usage the United States since the 1940s, and its use has climbed steadily decade over decade [1–3], becoming [1, 3], although application rates vary widely between jurisdictions [4]. It is indispensable for winter road safety. However, it introduces , but it also poses a widespread salinization threat to fresh waters across cold-climate regions [5, 6]. Road salts are effective only within a temperature window; below roughly −9.5 °C (15 °F) it becomes marginally effective, melting demands very high application rates, and most transportation agencies advise against its use [7] . In practice, it is nonetheless applied under these conditions and in amounts beyond what de-icing requires, with consequences that reach well beyond the roadway [4].

Structurally, road salts have corrosive effects that accelerate damage to automobiles, bridges, and other infrastructure [7]. Environmentally, they contaminate groundwater and degrade Beyond corroding vehicles and infrastructure [7] , road salt contaminates groundwater and degrades stream water quality [3, 8]. Their documented ecological effects range from salt-tolerant invasive species outbreaks [9] and disruption of roadside and aquatic habitat [10] to , with ecological effects that include longer-term , indirect shifts in ecosystem function [11]. Many of these effects propagate through aquatic food webs via osmoregulatory stress and community-level feedbacks, and they These effects occur at chloride concentrations at or below existing regulatory guidelines: in a coordinated experiment spanning lakes in North America and Europe, Hintz et al. [12] found that chloride levels at or beneath current water-quality thresholds caused substantial losses of zooplankton and, at nearly half of the study sites, cascading increases in phytoplankton. Because present guidelines do not reliably protect freshwater ecosystems, identifying in lakes across North America and Europe. Identifying *where* salt enters streams, and therefore where mitigation would be most effective, thus carries direct management value.

Although road salt is applied only in the cold months, its effects on freshwater salinity extend across the entire year [13]. While chloride Chloride concentrations are highest in the winter [14], road salts persist in soil for a minimum of 2.5–5 months after application [15], producing a lag-effect that elevates freshwater salinity but stored salt keeps stream salinity elevated into the summer months [16]. When stream discharge is low during the summer months, groundwater inputs keep [16], when groundwater inputs sustain many perennial streams flowing at baseflow. As road salts continue to infiltrate into groundwaterover recent decades [17], Road salt also reaches groundwater, in some settings partly through leakage from salt-laden streams [17], and through this exchange between groundwater and streams, summertime stream salt concentrations continue to risethrough surface-groundwater exchange, leading to examples of have continued to rise, with long-term salinity increases globally [5, 8, 18]. This baseflow signal reflects a growing legacy of salt stored in the subsurface: mass-balance studies in salted regions show that much increases documented in the northeastern United States and Canada [5, 8]. Much of the applied chloride does not flush through quickly but accumulates in groundwater , from which it and is released to streams over years to decades [19], so that summer baseflow salinity integrates decades of past application rather than the most recent winter alone.

This legacy signal is one facet of a broader systemic process, in which salinization is increasingly understood not as a set of isolated effects but as a single coupled phenomenon. Kaushal et al. [20] termed the concurrent, long-term rise in salinity, alkalinity, and associated major ions across fresh waters Salinization is increasingly viewed as a coupled process, the "freshwater salinization syndrome," documenting its progression across the contiguous United States. Subsequent work reframes salinization as a global biogeochemical disturbance: Kaushal et al. [21] describe an " [20] or "anthropogenic salt cycle" in which human activities accelerate the mobilization, storage, and delayed release of salts among soil, water, and air. Most relevant to the present study, Kaushal et al. [22] identify five state factors that govern the severity and trajectory of the syndrome: human activity, geology, flowpaths, climate, and time. This framework explicitly names subsurface geology and hydrologic flowpaths as first-order controls on where and how salt reaches streams. This framing motivates a search for the specific geologic structures and flowpaths that concentrate the delivery of stored salt to surface water[21], in which geology and hydrologic flowpaths are among five proposed state factors driving salinization [22]. This raises the question of which geologic structures control where that stored salt re-emerges.

Among the geologic structures that could route this stored groundwater to the surface, faults are a leading candidate. The clearest evidence to date comes from bedrockwells: Schalk and Stasulis [23] documented four

road-salt-contaminated wells along a fault zone in Maine with elevated specific conductance in both summer and winter, traced to a roadway running along the fault's trace. Faults are more generally recognized as preferential water flowpaths [24, 25], and specifically as conduit-barrier systems [26]. Yet Fault zones are one candidate control. They are commonly described as conduit–barrier systems, in which a low-permeability core is flanked by a fractured damage zone that can favor flow along the fault while hindering flow across it; whether a particular fault acts as a conduit, a barrier, or both depends on its architecture and hydrogeologic setting [27, 28]. In New England, road salt reaches groundwater in fractured bedrock: in Maine, Schalk and Stasulis [23] traced salt in four bedrock wells beside state roads, with specific conductance elevated in summer as well as winter, and they note that the state's highest-yielding bedrock wells coincide with faults and other geologic structures. Studies in the region's metamorphic bedrock also point to structural control of groundwater flow: foliation-parallel fractures can raise connectivity and add flow anisotropy [29], and the Hinesburg thrust fault in Vermont influences well yield and water chemistry [30] . Nevertheless, it remains unclear whether faults carry road salt and deliver it to streams. The Maine evidence links salt to bedrock fractures and not to a particular fault, and we found little direct evidence that faults deliver route highway road salt to streams remains scarce, leaving open whether these structures act as conduits routing contaminated groundwater to surface water. Resolving this has practical stakes: it would flag streams that are geologically connected to a highway is important because, if faults do act in this way, a stream could be at risk through a fault , and thus at risk, even where no road runs nearby.

Tributary confluences are a more familiar cause of abrupt longitudinal changes in stream conductance. Where a tributary joins the main stem, the conductance downstream of the junction is approximately the discharge-weighted average of the two inflowing waters, a two-end-member mixing relation of the kind used to separate flow components from tracer concentrations [31]. A tributary with lower conductance than the main stem therefore dilutes it, and one with higher conductance raises it, by an amount set by the ratio of discharges and the contrast in conductance. A step in conductance at a confluence is thus expected without any fault. A step at a fault crossing with no tributary entering requires a different explanation, such as solute added from groundwater along the reach. Dilution by a tributary could also partly mask a groundwater input at the same location, which we cannot separate without discharge measurements. We therefore treat tributary and fault boundaries as distinct kinds of contrast.

In this work, we ask whether sharp increases in stream salinity coincide spatially with mapped high-angle faults in a way consistent with fault-conduit transport of road-salt-contaminated groundwater from highway to stream. If faults do route contaminated such groundwater to streams, the expectation is specific and spatially testable. Where three predictions follow. First, where a conductive fault crosses a channel, salt-laden groundwater discharging along the structure should produce an abrupt, localized rise in specific conductance between the reaches immediately upstream and downstream of the crossing, rather than the gradual downstream drift expected from diffuse inputs. That ; dense longitudinal surveys have been used to locate point groundwater inputs of road salt to streams in this way [32–34]. Second, the step should persist into summer baseflow , when direct runoff is absent and streamflow is dominated by groundwater, and during baseflow in summer and early autumn, when groundwater-fed baseflow supplies much of the streamflow at low flow [35]. Third, it should be reflected in chloride, the ion that most directly fingerprints deicing salt . A dense longitudinal survey and in chloride-to-bromide ratios, which are widely used to distinguish deicing salt from other chloride sources [36].

We examined these predictions with a case study of Wappinger Creek in Dutchess County, New York, combining dense longitudinal surveys of specific conductance, paired with mapped fault tracesand a targeted , and a single chloride transect, provides exactly this test, and is the approach we take here.

Here, we present a case study of Wappinger Creek in Dutchess County, New York, testing whether sharp increases in stream salinity coincide spatially with mapped and focusing on reaches where mapped high-angle faults, as an example of fault-conduit transport of road-salt-contaminated groundwater from highway to stream. We focused on stream reaches where previously mapped high-angle faults are oriented to route groundwater preferentially from major highways to nearby streams, potentially over kilometers of distance and beneath topographic divides. faults cross the channel. We present this work as a hypothesis-generating case study: a low-cost survey of this kind can show whether the predicted pattern is visible, and what a conclusive test would require, but we do not claim that it can, by itself, demonstrate that faults transport road salt.

## 2 Methods

### 2.1 Site description

For our study we selected three segments of Wappinger Creek, a tributary to the Hudson River in Dutchess County, New York, USA. Each site was chosen based on two factors: whether one or more high-angle faults intersect the stream, and whether the segment could be accessed safely for field measurements. A geologic fault-line map of Dutchess

County [37] allowed us to locate each stream intersection with a high-angle fault and to create a map (Figure 1) containing both fault lines and major roads. Wappinger Creek intersects ~~State Highways~~ US Routes 44 ~~,~~ and 9, New York State Route 55, and ~~9, as well as~~ the Taconic State Parkway ~~,~~ in various sections. Multiple faults bisect the creek in its upper ~~east fork~~ East Branch and its middle section, and the traces of some of these structures appear to control the channel's course, most visibly at Sites 1 and 2. Budnik et al. [37] describe the fault locations as "largely conjectural since the faults themselves are rarely exposed at the surface" (p. 18), so we treat the mapped traces as approximate. The map states no positional accuracy, and we therefore draw the faults as lines and do not attach a width to them. Part of the Site 3 reach, on the East Branch of the creek, runs through conserved forest on the property of the Cary Institute of Ecosystem Studies.

The bedrock beneath the study area consists of metamorphosed clastic sedimentary rocks that were folded and faulted during the Taconic Orogeny, and it is cut by low-angle thrust faults as well as steeper, high-angle faults [37]. This structural setting is central to our hypothesis, because~~fault zones typically comprise a fractured, high-permeability damage zone flanking a lower-permeability core, and can therefore~~ , as described in the Introduction, fault zones can behave as preferential conduits, as barriers, or as combined conduit--barrier systems for groundwater flow ~~[25, 26] . Where the damage zone is well connected, faults can transmit groundwater rapidly and with strong directional anisotropy: at the Hidden Valley fault zone in central Texas, for instance, Ferrill et al. [38] used dye-tracer tests in the Cretaceous Glen Rose Formation (Trinity Aquifer) to document groundwater moving up to roughly 2,600 m/day parallel to the fault and about 990 m/day across the adjacent damage zone, yielding a bulk hydraulic conductivity more than seven times greater parallel to the fault than perpendicular to it. If the~~ [27, 28]. We hypothesize that, if the high-angle faults crossing Wappinger Creek ~~behave comparably~~are conduits, they could route road-salt-laden groundwater from a highway to the channel, potentially even where the two are separated by a topographic divide~~, motivating~~ . This motivated our focus on stream reaches that coincide with mapped fault traces.

## 2.2 In-situ sampling

Conductivity measurements were ~~obtained in October~~ made on four days in autumn 2018~~; taking measurements approximately every hundred meters~~ : Site 1 on 28 September, Site 2 on 5 October, and Site 3 on 19 and 26 October. Site 3 was surveyed over two days, and it therefore comprises three surveys: one on 19 October, and two on 26 October, an upper survey that repeats Zones 3-1 and 3-2 and a lower survey that continues downstream from the end of the 19 October survey. Site 1 was surveyed at very high flow after rain and Site 2 at very high flow, whereas Site 3 was surveyed at baseflow on both days. We measured from upstream to downstream, traversing either on foot inside or around the creek or floating along the channel~~. Sampling was performed~~ , and we sampled in the thalweg ~~of each study site using an electrical conductivity (EC) meter logging the specific conductance of the water, through which we~~ at each site to reduce variation due to incomplete lateral mixing. We used specific conductance as a proxy for salinity, and thus inferred changes in ~~levels of~~ the salt input to the stream along its length ~~.~~

~~Performing measurements in the thalweg kept our data objective by reducing potential variations due to lateral mixing. EC was converted to specific conductivity through adjusting the probe to 25 degrees Celsius. Measurements were taken using~~ from changes in specific conductance. We used a Thermo Scientific Orion 013010MD ~~Conductivity Cell calibrated using~~ conductivity cell, calibrated following the standard protocols outlined by the manufacturer~~.~~ , with readings temperature-compensated to 25 °C and reported as specific conductance (SC). We did not record the meter model, but the Orion meters compatible with this cell specify an accuracy of ±0.5% of reading ±1 digit, about ±1.7 $\mu$S/cm at 310 $\mu$S/cm. A calibration offset shared by all readings on one day cancels when zones are compared within that day, while random reading error does not.

~~Each site was surveyed at a nominal spacing of roughly 100 m from upstream to downstream~~Mean spacing between points was about 85 m at Site 1, 416 m at Site 2 and 83–118 m on the Site 3 surveys, yielding 9, 18, and 46 measurement points at Sites 1, 2, and 3, respectively, with point positions recorded using a handheld GPS unit. Along-channel distance for each survey was computed by summing great-circle distances between consecutive GPS fixes in survey order, with the surveys that were walked upstream reversed so that distance increases downstream.

Within each site we delineated zones bounded at ~~the locations~~ fault positions interpreted in the field or where the creek ~~crosses a mapped fault trace or~~ receives an active tributary, so that the reaches immediately upstream and downstream of a single geologic or hydrologic feature could be compared directly. To isolate the effect of faults, we restricted our fault-crossing contrasts to reaches where the creek intersects a mapped fault without a coincident tributary, because a tributary confluence introduces an independent salinity signal that would confound the comparison. At Site 1 a tributary enters where the channel meets the mapped fault, so we class its only contrast as a tributary contrast and do not count it among the fault contrasts. Because the fault traces are mapped at county scale~~[37], their horizontal positions carry an uncertainty of up to a few hundred meters; we therefore~~ , we treated each crossing as a reach-scale rather than a point-scale feature~~when assigning zone boundaries. Zones are numbered such~~ . We placed each fault





Figure 1: Study area~~overview~~. The three study reaches (a~~o~~range boxes) ~~The county fault map~~on Wappinger Creek, ~~taken directly~~ with high-angle faults digitized from Budnik et al. [37], Fig. 3.10, ~~showing high-angle faults~~ wastewater facilities (squares) and ~~thrust-fault areas across Dutchess County~~major highways. STP is a sewage treatment plant. Sources: US Geological Survey National Hydrography Dataset; US Census Bureau TIGER/Line files; US Environmental Protection Agency Enforcement and Compliance History Online (~~b~~ECHO) ~~The three study reaches on Wappinger Creek (black boxes) on an OpenStreetMap base, with the same high-angle faults overlaid~~database; ~~each site sits where a high-angle fault crosses the creek~~Esri.~~Reach-scale conductivity for each site is detailed in Figures 2–4.~~

boundary at an abrupt, roughly right-angle turn of the channel, which we took to be the creek turning to follow a fault; these field positions lie within a few hundred meters of, but not exactly at, the digitized trace crossings. At Site 2 the digitized county-scale trace runs along the creek for the whole surveyed reach, so it cannot resolve where the fault crosses the channel. The boundary between Zones 2-1 and 2-2, about 4 km along the survey, is therefore placed at the most abrupt bend on the reach, a roughly 90° turn of the channel. An abrupt bend is consistent with structural control of the channel, but it does not by itself show that groundwater flows along the fault there.

Zones are numbered so that they ascend ~~as the river goes~~ downstream: for example~~zone~~ , Zone 3-3 is downstream of Zone 3-2, which is downstream of Zone 3-1. ~~Comparable dense spatial surveys of specific conductance and chloride have been used elsewhere to trace groundwater-sourced road salt to streams and springs, including in a karstic watershed where springs showed the strongest long-term increases [39].~~ This gives five upstream/downstream contrasts (Table 1): A (Zones 1-1/1-2, tributary), B (2-1/2-2, fault), C (3-1/3-2, tributary), D (3-2/3-3, first fault) and E (3-3/3-4, second fault). During the surveys we also marked the points that we believed lay just downstream of a fault, and we call these fault points (Figures 2–6 and Appendix A). They record our judgment on the day and not an observed fault position, and they do not enter the statistical tests; we use them only as a reference when reporting where a change in conductance or chloride lies. At Site 2, where the mapped fault zone runs along the creek, the fault points include three at the upstream end of Zone 2-1, where the mapped fault zone first meets the creek, as well as points in Zone 2-2. These upstream points do not define a second contrast: Site 2 has a single contrast, B, at the bend.

~~Chloride was assessed electronically using a calibrated YSI multi-probe during July~~ On 20 July 2020 ~~within Site 3, upstream and downstream of~~ we measured chloride along a 2.35 km transect of the East Branch at Site 3, from point Z (0 m) to point Z′ (2,351 m), passing the long-term ~~monitoring location of Kelly et al. [40], to determine whether rises in chloride concentration occurred close to the mapped geologic faults. This longitudinal chloride transect spanned roughly one kilometer of the east fork, expressed as relative distance from an upstream point Z to a downstream point Z' (~~monitoring site of Kelly et al. [40] at about 1,224 m (Figure 6)~~, and was collected in summer, when the stream is at baseflow and any elevated chloride is more plausibly attributed to groundwater than to concurrent road-salt runoff. Sampling in July, nearly two years after the October 2018~~ . The aim was to see whether chloride rose near the mapped faults. We took 18 samples in the main channel and one in a side tributary. Chloride was measured with a calibrated YSI Pro Series 1005 chloride ion-selective electrode (YSI 605105) on a YSI handheld meter. The manufacturer gives an accuracy of ±15% of reading or ±5 mg/L, whichever is greater, which at our concentrations (about 14–50 mg/L) is ±5 to ±7.5 mg/L, so differences of a few mg/L between neighboring samples are within instrument error.

We sampled the transect in midsummer, when we expect streamflow to be dominated by baseflow and elevated chloride to come from groundwater more plausibly than from runoff, although we did not measure flow on that day. Because it is a single transect from a different year than the conductivity survey, ~~also provided an independent test of whether the same spatial patternrecurred across years and across a second, more salt-specific measurement~~it cannot confirm the conductivity pattern, and we treat it as descriptive.

### 2.3 Statistical analysis

The ~~specific conductance was normalized within each site using mean/standard-deviation (z-score) normalization (Equation **??**), with the sample mean $\overline{X}$ and sample standard deviation $\sigma_x$ computed separately for each site. This removes day-to-day differences in the overall conductivity level and streamflow between sampling dates and places all sites on a common, dimensionless scale so that the relative rise or fall across a feature can be compared regardless of a site's absolute salinity.~~

$$t_0 = \frac{x - \overline{X}}{\sigma_x}$$

~~Next, we separated the specific-conductance samples into zones defined by where geologic interactions occur, that is, where the stream crosses either a fault or a side-stream. We then~~ zone contrasts and the change-point analysis described below address the first prediction, an abrupt rise at a fault. The second prediction can be examined only at Site 3, which was surveyed at baseflow, and the chloride transect bears on the third. For each contrast we applied a two-sample Welch $t$-test (Equation 1) to evaluate the difference in mean specific conductance, in $\mu$S/cm, upstream and downstream of each feature. Unlike Student's pooled $t$-test, Welch's version does not assume equal variances ~~between the two zones, and it remains reliable when the groups have both unequal variances and unequal~~ and remains reliable with unequal sample sizes, as ours ~~do; for these reasons it~~ are, and is recommended as the default two-sample test [41].

$$t = \frac{\overline{x}_2 - \overline{x}_1}{\sqrt{\dfrac{s_1^2}{n_1} + \dfrac{s_2^2}{n_2}}} \tag{1}$$

Here $\overline{x}_1$ and $\overline{x}_2$ are the mean specific conductance of the upstream and downstream zones, $s_1$ and $s_2$ their standard deviations, and $n_1$ and $n_2$ their sample sizes. ~~Applying a $t$-test to measurements collected sequentially along a channel warrants caution, because closely spaced samples are not strictly independent. We treated the measurements within a zone as approximate replicates of that reach's ambient salinity and tested only the difference in means between adjacent zones; because the within-zone scatter is small relative to the between-zone contrasts (Table 1), we interpret a significant contrast as a genuine step change across the intervening feature rather than an artifact of fine-scale autocorrelation. Site~~ Zones are compared only within a single survey day. Synoptic comparisons along a stream assume steady conditions, because concentrations that change between sampling runs are a source of uncertainty in a longitudinal profile [42]. This matters at Site 3~~was surveyed over two days owing to its length, but every zone-to-zone contrast was computed within a single day's data, and the per-site normalization (Equation ??) removes any offset in baseline conductivity between~~, where conductance on the two survey days differed by about 28 $\mu$S/cm (Section 3.1), which is larger than any of the contrasts we test. We chose not to pool the two days or to subtract the offset, because the reach surveyed on both days shows that the offset is not constant along the channel. Thus, Contrast D is tested on 19 October and Contrast E on 26 October. Zone 3-3 was surveyed partly on each day, however, so the simplest analysis would pool the two days ~~, so the comparisons remain valid~~into one Site 3 data set. To show what that choice does, we also ran the Contrast E test on the pooled data, and we report it separately in Section 3.1. We evaluated significance with two-tailed tests at $\alpha = 0.05$. Because our zone samples are ~~realtively small in size~~ relatively small and not guaranteed to be normally distributed, we accompanied every Welch test with a distribution-free Mann–Whitney $U$ test and regard a contrast as robust only where the two approaches agree, which guards against over-interpreting the smaller contrasts.

Applying a $t$-test to measurements collected sequentially along a channel warrants caution, because closely spaced samples are not strictly independent and nominal $p$-values are therefore likely too small. For each contrast we estimated the lag-1 autocorrelation $\rho$ of the residuals from the two zone means, pooled in along-channel order. Negative values were set to zero and $\rho$ was capped at 0.9. We then computed an effective sample size for each zone, $n_{\mathrm{eff}} = n(1-\rho)/(1+\rho)$, floored at 2 and not exceeding $n$, and repeated the Welch test with $n_{\mathrm{eff}}$ in place of $n$ (degrees of freedom by the Welch–Satterthwaite approximation). With zones of three to eleven points, $\rho$ is poorly determined, so we treat the adjusted $p$-values as a sensitivity check rather than a correction.

Zone means cannot show whether a change in conductance is abrupt or gradual, so we also looked for change points along each transect. For each single-day transect separately (Site 1, Site 2, the 19 October survey at Site 3, and the upper and lower 26 October surveys at Site 3), we fitted continuous piecewise-linear regressions of specific conductance on along-channel distance with zero, one, or two breakpoints, requiring at least three points in each segment, and chose the number of breakpoints by the Bayesian information criterion (BIC). Uncertainty in each breakpoint was assessed with a residual bootstrap (500 replicates). As an independent check we applied a penalized change-in-mean analysis (the pruned exact linear time, or PELT, algorithm in the `ruptures` package). The same procedure was applied to the chloride transect.

Finally, because roads are a possible alternative source of the conductance differences, we computed the distance from each survey point to the nearest major road, defined as primary or secondary roads (US Census Bureau TIGER/Line 2024 road files, feature classes S1100 and S1200; the Taconic State Parkway is coded as a local road, S1400, and is therefore excluded). We report these distances descriptively by zone and do not test them.

# 3 Results

## 3.1 ~~Contrasts~~

## 3.1 Within-day zone contrasts

~~Site~~ In the following, we first report the zone contrasts survey by survey, then show what pooling the two Site 3 days does to them, and lastly describe the reach that was surveyed on both days. Table 1 gives each contrast with zone means $\pm$ SD and the number of points $n$; Table 2 gives the autocorrelation-adjusted $p$-values and the median distance from each zone's points to the nearest major road; Appendix A lists every measurement. Within a single day the zone standard deviations are 0.1–2.6 $\mu$S/cm.

Table 1: Within-day zone contrasts in specific conductance ($\mu$S/cm). $\Delta$ is downstream minus upstream, with its Welch 95% CI; $U$ and $p_{\mathrm{MW}}$ are from the Mann–Whitney test. $^{\dagger}$ marks a zone with fewer than five points.

| Contr. | Boundary | Date | Zones | $n_1, n_2$ | Up (mean±SD) | Down (mean±SD) | $\Delta$ [95% CI] | Welch $t$ (df) | $p$ | $U$ | $p_{\mathrm{MW}}$ |
|---|---|---|---|---|---|---|---|---|---|---|---|
| A | tributary | 28 Sep | 1-1→1-2 | 4,5$^{\dagger}$ | 259.9±0.7 | 259.4±0.1 | -0.5 [-1.5, +0.6] | -1.35 (3.2) | 0.264 | 5 | 0.266 |
| B | fault | 5 Oct | 2-1→2-2 | 10,8 | 308.8±1.1 | 313.1±1.9 | +4.3 [+2.6, +6.0] | 5.63 (10.8) | <0.001 | 79 | <0.001 |
| C | tributary | 19 Oct | 3-1→3-2 | 6,3$^{\dagger}$ | 340.1±0.4 | 336.3±2.2 | -3.8 [-9.2, +1.5] | -2.97 (2.1) | 0.093 | 0 | 0.028 |
| C | tributary | 26 Oct | 3-1→3-2 | 11,3$^{\dagger}$ | 370.5±2.6 | 364.9±1.1 | -5.6 [-7.9, -3.3] | -5.48 (8.8) | <0.001 | 0 | 0.012 |
| D | fault | 19 Oct | 3-2→3-3 | 3,11$^{\dagger}$ | 336.3±2.2 | 333.4±1.9 | -2.8 [-7.4, +1.7] | -2.02 (2.9) | 0.140 | 6 | 0.119 |
| E | fault | 26 Oct | 3-3→3-4 | 6,6 | 358.8±1.8 | 360.4±0.8 | +1.6 [-0.3, +3.4] | 1.96 (7.0) | 0.090 | 30 | 0.076 |

Table 2: Autocorrelation-adjusted tests and road distances for Table 1. $\hat{\rho}_1$ is the lag-1 autocorrelation and $n_{\mathrm{eff}} = n(1-\rho)/(1+\rho)$ the effective sample size; adjusted $p$-values are a sensitivity check. Road distances are zone medians to the nearest primary or secondary road and were not tested.

| Contr. | Date | Zones | $\hat{\rho}_1$ | $n_{\mathrm{eff},1}$ | $n_{\mathrm{eff},2}$ | $p$ (Welch) | $p$ ($n_{\mathrm{eff}}$) | Median road dist. (m) | |
|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | up | down |
| A | 28 Sep | 1-1→1-2 | -0.27 | 4.0 | 5.0 | 0.264 | 0.264 | 927 | 751 |
| B | 5 Oct | 2-1→2-2 | 0.37 | 4.6 | 3.7 | <0.001 | 0.017 | 335 | 726 |
| C | 19 Oct | 3-1→3-2 | -0.35 | 6.0 | 3.0 | 0.093 | 0.093 | 304 | 425 |
| C | 26 Oct | 3-1→3-2 | 0.54 | 3.2 | 2.0 | <0.001 | 0.041 | 245 | 414 |
| D | 19 Oct | 3-2→3-3 | 0.35 | 2.0 | 5.3 | 0.140 | 0.279 | 425 | 409 |
| E | 26 Oct | 3-3→3-4 | 0.30 | 3.2 | 3.2 | 0.090 | 0.243 | 312 | 368 |

**Site 1, Contrast A (28 September).** At Site 1 ~~was split into two zones (~~the tributary contrast showed no detectable change. Specific conductance fell from 259.9 ± 0.7 $\mu$S/cm in Zone ~~1-1 and Zone 1-2), with a single contrast (Contrast A)used for analysis where Wappinger Creek abruptly veers along the mapped fault trace (Figure 2). Before the fault interaction, the sample-mean specific conductance for Zone~~ 1-1 ~~was 259.9~~($n = 4$) to 259.4 ± 0.1 $\mu$S/cm ~~; after the fault, at~~ in Zone 1-2 ~~, it decreased slightly to 259.4~~($n = 5$), a change of $-0.5$ $\mu$S/cm ~~. This slight decrease across the fault, however, coincided with an active tributary entering the creek~~ that is not significant (Figure 2; Table 1). A tributary enters at the same ~~location, so the contrast at Site 1 cannot be attributed to the fault alone. Site 1 is instructive nonetheless: the channel veers to follow~~ place where the channel turns along the mapped fault trace~~(Figure 2), precisely the geometry in which a fault-conduit signal might be expected to appear, but the coincident tributary, together with a rainevent during sampling that lowered specific conductance across this reach by~~ , and Site 1 was at very high flow after rain; conductance there was 50–100 $\mu$S/cm ~~relative to the other two sites, makes this crossing unsuitable for isolating the fault . We therefore exclude Contrast A from the set of clean fault crossings.~~ lower than at the other sites, consistent with dilution by runoff, so this contrast cannot isolate a fault effect and, with four and five points, has little power.

**Site 2, Contrast B (5 October).** Site 2 ~~(Figure 3) has one contrast (Contrast B) between two zones (Zones 2-1 and 2-2). Wappinger Creek parallels a fault line, turns river right due to the topography, then sharply shoots river left at the faultline~~gave the only significant increase at a fault. Zone 2-1 ~~contained a mean specific conductance level of~~ averaged 308.8 ± 1.1 $\mu$S/cm ~~, while~~ ($n = 10$) and Zone 2-2 ~~had a value of~~ averaged 313.1 ± 1.9 $\mu$S/cm ~~. This increase indicates the creek increased in conductivity after the fault line intersection. Site 2 offers the cleanest geometry of the three: the creek runs parallel to a single mapped fault and then crosses it with no tributary entering the reach, so Contrast B provides the most direct test of the fault-conduit hypothesis. Although the mean increase across the crossing is modest at 4.3~~ ($n = 8$), an increase of $+4.3$ $\mu$S/~~cm, the~~ cm (95% CI $+2.6$ to $+6.0$; Welch $p < 0.001$; Mann–Whitney $p < 0.001$; Figure 3). Allowing for autocorrelation along the channel ($n_{\mathrm{eff}} = 4.6$ and 3.7), the adjusted $p$ is 0.017 (Table 2). The difference is larger than the within-zone ~~scatter is small enough that the rise is highly significant (Table 1)~~standard deviations and about 2.5 times the instrument's stated accuracy at this conductance. The Zone 2-1/2-2 boundary, about 4.0 km along the survey, is the channel bend described in Section 2.2. The digitized county-scale trace runs along the creek throughout and crosses the survey line at about 1.0 and 5.8 km, but those intersections are not reliable fault positions, so we did not use them. Flow was very high for the duration of the Site 2 survey, and we canoed part of it, so this survey may not represent baseflow.

**Site 3, Contrasts C, D and E (19 and 26 October).** At Site 3 (Figure 4)~~contains four zones (Zones 3-1, 3-2, 3-3, ~~, conductance fell at the tributary junction on both days, while neither fault contrast showed a significant increase. Contrast C, the tributary junction, is a decrease on both days: $-3.8$ $\mu$S/cm on 19 October (340.1 ± 0.4, $n = 6$, to





Figure 2: Site 1 ~~on a terrain base with highways/county roads~~ (~~brown~~28 September 2018) and ~~streams (blue)~~Contrast A. ~~Survey points~~ Points are ~~coloured~~ colored by specific conductance; ~~red-outlined regions are the survey zones, labelled with their mean specific conductance~~orange rings mark fault points. ~~Zones are numbered in ascending order downstream (~~Zone ~~1-1 upstream, 1-2 downstream). High-angle faults~~ labels give $n$ and mean ± SD (~~thick black lines~~$\mu$S/cm)~~are approximate, digitized~~. Faults from Budnik et al. [37].~~Statistical comparisons between zones are given in Table 1.~~

336.3 ± 2.2, $n = 3$; Welch $p = 0.093$; Mann–Whitney $p = 0.028$) and $-5.6$ $\mu$S/cm on 26 October (370.5 ± 2.6, $n = 11$, to 364.9 ± 1.1, $n = 3$; Welch $p < 0.001$; Mann–Whitney $p = 0.012$; adjusted $p = 0.041$). On 19 October the two tests disagree, and hence this contrast does not meet the robustness criterion of Section 2.3. We believe the disagreement says more about the sample than about the stream, because with groups of only six and three points the Mann–Whitney test cannot return an exact $p$ below about 0.024, and ~~3-4), with the zone transitions corresponding to a side stream (Contrast C) and two faults (Contrast D and E). The east fork of Wappinger Creek intersects a small side stream, turns river left at a fault intersection, then wraps around a hill and darts river left along a second fault line. Zones 3-1 and~~ the downstream zone has only three points on either day, so both tests have little power. Contrast D, the first fault, can be tested only on 19 October, because on 26 October Zones 3-2 ~~yielded mean specific conductance levels of 359.8 and 350.6~~ and 3-3 lie on different transects 1.1 km apart. It is a decrease of $-2.8$ $\mu$S/cm ~~respectively, while Zones~~ (336.3 ± 2.2, $n = 3$, to 333.4 ± 1.9, $n = 11$; 95% CI $-7.4$ to $+1.7$; $p = 0.140$). Contrast E, the second fault, can be tested only on 26 October. Conductance rose from 358.8 ± 1.8 $\mu$S/cm ($n = 6$) in Zone 3-3 ~~and 3-4 had mean values of 342.4 and~~ to 360.4 ± 0.8 $\mu$S/cm ($n = 6$) in Zone 3-4, an increase of $+1.6$ $\mu$S/cm ~~respectively. We collected data for Site~~ (95% CI $-0.3$ to $+3.4$; Welch $p = 0.090$; Mann–Whitney $p = 0.076$; adjusted $p = 0.243$), which is not significant and within the instrument's stated accuracy (±1.9 $\mu$S/cm at 360 $\mu$S/cm). The tributary contrast (C) is thus in the direction mixing predicts, a decrease where the tributary, which measured nearly 150 $\mu$S/cm lower than Zones 3-1 and 3-2, enters, while neither Site 3 ~~over two days, but this does not affect the contrasts reported here, because every zone-to-zone comparison was computed within a single day's data collected sequentially along the reach. Specific conductance decreased after the tributary junction (Contrast C) and after the first fault crossing (Contrast D), then increased sharply after the second fault crossing (Contrast E, Figure 4); as detailed below, only the increase~~fault contrast shows a significant increase.

**Pooling days.** The within-day rule matters most at Contrast E~~reached statistical significance. The three transitions at~~. When we pooled the two survey days, as a first analysis of the Site 3 ~~separate cleanly by feature type. The tributary junction (Contrast C)dilutes the main stem, consistent with lower-conductance side-stream input; the first fault crossing (Contrast D) carries the least statistical power of the survey and sits immediately downstream of that dilution, and its small decrease is not significant;~~ data naturally would, Contrast E appeared as a rise of $+18.0$ $\mu$S/cm ($p < 0.001$), larger than any other step in the survey. However, this value is an artifact of the pooling: Zone 3-3 then





Figure 3: Site 2 ~~, symbolised~~ (5 October 2018) and Contrast B. Symbols as in Figure 2~~: terrain base, roads (brown) and streams (blue), survey~~. The zone boundary is the fault position interpreted in the field at an abrupt 90° bend. The fault points ~~coloured by specific conductance,~~ at the upstream end of Zone 2-1 lie where the mapped fault zone first meets the creek and ~~red-outlined survey zones labelled with their mean specific conductance~~do not define a second contrast. ~~Zones~~ Squares are ~~numbered in ascending order downstream. High-angle faults~~ wastewater facilities (~~thick black) are approximate~~STP, ~~digitized from Budnik et al. [37]~~sewage treatment plant; WWTP, wastewater treatment plant; MHP, mobile home park).~~Statistical comparisons between zones are given in Table 1.~~





Figure 4: Site 3 and Contrasts C, D and E. Circles are 19 October and triangles 26 October 2018 points; the two days differ by about 28 $\mu$S/cm, so zones are compared within a day only. Orange rings mark fault points. The inset enlarges the reach surveyed on both days; the Contrast C boundary is drawn separately for each day because the survey points nearest the junction differ between days. The yellow band is the 2020 chloride transect (Z–Z′) and the red star the monitoring site of Kelly et al. [40].

combines 11 points from 19 October (333.4 $\mu$S/cm) with 6 from 26 October (358.8 $\mu$S/cm), giving a pooled mean of 342.4 $\mu$S/cm, while Zone 3-4 consists only of 26 October points. In other words, the "step" is the difference between days and not a change along the channel; the same pooling inflates the zone standard deviations to 12.6–15.8 $\mu$S/cm, against 0.4–2.6 $\mu$S/cm within a day at Site 3.

**Day offset and the repeated reach.** Eleven 19 October points have a 26 October point within 120 m, and the pairs differ by 23.5–29.7 $\mu$S/cm (mean 27.8, SD 2.2); two points 18 m apart at the seam between the surveys read 332.0 and ~~the second fault crossing (Contrast E)produces the largest step of the entire study, an 18.0~~355.5 $\mu$S/cm~~rise significant at $p < 0.001$. The spatial coincidence of the strongest increase with a mapped fault~~. This seam falls inside Zone 3-3, which is why Figure 4 shows an abrupt change of color partway along that zone. Hence, the offset is not constant, and its ~~absence at the tributary, is the core observation the statistics support.~~

~~Site 3, symbolised as in Figure 2: terrain base, roads (brown) and streams (blue), survey points coloured by specific conductance, and red-outlined survey zones labelled with their mean specific conductance. Zones are numbered in ascending order downstream. High-angle faults (thick black) are approximate, digitized from Budnik et al. [37] . Across the fault crossing between Zones 3-3 and 3-4 the mean specific conductance increases sharply, whereas the tributary junction and the weaker fault crossing show little change; statistical comparisons are given in Table 1.~~

~~Chloride sampling showed chloride measurements consistent with the long-term studies shown by Kelly et al. 2019 [40]~~ range of about 6 $\mu$S/cm exceeds Contrasts B and E, which is why we neither pooled days nor corrected for it. We do not know what caused the offset: Site 3 was at baseflow on both days, and we have no discharge or other measurements with which to explain it. Zones 3-1 and 3-2 were surveyed on both days (Figure ~~6). Strong contrasts in chloride occurred close to where the geological fault line exists with concentration peaking ~1000 meters upstream of the long-term study point. Because this transect was collected in summer,nearly two years after~~ 4, inset): Zone 3-1 averaged 340.1 $\pm$ 0.4 $\mu$S/cm ($n = 6$) on 19 October and 370.5 $\pm$ 2.6 ($n = 11$) on 26 October, and Zone 3-2 averaged 336.3 $\pm$ 2.2 ($n = 3$) and 364.9 $\pm$ 1.1 ($n = 3$), so within each day the zones are internally consistent, while the zone means differ between days by about 29–30 $\mu$S/cm, close to the ~~conductivity survey, its agreement with the Contrast E crossing corroborates the~~ offset between the paired points.

### 3.2 Change-point analysis of specific conductance

Segmented regression and a change-in-mean check on each single-day transect (Figure 5) find no specific-conductance ~~step with an independent ion,in an independent year,~~ breakpoint at a fault contrast boundary or at a point where the digitized trace crosses the transect. At Site 2 one breakpoint is selected at 2,355 m (bootstrap interval 1,327–3,384 m), after which conductance rises steadily downstream; the fitted slope increases from 0.1 to 1.6 $\mu$S/cm per km. This breakpoint lies about 1.6 km upstream of the Contrast B boundary at 3,993 m, the field-interpreted fault position at the channel bend (between 0.6 and 2.7 km upstream, given the bootstrap interval); the change-in-mean analysis places three small shifts ($+1.5$, $+2.3$ and ~~under baseflow conditions when direct road-salt runoff is not occurring. The chloride peak thus reinforces the interpretation that groundwater discharging near the fault, rather than surface runoff, carries the elevated salt into this reach~~$+3.3$ $\mu$S/cm) between 2.6 and 5.9 km. Contrast B is therefore better described as part of a gradual downstream ramp than as an abrupt step at the interpreted fault position.

At the other sites, the analysis gave even less indication of a step. At Site 1 and on the 19 October Site 3 transect no breakpoint is selected (for 19 October a one-breakpoint model ties with none, $\Delta$BIC = 0.03). Instead, on 19 October conductance fell downstream along most of the transect, from 340.5 $\mu$S/cm at its upstream end to 332.0 $\mu$S/cm at its downstream end, through both the tributary junction and the Contrast D boundary, which is the opposite of what a salt-laden fault input would produce. On the upper 26 October Site 3 transect two breakpoints (300 and 459 m) are only marginally preferred ($\Delta$BIC = 0.3) and lie 314–473 m upstream of the tributary junction and away from any trace. The tributary junction thus fares only slightly better than the faults by this test: the change-in-mean analysis places a shift of $-3.2$ $\mu$S/cm at the junction on 26 October, but on 19 October neither method places a change there, and conductance was already falling upstream of the junction on both days. On the lower 26 October transect (Contrast E) one breakpoint is selected at 194 m, where conductance rises from 355.5 to 359.7 $\mu$S/cm over the first 190 m and then stays near 360 $\mu$S/cm. This breakpoint is not at the fault by any measure we have. This breakpoint sits at the three-point minimum segment the method allows, 330 m upstream of where the channel crosses the digitized trace (at 523 m), 123 m in straight-line distance from the nearest trace, and 522 m upstream of the Contrast E boundary.

### 3.3 ~~Two-sample $t$-test~~

### 3.3 Chloride transect

~~Chloride measurements along zones 3-3 and 3-4 shown in relative distance from points Z to Z'. The red star indicates the sampling point from the 32-year dataset introduced by Kelly et al. 2019 [40].~~





Figure 5: Specific conductance along each single-day transect, with segmented fits (orange) and 95% breakpoint intervals (tan); where no breakpoint is selected, the best one-breakpoint fit is shown dashed, without an interval. Pink points are fault points; blue triangles are change-in-mean shifts; gray crosses are digitized fault-trace crossings; green and gray lines are tributary and fault-contrast zone boundaries.

~~Each contrast compares two adjacent reaches of Wappinger Creek separated by a geologic feature, tested with a two-sample Welch $t$-test on the raw specific-conductance measurements (Table 1). Here $\bar{x}_1$~~ The 20 July 2020 transect (Figure 6) ran 2,351 m from Z to Z′, starting near the Contrast D fault points and ending just downstream of the Contrast E fault points, so it lies mostly within Zone 3-3. Chloride across the 18 main-stem samples ranged from 13.75 to 50.0 mg/L, with the highest values at 474 m (50.0 mg/L), 690 m (36.25 mg/L) and 959 m (40.0 mg/L). These lie 133–468 m from the nearest Contrast D fault point and 293–391 m from the nearest digitized fault trace. The latter are straight-line distances; the transect itself crosses a digitized trace only once, at about 1.8 km (Figure 6). The segmented regression selects one breakpoint at 467 m (bootstrap interval 308–800 m), where the fitted slope changes from $+53$ to $-15$ mg/L per km; the change-in-mean analysis places shifts at 384 and ~~$\bar{x}_2$ are the upstream and downstream zone means ($\mu$S~~1021 m. Interestingly, the breakpoint is about 125 m from the nearest Contrast D fault point and about 300 m from the nearest trace; however, it is driven largely by the single 50 mg/~~cm), $n_1$ and $n_2$ their sample sizes, and the "Boundary" column records whether the separating feature is a mapped fault crossing or a tributary junction . At a significance threshold of $\alpha = 0.05$,~~ L sample. Near Contrast E, chloride is low and flat: only 2 of the ~~two fault crossings with the clearest geometry (Contrasts B and E) show significant increases in specific conductance ($p < 0.001$); the third fault crossing (Contrast D) and the two tributary-confounded contrasts (A and C) do not reach significance. A nonparametric Mann–Whitney $U$ test gives the same picture for B, D,~~ 18 samples lie downstream of the Contrast E fault points (13.75 and ~~E.~~ 15.0 mg/L), and the last five samples are 13.75–17.5 mg/L. The transect therefore shows no chloride increase at Contrast E. With so few points downstream of E we did not attempt a two-sample test.

~~Two-sample Welch $t$-test results for each upstream/downstream contrast. Contrasts B and E (fault crossings) are significant at $\alpha = 0.05$.~~





Figure 6: Chloride along the 20 July 2020 transect (Z–Z′). The orange line is the segmented fit, with its breakpoint (467 m) and 95% interval (tan); the breakpoint rests largely on the single 50 mg/L sample. Pink ticks mark the fault points at Contrasts D and E, the gray cross where the digitized fault trace crosses the transect, and the red star the monitoring site of Kelly et al. [40].

# 4 Discussion

## 4.1 ~~Contrasts~~

## 4.1 What the contrasts show

~~Two contrasts showed statistically significant changes in specific conductance: Contrasts B and E, from Sites 2 and 3 respectively. Each is a fault crossing, and each showed a statistically significant increase in specific conductance after the fault line interaction at $\alpha = 0.05$, indicating a likely increase in stream salinity. The tributary-confounded contrasts A and C both showed decreases in specific conductance that did not reach significance; in any case these~~

~~do not bear on our main conclusion about faults, because each corresponded to~~ Our survey offers little support for the ~~location of an active tributary inputting water to the main stem of the creek, and measurements at Site 1 were taken during a rain event that occurred during sampling that day. The salinity levels for this section of the creek were between 50–100~~hypothesis that fault zones route road-salt-contaminated groundwater to Wappinger Creek. Of the three fault contrasts, one shows a small, significant increase in specific conductance (Contrast B, $+4.3$ $\mu$S/cm~~lower than the measurements taken at the other two sites. At Contrast C the active tributary measured nearly 150~~), one shows a non-significant decrease (Contrast D, $-2.8$ $\mu$S/cm~~lower than the specific conductance measurements at Zones 3-1 and 3-2.~~

~~Of the three fault crossings that do not coincide with an active tributary (Contrasts B, D, and E), two showed a statistically significant increasein specific conductance, while the third , Contrast D, did not reach significance at $\alpha$ = 0.05 (Welch $t = -1.15$, $p = 0.286$). We do not read the~~ ) and one shows a non-significant ~~crossing as evidence against fault-mediated transport. Contrast D compares the two zones with the most unequal sample sizes ($n_1$ = 6, $n_2$ = 17; Table 1) and lies immediately downstream of the tributary-diluted Zone 3-2, so its two reaches begin from different baseline concentrations and the comparison carries the least statistical power of the five. A single non-significant crossing bounds the strength of any inference we can draw from three examples, but it does not weaken the significant increases at Contrasts B and E, each of which recovered a clear signal from the same small-sample setting. We therefore present these three crossings as an initial, spatially explicit example of the pattern rather than as a population-level test of it. Later additional observation of longitudinal chloride concentrations across Contrast E (Figure 6, Z to Z') indicated the same strong contrast associated spatially with mapped fault locations.~~ increase within instrument accuracy (Contrast E, $+1.6$ $\mu$S/cm). No conductance breakpoint on any transect coincides with a fault contrast boundary. Recall that we set out three predictions in the Introduction. The first, an abrupt step at a fault, was not met at any crossing. The second, persistence of the step at baseflow, could be examined only at Site 3, which was surveyed at baseflow on both days, and neither fault contrast there showed a significant increase; Sites 1 and 2 were surveyed at high flow, so Contrast B cannot speak to it. The third was examined only with a single chloride transect and no bromide. Hence, none of the three predictions is supported by this survey, although admittedly only the first could be examined at all three fault crossings.

~~A published 32-year dataset [40] from the same stream reach as our study (Figure 4, star; Figure 6, Z to Z') indicated that stream chloride has gradually increased in the area from annual means of roughly 15~~Although Contrast B is statistically significant, we do not claim it as evidence of fault transport. The rise is gradual and begins roughly 1.6 km upstream of the zone boundary, which marks the fault position we interpreted in the field at an abrupt channel bend, along a reach where the county-scale fault trace runs parallel to the creek and cannot show where the fault meets the channel. A rise of this kind could be produced either by diffuse groundwater input or by a fault-parallel flowpath delivering water along the reach, and our survey cannot tell the two apart. Nevertheless, we believe Contrast B is an observation worth testing further, because it is the one place where conductance rose along a fault-controlled reach. Contrast D, at a fault with no tributary, shows no increase. Indeed, on 19 October conductance fell steadily downstream through this boundary. Contrast E is within the instrument's stated accuracy and its only breakpoint lies near the start of a short transect, 330 m upstream of where the channel crosses the trace. The 2020 chloride transect adds a further observation worth testing, in the same limited way: its peak lies near the Contrast D fault points and about 300 m from the nearest trace, but it rests on one sample, comes from a different year, and chloride near Contrast E is low (about 14–15 mg/~~l in the 1980s to over 40 mg/l for annual means by the 2010s. This increase through time, as well as other findings [40], suggest a strong tie to human applications of road salt in the region. The elevated levels in streamflow in summer strongly suggest artificially elevated chloride levels overall, well above geologic background levels in groundwater~~L). We do not treat the chloride peak as support for the conductance result at any contrast.

The tributary contrast serves as an internal check, although admittedly a weak one. Conductance was lower below the junction on both days, which is the direction two-end-member mixing predicts when lower-conductance water joins the main stem [31]. However, ~~this study used only one location of data collection for long-term work on the stream [40], and was therefore not able to look at the spatial aspect of possible fault controls as transport pathways for road salts, as we have here. This new spatial conductivity and chloride data~~ the downstream zone has only three points, the two tests disagree on 19 October, and conductance was already falling along the reach above the junction (Figure ~~6), in combination with the findings of similar concentrations of chloride during this extensive long-term study in the same stream stretch [40], together offer a much stronger link to road salts and their spatial controls on transport from faults. Collectively, this provides strong initial evidence that linear fault zones are indeed aiding in the preferential input of salt-polluted groundwater into streams at locations that correspond to where these major km-scale geologic structures connect both streams and highways~~5), so we cannot say how much of the decrease the tributary itself supplies. Hence, we take Contrast C as an indication that the survey responds to a known input, and not as a measure of how small an input it can detect.

### 4.2 ~~Addressing possible alternative sources of salinity in Wappinger Creek~~

Furthermore, the differences we are discussing are small relative to what the instrument can resolve. The stated accuracy of the conductivity measurement is a bound on absolute error, and a calibration offset common to all readings on one day cancels in a within-day difference, but random reading error does not, and the manufacturer gives no repeatability figure. Contrast B exceeds that bound by a factor of about 2.5 and exceeds the within-zone scatter, which is why we report it as a statistically significant but small difference; Contrast E does not exceed it. Site 1 contributes little either way, because a coincident tributary and very high flow after rain confound its only contrast. Taken together, the survey is best read as a screening result: it shows what a low-cost survey can detect, namely a small gradual rise at one site and the dilution at a tributary, and it also shows that such a survey does not locate a fault-related input to within the spacing of a few hundred meters that a fault trace of uncertain position would require.

~~Increases in salinity can also occur as salts naturally enter the environment through the geological weathering of rock surfaces [43]. The bedrock below Wappinger Creek consists of metamorphosed clastic sedimentary rocks [37] known to have minimal influence of stream salt input. A 2008 study of sodium chloride retention in~~

### 4.2 Alternative explanations

Several explanations for the Site 2 increase, and for the ~~east branch of Wappinger Creek (a portion of our study site) identified average salt input to the stream from various sources such as road salt, parking area salt, sewage, or rock weathering. The result found road salt contributes to 83% of stream salt input, while geological rock weathering accounts for only 1% of the input [16]. Therefore, we argue that rock weathering is likely a tiny portion of total stream salt input and cannot account for the inferred changes in salinity we observed along fault zones in our study. This local partitioning is consistent with the wider regional picture. Syntheses of the anthropogenic salt cycle attribute the accelerating mobilization and accumulation of salt in temperate watersheds to human activities, with road deicing prominent among them [21], and mass-balance work across a comparable metropolitan region shows that a large fraction of applied road salt is retained in, and only slowly released from , groundwater rather than flushed directly to streams [19]. Both lines of evidence point to a mobile, human-derived chloride pool held in the subsurface, precisely the pool that a conductive fault could route preferentially toward the channel . The elevated summer conductivities we recorded, at a time of year when direct road-salt runoff is absent, are difficult to reconcile with a purely geologic source and instead implicate this stored anthropogenic salt. Stream salinity can also rise~~ conductance differences generally, are at least as plausible as fault-routed groundwater with the data in hand.

We first considered the roads themselves. Per-zone median distances from survey points to the nearest major road range from 245 to 927 m (Table 2). At Site 2 the downstream zone is farther from a major road than the upstream zone (median 726 versus 335 m), so proximity to a major road does not by itself explain Contrast B, although one upstream point lies only 39 m from a road and the distances do not capture drainage or road density. The Site 3 zones lie 245–425 m from the nearest major road, mainly US 44, with no monotone relation to the conductance pattern. These are descriptive medians, not a test, and they say nothing about salt stored in roadside soils and shallow groundwater, which may be flushed to the channel late in the season and which our survey cannot distinguish from deeper, fault-routed water. Our surveys were made in late September and October, so a late-season release of such stored salt is a possibility we cannot exclude; it would, like diffuse groundwater, favor a gradual rise over a step.

Developed land is a second possible source, as stream conductance also rises near developed land from ~~inputs~~ sources unrelated to faults or highways, such as residential runoff and lawn ~~or~~ and agricultural fertilizers. ~~Because our sampling took place entirely~~ Site 2 runs beside US 44 and ends near the settled area around Titusville (Figure 3); we did not quantify land cover, and thus cannot weigh this source. Part of Site 3 lies within conserved forest ~~, managed under a single entity with no fertilization practices, we can discount fertilizer runoff as a driver of the contrasts we observed~~(Section 2.1). Sampling within conserved land does not let us discount such inputs, because the sources lie in the contributing area and not only along the survey line.

### 4.3 ~~Placing fault-mediated transport within the freshwater salinization syndrome~~

~~The gradual, sustained salinization of temperate freshwaters is now commonly described as a freshwater salinization syndrome, a coupled set of physical, chemical, and biological changes driven by the accumulation of anthropogenic salts [6, 22]. Kaushal and coauthors organize the controls on this syndrome into a small set of state factors, among them the geology of a watershed and~~ Wastewater is a third possibility, and for Contrast B we believe it is the most specific one. Kelly et al. [16] estimated sodium chloride sources for the East Branch of Wappinger Creek and found that road salt contributed 83% and parking-area salt 8% (91% from deicing), sewage including septic systems 4%, and water softeners 3%. We did not map septic systems along our reaches. The Millbrook sewage treatment plant that they describe is upstream of all three of our sites, about 2.4 km along the channel above Site 3 and 15.3 and

25.3 km above Sites 1 and 2 (facility locations from the US Environmental Protection Agency's Enforcement and Compliance History Online database, ECHO). As a continuous upstream source it would raise baseline conductance but would not by itself create a step at a zone boundary. More relevant to Contrast B, two small private plants, Stratford Farms and Ennis Mobile Home Park, have listed locations 240–370 m from Zone 2-1 (Figure 3), at about 1.6 and 0.9 km along the survey, upstream of the ~~flowpaths that connect salt sources to receiving waters [22]. Our results speak directly to the intersection of those two factors. Rather than treating the subsurface as a uniform reservoir that releases stored road salt diffusely,we find that a specific geologic structure, the high-angle fault, appears to organize where that release reaches the stream. This is mechanistically plausible. Fault zones are well documented to act as high-permeability conduits, or, where mineralized and sealed, as barriers, that focus groundwater flow [26, 38], and recent three-dimensional modeling shows that the hydraulic-conductivity contrast between a fault and the surrounding rock can control how recharge is partitioned and where groundwater discharges to the surface [44]. Viewed through the syndrome framework,~~ 2,355 m breakpoint and, for the former, within its 1.3–3.4 km bootstrap interval. These are facility locations rather than outfalls, and flows are not listed, so we cannot test whether they contribute, but they are a plausible, untested alternative source for the Site 2 increase. The Titusville plant lies just downstream of the last Site 2 survey point, so it cannot affect Contrast B, and the Valley Dale plant discharges to a tributary about 2 km away, off the frame of Figure 3. A sixth listed facility, at a state police headquarters, lies about 0.8 km west of the downstream end of the Site 3 survey, on a tributary of the East Branch and not on the surveyed channel (the unlabeled square beside Site 3 in Figure 1); no flow is listed for it.

Finally, groundwater unrelated to faults can enter the creek anywhere along a reach. Such diffuse inputs would raise conductance gradually downstream rather than in a ~~fault is not a separate salt source but a flowpath that concentrates an existing anthropogenic source at discrete points along a channel . This distinction matters for consequences as much as for causes, because chloride delivered to a stream in such a focused way can raise local concentrations toward levels shown to restructure freshwater plankton communities [45], and to act together with warming to compound those community-level effects [46].~~ step, and longitudinal surveys elsewhere show that local groundwater inputs and land use drive spatial variation in stream chloride [34]; the gradual ramp at Site 2 is consistent with such inputs. Long-term records show that stream chloride in the East Branch has risen from roughly 15 mg/L in the mid-1980s to over 40 mg/L by the mid-2000s [16], consistent with a regional anthropogenic source and a large store of salt in the subsurface [19], but a single monitoring location cannot show where along the channel that salt enters.

### 4.3 ~~Suggestions for future research~~

### 4.3 Comparison with other studies and implications

~~More investigations are needed in the coming years to better understand this newly observed process of salt movement through groundwater from road to stream along geologic faults. Additional sampling in bodies of water where major fault lines are present is required to concretely determine to what extent fault lines are adding saltier groundwater into streams in other regions globally. This sampling technique needs to be replicated at greater spatial scales to come to a more comprehensive conclusion regarding the prevalence of faults in contributing to the movement of road salts from highways through groundwater, particularly in regions with different lithologies and tectonic history. Our evidence has shown that of these three case examples of highway-fault-stream connections that we could isolate, all three point to a potential link between pre-existing fault lines and hint at the processes by which stream salinity levels are increasing, but additional research could further strengthen these findings. Beyond broader spatial replication, several targeted methods could test the transport mechanism itself more directly. Paired groundwater and surface-water sampling at fault crossings, combined with environmental age tracers, would establish whether the water discharging near a fault is older, deeper groundwater rather than recent local runoff, an approach already used to infer fault hydrology from apparent groundwater ages along bore transects [47]. Chloride-to-bromide ratios could further fingerprint deicer-derived saltagainst geologic end-members, and repeating the survey across contrasting lithologies and tectonic settings would show how far the pattern generalizes.~~ Our mixed result is not at odds with what is known about faults in rock like ours. The conduit–barrier model does not predict that every fault leaks, as a fault may carry water along its damage zone, block flow across its core, or do both, depending on its architecture and setting [27, 28]. In New England metamorphic bedrock, structural control has been shown at the scale of wells, through foliation-parallel fractures that raise connectivity and add anisotropy [29] and through a thrust fault that influences well yield and water chemistry [30]. Thus, a survey in which one of three faults shows a small rise and two show none does not tell us whether the other two faults act as barriers, are not connected to a source of salt, or simply discharge too little to register in the thalweg. These studies make fault-routed delivery plausible, but none of them involves road salt, and hence none of them tests it.

### 4.4 ~~Management implications of conclusions~~

~~Salt input to streams, rivers, and lakes through groundwater input will continue, even if the use of road salts ceases due to the long transit time of water in groundwater flow systems [48]. This is concerning for human and aquatic life. Mitigation options to reduce road salt contamination could involve alternative or spatially unique methods to de-ice roads [49]. Roads should not be treated as homogeneous due to the differences in vegetation and biome around them and unique geologic structures below them, and prior to treatment, mitigation of road salt impacts to the environment should be further taken into account [50].~~

~~Although road salts are cost-effective, their true cost is higher than similar de-icing agents due to its environmental cost [7]. There exist various de-icing agents and methods that pose less of a threat to the environment such as anti-icing and pre-wetting [40, 51]. To aid in reducing the negative impacts of road salts, small and large local governments could develop a salt management plan,~~ Other longitudinal surveys locate salt-laden groundwater inputs more directly than ours. Electromagnetic mapping of a New Hampshire streambed found discrete reaches of high-conductivity discharge [32], and streambed conductivity and temperature mapping in urban streams found porewater chloride ranging from under 100 to over 5,000 mg/L within about 10 m [33]. Longitudinal chloride and radon-222 in mixed-land-use streams showed that local groundwater inputs and land use drive spatial variation [34], and long-term sampling of chloride in streams and springs has been used to trace groundwater-sourced road salt, with the highest chloride in a karst watershed in Pennsylvania occurring in summer baseflow [39]. Compared with these approaches, a thalweg survey at roughly 100–400 m spacing integrates over the whole channel flow and is presumably less sensitive to focused inputs that vary over 10 m. In other words, a survey like ours could miss a real fault signal as well as ~~effectively train staff and local populations about the harmful effects of road salts and how to monitor for their impacts [7]. The first step in a salt managementplan is to identify salt sensitive areas~~report a spurious one.

We do not claim that the evidence here justifies changing deicing practice on the basis of fault locations. Mapped faults are, at most, a candidate screening layer, and future work should test them with the design in Section 4.4 before they are put to any use in salt management. Measures that reduce the total salt load, such as ~~groundwater recharge areas, wetlands, shallow water tables, drinking water sources, salt-sensitive vegetation. With these new findings outlined here, we argue that known geologic information on locations of high-angle faults should also be included. Based on these different sets of geographic information, the salt management plan outlines steps to use another different de-icing agent if a road section intersects any known fault zones. Such geologically informed targeting complements, rather than replaces, the broader operational practices now being formalized at the state level. In New York, the Adirondack Road Salt Reduction Task Force has recommended a coordinated program of application-rate reductions, calibrated and pre-wetting equipment,~~ lower application rates, calibrated equipment, brine-based ~~anti-icing,~~ anti-icing and staff training, as recommended by the Adirondack Road Salt Reduction Task Force [52], remain the better-supported response everywhere.

### 4.4 Limitations and a test of the hypothesis

Admittedly, several limitations constrain how far these results can be taken. We have no discharge measurements, so we cannot estimate the volume of any groundwater input, convert conductance to load, or separate dilution from addition. We have no source tracers, so we cannot attribute salt to roads, wastewater or other sources. Future work with paired discharge and tracer measurements could address both of these gaps, as we describe at the end of this section.

Each reading is a single thalweg value, with no repeats across the channel or at depth, so lateral and vertical variation, which could exceed the small contrasts, is unmeasured. This matters because Contrasts B and E are close to the instrument's stated accuracy (Section 4.1), and we cannot rule out that reading error accounts for part of Contrast B. At Site 3 we surveyed on two days; the reach repeated on both days gave an offset that varied by about 6 $\mu$S/cm (Section 3.1), too much to tie the days together, which limited us to within-day comparisons of small zones and left Contrast D untestable on 26 October.

The chloride data are more limited still, as they come from a single transect in a different year, measured with an ion-selective electrode whose stated accuracy ($\pm$15% of reading or $\pm$5 mg/L) is a substantial fraction of the concentrations we measured; only the larger differences, such as the 50 and ~~staff training [52], measures that lower the total salt load entering the subsurface everywhere. Our findings suggest that where such programs must prioritize limited resources, road segments that cross mapped fault zones are logical candidates for the earliest and most aggressive reductions, because the salt applied there has a direct structural pathway to nearby streams.~~ 40 mg/L peaks against a background of about 14–25 mg/L, exceed it. We therefore treat the chloride results as descriptive.

The fault traces come from a county-scale map for which no positional accuracy is stated (Section 2.1), so we cannot say how far a real fault lies from any mapped position. This is admittedly a weakness for a study whose hypothesis is spatial: if a mapped trace is off by a few hundred meters, a real step could fall outside the zone boundaries we

tested. Field mapping of the fault zone at each crossing would remove this uncertainty. Moreover, our zones contain only three to eleven points, so the tests have little power and the autocorrelation used to discount them is itself poorly determined. Finally, three fault contrasts in one lithology cannot support a general statement about faults, and we leave it to future work with many crossings in several rock types to test whether any pattern holds.

The survey nonetheless suggests how the fault-conduit hypothesis could be tested. Our Site 3 data show why surveys should be completed within a single day, or tied across days by repeated points at a steady offset: pooling the two survey days produces an apparent 18 $\mu$S/cm step at the second fault that is entirely the offset between days. Future work should pair each survey with discharge measurements, which would turn conductance into load and separate dilution from addition. Furthermore, chloride-to-bromide ratios would fingerprint deicing salt against wastewater and other sources [36], while environmental age tracers would indicate whether water entering near a fault is older groundwater [47]. Repeated readings across the channel and at depth would show whether contrasts as small as ours exceed lateral variation. We also believe that fault zones should be located in the field rather than from county maps, and that change-point analysis should be applied to single-day transects so that gradual ramps and abrupt steps can be distinguished. Finally, surveys covering many crossings in several lithologies would show whether any pattern holds beyond one creek. We hypothesize that, if faults do route road salt to streams, such a design would find a step at a field-located fault that persists at baseflow and carries a deicing-salt signature and an older age; if it found none, the hypothesis could be set aside for faults of this kind.

## 5 Conclusions

~~We set out to test whether~~

In this work, we used longitudinal surveys of specific conductance and a single chloride transect to ask whether high-angle ~~geologic faults act as preferential pathways that route~~ fault zones route road-salt-contaminated ~~groundwater from highways into streams, using three fault-crossing reaches of Wappinger Creek as a spatially explicit case study. Applying a two-sample Welch $t$-test to reach-scale specific-conductance surveys, we found that two of the three fault crossings not confounded by an active tributary showed statistically significant increases in stream salinity across the structure ($p < 0.001$~~groundwater to Wappinger Creek, and our survey does not answer the question clearly. Comparing specific conductance within single survey days, we found a small but significant increase of 4.3 $\mu$S/cm at one of three fault contrasts (Site 2), ~~while the third did not reach significance in the comparison with the least statistical power. A later longitudinal chloride survey reproduced the strongest of these steps at~~ about 2.5 times the instrument's stated accuracy. However, change-point analysis suggests that this increase is part of a gradual rise beginning roughly 1.6 km upstream of the channel bend where we placed the fault, rather than a step at it, and two private wastewater plants beside that reach offer an alternative explanation we could not test. At the other two faults, conductance either did not increase or rose by less than the instrument's accuracy, and no conductance breakpoint on any transect coincided with a fault contrast boundary. Conductance fell at the tributary junction, in the direction mixing predicts, which gives us some confidence that the survey responds to a known input. The single chloride transect from 2020 peaked near a different fault, but that peak rests on one sample.

We believe the most transferable result is methodological. When we pooled the two Site 3 survey days, the ~~same mapped fault location, and a published 32-year record from the same reach independently ties the elevated, summer-persistent salinity to decades of anthropogenic road-salt application rather than to geologic weathering. Taken together, these observations provide initial, spatially resolved evidence thatfaults can concentrate an existing anthropogenic salt pool at discrete points along a channel, placing this mechanism at the intersection of the geology and flowpath state factors of the freshwater salinization syndrome. Because our conclusions rest on three crossings within a single lithology, we present them as an illustrative example rather than a definitive population-level test, and we have outlined age-tracer, ionic-ratio, and multi-lithology studies that could test the mechanism more directly. If the pattern holds more broadly, it carries a concrete management implication: mapped fault locations are readily available geologic information that could help target salt-reduction efforts toward the road segments where contaminated groundwater has the most direct route to surface water.~~ second fault appeared as the largest and most significant step in the survey (18.0 $\mu$S/cm), but within a single day the contrast was only $+1.6$ $\mu$S/cm; the apparent step was an artifact of the offset between days. Longitudinal surveys aimed at locating point inputs therefore need single-day sampling, or repeated points that tie survey days together at a steady offset, effective sample sizes that account for spatial autocorrelation, and analyses that can distinguish gradual ramps from abrupt steps.

~~Two broader points follow. Methodologically, matching the statistical test to the structure of the data matters here: a two-sample Welch test, which accommodates the unequal variances and unequal sample sizes of our zones, concentrates significance at the unconfounded fault crossings rather than spreading it across tributary junctions, and pairing it with a distribution-free check guards against over-interpreting the smaller contrasts. Substantively, because~~

~~high-angle fault maps already exist for many regions, much of the geologic information needed to flag at-risk reaches is already in hand, and fault traces could be adopted as a planning layer wherever highways and salt-sensitive streams share a faulted catchment. Confirming how widely the mechanism operates will require the multi-site, multi-lithology sampling outlined above, but the case presented here establishes both the pattern and a practical way to search for it elsewhere~~Nevertheless, we do not think the hypothesis should be set aside. Studies of fault zones in fractured and metamorphic rock make fault-routed delivery plausible, and our survey could not have ruled it out, so we regard the hypothesis as plausible but unresolved. Until it is tested, we suggest that mapped faults be treated as a candidate screening layer to evaluate, and not as a basis for changing deicing practice. Future work should follow the design in Section 4.4, with single-day surveys, discharge measurements and tracers, and should extend to other creeks and rock types to see whether any pattern holds.

## Acknowledgements

We would like to thank Marist University for providing funding and equipment to carry out our research as part of the first author's senior honors thesis and John Kittredge for collecting the data for the ~~Chloride~~ chloride samples within Figure 6. We also would like to thank the Cary Institute of Ecosystem Studies for allowing us access to walk sections of the ~~east-fork~~ East Branch of Wappinger Creek which fall under their property line.

During the preparation of this work, the authors used an LLM agent to assist with language editing. All AI-generated content was carefully reviewed and edited by the authors, who take full responsibility for the final version of the manuscript.

## Conflict of interest

The authors declare that they have no conflict of interest.

## Data Availability

~~Both the data , and the code , to reproduce~~ The data and code needed to reproduce the figures and statistics ~~from~~ in this paper are ~~made~~ available at the following GitHub Repository: `https://github.com/taddyb/wappingers_road_salts`. All individual specific-conductance measurements are also listed in Appendix A. Road and stream layers are from the US Census Bureau TIGER/Line 2024 files and the USGS National Hydrography Dataset, and wastewater facility locations are from the EPA ECHO database (retrieved 2026-11-08).

## References

[1] A. Tiwari and J. W. Rachlin. A review of road salt ecological impacts. *Northeastern Naturalist*, 25(1):123–142, 2018. doi:10.1656/045.025.0110.

[2] R. C. Bubeck, W. H. Diment, B. L. Deck, A. L. Baldwin, and S. D. Lipton. Runoff of deicing salt: Effect on Irondequoit Bay, Rochester, New York. *Science*, 172(3988):1128–1132, 1971. doi:10.1126/science.172.3988.1128.

[3] R. B. Jackson and E. G. Jobbagy. From icy roads to salty streams. *Proceedings of the National Academy of Sciences*, 102(41):14487–14488, 2005. doi:10.1073/pnas.0507389102.

[4] A. Jamshidi, A. R. Goodarzi, and P. Razmara. Long-term impacts of road salt application on the groundwater contamination in urban environments. *Environmental Science and Pollution Research*, 27:30162–30177, 2020. doi:10.1007/s11356-020-09261-7.

[5] S. S. Kaushal, P. M. Groffman, G. E. Likens, K. T. Belt, W. P. Stack, V. R. Kelly, et al. Increased salinization of fresh water in the northeastern United States. *Proceedings of the National Academy of Sciences*, 102(38): 13517–13520, 2005. doi:10.1073/pnas.0506414102.

[6] H. A. Dugan and S. E. Arnott. The ecosystem implications of road salt as a pollutant of freshwaters. *WIREs Water*, 10(2):e1629, 2023. doi:10.1002/wat2.1629.

[7] D. L. Kelting and C. L. Laxson. Review of effects and costs of road de-icing with recommendations for winter road management in the Adirondack Park. Technical Report AWI2010-01, Adirondack Watershed Institute, Paul Smith's College, 2010. URL `https://www.adkwatershed.org/all-publications/review-of-effects-and-costs-of-road-de-icing-with-recommendations-for-winter-road-management-in-the-adirondack-park`.

[8] D. D. Williams, N. E. Williams, and Y. Cao. Road salt contamination of groundwater in a major metropolitan area and development of a biological index to monitor its impact. *Water Research*, 34:127–138, 2000. doi:10.1016/S0043-1354(99)00129-3.

[9] J. A. Richburg, W. A. Patterson, III, and F. Lowenstein. Effects of road salt and *Phragmites australis* invasion on the vegetation of a western Massachusetts calcareous lake-basin fen. *Wetlands*, 21:247–255, 2001. doi:10.1672/0277-5212(2001)021[0247:EORSAP]2.0.CO;2.

[10] R. T. T. Forman and L. E. Alexander. Roads and their major ecological effects. *Annual Review of Ecology and Systematics*, 29:207–231, 1998. doi:10.1146/annurev.ecolsys.29.1.207.

[11] S. E. G. Findlay and V. R. Kelly. Emerging indirect and long-term road salt effects on ecosystems. *Annals of the New York Academy of Sciences*, 1223:58–68, 2011. doi:10.1111/j.1749-6632.2010.05942.x.

[12] W. D. Hintz et al. Current water quality guidelines across North America and Europe do not protect lakes from salinization. *Proceedings of the National Academy of Sciences*, 119(9):e2115033119, 2022. doi:10.1073/pnas.2115033119.

[13] M. D. Shattuck, H. M. Fazekas, A. S. Wymore, A. Cox, and W. H. McDowell. Salinization of stream water and groundwater at daily to decadal scales in a temperate climate. *Limnology and Oceanography Letters*, 8:131–140, 2023. doi:10.1002/lol2.10306.

[14] S. R. Corsi, L. A. De Cicco, M. A. Lutz, and R. M. Hirsch. River chloride trends in snow-affected urban watersheds: increasing concentrations outpace urban growth rate and are common among all seasons. *Science of the Total Environment*, 508:488–497, 2015. doi:10.1016/j.scitotenv.2014.12.012.

[15] H. K. Robinson, E. A. Hasenmueller, and L. G. Chambers. Soil as a reservoir for road salt retention leading to its gradual release to groundwater. *Applied Geochemistry*, 83:72–85, 2017. doi:10.1016/j.apgeochem.2017.01.018.

[16] V. R. Kelly, G. M. Lovett, K. C. Weathers, S. E. G. Findlay, D. L. Strayer, D. J. Burns, et al. Long-term sodium chloride retention in a rural watershed: Legacy effects of road salt on streamwater concentration. *Environmental Science & Technology*, 42(2):410–415, 2008. doi:10.1021/es0713911.

[17] M. O. Rivett, M. O. Cuthbert, R. Gamble, L. E. Connon, A. Pearson, M. G. Shepley, et al. Highway deicing salt dynamic runoff to surface water and subsequent infiltration to groundwater during severe UK winters. *Science of the Total Environment*, 565:324–338, 2016. doi:10.1016/j.scitotenv.2016.04.095.

[18] A. Foos. Spatial distribution of road salt contamination of natural springs and seeps, Cuyahoga Falls, Ohio, USA. *Environmental Geology*, 44:14–19, 2003. doi:10.1007/s00254-002-0724-7.

[19] K. J. Van Meter and E. Ceisel. Road salt legacies: quantifying fluxes of chloride to groundwater and surface water across the Chicago metropolitan statistical area. *Water Resources Research*, 60(2):e2023WR035103, 2024. doi:10.1029/2023WR035103.

[20] S. S. Kaushal, G. E. Likens, M. L. Pace, et al. Freshwater salinization syndrome on a continental scale. *Proceedings of the National Academy of Sciences*, 115(4):E574–E583, 2018. doi:10.1073/pnas.1711234115.

[21] S. S. Kaushal et al. The anthropogenic salt cycle. *Nature Reviews Earth & Environment*, 4(11):770–784, 2023. doi:10.1038/s43017-023-00485-y.

[22] S. S. Kaushal et al. Five state factors control progressive stages of freshwater salinization syndrome. *Limnology and Oceanography Letters*, 8(1):190–211, 2023. doi:10.1002/lol2.10248.

[23] C. W. Schalk and N. W. Stasulis. Relations among water levels, specific conductance, and depths of bedrock fractures in four road-salt-contaminated wells in Maine, 2007–9. Scientific Investigations Report 2012–5205, U.S. Geological Survey, 2012.

[24] J. D. Bredehoeft, K. Belitz, and S. Sharp-Hansen. The hydrodynamics of the Big Horn Basin: a study of the role of faults. *American Association of Petroleum Geologists Bulletin*, 76:530–546, 1992. doi:10.1306/BDFF8862-1718-11D7-8645000102C1865D.

[25] A. Gudmundsson. Active fault zones and groundwater flow. *Geophysical Research Letters*, 27:2993–2996, 2000. doi:10.1029/1999GL011266.

[26] V. F. Bense, M. A. Person, K. Chaudhary, Y. You, N. Cremer, and S. Simon. Thermal anomalies indicate preferential flow along faults in unconsolidated sedimentary aquifers. *Geophysical Research Letters*, 35:L24406, 2008. doi:10.1029/2008GL036017.

[27] J. S. Caine, J. P. Evans, and C. B. Forster. Fault zone architecture and permeability structure. *Geology*, 24(11): 1025, 1996. doi:10.1130/0091-7613(1996)024<1025:FZAAPS>2.3.CO;2.

[28] V. F. Bense, T. Gleeson, S. E. Loveless, O. Bour, and J. Scibek. Fault zone hydrogeology. *Earth-Science Reviews*, 127:171–192, 2013. doi:10.1016/j.earscirev.2013.09.008.

[29] A. K. Manda, S. B. Mabee, and D. U. Wise. Influence of rock fabric on fracture attribute distribution and implications for groundwater flow in the Nashoba Terrane, eastern Massachusetts. *Journal of Structural Geology*, 30(4):464–477, 2008. doi:10.1016/j.jsg.2007.12.006.

[30] J. Kim, P. Ryan, K. Klepeis, T. Gleeson, K. North, J. Bean, L. Davis, and J. Filoon. Tectonic evolution of a Paleozoic thrust fault influences the hydrogeology of a fractured rock aquifer, northeastern Appalachian foreland. *Geofluids*, 14(3):266–290, 2014. doi:10.1111/gfl.12076.

[31] D. Genereux. Quantifying uncertainty in tracer-based hydrograph separations. *Water Resources Research*, 34(4): 915–919, 1998. doi:10.1029/98WR00010.

[32] P. T. Harte and P. R. Trowbridge. Mapping of road-salt-contaminated groundwater discharge and estimation of chloride load to a small stream in southern New Hampshire, USA. *Hydrological Processes*, 24(17):2349–2368, 2010. doi:10.1002/hyp.7645.

[33] G. Hodgins, C. E. Robinson, C. Power, and J. W. Roy. Road salt chloride exposure in urban streambeds and links to groundwater – surface water interactions and salt sources. *Science of The Total Environment*, 957:177488, 2024. doi:10.1016/j.scitotenv.2024.177488.

[34] G. Hodgins, J. W. Roy, and C. E. Robinson. Influence of groundwater discharge on stream chloride concentrations in mixed urban land use sub-watersheds receiving road salt applications. *Journal of Hydrology*, 665:134757, 2026. doi:10.1016/j.jhydrol.2025.134757. Crossref issue year 2026 (vol. 665); OpenAlex lists online year 2025.

[35] M. P. Miller, D. D. Susong, C. L. Shope, V. M. Heilweil, and B. J. Stolp. Continuous estimation of baseflow in snowmelt-dominated streams and rivers in the Upper Colorado River Basin: A chemical hydrograph separation approach. *Water Resources Research*, 50(8):6986–6999, 2014. doi:10.1002/2013WR014939.

[36] J. R. Mullaney, D. L. Lorenz, and A. D. Arntson. Chloride in Groundwater and Surface Water in Areas Underlain by the Glacial Aquifer System, Northern United States. Scientific Investigations Report 2009–5086, U.S. Geological Survey, 2009.

[37] R. T. Budnik, J. R. Walker, and K. Menking. Geology and topography of Dutchess County, NY. In *Natural Resource Inventory of Dutchess County, NY*. Cornell Cooperative Extension Dutchess County, 2010. URL `https://www.dutchessny.gov/Departments/Planning/Docs/nrichapthree.pdf`. Chapter 3 (May 2010) of The Natural Resource Inventory of Dutchess County, NY, November 2010. No DOI.

[38] D. A. Ferrill, S. B. Johnson, R. N. McGinnis, F. P. Bertetti, G. R. Walter, K. J. Smart, and A. J. Cawood. Fault zone control on rapid groundwater flow in Cretaceous carbonates of the Hidden Valley fault zone, Texas. *Lithosphere*, 2024(Special 15):lithosphere_2024_178, 2025. doi:10.2113/2024/lithosphere_2024_178.

[39] A. Orr and E. W. Boyer. Road salt impacts on streams and springs in a karstic watershed. *Environmental Research Communications*, 8(5):055036, 2026. doi:10.1088/2515-7620/ae6035.

[40] V. R. Kelly, S. E. G. Findlay, and K. C. Weathers. Road salt: The problem, the solution, and how to get there. Technical report, Cary Institute of Ecosystem Studies, 2019. URL `https://www.caryinstitute.org/sites/default/files/downloads/report_road_salt.pdf`.

[41] G. D. Ruxton. The unequal variance t-test is an underused alternative to Student's t-test and the Mann-Whitney U test. *Behavioral Ecology*, 17(4):688–690, 2006. doi:10.1093/beheco/ark016.

[42] R. L. Runkel, K. Walton-Day, B. A. Kimball, P. L. Verplanck, and D. A. Nimick. Estimating instream constituent loads using replicate synoptic sampling, Peru Creek, Colorado. *Journal of Hydrology*, 489:26–41, 2013. doi:10.1016/j.jhydrol.2013.02.031.

[43] M. T. Nimiroski and M. C. Waldron. Sources of sodium and chloride in the Scituate Reservoir drainage basin, Rhode Island. Water-Resources Investigations Report 2002-4149, U.S. Geological Survey, 2002.

[44] E. Marti et al. Assessing structural geological controls on groundwater processes in mountain settings: insights from three-dimensional numerical modeling. *Water Resources Research*, 61(8):e2024WR037474, 2025. doi:10.1029/2024WR037474.

[45] D. A. Greco, S. E. Arnott, I. B. Fournier, and B. S. Schamp. Effects of chloride and nutrients on freshwater plankton communities. *Limnology and Oceanography Letters*, 8(1):48–55, 2023. doi:10.1002/lol2.10202.

[46] A. McClymont, S. E. Arnott, and J. A. Rusak. Interactive effects of increasing chloride concentration and warming on freshwater plankton communities. *Limnology and Oceanography Letters*, 8(1):56–64, 2023. doi:10.1002/lol2.10278.

[47] P. G. Cook, E. W. Banks, S. K. Marshall, G. A. Harrington, J. Batlle-Aguilar, S. Dogramaci, and C. Turnadge. Inferring fault hydrology using groundwater age tracers. *Journal of Hydrology*, 610:127905, 2022. doi:10.1016/j.jhydrol.2022.127905.

[48] N. Perera, B. Gharabaghi, and K. Howard. Groundwater chloride response in the Highland Creek watershed due to road salt application: A re-assessment after 20 years. *Journal of Hydrology*, 479:159–168, 2013. doi:10.1016/j.jhydrol.2012.11.057.

[49] H. M. Willmert, J. D. Osso, Jr., M. R. Twiss, and T. A. Langen. Winter road management effects on roadside soil and vegetation along a mountain pass in the Adirondack Park, New York, USA. *Journal of Environmental Management*, 225:215–223, 2018. doi:10.1016/j.jenvman.2018.07.085.

[50] S. H. Ledford, L. K. Lautz, and J. C. Stella. Hydrogeologic processes impacting storage, fate, and transport of chloride from road salt in urban riparian aquifers. *Environmental Science & Technology*, 50:4979–4988, 2016. doi:10.1021/acs.est.6b00402.

[51] D. M. Ramakrishna and T. Viraraghavan. Environmental impact of chemical deicers – a review. *Water, Air, and Soil Pollution*, 166:49–63, 2005. doi:10.1007/s11270-005-8265-9.

[52] Adirondack Road Salt Reduction Task Force. Adirondack road salt reduction task force assessment and recommendations. Technical report, New York State Department of Environmental Conservation, Albany, New York, 2023. URL `https://extapps.dec.ny.gov/docs/administration_pdf/adirondackroadsaltreport.pdf`.

# A Survey measurements

Table A1 lists every specific-conductance measurement from the 2018 survey: the survey and point number (Field and Pt; at Site 3, surveys 3, 5 and 4 are the 19 October, upper 26 October and lower 26 October surveys), the survey date, the along-channel distance from the upstream end of each single-day transect, the position, specific conductance (SC, $\mu$S/cm), water temperature ($T$, °C), the zone, and whether the point is a fault point, located downstream of a fault (Fault: yes).

Table A1: All specific-conductance (SC) measurements, 28 September–26 October 2018 survey. Distance is along-channel from the upstream end of each survey (field site; haversine sum of GPS fixes).

| Site | Field | Pt | Date | Dist (m) | Lat | Lon | SC | $T$ | Zone | Fault |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 2018-09-28 | 0 | 41.80363 | -73.78189 | 258.9 | 15.3 | 1-1 | no |
| 1 | 1 | 2 | 2018-09-28 | 13 | 41.80370 | -73.78202 | 260.4 | 15.2 | 1-1 | no |
| 1 | 1 | 3 | 2018-09-28 | 200 | 41.80275 | -73.78388 | 260.0 | 15.2 | 1-1 | no |
| 1 | 1 | 4 | 2018-09-28 | 298 | 41.80314 | -73.78494 | 260.1 | 15.2 | 1-1 | no |
| 1 | 1 | 5 | 2018-09-28 | 428 | 41.80420 | -73.78561 | 259.5 | 15.2 | 1-2 | yes |
| 1 | 1 | 6 | 2018-09-28 | 514 | 41.80359 | -73.78623 | 259.5 | 15.2 | 1-2 | yes |
| 1 | 1 | 7 | 2018-09-28 | 592 | 41.80295 | -73.78663 | 259.4 | 15.2 | 1-2 | yes |
| 1 | 1 | 8 | 2018-09-28 | 649 | 41.80251 | -73.78697 | 259.4 | 15.2 | 1-2 | yes |
| 1 | 1 | 9 | 2018-09-28 | 677 | 41.80237 | -73.78726 | 259.2 | 15.2 | 1-2 | yes |
| 2 | 2 | 1 | 2018-10-05 | 0 | 41.74113 | -73.83050 | 307.8 | 15.4 | 2-1 | yes |
| 2 | 2 | 2 | 2018-10-05 | 563 | 41.73644 | -73.83305 | 307.9 | 15.4 | 2-1 | yes |
| 2 | 2 | 3 | 2018-10-05 | 878 | 41.73422 | -73.83541 | 308.3 | 15.4 | 2-1 | yes |
| 2 | 2 | 4 | 2018-10-05 | 1591 | 41.72798 | -73.83739 | 308.3 | 15.5 | 2-1 | no |
| 2 | 2 | 5 | 2018-10-05 | 1995 | 41.72470 | -73.83949 | 308.7 | 15.6 | 2-1 | no |
| 2 | 2 | 6 | 2018-10-05 | 2362 | 41.72140 | -73.83969 | 307.3 | 15.5 | 2-1 | no |
| 2 | 2 | 7 | 2018-10-05 | 2872 | 41.71792 | -73.84369 | 309.5 | 15.6 | 2-1 | no |
| 2 | 2 | 8 | 2018-10-05 | 3240 | 41.71499 | -73.84574 | 309.3 | 15.6 | 2-1 | no |
| 2 | 2 | 9 | 2018-10-05 | 3357 | 41.71397 | -73.84609 | 309.7 | 15.6 | 2-1 | no |
| 2 | 2 | 10 | 2018-10-05 | 3820 | 41.71455 | -73.85161 | 311.1 | 15.7 | 2-1 | no |
| 2 | 2 | 11 | 2018-10-05 | 4166 | 41.71193 | -73.85387 | 310.8 | 15.7 | 2-2 | yes |
| 2 | 2 | 12 | 2018-10-05 | 4540 | 41.70899 | -73.85606 | 311.4 | 15.7 | 2-2 | no |
| 2 | 2 | 13 | 2018-10-05 | 4836 | 41.70650 | -73.85732 | 311.9 | 15.8 | 2-2 | no |
| 2 | 2 | 14 | 2018-10-05 | 5335 | 41.70284 | -73.86080 | 312.7 | 15.8 | 2-2 | no |
| 2 | 2 | 15 | 2018-10-05 | 5704 | 41.69994 | -73.86296 | 312.6 | 15.8 | 2-2 | no |
| 2 | 2 | 16 | 2018-10-05 | 6191 | 41.69676 | -73.86699 | 313.5 | 15.7 | 2-2 | yes |
| 2 | 2 | 17 | 2018-10-05 | 6582 | 41.69324 | -73.86698 | 316.0 | 15.8 | 2-2 | no |
| 2 | 2 | 18 | 2018-10-05 | 7066 | 41.68951 | -73.86997 | 315.7 | 15.8 | 2-2 | yes |
| 3 | 3 | 1 | 2018-10-19 | 0 | 41.79652 | -73.71534 | 340.5 | 9.4 | 3-1 | no |
| 3 | 3 | 2 | 2018-10-19 | 61 | 41.79607 | -73.71577 | 340.2 | 9.4 | 3-1 | no |

| Site | Field | Pt | Date | Dist (m) | Lat | Lon | SC | $T$ | Zone | Fault |
|---|---|---|---|---|---|---|---|---|---|---|
| 3 | 3 | 3 | 2018-10-19 | 133 | 41.79582 | -73.71656 | 340.1 | 9.5 | 3-1 | no |
| 3 | 3 | 4 | 2018-10-19 | 233 | 41.79613 | -73.71770 | 340.5 | 9.5 | 3-1 | no |
| 3 | 3 | 5 | 2018-10-19 | 319 | 41.79673 | -73.71835 | 339.8 | 9.6 | 3-1 | no |
| 3 | 3 | 6 | 2018-10-19 | 368 | 41.79674 | -73.71894 | 339.4 | 9.5 | 3-1 | no |
| 3 | 3 | 7 | 2018-10-19 | 471 | 41.79639 | -73.72009 | 338.8 | 9.6 | 3-2 | no |
| 3 | 3 | 8 | 2018-10-19 | 789 | 41.79467 | -73.72316 | 334.8 | 9.7 | 3-2 | no |
| 3 | 3 | 9 | 2018-10-19 | 872 | 41.79394 | -73.72337 | 335.2 | 9.7 | 3-2 | no |
| 3 | 3 | 10 | 2018-10-19 | 973 | 41.79374 | -73.72455 | 336.9 | 9.7 | 3-3 | yes |
| 3 | 3 | 11 | 2018-10-19 | 1056 | 41.79331 | -73.72537 | 336.1 | 9.7 | 3-3 | yes |
| 3 | 3 | 12 | 2018-10-19 | 1175 | 41.79251 | -73.72633 | 335.9 | 9.8 | 3-3 | yes |
| 3 | 3 | 13 | 2018-10-19 | 1322 | 41.79155 | -73.72755 | 332.7 | 10.0 | 3-3 | no |
| 3 | 3 | 14 | 2018-10-19 | 1479 | 41.79168 | -73.72944 | 333.2 | 10.0 | 3-3 | no |
| 3 | 3 | 15 | 2018-10-19 | 1590 | 41.79136 | -73.73070 | 333.2 | 10.0 | 3-3 | no |
| 3 | 3 | 16 | 2018-10-19 | 1706 | 41.79091 | -73.73196 | 331.4 | 10.0 | 3-3 | no |
| 3 | 3 | 17 | 2018-10-19 | 1771 | 41.79048 | -73.73142 | 332.5 | 10.1 | 3-3 | no |
| 3 | 3 | 18 | 2018-10-19 | 1881 | 41.78949 | -73.73137 | 332.2 | 10.1 | 3-3 | no |
| 3 | 3 | 19 | 2018-10-19 | 2034 | 41.78819 | -73.73197 | 331.8 | 10.2 | 3-3 | no |
| 3 | 3 | 20 | 2018-10-19 | 2130 | 41.78765 | -73.73287 | 332.0 | 10.2 | 3-3 | no |
| 3 | 5 | 14 | 2018-10-26 | 0 | 41.79600 | -73.71273 | 375.2 | 8.7 | 3-1 | no |
| 3 | 5 | 13 | 2018-10-26 | 83 | 41.79581 | -73.71370 | 374.0 | 8.7 | 3-1 | no |
| 3 | 5 | 12 | 2018-10-26 | 154 | 41.79640 | -73.71401 | 374.1 | 8.7 | 3-1 | no |
| 3 | 5 | 11 | 2018-10-26 | 254 | 41.79660 | -73.71519 | 369.8 | 8.8 | 3-1 | no |
| 3 | 5 | 10 | 2018-10-26 | 309 | 41.79614 | -73.71543 | 369.7 | 8.8 | 3-1 | no |
| 3 | 5 | 9 | 2018-10-26 | 394 | 41.79573 | -73.71630 | 369.8 | 8.7 | 3-1 | no |
| 3 | 5 | 8 | 2018-10-26 | 428 | 41.79556 | -73.71664 | 369.8 | 8.7 | 3-1 | no |
| 3 | 5 | 7 | 2018-10-26 | 507 | 41.79607 | -73.71730 | 369.2 | 8.8 | 3-1 | no |
| 3 | 5 | 6 | 2018-10-26 | 583 | 41.79652 | -73.71799 | 369.1 | 8.8 | 3-1 | no |
| 3 | 5 | 5 | 2018-10-26 | 658 | 41.79688 | -73.71876 | 367.8 | 8.8 | 3-1 | no |
| 3 | 5 | 4 | 2018-10-26 | 714 | 41.79656 | -73.71928 | 367.4 | 8.8 | 3-1 | no |
| 3 | 5 | 3 | 2018-10-26 | 831 | 41.79620 | -73.72061 | 366.1 | 8.7 | 3-2 | no |
| 3 | 5 | 2 | 2018-10-26 | 972 | 41.79515 | -73.72156 | 364.8 | 8.8 | 3-2 | no |
| 3 | 5 | 1 | 2018-10-26 | 1077 | 41.79478 | -73.72272 | 363.9 | 8.9 | 3-2 | no |
| 3 | 4 | 1 | 2018-10-26 | 0 | 41.78772 | -73.73268 | 355.5 | 8.3 | 3-3 | no |
| 3 | 4 | 2 | 2018-10-26 | 80 | 41.78704 | -73.73298 | 358.2 | 8.2 | 3-3 | no |
| 3 | 4 | 3 | 2018-10-26 | 188 | 41.78674 | -73.73423 | 359.7 | 8.2 | 3-3 | no |
| 3 | 4 | 4 | 2018-10-26 | 343 | 41.78550 | -73.73508 | 359.7 | 8.1 | 3-3 | no |
| 3 | 4 | 5 | 2018-10-26 | 520 | 41.78416 | -73.73623 | 360.2 | 8.1 | 3-3 | no |
| 3 | 4 | 6 | 2018-10-26 | 628 | 41.78364 | -73.73732 | 359.6 | 8.2 | 3-3 | no |
| 3 | 4 | 7 | 2018-10-26 | 804 | 41.78239 | -73.73864 | 361.5 | 8.1 | 3-4 | yes |
| 3 | 4 | 8 | 2018-10-26 | 930 | 41.78302 | -73.73989 | 360.9 | 8.1 | 3-4 | yes |
| 3 | 4 | 9 | 2018-10-26 | 1099 | 41.78305 | -73.74193 | 359.3 | 8.3 | 3-4 | no |
| 3 | 4 | 10 | 2018-10-26 | 1153 | 41.78323 | -73.74254 | 360.2 | 8.3 | 3-4 | no |
| 3 | 4 | 11 | 2018-10-26 | 1269 | 41.78308 | -73.74392 | 359.7 | 8.4 | 3-4 | no |
| 3 | 4 | 12 | 2018-10-26 | 1299 | 41.78325 | -73.74421 | 360.6 | 8.3 | 3-4 | no |