Python For Data Science Cheat Sheet

NumPy Basics

Learn Python for Data Science Interactively at www.DataCamp.com




NumPy

The **NumPy** library is the core library for scientific computing in Python. It provides a high-performance multidimensional array object, and tools for working with these arrays.

Use the following import convention: >>> import numpy as np



NumPy Arrays



Creating Arrays

```
>>> a = np.array([1,2,3])
>>> b = np.array([(1.5,2,3), (4,5,6)], dtype = float)
>>> c = np.array([[(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)]],
                 dtype = float)
```

Initial Placeholders

>>> np.zeros((3,4)) >>> np.ones((2,3,4),dtype=np.int16) >>> d = np.arange(10,25,5)	Create an array of zeros Create an array of ones Create an array of evenly
>>> np.linspace(0,2,9)	spaced values (step value) Create an array of evenly spaced values (number of samples)
>>> e = np.full((2,2),7) >>> f = np.eye(2) >>> np.random.random((2,2)) >>> np.empty((3,2))	Create a constant array Create a 2X2 identity matrix Create an array with random values Create an empty array

1/0

Saving & Loading On Disk

```
>>> np.save('my_array', a)
>>> np.savez('array.npz', a, b)
>>> np.load('my array.npy')
```

Saving & Loading Text Files

>>>	np.loadtxt("myfile.txt")
>>>	<pre>np.genfromtxt("my file.csv", delimiter=',')</pre>
>>>	np.savetxt("mvarrav.txt", a, delimiter=" ")

Data Types

>>> np.int64	Signed 32-bit integer types
>>> np.float32	Standard double-precision floating point
>>> np.complex	Complex numbers represented by 128 floats
>>> np.bool	Boolean type storing TRUE and FALSE values
>>> np.object	Python object type
>>> np.string_	Fixed-length string type
>>> np.unicode_	Fixed-length unicode type

Inspecting Your Array

>>> a.sh	nape	Array dimensions
>>> len	(a)	Length of array
>>> b.nc	lim	Number of array dimensions
>>> e.si	ze	Number of array elements
>>> b.dt	уре	Data type of array elements
>>> b.dt	ype.name	Name of data type
>>> b.as	stype(int)	Convert an array to a different type

Asking For Help

>>> np.info(np.ndarray.dtype)

Array Mathematics

Arithmetic Operations

>>> g = a - b array([[-0.5, 0., 0.],	Subtraction
[-3., -3., -3.]]) >>> np.subtract(a,b) >>> b + a array([[2.5, 4., 6.],	Subtraction Addition
[5. , 7. , 9.]]) >>> np.add(b,a) >>> a / b array([[0.66666667, 1. , 1.], [0.25 , 0.4 , 0.5]]	
>>> np.divide(a,b) >>> a * b array([[1.5, 4., 9.],	Division Multiplication
<pre>[4., 10., 18.]]) >>> np.multiply(a,b) >>> np.exp(b) >>> np.sqrt(b) >>> np.sin(a)</pre>	Multiplication Exponentiation Square root Print sines of an array
>>> np.cos(b) >>> np.log(a) >>> e.dot(f) array([[7., 7.], [7., 7.]])	Element-wise cosine Element-wise natural logarithm Dot product

Comparison

>>> a == b array([[False, True, True],	Element-wise comparison
<pre>[False, False, False]], dtype=bool) >>> a < 2 array([True, False, False], dtype=bool)</pre>	Element-wise comparison
4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Array-wise comparison

Aggregate Functions

>>> a.sum()	Array-wise sum
>>> a.min()	Array-wise minimum value
>>> b.max(axis=0)	Maximum value of an array row
>>> b.cumsum(axis=1)	Cumulative sum of the elements
>>> a.mean()	Mean
>>> b.median()	Median
>>> a.corrcoef()	Correlation coefficient
>>> np.std(b)	Standard deviation

Copying Arrays

>>> h = a.view()	Create a view of the array with the same data
>>> np.copy(a)	Create a copy of the array
>>> h = a.copy()	Create a deep copy of the array

Sorting Arrays

>>> a.sort()	Sort an array
>>> c.sort(axis=0)	Sort the elements of an array's axis

Subsetting, Slicing, Indexing

1.5 2 3

1 2 3

Subsetting

>>> a[2]

>>> b[1,2]

>>> a[0:2]

>>> b[:1]

array([1, 2])

array([2., 5.])

array([[1.5, 2., 3.]])

array([[[3., 2., 1.], [4., 5., 6.]]])

>>> b[0:2,1]

>>> c[1,...]

>>> a[: :-1]

>>> a[a<2]

array([1])

Fancy Indexing

array([3, 2, 1]) **Boolean Indexing**

6.0 Slicina

```
1 2 3
            Select the element at the 2nd index
            Select the element at row o column 2
```

Also see Lists

(equivalent to b[1][2]) Select items at index 0 and 1

Select items at rows 0 and 1 in column 1

4 5 6 Select all items at row o (equivalent to b[0:1, :]) Same as [1,:,:]

Reversed array a

Select elements from a bigger than 2

Select elements (1,0), (0,1), (1,2) and (0,0)

Select a subset of the matrix's rows and columns

Array Manipulation

>>> b[[1, 0, 1, 0],[0, 1, 2, 0]]

>>> b[[1, 0, 1, 0]][:,[0,1,2,0]]

array([4. , 2. , 6. , 1.5])

Transposing Array >>> i = np.transpose(b)

>>> i.T **Changing Array Shape**

>>> b.ravel() >>> g.reshape(3,-2)

Adding/Removing Elements

>>> h.resize((2,6)) >>> np.append(h,g) >>> np.insert(a, 1, 5) >>> np.delete(a,[1])

Combining Arrays

```
>>> np.concatenate((a,d),axis=0)
  array([ 1, 2, 3, 10, 15, 20])
>>> np.vstack((a,b))
 array([[ 1. , 2. , 3. ], [ 1.5, 2. , 3. ], [ 4. , 5. , 6. ]])
>>> np.r [e,f]
>>> np.hstack((e,f))
 array([[ 7., 7., 1., 0.],
         [ 7., 7., 0., 1.]])
>>> np.column stack((a,d))
 array([[ 1, 10],
          2, 15],
         [ 3, 20]])
>>> np.c [a,d]
```

Splitting Arrays

```
>>> np.hsplit(a,3)
[array([1]),array([2]),array([3])]
>>> np.vsplit(c,2)
```

Permute array dimensions Permute array dimensions

Flatten the array Reshape, but don't change data

Return a new array with shape (2,6) Append items to an array Insert items in an array

Concatenate arrays

Delete items from an array

Stack arrays vertically (row-wise)

Stack arrays vertically (row-wise) Stack arrays horizontally (column-wise)

Create stacked column-wise arrays

Create stacked column-wise arrays

Split the array horizontally at the 3rd

Split the array vertically at the 2nd index

