1.VISION & MISSION

1.1 VISION

To be in the leading role to maintain HSE excellence through integrating into all business processes of the Company with continual improvement by protecting health of its employees and interested parties, safe operation of its activities and ensuring compliance to environmental legislation in line with the Company's vision and HSE Policy.

1.2 MISSION

A commitment to provide safe, healthy and environmental friendly work practices through promotion of HSE driven culture, standardization, active consultation and participation of employees along with training and raising awareness and conformance to environmental standards.

2.PREFACE/ BACKGROUND

2.1 INTRODUCTION

HSE Department was established in 2003. Third party Consultant was engaged in 2007 in order to develop HSE Procedures describing scope, roles and responsibilities of all concerned along with required documentation in line with ISO 14001 and OHSAS 18001 Standards and the same were circulated to all HSE Focal Points by HSE department for implementation.

SNGPL got certification of ISO-14001 (Environmental Management System) and OHSAS-18001 (Occupational Health & Safety Assessment Series) in 2008 by M/s URS (Certification Body). HSE Management System was upgraded from OHSAS 18001:1999 to OHSAS 18001:2007 in May 2009, and from ISO 14001:2004 to ISO 14001:2015 in Sept 2018. OHSAS 18001:2007 has been upgraded to ISO 45001:2018 in July 2021. Company has been certified successfully 03 times for up-gradation of HSE Standards.

Surveillance Audits are conducted on Bi- Annual Basis, to ensure the effectiveness of HSE Management System at SNGPL and as essential requirement of Certification. To ensure Health, Safety and Environmental Policy of the Company is systematically applied and best industry practices are adopted within all operations, SNGPL has developed an Integrated HSE Management System (IMS) based upon these standards. Maintaining outstanding HSE Performance is a core value of SNGPL.

The Budget (Capital and Revenue) of HSE Department is allocated as per Company's Financial Procedure, after getting necessary approval from OGRA and Board.

Corporate Social Responsibility (CSR) function in the Company was formally started in 2013. Presently HSE department is looking after the function of CSR. CSR initiatives are mainly focused in the areas of Health, Education and Environment as per Company's CSR Policy approved by BOD.

2.2 ORGANOGRAM

HSE department is headed by General Manager (HSE), who is directly reported to worthy Managing Director. As per currently approved strength, 41 executives including 01 Chief Engineer, 04 Dy. Chief Engineers and 36 Engineers of different grades are working at Head Office and operational sites. Detailed Organogram is attached as Appendix-D.

4 MANUAL

The 1st Chapter of HSE Manual consists of "ISO 14001 / ISO 45001 Certification Scope" and is a description of the processes used by Sui Northern Gas Pipelines Limited (SNGPL), to implement Integrated Management System (IMS) / HSE Procedures at its different sites and location. Its intended purpose is to provide a summary of SNGPL approach to the implementation for certification of ISO 14001 and ISO 45001, and refer the content and location of other documentation that provides details (in accordance with clause 7.5.1 of the said standards). Management representative (MR) at SNGPL will continue to document the day-to-day practices and, as appropriate, include and update them in Chapter No 01 pertaining to "ISO 14001 / ISO 45001 Certification Scope" as on-going basis.

The 2nd Chapter comprises of "Corporate Social Responsibility" and it defines the CSR Policy and Guidelines at SNGPL.

4.1 CHAPTER 01: "ISO 14001 / ISO 45001 CERTIFICATION SCOPE"

4.1.1 PURPOSE

This manual defines the scope of the SNGPL Environmental and Occupational Health & Safety Management System and provides linkages of system documents to the various elements of the ISO 14001 and ISO 45001 Standards. Further Corporate Social Responsibility (CSR) Policy of the Company and guidelines to implement is described in HSE Manual.

HSE Manual has been divided into 02 Chapters i.e "Chapter 01 - ISO 14001 / ISO 45001 Certification" and "Chapter 02 - Corporate Social Responsibility (CSR)**.** The principle elements of the system described in this manual are as in Table of Contents.

4.1.2SCOPE

The SNGPL Integrated Management System (**IMS**), comprising Environmental Management System (**EMS)** & Occupational Health Safety Management System **(OHSMS**), provides a mechanism for Environmental, Occupational Health & Safety Management System throughout all areas, units and departments of SNGPL.

The Integrated management system covers requirement of:

i. External and internal issues that are relevant to Company's purpose and that affect its ability to achieve the intended outcomes of its environmental **and Occupational** Health & Safety Management System.

ii. Workers and other interested parties that are relevant to Environmental and Occupational Health & Safety Management System.

iii. The relevant needs and expectations (i.e. requirements) of workers and other interested parties and which of these needs and expectations are, or could become its compliance obligations or other requirement.

iv. Development and Implementation of work-related SOP's by the concerned department for ensuring protection of occupational health & safety of relevant interested parties and environment.

v. Environmental Aspects and Impacts, Occupational Health & Safety Hazards and Risks which SNGPL can control and directly manage, and those it does not control or directly manage but can be expected to have an influence.

The scope of Integrated Management System (EMS & OHSMS) includes all operational activities that physically occur within the physical boundaries of SNGPL's sites.

The activities of "Transmission, Distribution and Sales of Natural Gas" are defined as below.

Activities of Transmission:

1.Welding / Hot Welding
2.Sleeving
3.Hot Tapping
4.Stoppling
5.Commissioning / Decommissioning
6.Pigging
7.Coat / Wrap
8.Lowering of Live Lines
9.Hot cutting and Cold Cutting Operations.
10.Metering
11.Radiography
12.Maintenance of valve assemblies

Activities of Distribution:

1. Construction of Mains
2. Tie – Ins
3. Commissioning
4. Coat / Wrap and Dope Yard
5. Excavations
6. Welding
7. Testing
8. Construction of Service Lines
9. Metering
10. Operations and Maintenance of Underground valves

Activities of Gas Sales:

1.Survey of Site (where gas connection required)
2.Acknowledgement of Application
3.Issuance of Demand Notice
4.Dispatch of Demand Notice
5.Negotiation and Finalization of Gas Sale & Purchase Contracts with gas consumers

4.1.3ISSUE AND UPDATE

Control of HSE Manual is based on the revision of this document and upon the approval from Competent Authority. The Control of the "Chapter No. 01 of ISO 14001 / ISO 45001 Certification" is based in accordance with the SNGPL, General procedure SNGPL-GPR-001. All copies of this HSE Manual not marked "CONTROLLED DOCUMENT" are uncontrolled and should be used for reference purposes only. General Manager (HSE) or Designee of SNGPL will issue amendments to this HSE manual, after necessary approval from Competent Authority.

CHAPTER No. 01 – ISO 14001 / ISO 45001 CERTIFICATION

This Chapter consists of Appendices and HSE Procedures.

Appendices have been enlisted as below:

i. Appendix A – HSE Policy
ii. Appendix B – Smoking Policy
iii. Appendix C – Master Document List
iv. Appendix D – Organogram

HSE Procedures based on ISO 14001 / ISO 45001 Standards have been divided as follows:

i. Appendix E - General Procedures (GPR)
ii. Appendix F - Occupational Health and Safety Procedures (HPR)
iii. Appendix G - Environmental Procedures (EPR)

4.1.4 ENVIRONMENTAL, OCCUPATIONAL HEALTH & SAFETY POLICY

The Managing Director endorses the SNGPL Environmental, Occupational Health and Safety Policy. The policy is appropriate to the purpose, size and context including nature, scale and environmental impacts of all activities at the SNGPL. The Policy includes a commitment to continual improvement and prevention of pollution and to provide safe and healthy working conditions for the prevention of work related injuries and ill health as well as commitment to meet or exceed relevant environmental, occupational health & safety legislation, regulations and other requirements.

Referred Applicable Material: Appendix "A"

4.1.4.1 SMOKING POLICY

The Managing Director endorses the Smoking Policy. The Policy includes a commitment to occupational health & safety of the employees.

Referred Applicable Material: Appendix "B"

4.1.5Occupational Health & Safety and Environmental Assessment
4.1.6 Environmental Aspects and Impacts

SNGPL has established and maintained a procedure for identifying environmental aspects and impacts. The HSE Focal Point identifies the environmental aspects, which the SNGPL Controls and over which it may be expected to have an influence, and determines which of those aspects are considered significant.

Environmental aspects are reviewed at least annually by HSE Focal Point or when there is new / changed process or activity at the SNGPL. The HSE Focal Point maintains HSE Site Committee minutes and other records.

Referred Applicable Procedure: SNGPL-EPR-001

4.1.7 Occupational Health & Safety Hazard and Risks

SNGPL has established and maintained a procedure for identifying OH&S Hazards and risks. The HSE Focal Point identifies the occupational health & safety hazards, assesses the risks and implements the necessary control measures. SNGPL has defined methodology for hazard identification and risk assessment with respect to its scope, nature and timing as proactive strategy.

OHS hazards are reviewed at least annually by HSE Focal Point or when there is a new / changed process or activity at the SNGPL. The HSE Focal Point maintains HSE Site Committee minutes and other records.

Referred Applicable Procedure: SNGPL-HPR-001, SNGPL-HPR-014
SNGPL-HPR-015

4.1.8 LEGAL AND OTHER REQUIREMENTS:

The SNGPL has established and maintained a procedure for the purpose of identifying, accessing and communicating legal and other requirements that are applicable to the SNGPL in relation with Environment, Occupational Health and Safety. Additional information is also available through legal publications. Local regulations are identified, accessed and communicated by the Management Representative (MR).

At least annually the MR will review the most current federal, provincial and local legal and other requirements pertaining to HSE as applicable to SNGPL.

Referred Applicable Procedure: SNGPL-GPR-009

4.1.9 OBJECTIVES AND TARGETS

4.1.9.1 Environmental Objectives and Targets

The MR in consultation with respective Departmental Head / HSE Focal Point develops objectives and targets for significant Environmental Aspects. The objectives and targets define:

1. The performance objectives (Investigate / Study, Control / Maintain, or Improve) for each significant environmental aspect:
2. The Specific, quantified targets which define those performance objectives and
3. The planned deadlines for the achievement of those targets.

Objectives and targets are developed and reviewed annually considering its compliance obligation, risks and opportunities, significant environmental aspects, technological options, financial, operational and business plans and the views of interested parties.

The objectives and targets are consistent with the Occupational Health, Safety & Environmental Policy.

Referred Applicable Procedure: SNGPL-EPR-001, SNGPL-EPR-002 SNGPL-EPR-003, SNGPL-EPR-004

4.1.9.2 Occupational Health & Safety Objectives and Targets

MR in consultation with respective Departmental Head / HSE Focal Point develops Occupational Health and Safety objectives and targets. Objectives are quantified where applicable.
Objectives are established and reviewed annually, considering its Compliance obligation and applicable requirements, results of assessment of risks and opportunities, results of consultation with workers, OH&S hazards and risks, technological options, financial, operational, business requirements, and the views of interested parties.
The objective shall be consistent with the Occupational Health, Safety & Environmental Policy, including the commitment to continual improvement.

Referred Applicable Procedure: SNGPL-HPR-001

4.1.10 ORGANIZATIONAL STRUCTURE AND RESPONSIBILITY

Resources, roles, responsibility, accountability and authorities of Environmental Management System and Occupational Health and Safety Management System are defined at relevant functions and levels within the SNGPL.
Referred Applicable Procedure: SNGPL-GPR-006

4.1.11 COMPETENCE, TRAINING AND AWARENESS

The SNGPL identifies, plans, monitors and records training needs for personnel whose work may create a significant impact upon the environment and risk upon occupational Health & Safety at SNGPL.

HSE Focal Point is responsible for maintaining employees training records. Appropriate records are monitored and reviewed on scheduled basis.

Employee's supervisor analyzes the competency of trainee and effectiveness of the training.

Referred Applicable Procedure: SNGPL-GPR-003, SNGPL-GPR-015

4.1.12 COMMUNICATION, PARTICIPATION AND CONSULTATION

The SNGPL has established and maintained a procedure for internal & external communications regarding environmental aspects & impacts, occupational health & safety hazards and risks, and the Integrated Management System.

The SNGPL has defined within the procedures to ensure the participation of workers during risk assessment process, objective and management programs determination.

Referred Applicable Procedure: SNGPL-GPR-007, SNGPL-GPR-017
SNGPL-HPR-004

4.1.13 DOCUMENT CONTROL

The SNGPL has established a procedure for IMS for controlling all documents related to the EMS & OH&S Management System. This procedure describes where documents can be located and how and when they are reviewed. The procedure ensures that current versions are available and the obsolete documents are promptly removed from use or are suitably identified.

Controlled documents are available with the Management Representative (MR) or Designee. A list of controlled documents is provided in Appendix C – Master Document List.

Referred Applicable Procedure: SNGPL-GPR-001, SNGPL-GPR-002

4.1.14 OPERATIONAL CONTROL

HSE Focal Point is responsible for identifying operations and activities associated with significant environmental aspects and impacts, occupational health & safety hazards and

risks that require operational controls in procedures, SOPs or EMS & OH&S Management System.

- System Procedures cover the management and control of the EMS & OH&S management system and the principal environmental aspects & impacts, occupational health & safety hazards and risk, which the system manages.

- SOPs cover the environmental control, occupational health & safety control of specific operational activities and are usually activity specific in their application.

Referred Applicable Procedure:
SNGPL-GPR-013, SNGPL-GPR- 014, SNGPL-GPR-016, SNGPL-HPR-002, SNGPL-HPR-003, SNGPL-HPR-005, SNGPL-HPR-006, SNGPL-HPR-007, SNGPL-HPR-008, SNGPL-HPR-009, SNGPL-HPR-010, SNGPL-HPR-013, SNGPL-EPR-001

4.1.15 EMERGENCY PREPAREDNESS AND RESPONSE

The SNGPL has a procedure to identify potential for and respond to incidents and emergency situations, and for preventing and mitigating the environmental impacts, and occupational health & safety risks that may be associated with them. Site based Emergency methods are reviewed by the HSE Site Committee on an annual basis and after the occurrence of incident or emergency situation.

Referred Applicable Procedures: SNGPL-GPR-012, SNGPL-HPR-011

4.1.16 MONITORING AND MEASUREMENT

The SNGPL has established a procedure to monitor and measure the key characteristics of its operations and activities that can have a significant impact on the environment and significant risk for occupational health & safety at SNGPL. This procedure includes calibration and maintenance requirements of plant / equipment / machinery and ensures that records are retained.

The SNGPL has established Environmental, Occupational Health & Safety regulatory compliance program. Procedure SNGPL-GPR-009 outlines the requirements of the program and to periodically review regulatory compliance and report results to HSE Management Committee on a yearly basis.

Referred Applicable Procedures: SNGPL-GPR- 009, SNGPL-GPR- 011
SNGPL-HPR-012

4.1.17 INCIDENT INVESTIGATION, NON-CONFORMANCE AND CORRECTIVE ACTION

The SNGPL has EMS & OH&S procedure for defining responsibility and authority for handling and investigating non-conformances, for taking action to mitigate impacts and risks, and for initiating and completing corrective action. Change in procedure resulting from corrective actions are implemented and recorded. The Management Representative (MR) maintains their records.

Referred Applicable Procedures: SNGPL-GPR-010, SNGPL-GPR- 008

4.1.18 HSE SYSTEM AUDITS: (EMS & OHS Management System Audit)

Periodic System Audits are conducted to ensure that the EMS & OHS Management System has been properly implemented and maintained. The results of these audits are provided to HSE Management Committee. Audits are performed according to a schedule, which is based on the environmental, occupational health & safety importance of an activity, the results of previous audits, and the audit schedule. All auditors are trained and audit records are kept with the Management Representative (MR).

Referred Applicable Procedures: SNGPL-GPR-004

4.1.19 MANAGEMENT REVIEW

The HSE Management Committee reviews all elements of the Integrated Management System (EMS & OH&S) at least half yearly to ensure its continuing suitability, adequacy and effectiveness for continual improvement. The reviews are recorded as Minutes of the Meeting and are kept by the Management Representative (MR).

Referred Applicable Procedures: SNGPL-GPR-005

4.2 Chapter No 02: Corporate Social Responsibility:

SNGPL believes in business that should be both profitable and beneficial to the society and improving the quality of life of the communities in the area of domain of licensee. The objectives and allocation of resources for CSR activities are laid out in the CSR Policy.

4.2.1 CSR AT SNGPL

SNGPL’s Corporate Social Responsibility policy is based on global best practices envisaging management of the business processes by producing an overall positive impact on society and the environment. CSR policy comply with the guidelines provided by Securities and Exchange Commission of Pakistan (SECP) 2013, new tariff regime for regulated gas sector in Pakistan by OGRA, Principles of United Nations Global Compact (UNGC) - relevant Sustainable Development Goals (SDG’s) and Company’s vision, mission and business code of conduct.

5. ABBREVIATIONS/ GLOSSARY

SNGPL	:	Sui Northern Gas Pipelines Limited
HSE	:	Health, Safety and Environment
HOD	:	Head of Department
MR	:	Management Representative
DMR	:	Deputy Management Representative
IMS	:	Integrated Management System
EMS	:	Environmental Management System
OH&S	:	Occupational Health & Safety
OH&S MS	:	Occupational Health and Safety Management System
RMC	:	Record Management Committee
MRM	:	Management Review Meeting
HSC	:	HSE Site Committee
PPE	:	Personal Protective Equipment

6. Appendices
   a) Appendix A -HSE Policy
   b) Appendix B - smoking Policy
   c) Appendix C -Master document list
   d) Appendix D -organogram
   e) Appendix E -General procedure (GRP)
   f) Appendix F -Occupational health and safety procedure
   g) Appendix G -Environmental procedure (EPR)

The **General Procedures** under the **Health, Safety and Environment Department** include a list of documents with their issue history.

1. **Document SNGPL-GPR-001**, titled **Documents Management**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, and **04-02-21**.
2. **Document SNGPL-GPR-002**, titled **Records Management**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **22-02-16**, **08-11-16**, and **04-02-21**.
3. **Document SNGPL-GPR-003**, titled **Competence, Training and awareness**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **02-08-16**, and **04-02-21**.
4. **Document SNGPL-GPR-004**, titled **Internal Audits**, has the following issue dates: **01-10-07**, **20-05-09**, **02-12-12**, **02-08-16**, and **04-02-21**.
5. **Document SNGPL-GPR-005**, titled **Management Review Meeting**, has the following issue dates: **01-10-07**, **20-05-09**, and **04-02-21**.
6. **Document SNGPL-GPR-006**, titled **Structure, Roles and Responsibilities**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **08-11-16**, and **04-02-21**.
7. **Document SNGPL-GPR-007**, titled **Communication, Participation and consultation**, has the following issue dates: **01-10-07**, **20-05-09**, **02.08.16**, and **04-02-21**.
8. **Document SNGPL-GPR-008**, titled **Incident Reporting and Investigation**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **02-08-16**, and **04-02-21**.
9. **Document SNGPL-GPR-009**, titled **Identification, Tracking and Control of Compliance Obligations, Regulatory and other requirements and Evaluation of compliance**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, and **04-02-21**.

The **General Procedures** under the **Health, Safety and Environment Department** include a list of documents with their issue history.

- **Document SNGPL-GPR-010**, titled **Control of Non-conformance and Corrective Actions**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, and **04-02-21**.
- **Document SNGPL-GPR-011**, titled **Monitoring and Measurement, Analysis and Evaluation**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **08-11-16**, and **04-02-21**.
- **Document SNGPL-GPR-012**, titled **Identification of emergency situations, Emergency preparedness and response**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **08-11-16**, and **04-02-21**.
- **Document SNGPL-GPR-013**, titled **Contractors, Outsource Function & Procurement control**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, and **04-02-21**.
- **Document SNGPL-GPR-014**, titled **Operational control**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-GPR-015**, titled **Safety Talk**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **08-11-16**, and **04-02-21**.
- **Document SNGPL-GPR-016**, titled **Gas Safety Management**, has the following issue dates: **07-04-10**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-GPR-017**, titled **Context of the Organization**, has the following issue dates: **09-07-17** and **04-02-21**.

The **OH & S Procedures** under the **Health, Safety and Environment Department** include a list of documents with their issue history:

- **Document SNGPL-HPR-001**, titled **OH&S Hazard Identification and Risk Assessment, Objective and management programs**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-HPR-002**, titled **Work Permit**, has the following issue dates: **01-10-07**, **20-05-09**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-HPR-003**, titled **Safety Checklist Procedure for Transmission, Distribution and Projects**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-HPR-004**, titled **General Safety Management**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-HPR-005**, titled **PPEs Management**, has the following issue dates: **01-10-07**, **20-05-09**, **30-01-14**, **03-04-17**, and **04-02-21**.
- **Document SNGPL-HPR-006**, titled **Plant & Equipment Modification**, has the following issue dates: **01-10-07**, **20-05-09**, and **04-02-21**.
- **Document SNGPL-HPR-007**, titled **Safe Operation of vehicle / Equipment**, has the following issue dates: **20-05-09**, **20-05-09**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-HPR-008**, titled **Handling, Stacking & Storage of Line Pipe (MS/PE)**, has the following issue dates: **16-06-09**, **09-12-10**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-HPR-009**, titled **Occupational Health Surveillance**, has the following issue dates: **02-08-16** and **04-02-21**.

The **OH & S Procedures** under the **Health, Safety and Environment Department** include a list of documents with their issue history:

- **Document SNGPL-HPR-010**, titled **Occupational Health Guidelines**, has the following issue dates: **02-08-16** and **04-02-21**.
- **Document SNGPL-HPR-011**, titled **Emergency Treatment of Occupational and Non-Occupational Medical Emergencies**, has the following issue dates: **08-10-09**, **30-01-14**, **08-11-16**, and **04-02-21**.
- **Document SNGPL-HPR-012**, titled **HSE Site Committee & Housekeeping Inspection**, has the following issue dates: **28-10-09**, **30-01-14**, **08-11-16**, and **04-02-21**.
- **Document SNGPL-HPR-013**, titled **Potable Drinking Water at Workplace**, has the following issue dates: **26-11-10**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-HPR-014**, titled **Routine Safety Audit**, has the following issue dates: **01-02-10**, **30-01-14**, **02-08-16**, and **04-02-21**.
- **Document SNGPL-HPR-015**, titled **Guidelines for Color coding of Pipes**, has the following issue dates: **06-08-10**, **30-01-14**, **02-08-16**, and **04-02-21**.

The **Environment Procedures** under the **Health, Safety and Environment Department** include a list of documents with their issue history:

- **Document SNGPL-EPR-001**, titled **EMS Aspects & Impacts Identification, Setting of Objectives & Targets and Management Programs**, has the following issue dates: **01-10-07**, **28-10-09**, **30-01-14**, **02-08-16**, **09-07-17**, and **04-02-21**.
- **Document SNGPL-EPR-002**, titled **Environmental Monitoring Procedure**, has the following issue dates: **01-10-07**, **28-10-09**, **30-01-14**, **02-08-16**, **09-07-17**, and **04-02-21**.
- **Document SNGPL- EPR -003**, titled **Initial Environmental Examination / Environmental Impact Assessment**, has the following issue dates: **01-10-07**, **28-10-09**, **30-01-14**, **02-08-16**, **09-07-17**, and **04-02-21**.
- **Document SNGPL- EPR -004**, titled **Waste Management**, has the following issue dates: **01-10-07**, **28-10-09**, **30-01-14**, **02-08-16**, **09-07-17**, and **04-02-21**.

1.0 Purpose:

This procedure:

- Defines the format to be used in creating IMS Procedures; Standard Operating Procedures (SOP), Forms and check Lists.
- Defines the mechanism for controlling IMS Management System documents, and to ensure that those personnel requiring access to those system documents have the most up-to-date issues and are aware of the document control process.

2.0 SCOPE:

This procedure covers the generation, review, approval, distribution and change mechanism in all internal and external documents as shown in the manuals and all health, safety and environment activities throughout the organization.

3.0 DEFINITIONS, ABBREVIATIONS AND CONCEPTS:

SNGPL:	Sui Northern Gas Pipelines Limited
IMS:	Integrated Management System
EMS:	Environmental Management System
OHSAS:	Occupational Health and Safety Assessment Series
OH&S MS:	Occupational Health and Safety Management System
HSC:	HSE Site Committee
SOP:	Standard Operating Procedures

4.0 RESPONSIBILITIES AND AUTHORITIES:

4.1 Management Representative (MR)
4.2 Concerned Department Heads
4.3 EMS & OHSAS Deputy Management Representatives (DMRs)
4.4 HSE Focal Point
4.5 HSE Site Committee
4.6 DMR Coordination

5.0 Procedure

5.1 Preparation

5.1.1 Any department identifies the need for preparation of a new system document.

5.1.2 Focal Point / Head of Departmental / MR assign a suitable HSE site committee member / DMR to prepare and manage standard operating procedures (SOPs) related to his department.

5.1.3 The person preparing the system document gathers all related data, information, and relevant documents for reference and inclusion as appropriate.

5.2. REVIEW

5.2.1. On completion, the draft version of the system document is sent to HSE Department who check that all OH&S Hazards, Environmental Impacts and legal and other requirements are included.

5.2.2. The draft version of the Departmental SOP is then sent to HSE Site committee for Review.

5.2.3. The comments received from committee are incorporated where appropriate.

5.2.4. After the preparation of system document a number is allotted according to the **Document Management Chart (SNGPL-GPR001-CH-001)** and **List of Departmental Abbreviation (SNGPL-GPR001-F-006).**

5.3. APPROVAL

5.3.1. The reviewing authority checks the system document finally for contents, style, correction, completeness and comprehensiveness. If found acceptable, the system document is approved and signed off according to the **Document Management Chart (SNGPL-GPR001-CH-001)**.

5.4. INITIAL RELEASE

5.4.1. DMR Coordination receives all the original system documents (manual and system procedures) from originators.

5.4.2. HSE Site Committee member of concerned department as per **List of Document Management Committee (SNGPL-GPR001-F-007)** will be responsible for document management activity within his department.

5.4.3.All system documents will then be entered in the **Document Master list (SNGPL-GPR001-F-001)** by DMR Coordination which, contains the information as follows:

5.4.2.1. Document Number
5.4.2.2. Document Title
5.4.2.3. Issue Date
5.4.2.4. Latest Issue status (Current status)

5.4.3.HSE Documents management committee member of each site under the guidance of DMR Coordination prepares **Document Master List (SNGPL-GPR001-F-001)** for their departmental SOPs and forms**.**

5.4.4.**Document Distribution Matrix (SNGPL-GPR001-F-002)** will be prepared by concerned HSE Site Committee member for Standard Operating Procedures (SOPs).

5.4.5.**Document Distribution Matrix (SNGPL-GPR001-F-002)** of IMS System documentswill be prepared by DMR Coordination and approved by MR for:

5.4.4.1 IMS Manual
5.4.4.2 General Procedures
5.4.4.3 EMS Procedures
5.4.4.4 OH&S Procedures

5.4.6.DMR Coordination will be responsible only for distribution of documents identified in 5.4.5. DMR Coordination makes photocopies of document as per **Document Distribution Matrix (SNGPL-GPR001-F-002)** duly approved by MR and stamped them "**CONTROLLED COPY**" in red and distribute these documents to the concerned.

5.4.7.Document Management Committee member of concerned department will be responsible for distribution of document identified in 5.4.4 as per **Document Distribution Matrix (SNGPL-GPR001-F-002)** duly approved by focal point and stamped them "**CONTROLLED COPY**" in red. Committee member distributes the documents by getting acknowledgment in **Document Distribution List (SNGPL-GPR001-F-003)** and distributes these documents to concern.

5.4.5.DMR Coordination under the supervision of MR distributes documents through mail or any other mean. Record of distribution is maintained on **Document Distribution List (SNGPL-GPR001-F-003)** by DMR Coordination

5.4.6.Two sets of master IMS system documents shall be maintained. One **Master Controlledset** is maintained at MR office; for reference purpose and the other **original signedDMR Coordination** maintains set for distribution purpose. All two DMRs can have access to those master documents.

5.4.7. Two sets of master IMS departmental documents (SOP's Specifications, Forms etc.) shall be maintained. One master set of documents should be sent to HSE Department for information purpose.

5.5 DOCUMENT MANAGEMENT ON INTRANET (OPTIONAL):

5.5.1 After the approval of system document, under supervision of IMS-DMR, DMR Coordination converts system document to Adobe PDF. (For read only) and uploads / Update the latest version of system documents on a designated folder at Domain.

5.5.2 DMR Coordination hosts these IMS system documents at domain under the supervision of DMR. Only MR / DMR (S) have full access of document.

5.6. DOCUMENT CHANGE MECHANISM

5.6.1. **Document Update Request (SNGPL-GPR001-F-004)** can be raised by any employee in case of any changes identified within system documents on the basis of Environment, Health & Safety issues.

5.6.2. **Document Update Request (SNGPL-GPR001-F-004)** is then submitted to DMR Coordination.

5.6.3. DMR Coordination forwards the same **Document Update Request (SNGPL-GPR001-F-004)** for necessary review and approval to designee who initially reviewed and approved the same documents. In case of new document creation, the **Document Management Chart (SNGPL-GPR001-CH-001)** will be followed for preparation, review and approval.

5.6.4. In case of approval of **Document Update Request (SNGPL-GPR001-F-004),** the said document will be submitted to DMR Coordination duly prepared, reviewed and approved by designee as per **Document Management Chart (SNGPL-GPR001-CH-001).**

5.6.5. DMR Coordination verifies the revision status of revised system document and releases it on current status. DMR Coordination updates the **Document Master list (SNGPL-GPR001-F-001)** accordingly and distributes as per **Document Distribution Matrix (SNGPL-GPR001-F-002)**. During distribution it should be ensured by all concerned Head of Departments that obsolete documents are removed and destroyed.

5.6.6. DMR Coordination also uploads / updates Intranet Domain Directory as per activity 5.5.

5.6.7. In case changes identified in SOP's after approval of **Document Update Request (SNGPL-GPR001-F-004),** DMR Coordination informs Concern Documents Management Committee member for document updation and distribution.

5.6.8. Concerned Documents Management Committee member follows activity 5.4.

5.6.9. DMR Coordination kept one original copy of old document as record with "**OBSOLETE DOCUMENT**" stamp in Blue.

5.6.10. If **Document Update Request (SNGPL-GPR001-F-004)** is rejected, DMR Coordination informs the related department about the status and reason of rejection and keeps the **Document Update Request (SNGPL-GPR001-F-004)** in record.

5.7. EXTERNAL DOCUMENT CONTROLLING

5.7.1. All concerned Head of Departments / MR / EMS & OHSAS DMRs will control all relevant external documents.

6.0. REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1. ISO 14001:2015, Clause 7.5

6.2. ISO 45001:2018, Clause 7.5

The related documentation for **SNGPL-GPR-001 Documents Management** includes:

- **Document Master list** (**SNGPL-GPR001-F-001**)
- **Document Distribution Matrix** (**SNGPL-GPR001-F-002**)
- **Document Distribution List** (**SNGPL-GPR001-F-003**)
- **Document Update Request** (**SNGPL-GPR001-F-004**)
- **Master List for External Documents** (**SNGPL-GPR001-F-005**)
- **List of Departmental Abbreviation** (**SNGPL-GPR001-F-006**)
- **List of Documents Management Committee** (**SNGPL-GPR001-F-007**)
- **Document Management Chart** (**SNGPL-GPR001-CH-01**)
- **Format for Procedure Annexure-A**

The source provides a **Documents Management Chart** that specifies who is responsible for preparing, reviewing, and approving different types of documents.

- **HSE Policy**: Prepared by the Management Representative (MR), reviewed by the Senior General Manager (SGM) or General Manager (GM), and approved by the Managing Director (MD). Document number SNGPL-POL-001.
- **HSE Objectives**: Prepared by the concerned HSE Site committee member, reviewed by the concerned focal point/Departmental Head, and approved by the MD. Document number SNGPL - Dept. Abb.- /Section Abb.-OBJ-001.
- **IMS Manual**: Prepared by Deputy Management Representatives (DMR(s)), reviewed by the MR, and approved by the MD. Document number SNGPL.-MAN-001.
- **General Procedures**: Prepared and reviewed by DMR-EMS / OHSAS and approved by the MR. Document number SNGPL.-GPR-001, 002……..
- **EMS Procedures**: Prepared by DMR-EMS, reviewed by DMR-OHSAS, and approved by the MR. Document number SNGPL - EPR-001, 002……..
- **OH&S Procedures**: Prepared by DMR-OHSAS, reviewed by DMR- EMS, and approved by the MR. Document number SNGPL.-HPR-001, 002……..
- **Standard Operating Procedures (SOPs)**: Prepared by the concerned HSE Site Committee (HSC) member, reviewed by the concerned Focal Point, and approved by the Departmental Head. SOPs are specified by the Department or identified by title.
- **Internal Specification**: Prepared and reviewed by the concerned HSE Site committee member and approved by the concerned focal point/Departmental Head. Document number SNGPL - Dept. / Section Abb.- Procedure # / FCH# / SOP #- SPEC-001.
- **Chart**: No specific personnel are listed in the source for preparation, review, or approval. Document number SNGPL-Dept./Section Abb./-Procedure # / FCH# / SOP #-CH-001.
- **Forms**: No specific personnel are listed in the source for preparation, review, or approval. Document number SNGPL-Dept. / Section Abb./Procedure # / FCH# / SOP #-F-001.

The document provides a **list of sites and their abbreviations**. These abbreviations are used by Sui Northern Gas Pipelines Limited (SNGPL). The list includes various regions, transmission sections, compression facilities, control centers, metering locations, coating plants, workshops, head offices, and camps.

Here is the list of sites and their abbreviations as presented in the source:

- Lahore East: LHR East
- Lahore West: LHR West
- Multan Region: MUL-D
- Peshawar Region: PSR-D
- Abbottabad Region: ABT-D
- Islamabad Region: ISD-D
- Bahawalpur Region: BWP-D
- Faisalabad Region: FSD-D
- Gujranwala Region: GUJ-D
- Sheikhupura Region: SKP-D
- Sahiwal Region: SWL-D
- Sargodha Region: SGD-D
- Rawalpindi Region: RWP-D
- Gujrat Region: GRT-D
- Sialkot Region: SKT-D
- Mardan Region: MRD-D
- Faisalabad Transmission: FSD-T
- Multan Transmission: MUL-T
- Wah Transmission: WAH-T
- Section IV – Lahore Transmission: LHR-T
- Multan Compression: MUL-C
- Faisalabad Compression: FSD-C
- Corrosion Control Centre: CCC
- Metering W/S: MET-W/S
- Coating Plant–UCH Sharif: CP-UCH
- Manga W/S: Manga-W/S
- Manga Stores: Manga-STR
- Civil Head Office: Civil-HO
- Nowshera Camp: NSR Camp
- Lachi Camp: Lachi Camp
- Sheikhupura Camp: SKP Camp
- Phool Nagar Camp: PHL-NGR-Camp
- Sadiqabad Camp: SDQ-Camp
- Taranda Camp: TAR-Camp
- Habibabad Camp: HBD-Camp
- Kacha Khu Camp: KKU-Camp
- Shujaabad Camp: SHU-Camp
- Kamonki Camp: KMK-Camp
- Manga Camp: MNG-Camp

1.0 PURPOSE

To establish a procedure for managing all Company records which includes record identification, maintenance, retention, storage, access, disposition and disposal.

2.0 SCOPE

The procedure applies to all Company records in order to meet standards ISO 14001 and ISO 45001 requirements.

3.0 DEFINITIONS

Document	Information and its supporting medium. The medium can be paper, magnetic, electronic or optical computer disk, photograph or a combination thereof.
Record	Document stating results achieved or providing evidence of activities performed. Record is required to be retained for future reference.
RMC	Record Management Committee
HOD	Head of Department

4.0 RESPONSIBILITIES:

4.1 Head of departments (HODs)

4.2 HSE Focal Point

4.3 Record Management Committee

4.4 Record Officer (Manga)

5.0 REQUIREMENTS

Company's Archive at Manga	- Designated place for placement of record at Manga.
Record Officer (Manga)	- Responsible for proper storage / disposal and authorized access of Company record at "Company's Archive at Manga".
Shredder	- For disposal of record

6.0 PROCEDURE

6.1 Record Management Committee (RMC) is to be developed at Head Office by each department as per proforma **Record Management Committee** (**SNGPL-GPR002-F-001).**

6.2 All RecordManagementCommittee members should comprise of at least members of Executive cadre.

6.3 All Company records are to be identified by RMC on **List ofRecords (SNGPL-GPR002-F-002).**

6.4 No record / file is kept without appropriate identification.

6.5 Retention Period of each document / file is to be defined **on List of Records (SNGPL-GPR002-F-002)** by RMC and approved by HOD.

6.6 Record is to be transferred to "**Company's Archive at Manga**" (or designated location subject to availability) as per ***Initiator (Record Transfer)***'s request approved by respective HOD (for Head Office) and HSE Focal Point (for Sites). It must be converted into soft form in coordination with IT/MIS department if recommended by initiator (Record Transfer).

6.7 It is the responsibility of Initiator (Record Transfer) to arrange transfer of their respective records to "Company's Archive at Manga" (or designated location subject to availability) as per approved List of Records (SNGPL-GPR002-F-002) of their respective department.

6.8 All record should be transferred as per **"Request for Record Transfer" (SNGPL-GPR002-F003)**.

6.9 It is the responsibility of Record officer (Manga) to maintain soft form of record in coordination with IT / MIS department as per recommendation on proforma SNGPL-GPR002-F003**.**

6.10 Record declared for permanent retention period shall never be disposed off and is to be placed as per recommendation of RMC and HOD. Record under any litigation or under consideration of internal / commercial audit shall never be disposed off till the settlement of Case / Audit Para.

6.11 Record after completion of its retention period is to be disposed off at "Company's Archive at Manga" after taking necessary approval on **"Request for Record Disposal-Manga" (SNGPL-GPR002-F004)** which is to be timely initiated by Record Officer (Manga) after taking necessary approval from respective HOD.

6.12 It is the responsibility of Record officer (Manga) to arrange disposal of record placed at 'Company's Archive at Manga' in the presence of respective department representative.

6.13 All documents / records related to this procedure (SNGPL-GPR002-F001, F-002, F-003 and F-004) are to be maintained.

7.0 ACCESS TO RECORD:

Record Officer (Manga) is responsible for ensuring that accessibility to Company records placed
at "Company's Archive at Manga" is restricted to authorized staff only.

8.0 GENERALHSEGUIDELINES:

All safety guidelines mentioned in HSE Procedure "General Safety Management" (SNGPL-HPR-004) should be followed.

9.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

9.1 ISO 14001:2015, Clause 7.5

9.2 ISO 45001:2018, Clause 7.5

10.0RELATED DOCUMENTATION

10.1 Record Management Committee	(SNGPL-GPR002-F-001)
10.2 List of Records	(SNGPL-GPR002-F-002)
10.3 Request for Record Transfer	(SNGPL-GPR002-F-003)
10.4 Request for Record Disposal-Manga	(SNGPL-GPR002-F-004)

1.0 PURPOSE

To establish a procedure for establishing competence criteria, identification, planning & execution of trainings and awareness of all employees for effective implementation of Integrated Management System (IMS)

2.0 SCOPE

2.1. All section and departments of SNGPL as defined in IMS Manual.

2.2 All on site SNGPL / contractual employees working within SNGPL facility.

2.3 All on site casual employees working within SNGPL facility

3.0 DEFINITIONS

HSE	Health, Safety, Environment
TNM	Training Needs Matrix
HSE-MS	Health, Safety, Environment Management System
MR	Management Representative
DMR	Deputy Management Representative
HOD	Head Of Department
SOP's	Standard Operating Procedures
Competent Authority	MR in case of HSE / IMS courses and concerned HSE Focal Point / Departmental Head in case of establishing competence criteria and training on SOP's of departments

4.0 RESPONSIBILITIES:

4.1 Management Representative (MR)

4.2 Concerned HOD / HSE Focal Point

4.3 EMS & OHSAS Deputy Management Representatives (DMRs)

5.0 PROCEDURE

5.1 TRAINING NEEDS IDENTIFICATION:

5.1.1**Training Need Matrix for HSE Courses and SOP's (SNGPL-GPR003-F-001)** is developed by MR / Departmental Head / HSE Focal Point on annual basis. (For HSE Courses in EMS & OHSAS Deputy Management Representatives (DMRs) be consulted)

5.1.2Training needs of individuals identified for IMS on form **Training Need Matrix(SNGPL-GPR003-F-001**) ison the basis of following:

5.2.3.1 Whose jobs may create a significant impact on the environment.

5.2.3.2 Who are involved and affected by hazard / risks for occupational health and safety at SNGPL.

5.2.3.3 Identification of new hazard.

5.2.3.4 Identification of new environmental aspect.

5.2.3.5 Change in legal requirements or Compliance Obligations

5.2.3.6 Changes in facility / process identified through new project.

5.2.3.7 Identification of Non-conformance in internal / external audit.

5.2.3.8 Corrective / preventive action identified through accident / incident investigation.

5.2.3.9 Consistent Non-conformance observed.

5.2.3.10 Identification of Risks and Opportunities

Site HSE Engineer will identify training against IMS procedures / HSE Courses and respective HOD / HSE Focal Point will identify training against SOPs.

5.1.3New, part-time and transferred Management & Non-Management employees, as well as permanent on-site contractor employees shall be included in the IMS training programs.

5.1.5.1 All the new employees whether executives / staff / casual or contractual staff shall be imparted training. Training record will be verified by trainer on **Attendance Sheet(SNGPL-GPR003-F-003)** and maintained by Concerned HOD / Section Head / HSE Focal Point or MR respectively.

HSEORIENTATIONFOREXECUTIVES:

5.1.3.1 Executives shall be trained during Company's orientation programme by HR department. HSE department will impart the awareness about HSE based upon the following:

- HSE Policy of SNGPL.
- HSE Certification of SNGPL.
- General HSE Rules and Regulations. Online Accident Reporting System.
- Health & Safety hazards.
- Environmental Management System.
- Weekly Safety Talk.
- Weekly RSA

5.1.3.2 Some specific HSE awareness shall be imparted by executives of concerned department based upon the following:

- General Safety Rules.
- Safety Talks.

5.1.3.3 HSE Focal Point shall ensure that the training is provided to executives of engineering group upon posting, regarding the possible hazards of their related activities.

HSEORIENTATIONFORSN/CASUAL/CONTRACTUALEMPLOYEES:

5.1.3.4 SN/ Casual Employees shall be trained prior to assigning any responsibility by the HSE Focal Point through relevant sectional Incharges.

5.1.3.5 SN/ Casual employees shall be made aware of the possible work related hazards and precautions to be taken by the HSE Focal Point through first line executives.

5.1.3.6 SN/Casual field employees shall be trained to identify and evaluate potential risk and remove themselves from certain situations that can present serious health or life hazard.

5.2 TRAINING PLAN:

5.2.1 **Training Schedule(SNGPL-GPR003-F-002) will be prepared by HSE Focal point** in consultation with MR on the basis of **TNM** for HSE Courses / IMS Procedures **(SNGPL-GPR003-F-001)** for internal / external training on annual basis.

5.2.2HSE Focal point shall plan training of HSE Courses / IMS procedures at sites on Fiscal Year basis, as per requirement raised on **Training Schedule (SNGPL-GPR003-F-002)**, in consultation with MR. Copy of approved Training schedule (HSE Courses / IMS Procedures) shall be sent to MR.

5.2.3HSE Focal Point / HOD in consultation with Sectional heads plans the training of respective JDs and SOPs on **Training Schedule(SNGPL-GPR003-F-002)** as per TNM for SOP's, on Fiscal year basis. Copy of approved Training schedule (HSE Courses / IMS Procedures) will be sent to MR.

5.2.4Competence of Trainer would be assessed by the competent authority on the basis of appropriate qualification, skill, experience and proper training.

5.2.5Competence criteria of permanent staff including executives and subordinate will be established by HR department and for contractual / casual staff, relevant HSE Focal point will establish competence criteria on the basis of appropriate education, training or experience.

5.3 TRAINING EXECUTION:

5.3.1EXTERNAL TRAINING:

5.3.1.1 HSE department shall search the source in consultation with DMR (EMS & OHSAS). MR shall evaluate market reputation of institute / instructors in consultation with DMR (ISO & OHSAS).

5.3.1.2 In case of external training, MRis responsible to arrange necessary resources.

5.3.1.3 Course Participants will submit a copy of course material and copy of certificate to HSE Dept.

5.3.2IN-HOUSE TRAINING:

5.3.2.1 Focal Point / HOD is responsible to implement clause 5.2.3, 5.2.4 ontheir site.

5.3.3Training record will be verified by trainer on **Attendance Sheet(SNGPL-GPR003-F-003)** and maintained by Concerned HOD / Section Head / HSE Focal Point or MR respectively.

5.3.4MR / HSE Focal Point shall ensure that trainer is competent enough on the basis of appropriate education, training and experience, and shall maintain its records.

5.4 EVALUATION OF TRAINING:

5.4.1 Effectiveness of training is assessed by Concerned HOD / HSE Focal Point or MR respectively within one month on **Individual Training Record (SNGPL-GPR003-F-004).**

5.4.2 Effectiveness of training is assessed on following basis (within scale of 1 to 5).

5.4.2.1 Performance observed (on the job)

5.4.2.2 Oral / Written tests.

5.4.2.3 Demonstration

5.4.2.4 Questions / interviews

5.4.3 If rated poor by Evaluator then MR or Concerned HOD / HSE Focal Point respectively will recommend him to repeat the training.

5.4.4 HOD / HSE Focal Point will maintain **individual Training Record (SNGPL-GPR003-F-004).**

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

The relevant section discusses documentation and standards related to **Competence, Training, and Awareness**, particularly within the context of ISO 14001:2015 and ISO 45001:2018.

- **HSE Focal Point Responsibilities** HSE Focal point shall plan training of HSE Courses / IMS procedures at sites on Fiscal Year basis, as per requirement raised on Training Schedule (SNGPL-GPR003-F-002), in consultation with MR. Copy of approved Training schedule (HSE Courses / IMS Procedures) shall be sent to MR.
- **ISO Standards** The documentation adheres to **ISO 14001:2015, Clause 7.2, 7.3** and **ISO 45001:2018, Clause 7.2, 7.3**.
- **Related documentation** includes:
  - **TNM (Training Needs Matrix) for Courses (SNGPL-GPR003-F-001)**.
  - **Training Schedule (SNGPL-GPR003-F-002)**.
  - **Attendance Sheet (SNGPL-GPR003-F-003)**.
  - **Individual Training Record (SNGPL-GPR003-F-004)**.
- **Training Needs Matrix** The Training Needs Matrix (TNM) for HSE courses or Departmental SOPs includes the course, employees requiring training, source of training, duration (hours), and frequency. A recommendation from the HSE Focal Point or MR, along with the date, is also included.
- **Training Schedule** The training schedule includes the course/IMS procedures/SOPs, approximate number of employees requiring training, the source of training, duration (hours), scheduled date, actual employees trained, actual date, and remarks. The HSE focal point signs and dates the schedule.
- **Attendance Sheet**: The attendance sheet captures the date, description/contents of training, name of instructor, training place, duration, names of participants, their section/department, designation, and signature. There is also a section for remarks. The instructor verifies the participants with their signature and date.

- **Individual Training Record**: The individual training record captures SN. No / Employee No, Name, Designation, Site/ Department. It also evaluates effectiveness/competence by supervisor. Prepared By and Verified By sections are included.

1.0 PURPOSE

1.1 To establish a procedure to enable SNGPL to verify the results of the planned HSE activities that complies with HSE requirements.

1.2 To make certain that planned HSE activities demonstrate the effectiveness of the HSE Management System.

1.3 To define the activities and procedure carried out of Internal Audit function.

2.0 SCOPE

All Company premises, sites and activities.

3.0 DEFINITIONS

Audit Notification	A letter informing the auditee of the proposed date of audit, scope and purpose of the audit, type of audit and approximate duration of the audit.
Auditee:	Person or department being audited.
Lead Auditor:	The individual who functions as the team leader and supervises the audit team during an audit.
Auditor:	The individual who performs the audit.
Process Audit:	An analysis of an element of a process and appraisal of completeness, correctness of conditions and probable effectiveness.
System Audit:	An analysis of all elements of an organization to determine the organization's development, integrity, documentation and effectiveness of implementation.
Audit Schedule:	A document setting out the departments or functions to be audited, the schedule for each audit, the lead auditors and any other details that may be needed.
Major Non-Conformance	Total Gap in standards and / or procedures compliance/ implementation
Minor Non-Conformance	Partial Gap in standards and / or procedures compliance/ implementation
Observation	Future Improvement opportunity / potential non conformance

4.0 RESPONSIBILITIES

4.1 Management Representative (MR)
4.2 Head of Departments / HSE Focal Point
4.3 EMS & OHSAS Deputy Management Representatives (DMRs)
4.4 Audit Team

5.0 PROCEDURE

5.1 AUDIT SCHEDULE

5.1.1 OHSAS and EMS DMRs prepare an **Audit Schedule (SNGPL-GPR004-F-001)** for audit, taking into consideration the status and importance of the process and areas to be audited.

5.1.2 Based on critical deviations / non-conformances, reported critical customer complaints, major volume of work or flow of activities etc., MR can conduct or arrange an unscheduled / additional audit. Additional audits or decrease in the frequency of audits may also be incorporated in the future Audit Schedule (SNGPL-GPR004-F-001) based on the previous audit reports, results of statistical techniques interpretation, customer complaints etc.

5.1.3 MR ensures that every department is audited at least twice in a year.

5.1.4 OHSAS DMR and EMS DMR review and MR approves the Audit Schedule (SNGPL-GPR004-F-001).

5.1.5 OHSAS-DMR ensures that the Audit Schedule (SNGPL-GPR004-F-001) is distributed to concerned department.

5.1.6 The Audit Schedule (SNGPL-GPR004-F-001) contains the following details:

5.1.6.1 Audit dates
5.1.6.2 Department to be audited
5.1.6.3 Applicable clauses
5.1.6.4 Name of auditor (s)

5.2 SELECTION OF AUDIT TEAM:

5.2.1 OHSAS-DMR selects a team of auditors and a lead auditor from a **Trained Auditor List (SNGPL-GPR004-F-003)**. Competence of the auditor is to be evaluated through a process that considers personal behavior and the ability to apply the knowledge and skills gained through education, work experience, auditor training and audit experience.

5.2.2 OHSAS -DMR informs the auditors of their selection, audit criteria, department to be audited, and scope of audit via Audit Schedule (SNGPL-GPR004-F-001).

5.2.3 OHSAS -DMR ensures that:

5.2.3.1 Auditors are selected and assigned audit activities in a manner that they don't audit their own department / section.

5.2.3.2 Auditors have the basic knowledge of the activities of the area within their scope.

5.2.3.3 Auditors have demonstrated their competency in the previous audits.

5.3 AUDIT NOTIFICATION:

5.3.1 Once the Audit Schedule (SNGPL-GPR004-F-001) has been developed, the OHSAS –DMR or EMS-DMR notifies the auditee in writing, **at least 07 days prior** to audit through **Audit Notification (SNGPL-GPR004-F-002)** for the system audit.

5.3.2 The Audit Notification (SNGPL-GPR004-F-002) will include:-

5.3.2.1 Proposed dates and time of the audit.

5.3.2.2 Scope and purpose of the audit.

5.3.2.3 Type of audit.

5.3.2.4 Approximate duration of the audit.

5.3.2.5 Auditee's responsibilities to the audit and audit team.

5.4 AUDITEE RESPONSIBILITIES:

5.4.1 OHSAS -DMR or EMS-DMR makes the auditee aware of the responsibilities in the Audit Notification (SNGPL-GPR004-F-002).

5.4.2 OHSAS –DMR or EMS-DMR makes known to the auditee any deficiencies on the later part that may substantially impact the performance of the audit or results of the audit.

5.4.3 The Auditee's responsibilities include:-

5.4.3.1 Provide location for the conducting the audit.

5.4.3.2 Provide support for the audit team (if required)

5.4.3.3 Make available all staff for audit.

5.4.3.4 Provide records for auditor's inspection and sampling.

5.4.3.5 Review and comment on the auditor's observations and findings. 5.4.3.6 Provide timely corrective actions to eliminate detected non-conformances & their root causes.

5.5 AUDIT PREPARATION:

5.5.1 Contacting the auditee to confirm (verbally) that the auditee has made all arrangements.

5.5.2 If arrangements are lacking or circumstances are such that the audit cannot be performed at the specified time the auditee shall submit a written explanation and request to reschedule the audit.

5.6CONDUCTING THE AUDIT

5.6.1Opening Meeting:

Audit execution will be formally started with opening meeting by assigned Lead Auditor as per Audit Schedule (SNGPL-GPR004-F-001). This meeting will be attended by HSE Focal Point, all departments / section heads, and members of Audit team. The attendance sheet will be maintained on **Audit Meeting Attendance form(SNGPL-GPR004-F008)**. The agenda of opening meeting will be as follows:

5.6.1.1 Introduction of Audit Team

5.6.1.2 A review of Audit Program and seek confirmation from auditee

5.6.2Recording Audit Non-conformities:

5.6.2.1a) The auditor shall take the notes at site (hand written)on form **AuditorNotes (SNGPL-GPR004-F004).** The evidences seen for the Compliance / Non Compliance should also be noted.

b)The auditor shall record the non-conformities identified during the audit on **Non-Conformance Request (SNGPL-GPR004-F-005**).

5.6.3.2 The auditor notes each non-conformity whether related to same clause / procedure etc., or two different clauses / procedures on separate Non-Conformance Request (SNGPL-GPR004-F-005) which will be acknowledged by Auditee.

5.6.3.3 Auditee after acknowledging, takes the necessary corrections, investigate the non conformity / reasons of non-conformity and suggests the corrective action(s) along with their target implementation date, on Non-Conformance Request (SNGPL-GPR004-F-005) the moment a non-conformity is identified related to his department / section.

5.6.3.4 If the non-conformity is caused by some other department / section, the auditee gives an agreement and the lead auditor later collects the corrective action(s) along with the target implementation dates from the relevant department / section.

5.6.3.5 The auditor assigns the Non-Conformance Request # (SNGPL-GPR004-F-005) in the following manner:

A – Dept. /Sec – S.No. (XXX)

Where A = Audit, Dept. = Departmental Abbreviations, Sec.= Section Abbreviation
S.No = Consecutive serial numbers of CAR with respect to Dept. Under audit i.e.: A-HSE-002.

5.6.3Closing Meeting:

Assigned lead auditor as per audit program will formally announce completion of audit execution in closing meeting. This meeting will be attended by Focal Point, all departments / section heads and members of Audit team. The agenda of closing meeting will be as follows:

5.6.3.1Thanks to Auditee
5.6.3.2Present / Explain Compliances and Non-compliances
5.6.3.3Conclusion / Recommendations

5.7 AUDIT REPORT:

5.7.1Lead Auditor submits the **Audit Report (SNGPL-GPR004-F-006)** along with Non-Conformance Request # (SNGPL-GPR004-F-005) to the OHSAS-DMR **within 7 days after completion of the audit**.

5.7.2OHSAS-DMR or EMS-DMR reviews the Audit Report (SNGPL-GPR004-F-006), Auditor Notes (SNGPL-GPR004-F004) and Non-Conformance Request # (SNGPL-GPR004-F-005), make amendments in the corrective action(s) / the target implementation and follow up date(s) if required, after concurrence with the auditee.

5.7.3After reviewing Auditor Notes (SNGPL-GPR004-F004) and Non-Conformance Requests (SNGPL-GPR004-F-005), MR may ask Auditor for any specific Requirement / Clause of the Standard / area of deficiencies. MR has the authority to cancel or alter the Non-Conformance Requests (SNGPL-GPR004-F-005) raised by the Auditor if deemed necessary.

5.7.4OHSAS –DMR or EMS-DMR assigns the audit number to audit report in the following manner:-

AR – Dept./Sec. – S. No.(XXX)

AR = Audit Report
Where Dept. = Departmental Abbreviations
Sec.= Section Abbreviation
S. No = Consecutive Serial Numbers of audit with respect to Dept. under audit i.e. AR-HSE-02

5.7.5OHSAS –DMR or EMS-DMR logs the Audit # and related CAR # (s) along with the target implementation dates in the **Audit Log Sheet (SNGPL-GPR004-F-007**).

5.7.6HSE Focal Point shall ensure that the Internal Audit Non-Conformance Requests (SNGPL-GPR004-F-005) are communicated to the relevant sectional heads, subordinate & casual staff and other relevant interested parties for the input, subsequent corrective actions and trainings.

5.8 FOLLOW UP AUDIT:

5.8.1 After corrective action(s) completion dates are crossed over, OHSAS –DMR or EMS-DMR arranges auditors for follow-up audit (if required), preferably the same auditors who audited previously.

5.8.2 If the audit non-conformity is not effectively closed out after surpassing the completion date; even after 2nd follow-up audit, the auditor raises the new Non-Conformance Request # (SNGPL-GPR004-F-005) with higher category of non-conformity.

5.9 AUDIT STATUS REPORT:

OHSAS –DMR or EMS-DMR prepares the **Internal Audit Status** which is to be presented in the Management Review Meeting.

5.10 AUDIT FILES:

5.10.1 OHSAS –DMR or EMS-DMR ensures that working documents used by audit team are maintained in audit file.

5.10.2 The working documents include, but not limited to are:

5.10.2.1 Notification's Letters
5.10.2.2 Audit Schedule
5.10.2.3 Auditor Notes
5.10.2.4 Audit Report.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

The source material relates to **internal audits** conducted by SNGPL, and lists documentation and standards related to ISO 14001:2015 and ISO 45001:2018.

- **ISO Standards**: The documentation adheres to **ISO 14001:2015, Clause 9.2** and **ISO 45001:2018, Clause 9.2**.
- **Related Documentation**:
  - **Audit Schedule** (**SNGPL-GPR004-F-001**)
  - **Audit Notification** (**SNGPL-GPR004-F-002**)
  - **Trained Auditor List** (**SNGPL-GPR004-F-003**)
  - **Auditor Notes** (**SNGPL-GPR004-F-004**)
  - **Non-Conformance Request** (**SNGPL-GPR004-F-005**)
  - **Audit Report** (**SNGPL-GPR004-F-006**)
  - **Audit Log Sheet** (**SNGPL-GPR004-F-007**)
  - **Audit meeting attendance** (**SNGPL-GPR004-F-008**)
- **Audit Schedule Details**: The Audit Schedule (**SNGPL-GPR004-F-001**) should contain:
  - Audit dates
  - Department to be audited
  - Applicable clauses
  - Name of auditor(s)
- **Audit Notification Contents**: The Audit Notification (**SNGPL-GPR004-F-002**) should include:

    - Proposed dates and time of the audit
    - Scope and purpose of the audit
    - Type of audit
    - Approximate duration of the audit
    - Auditee's responsibilities to the audit and audit team
- **Auditee Responsibilities** include:
    - Providing a location for conducting the audit
    - Providing support for the audit team (if required)
    - Making available all staff for the audit
    - Providing records for auditor's inspection and sampling
    - Reviewing and commenting on the auditor's observations and findings
    - Providing timely corrective actions to eliminate detected non-conformances and their root causes
- **Auditor Responsibilities**:
    - The auditor shall take notes at the site (handwritten) on the form **Auditor Notes (SNGPL-GPR004-F004)**. The auditor should also note the evidence seen for Compliance / Non-Compliance.
    - The auditor shall record the non-conformities identified during the audit on the **Non-Conformance Request (SNGPL-GPR004-F-005)**.
- **Non-Conformance Request Number**: The auditor assigns the Non-Conformance Request number (**SNGPL-GPR004-F-005**).
- **Audit Report Number**: OHSAS –DMR or EMS-DMR assigns the audit number to the audit report.
- **Communication of Audit Results**: HSE Focal Point ensures that the Internal Audit Non-Conformance Requests (**SNGPL-GPR004-F-005**) are communicated to relevant parties for corrective actions and training.
- **Follow-Up Audits**: OHSAS –DMR or EMS-DMR arranges auditors for follow-up audit (if required), preferably the same auditors who audited previously.

From: _GM (HSE)/MR_ **To:**EIC (Peshawar/ Badhber Camp)

Date: _12.10.2018

Audit Type: Scheduled Rescheduled Follow – up

Purpose: The purpose of audit is to verify the implementation of IMS System compliance (where applicable).

Audit Type (the appropriate box)

√ Environmental Management System √ Health & Safety Management System

Scope: The scope of audit is for "**ISO 14001:2015 & ISO 45001:2018 Standards"**

Audit Schedule:

Audit Duration: 01 Day

Date: 16.10.2018

Time: Office Timings

Site:**Peshawar/ Badhber Camp**

Lead Auditor: LA: Mr. Muhammad Qasim (Sr. Engineer (HSE), Fsd-T)

Observer: OB: Mr. Muhammad Saeed Khan (Exec. Engineer (HSE), Peshawar/ Badhber Camp)

Auditee Responsibilities:

- ☐ Make available All staff for audit.
- ☐ Provide inspection and testing records for auditor inspection and sampling.
- ☐ Review and comment on the auditor's observations and findings.
- ☐ Provide timely corrective actions of identified non-conformances.

Regards,

GM (HSE) / MR

Cc: GM (P)

1.0 PURPOSE

To establish a procedure for periodic review and evaluation of SNGPL's HSE Management System to ensure its continuing suitability adequacy and effectiveness for continual improvement.

2.0 SCOPE

2.1. All relevant activities, area and department of SNGPL as defined in IMS Manual.

3.0 DEFINITIONS

HSE Health, Safety and Environment

MRM Management Review Meeting

HSC HSE Site Committee

OH&S Occupational Health & Safety

EMS Environmental Management System

4.0 RESPONSIBILITIES:

4.1 HSE Management Committee

4.2 IMS Management Representative (MR)

4.3 EMS & OHSAS Deputy Management Representatives (DMRs)

4.4 HSE Site Committee

5.0 PROCEDURES

5.1 MANAGEMENT REVIEW MEETING PLAN

5.1.1 The HSE Management Committee shall conduct a review of HSE Management System at least half yearly.

5.2.2The MR shall prepare **Management Review Meeting Schedule** (**SNGPL-GPR005-F-001)** at beginning of the year and get it approved by MD.

5.2.3Management review meetings shall be scheduled in advance by the MR and a **Management Review Meeting Agenda** (**SNGPL-GPR005-F-002)** will be issued

before the MRM to ensure appropriate preparation and submission of their reports to MR by all concerned.

5.2 MANAGEMENT REVIEW MEETING EXECUTION:

5.2.1 MD shall steer the Management Review Meeting. In his absence, most senior designee conducts Management Review Meeting.

5.2.2 The HSE Management Committee shall review all applicable components of the SNGPL HSE Management System. HSE-Management Committee will be comprised of following:

- 5.2.2.1 MD
- 5.2.2.2 MR
- 5.2.2.3 Head of Departments
- 5.2.2.4 OHSAS & EMS DMRs
- 5.2.2.5 MR may invite any one to attend the meeting.

5.2.3 Management Representative shall present information for review and concurrence, which includes but not limited to:

- 5.2.3.1 Follow-up from last MRM minutes
- 5.2.3.2 HSE Policy.
- 5.2.3.3 OH&S and Environmental Objectives, Targets and Management Programs
- 5.2.3.4 Legal and Other Requirements
- 5.2.3.5 Training, Awareness and Competence
- 5.2.3.6 Environmental Evaluation of compliance
- 5.2.3.7 Emergency Preparedness and Response
- 5.2.3.8 Non-Conformance, Corrective Actions Status
- 5.2.3.9 Accident / Incident status
- 5.2.3.10 Internal Audit Status
- 5.2.3.11 external and internal issues;
- 5.2.3.12 the needs and expectations of interested parties, including compliance obligations

5.2.3.13 significant environmental aspects;

5.2.3.14 risks and opportunities.

5.2.3.15 Opportunities to improve integration of the HSE management system with other business processes, if needed;

5.2.3.16 Continual improvement

5.2.3.17 Monitoring and measurement results

5.2.3.18 Consultation and participation of workers

Any other relevant point identified

5.2.3.19 5.2.4The HSE Management Committee shall review and confirm their approval and continual suitability, adequacy and effectiveness of the HSE Policy, EMS, OH&S Objectives and targets, EMS & OH&S Management Programs and other elements of the system as well as regulatory compliance requirements are met. Continual improvement of HSE Management System shall be reviewed and endorsed.

5.2.5Attendance of Management Review Meeting will be recorded on **MRM Attendance Sheet (SNGPL-GPR005-F-004)**.

5.2.6The MR will take the notes, maintain and circulate **Management Review Meeting Minutes** (**SNGPL-GPR005-F-003)** identifying issues discussed and corrective and preventive actions to be taken. Required actions will be assigned to the responsibility of process, areas, unit, department and functional management.

5.2.7MR will follow the progress and continuously update the status to MD.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1. ISO 14001:2015, Clause 9.3

6.2. ISO 45001:2018, Clause 9.3

The source material lists **documentation related to Management Review Meetings** at Sui Northern Gas Pipelines Limited (SNGPL). These meetings aim to periodically review and evaluate SNGPL's Health, Safety, and Environment (HSE) Management System to ensure its suitability, adequacy, and effectiveness for continual improvement.

The documentation includes:

- **Management Review Meetings Schedule (SNGPL-GPR005-F-001)**
- **Management Review Meeting Agenda (SNGPL-GPR005-F-002)**
- **Management Review Meeting Minutes (SNGPL-GPR005-F-003)**
- **MRM Attendance Sheet (SNGPL-GPR005-F-004)**

Further details on these documents and the Management Review Meeting include:

- **Purpose of the Management Review Meeting**: To ensure the continuing suitability, adequacy, and effectiveness of SNGPL's HSE Management System for continual improvement.
- **Frequency of the Management Review Meeting**: The HSE Management Committee must conduct a review of the HSE Management System at least half-yearly.
- **Preparation of Meeting Schedule**: The Management Representative (MR) prepares the Management Review Meeting Schedule (**SNGPL-GPR005-F-001**) at the beginning of the year and gets it approved by the Managing Director (MD).
- **Issuance of Agenda**: Management review meetings are scheduled in advance by the MR, and a Management Review Meeting Agenda (**SNGPL-GPR005-F-002**) is issued before the meeting to ensure appropriate preparation and submission of reports to the MR by all concerned.
- **Steering the Meeting**: The MD steers the Management Review Meeting. In their absence, the most senior designee conducts the meeting.
- **HSE Management Committee Composition**: The HSE-Management Committee consists of the MD, MR, Heads of Departments, and EMS & OHSAS Deputy Management Representatives (DMRs). The MR may invite others to attend the meeting.
- **Information Presented by Management Representative**: The Management Representative presents information for review and concurrence, including but not limited to:
    - Follow-up from last MRM minutes
    - HSE Policy
    - OH&S and Environmental Objectives, Targets, and Management Programs
    - Legal and Other Requirements
    - Training, Awareness, and Competence
    - Environmental Evaluation of compliance
    - Emergency Preparedness and Response
    - Non-Conformance, Corrective Actions Status
    - Accident / Incident status
    - Internal Audit Status
    - External and internal issues
    - The needs and expectations of interested parties, including compliance obligations
    - Significant environmental aspects
    - Risks and opportunities
    - Opportunities to improve integration of the HSE management system with other business processes, if needed
    - Continual improvement
    - Monitoring and measurement results
    - Consultation and participation of workers
    - Any other relevant point identified
- **Review and Approval**: The HSE Management Committee reviews and confirms their approval and continual suitability, adequacy, and effectiveness of the HSE Policy, EMS, OH&S Objectives and targets, EMS & OH&S Management Programs, and other system elements, as well as ensuring regulatory compliance requirements are met. Continual improvement of the HSE Management System is also reviewed and endorsed.
- **Recording Attendance**: Attendance of the Management Review Meeting is recorded on the MRM Attendance Sheet (**SNGPL-GPR005-F-004**).
- **Meeting Minutes**: The MR takes notes, maintains, and circulates Management Review Meeting Minutes (**SNGPL-GPR005-F-003**), identifying issues discussed and corrective and preventive actions to be taken. Required actions are assigned to the responsibility of process, areas, unit, department, and functional management.
- **Follow-Up**: The MR follows the progress and continuously updates the status to the MD.
- **ISO Standards**: The procedure adheres to **ISO 14001:2015, Clause 9.3** and **ISO 45001:2018, Clause 9.3**.

AGENDA FOR MRM TO BE HELD ON _____

1. Follow-up from last MRM minutes
2. HSE Policy.
3. OH&S and Environmental Objectives, Targets and Management Programs
4. Legal and Other Requirements
5. Training, Awareness and Competence
6. Environmental Evaluation of compliance
7. Emergency Preparedness and Response
8. Non-Conformance, Corrective Actions Status
9. Accident / Incident status
10. Internal Audit Status
11. external and internal issues;
12. the needs and expectations of interested parties, including compliance obligations
13. significant environmental aspects;
14. risks and opportunities.
15. Opportunities to improve integration of the HSE management system with other business processes, if needed;
16. Continual improvement
17. Monitoring and measurement results
18. Consultation and participation of workers
19. Any other relevant point identified

1.0 PURPOSE

This procedure defines the organization structure for Integrated Management System and responsibilities of the relevant personnel at SNGPL.

2.0 SCOPE

All section and departments of SNGPL as defined in IMS Manual.

3.0 Definitions

The definitions provided relate to Sui Northern Gas Pipelines Limited's (SNGPL) **Integrated Management System (IMS)**.

Key definitions include:

- **IMS (Integrated Management System)**: An integrated management system based on Environmental Management System (EMS) and Occupational Health & Safety (OH&S) standards. The purpose of the IMS is to provide a mechanism for Environmental, Occupational Health & Safety Management System throughout all areas, units and departments of SNGPL.
- **EMS (Environmental Management System)**: Part of the management system used to manage environmental aspects, fulfill compliance obligations, and address risks and opportunities.
- **OH&S (Occupational Health & Safety)**: Relates to the management of occupational health and safety.
- **JD's (Job Description)**: Outlines the responsibilities of different roles within the organization. The responsibilities of designations identified in the manual and procedures are defined in their respective Job Descriptions.
- **MR (Management Representative)**: General Manager (HSE) is nominated by the Management as MR. The Management Representative is responsible for ensuring the development and review of the Environmental Management System (EMS) and Occupational health and safety (OH &S) Management System.

Based on the provided text, here's a breakdown of the definitions and roles within Sui Northern Gas Pipelines Limited (SNGPL) related to Health, Safety, and Environment (HSE):

- **Management Representative (MR)**: The General Manager (HSE) is nominated by the Management as the Management Representative. The MR is responsible for ensuring the development and review of the Environmental Management System (EMS) and Occupational Health and Safety (OH&S) Management System.
- **Site**: Company's Head Office, Main Regional Offices, Transmission Section Offices, Compression Faisalabad / Multan, Project Camps, Corrosion Control Center (CCC), Central Metering Shop (CMS) and SNGTI etc. are designated as 'Sites'.
- **Sub-Site**: Company's Sub Area Offices, Customer Service Centers (CSC), Complaint Centers (CC), Repeater Stations, and Remote Compressor Stations etc. are designated as 'Sub-Sites'.
- **HSE Focal Point**: The In-charge of a Site is designated as the HSE Focal Point.
- **HSE Management Committee**: HSE Management Committee members are nominated by the Management. Senior management is part of this committee, which is overall responsible for monitoring and implementation of the HSE Policy and procedures. The Management Committee will meet at least bi-annually.
- **HSE Site Committee (HSC)**: This committee is developed at each Company Site. It consists of the In-charge Admin, HSE Engineer, and any other Sectional Head(s) of the concerned Site as

nominated by the HSE Focal Point. The HSE Focal point chairs the HSE site committee meeting at a frequency of two months.

- **Deputy Management Representatives (DMR)**: These are the Deputy Management Representatives for EMS and OHSAS.

4.0 RESPONSIBILITIES

4.1 Managing Director

4.2 HSE Management Committee

4.3 Head of departments

4.4 Management Representative (MR)

4.5 HSE Focal Points

4.6 HSE Site Committee (HSC)

4.7 EMS & OHSAS Deputy Management Representatives (DMRs)

5.0 PROCEDURE

5.1ORGANIZATIONAL STRUCTURE:

5.1.1 Organization Chart clearly defined Organizational structure of the SNGPL.

5.1.2 HSE Management Committee members are nominated in HSE Management Committee members list. Responsibilities of Management committee members are defined in clause 5.2 of this procedure.

5.1.3 Responsibilities of the designations identified in manual, procedures are defined in their respective JDs and in clause 5.2 of this procedure.

5.1.4 Managing Director of SNGPL has appointed General Manager (HSE) as Management Representative (MR) for IMS at SNGPL. Responsibilities of MR are defined in clause 5.3.3 of this procedure

5.1.5 EMS DMR and OHSAS DMR have been appointed to assist in IMS implementation.

5.1.6 Irrespective to his current job responsibility, MR ensures the execution of all roles and responsibilities defined in Job description of MR.

5.2 ROLES AND RESPONSIBILITIES OF MANAGEMENT:

5.2.1**MANAGING DIRECTOR:**

- Set Environmental, Occupational Health & Safety Policy, and direct & review implementation status.
- Delegate responsibility for the effectiveness of EMS & OHSMS to GM (HSE) as MR, however will still retain accountability.

Demonstrate leadership and commitment to the integrated management system, as Chairman HSE Management Committee by:

a. ensuring that HSE policy and OHS & environmental objectives are established and are compatible with the strategic direction and the context of the organization;
b. ensuring the integration of the integrated management system requirements into the organization's business processes;
c. ensuring that the resources and Finances needed for the implementation of HSE Management System are available;
d. communicating the importance of effective integrated management and of conforming to the integrated management system requirements; e. Developing, leading and promoting a culture in the organization ensuring that the integrated management system achieves its intended outcomes; directing and supporting persons to contribute to the effectiveness of the integrated management system;
f. promoting continual improvement;
g. supporting other relevant management roles to demonstrate their leadership as it applies to their areas of responsibility.
h.protecting workers from reprisals when reporting incidents, hazards, risks and opportunities.

5.2.2 ALL HEAD OF DEPARTMENTS (HODs):

- Implement the SNGPL Environmental, Occupational Health & Safety Policy by obtaining the resources and finances needed.
- Set and monitor Environmental, Occupational Health & Safety objectives and targets for Environmental, Occupational Health & Safety performance as member of HSE Management Committee.
- Periodically review the progress of Environmental, Occupational Health & Safety status / projects.

5.2.3 ALL HSE FOCAL POINTS:

- Obtain, understand and communicate the basic requirements associated with the EMS & OH & S MS and provide visual and vocal support to the EMS & OSHAS Programs.
- Obtain plans and policies recommended and approved by HSE Management Committee, initiate seeking assistance from other Departments for implementation.
- Integrate EMS & OHSAS consideration into procurement of supplies, raw materials, solvents chemicals and services including buying recycled content materials where practical.
- Conform to Occupational health, safety and environmental requirements.
- Develop, approve and communicate operational procedures to operations staff, giving due consideration to EMS aspects and impacts, OH &S hazards

and their risks, and requesting the assistance of HSE Department when needed.

- Identify and communicate staff training needs, including Environmental, Occupational Health and Safety training.

5.2.4 ALL SECTIONAL HEADS:

- Take into account, wherever possible, EMS & OHSAS issues in the design, including implementation of projects, new construction, renovation, equipment replacement, modifications and maintenance.
- Review and oversee the development of operating procedures for incorporating the Occupational health, safety and environmental controls.
- Ensure that assigned facility operations and activities are in conformance with the EMS & OH & S IMS requirements.
- Assist HSE Focal Point in communicating and promoting the basic requirements of the EMS & OH & S IMS to First line executives and subordinates.

5.2.5 ALL FIRST LINE EXECUTIVES:

- Develop operating procedures incorporating Occupational health, safety and environmental controls, seeking technical advise from sectional incharge and HSE Department.
- Assist HSE Focal Point / Sectional incharge in communicating and promoting the basic requirements of the EMS & OH & S MS to subordinates.
- Suggest measures for improving area / unit operational flexibility, economy and fulfilling of EMS & OHSAS Objectives.
- To ensure availability of updated 'hazard identifications and risk assessment' of operational sites and subsequent communication / awareness to the concerned staff.
- Conduct regular checks to establish equipment operating conditions and ensuring general housekeeping and conformance with safety, Occupational health and Environmental requirements.
- Identify and communicate training needs for first line supervisors and operators including EMS & OHSAS needs and awareness.
- Directly responsible for implementation of HSE policy / procedure / initiatives.

5.2.6 ALL SUPERVISORS (SN Staff):

- Follow the Standard Operating Procedure (SOP's), defined for an activity.
- Check availability of identified controls mentioned in operational site's hazards identification and risk assessment'. Communicate anomalies (if any) to first line executive.
- Ensure good housekeeping, safe operation and fulfilling EMS & OHSAS related responsibilities.

- Provide continues on-the-job training, guidance and skill improvement for operators / workers including EMS & OHSAS awareness and protection.
- Document all operational problem (including EMS & OHSAS Issues) or help required through the logbook and log sheet.

5.2.7 ALL CASUAL / CONTRACTOR STAFF:

- Maintain a clean, safe and healthy working environment by good house keeping.
- Follow environmental health and safety procedures, and safe work practices.
- Use personal protective equipments (PPEs) relevant to job area.

5.3 ROLES AND RESPONSIBILITIES WITH RESPECT OF IMS

5.3.1 HSE MANAGEMENT COMMITTEE:

The Management Committee will meet at-least bi-annually, in order to:

- Communicate the Commitment of SNGPL Management for EMS ISO 14001 and OHSAS ISO 45001 in SNGPL.
- Monitor the progress of EMS & OHSAS Project.
- Allocate resources identified by Management Representative
- Review and approve the Policy & Objectives for EMS & OHSAS on annual basis.
- Approve EMS-OHSAS Management Program & monitor its implementation.

5.3.2 ROLES AND RESPONSIBILITIES OF HSE SITE COMMITTEE:

- Prepare documentation, SOP's for IMS.
- Monitoring and implementation of IMS at Site.
- Monitoring and measurement of the objectives and targets of Site.
- Ensure and evaluate compliance of legal and other requirements of Site.
- Ensure training awareness and competences of all stakeholders for IMS at Site.

5.3.3 ROLES AND RESPONSIBILITIES OF MANAGEMENT REPRESENTATIVE (MR)

- Ensure development and review of Environmental Management System (EMS) and Occupational health and safety (OH &S) Management System
- Proactively identify and propose systems and policies to effectively manage environmental aspects / impact, occupational health and safety hazards risks, opportunities and issues
- Update top management on IMS performance and raise issues to management's attention as they arise.

- Track emerging laws / regulations requirements and issues guidance to affected parties.
- Coordinate identifying environmental / Occupational health and safety training needs for all site staff and coordinate General Manager (Training & Dev) in developing training programs as needed.
- Share good practice and problems / lessons learnt with HSE Focal Points.
- Coordinate with all HSE Focal points for emergency response planning to ensure environmental, occupational health and safety considerations have been incorporated as needed.
- Maintain all relevant records according to document control and retention policies.
- Coordinate with concerned Environment Protection Agencies to fulfill the requirements of environment Protection Act and other laws regulations applicable to the organization

Roles and Responsibilities of DMR EMS:

- **EMS aspect and impact identification**: The DMR EMS helps identify environmental aspects and their impacts.
- **Assisting MR in setting objectives**: The DMR EMS assists the Management Representative (MR) in setting objectives and monitoring the Management program.
- **Monitoring of EMS operational control**: The DMR EMS is responsible for monitoring the operational control of the EMS.
- **Periodic monitoring of EMS regulatory compliance**: This involves regularly checking compliance with environmental regulations.
- **Identifying emergency situations**: DMR EMS is responsible for identifying emergency situations and helping with emergency preparedness and response planning.
- **Monitoring and measurement of HSE Focal Points**: This involves overseeing the monitoring and measurement activities of HSE Focal Points.
- **Evaluation of legal and other requirement compliances**: DMR EMS evaluates compliance with legal and other requirements.

- **Roles and Responsibilities of DMR OHSAS:**
  - **Hazard identification and Risk Assessment Analysis**: DMR OHSAS is responsible for identifying hazards and analyzing risks.
  - **OHSAS objectives monitoring**: This involves monitoring the objectives related to Occupational Health and Safety Assessment Series (OHSAS).
  - **Identifying emergency situation, emergency preparedness and response planning**: The DMR OHSAS helps in identifying emergency situations and planning for emergency preparedness and response.
  - **Corrective Action Request (CAR) follow up**: DMR OHSAS follows up on Corrective Action Requests.
  - **HSE Internal Audits**: DMR OHSAS conducts internal audits related to Health, Safety, and Environment (HSE).

These responsibilities align with **ISO 14001:2015** and **ISO 45001:2018** standards, specifically elements **5.1, 5.3, and 7.1**. Additional information can be found in the **organogram** (SNGPL-MAN-01 Appendix "D") and individual **Job Descriptions**.

1.0 PURPOSE

This procedure defines the method for receiving and responding to:

- Internal Communication / awareness within SNGPL for Occupational Health, Safety and Environment.
- External Communication regarding HSE between SNGPL and external interacted parties, such as stakeholders, regulatory authorities and the public / local community groups.
- Communication with consultants for HSE training, documentation and implementation.
- Consultation and participation of workers at all applicable levels and functions for improvement of the integrated management system.

2.0 SCOPE

2.1. All relevant activities, areas and departments of SNGPL as defined in HSE Manual.

2.2. All employees and components of the public including stakeholders, customers, media & environmental groups, agencies and so on as applicable.

3.0 DEFINITIONS

HSE	Health, Safety, Environment
MRM	Management Review Meeting
OH&S	Occupational Health & Safety
EMS	Environmental Management System

4.0 RESPONSIBILITIES:

4.1 Management Representative (MR)

4.2 General Manger (Regulatory Affairs)

4.3 Incharge (Media Affairs)

4.4 EMS & OHSMS Deputy Management Representatives (DMRs)

4.5 HSE Site Committee

5.0 PROCEDURES

5.1 INTERNAL COMMUNICATIONS /AWARENESS:

Internal Health, Safety and Environment related communications shall be established to ensure interactions at each relevant level and function and among other interested parties to make aware of the following:

5.1.1 The importance of conformance with the SNGPL HSE Policy, procedures and systems and the benefits of improved personal skills & performance.

5.1.2 The potential effects of system non-conformances on employees Health & safety and internal and external environment.

5.1.3 Individual roles and responsibilities in achieving conformance with procedures including emergency preparedness and response.

5.1.4 The significant environmental aspects / impacts, health and safety hazards / risks associated with work activities. All concerned employees (executives, Subordinates / casual) is to be consulted in OHS and Environmental hazard identification and risk assessment.

5.2 Internal health, safety and environment related communication may be accomplished by the use of:

5.2.1 Notice Boards
5.2.2 Sign Boards.
5.2.3 Awareness training of SNGPL personnel, as appropriate in line with job function.
5.2.4 Environmental / Occupational Health & Safety training of relevant job functions, as appropriate (reference procedure).
5.2.5 Newsletter (Pride)
5.2.6 Web Portal
5.2.7 Electronic mails / notes / Interoffice Memo's.
5.2.8 HSE Site Committee meetings.
5.2.9 Management reviews and meeting minutes.
5.2.10 Corrective Action Requests & Incident reporting system.
5.2.11 Suggestion Boxes.

5.3 HSE Site Committee members representing the affected area, in coordination with MR, shall handle communication of OH&S and Environment issues from workers in the form of suggestion to contribute to continual improvement. These communications is to be documented using **Corrective Action procedure (SNGPL-GPR-010)**.

5.4 The General Manager – Regulatory Affairs shall handle communication of changes to legal & other requirements, received from MR, to employees. These communications shall be documented through **Identification, Tracking and control for Regulatory and other Requirements and Evaluation of Compliance (SNGPL-GPR-009)**.

5.5 EXTERNAL COMMUNICATIONS:

5.5.1 External Communications concerning the health, safety and environment aspects of the SNGPL should be directed to the MR or related HSE Site Committee Member.

5.5.2 The MR and Related HSE Site Committee Member is responsible for responding to inquiries from interested parties and regulatory agencies.

5.5.3 The IMS-MR or Related HSE Site Committee Member is responsible for sending current copies of the HSE Policy to interested parties. These requests will be documented on the **External Communication Log (SNGPL-GPR007 -F-001)**.

5.5.4 The Incharge Media Affair in consultation with the MR is responsible for responding to media communications.

5.5.5 External interested parties concerns shall be identified in the form SNGR-002. **Corrective Action procedure (SNGPL-GPR-010)** may be followed where necessary.

5.5.6 The MR or his designee is responsible for determining the need for and preparations of any notification to regulatory agencies on as and when required and forward it to GM-Regulatory Affairs.

5.6 COMMUNICATION WITH CONSULTANTS:

MR shall communicate with the consultants for the guidance needed to document and implement the HSE Management System, and training of the staff at the relevant job functions.

5.6.1 First line executive with support of HSE focal point and sectional head shall impart training to workers giving them confidence to give their inputs for improvement of the OH&S management system including development, planning, implementation and performance evaluation.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1. ISO 14001:2015, Clause 7.4

6.2. ISO 45001:2018, Clause 7.4

7.0 RELATED DOCUMENTATION

7.1. External Communication Log (SNGPL-GPR007 -F-001)

1.0 PURPOSE

The purpose of the procedure is to provide guidelines for reporting and investigation of dangerous occurrences, incidents, fires, environmental incidents and vehicle incidents. It enables identification of the causes and planning of corrective actions to prevent recurrence.

2.0 SCOPE

This procedure is applicable to all personnel, businesses, functional areas and offices throughout SNGPL. This procedure does not replace the requirement of reporting incidents / injuries to the Government under Factories Act or the reporting required for insurance purposes or any other regulation.

Based on the source text, here are some definitions related to Health, Safety, and Environment (HSE) within Sui Northern Gas Pipelines Limited (SNGPL):

- **HSE**: This abbreviation stands for **Health, Safety, and Environment**.
- **HOD**: This abbreviation stands for **Head of Department**.
- **Incident**: An **event that gives rise to an accident or has the potential to lead to an accident**.

Environmental Incident Any spillage, drainage, emission or release of toxic/hazardous material or any other event that could have an adverse effect on the environment.

Near Miss An event which could have resulted in injuries, equipment damage, fire, material loss or an environmental incident.

Vehicle Incident All minor or major accidents involving SNGPL owned vehicles or those contract vehicles which are carrying SNGPL employees for official duty.

Non Lost Workday Injury Minor injury requiring First Aid which does not fall under Lost Workday Injury.

Lost Workday Injury An injury which results in an employee being absent or unable to perform duties of his job for one day following the day of injury on which the employee was scheduled to work.

Fatal Injury An injury that results in death or permanent disability.

Root Cause Basic cause which can be reasonably identified.

Contractor Any non-company employee who is working on SNGPL site

or location/pipeline/equipment/vehicle owned or operated by SNGPL.

4.0 RESPONSIBILITIES:

4.1 Head of Department / General Manager

4.2 HSE Focal Point

4.3 Management Representative (MR)

5.0 PROCEDURE

5.1 All Incidents must be reported within 24 hours using **Incident Reporting & Investigation Form (SNGPL-GPR-008-F-001)**.

5.2 All Vehicle Incidents must be reported within 24 hours using **Vehicle Incident Reporting & Investigation Form (SNGPL-GPR-008-F-002)**.

5.3 Online Incident Reporting System has been established for ensuring smooth and timely reporting of all the incidents. The steps for proceeding is attached as **(SNGPL-GPR-008-Annexure A).**

5.4 All major Incidents resulting in fatality, permanent disability, major fire requiring outside assistance, significant property or equipment damage or substantial emission must immediately be reported to respective HSE Focal point by best available means who in turn will report the incident to the GM (HSE) and / Managing Director.

The same incident must be reported to HSE department within 48 hours, using relevant forms **(SNGPL-GPR-008-F-001)** or **(SNGPL-GPR-008-F-002)**.

5.5 Any incident requiring reporting to the relevant Government agencies shall be reported to the concerned, using their devised system as per Departmental manual.

5.6 In case of any fatality HSE department will respond immediately for investigation purposes.

5.7 In absence of on line system appropriate Form should be filled by the respective first line Executive, reviewed by his supervisor, countersigned by the respective HSE Focal Point and should be sent to HSE department, with a copy to respective GM/HOD.

5.8 HSE department assigns report no to the respective **forms (SNGPL-GPR-008-F- -001) or (SNGPL-GPR-008-F-002)** in the following manner.

INC – HSE- Site Abbreviation– S.No (XXX)- Year

Where INC = Incident, (***In case of Vehicle Incident, use INC-VEH)***
Site Abbreviation e.g for Faisalabad Transmission Abbreviation will be FSD (T)
S.No = Consecutive serial numbers of INC with respect to Site / Dept
For example
INC-HSE-FSD (T)-001-10

5.9 The reporting Executive shall evaluate the incident to identify the Root Cause to the best of his judgment with the participation of workers and the involvement of other relevant interested parties and will give recommendations for the prevention of recurrence.

5.10 HSE Focal Point after approving the recommendations will assign the responsibility of its implementation to the concerned executive/ department.

5.11 HSE Department on receipt of the form and depending upon the severity of the incident, will advise the respective GM and HSE Focal Point, if further investigation is required. Whenever required HSE Engineer will carry out the investigation within 03 days.

5.12 HSE Department will review the recommendations of the Reporting Executive / HSE Focal Point for the prevention of reoccurrence and will send its comments, if any, to the respective HSE Focal Point. It will be the responsibility of the HSE Focal Point to raise CAR against the recommended actions with the hierarchy of controls to ensure follow up for implementation and effectiveness of the corrective actions.

5.13 Results of investigation shall be communicated to relevant workers, and, where they exist, workers' representatives, and other relevant interested parties.

5.14 Respective HSE Focal point and the HSE Department will be responsible to maintain record.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1. ISO 14001:2015, Element 10.2

6.2. ISO 45001:2015, Element 10.2

The source text specifies the related documentation for **Incident Reporting and Investigation** at Sui Northern Gas Pipelines Limited (SNGPL). The following documents are used in the SNGPL's incident management process:

- **Incident Reporting & Investigation Form (SNGPL-GPR-008-F-001)**. This form is used to report all incidents within 24 hours.
- **Vehicle Incident Reporting & Investigation Form (SNGPL-GPR-008-F-002)**. This form is used to report all vehicle incidents within 24 hours.
- **Steps to proceed (On-Line reporting) (SNGPL-GPR-008-Annexure A)**. This document outlines the steps for online incident reporting.

These forms can be accessed through SNGPL's online Incident Reporting System (IRS). Incidents must be reported within 24 hours using the appropriate form. In the absence of the online system, the appropriate form should be filled by the respective first line Executive, reviewed by their supervisor,

countersigned by the respective HSE Focal Point, and sent to the HSE department, with a copy to the respective GM/HOD.

STEPS TO PROCEED

1) Go to http://as-prod.sngpl.com.pk and then click on IRS web Link
   Or paste the link http://as-prod.sngpl.com.pk/forms/frmservlet?config=ims
2) Your email id on Lotus Notes is your User Name and Password is 123456. e.g. Email on Lotus Notes is mirza.waqar@sngpl.com.pk then User Name on Incident Reporting System will be mirza.waqar
3) Please change your password on first login.
4) You will now have access to Incident Reporting form and Vehicle Incident Reporting form.
5) Access the required form and fill in the details.
6) Status is to be kept **"in process"** until report is completed.
7) After completion of the report status should be changed to **"Submit for Approval."** 8) After submitting for approval click the save button on the status bar so that the auto generated reference # is displayed on report.
9) The fields highlighted in yellow are mandatory.
10) The report will be forwarded to Administrator (Who is the focal point of the site) for approval.
11) After approval from the administrator report will be received in the HSE department.

4.0 Responsibilities:

The source text outlines the responsibilities of several key personnel with regards to **Identification, Tracking and Control for Compliance Obligations, Regulatory and other Requirements**.

The individuals include:

- **IMS Management Representative (MR)**: The General Manager (HSE) is nominated by the Management as MR. The MR's responsibilities include, ensuring development and review of Environmental Management System (EMS) and Occupational health and safety (OH &S) Management System.
- **EMS & OHSMS Deputy Management Representatives (DMRs)**: DMR EMS helps identify environmental aspects and their impacts, assists the Management Representative (MR) in setting objectives and monitoring the Management program, and monitors the operational control and regulatory compliance of the EMS. DMR OHSAS is responsible for identifying hazards and analyzing risks, monitoring the objectives related to Occupational Health and Safety Assessment Series (OHSAS), and following up on Corrective Action Requests (CAR).
- **Concerned Departmental Head / HSE Focal Point**: The In-charge of a Site is designated as the HSE Focal Point.
- **General Manager Regulatory Affairs**: Shall handle communication of changes to legal & other requirements, received from MR, to employees.
- **General Manager Law**: Responsible for identification and tracking of laws applicable to SNGPL activities and services in relation to Health, Safety and Environment.

5.0 Procedure:

5.1 Identification, Tracking for Regulation and other Requirements:

5.1.1 Law department is responsible for identification and tracking of laws applicable to SNGPL activities and services in relation with Health, Safety and Environment. Law department is also responsible for evaluating the potential impacts of these laws on the organization and its activities, and services.

5.1.2 Regulatory Affairs (RA) department is responsible for identification and tracking of regulations applicable to SNGPL activities and services in relation with Health, Safety and Environment. RA Department is also responsible for evaluating the potential impacts of these regulations on the organization and its activities, and services.

5.1.3 IMS Procedure, Context of the Organization (SNGPL-GPR-017) is established for identification of needs & expectations, legal and other requirements and Compliance obligations of interested parties.

5.1.4Related departmentsemploy a variety of techniques and information sources to identify and track applicable laws and regulations. These include, but not limited to:

5.1.4.1Information provided by related committee (e.g. OGRA).

5.1.4.2Communications with federal and provincial regulatory agencies.

5.1.4.3Company environmental, occupational health, and safety meetings

5.1.4.4Periodic EMS & OHSMS refresher training.

5.1.4.5MR monitors these information sources on a regular basis to ensure that new issues are identified on a timely basis.

5.1.5Any necessary, "off-site" resources (Such as consultants and attorneys) may be called upon to assist the departments in evaluating applicable laws and regulations or in developing programs in response to applicable laws and regulations. Where off-site recourses are used in this manner, MR of SNGPL will coordinate such efforts with departments.

5.1.6HSE Department in consultation with Law department and Regulatory affairs department will maintain information on applicable laws and regulations (and their potential impacts on SNGPL activities and services) on **List of Applicable Laws & Regulations (SNGPL-GPR009-F001)**. HSE Focal point will send a copy of updated **List of Applicable Laws & Regulations (SNGPL-GPR009-F001)** along with extract of laws & regulations for monitoring purpose to MR.

5.1.7MR maintains copies of significant applicable EMS & OHSMS related laws and regulations received from above said departments on **List of Applicable Laws & Regulations (SNGPL-GPR009-F001)** and updates it as and when required.

5.1.7 If EMS & OHSMS site audit indicate that few more laws and regulations must be tracked and evaluated, then the MR ensures that these activities take place and list is updated.

5.2Evaluation of Compliance:

5.2.1 HSE Focal Point of each site will monitor the key characteristics of Environmental / Occupational Health and Safety related legal and regulatory requirements on six monthly basis on the form namely **Evaluation of compliance with applicable Legal & other requirements(SNGPL-GPR009-F002)** and forward it to HSE department.

5.2.2 EMS DMR & OHSMS DMR will prepare summary on legal and regulatory compliance on Annual basis.

5.2.4Legal and regulatory compliance summary will be discussed in the Management Review in order to update HSE Management Committee on compliance evaluation.

5.2.5If requirement against Related Environmental, Health and Safety legal and regulatory requirements are not met for any one or other, then mitigating actions through **corrective action procedure (SNGPL-GPR-010)** are taken till all the requirements are met.

The source text lists applicable laws, regulations, and circulars relevant to Sui Northern Gas Pipelines Limited (SNGPL), with columns to indicate if they are applicable and when they were last updated at the SNGPL HSE Department, including a space for a signature.

The list includes:

- **Pakistan Environment Protection Act 1997**
- **SRO.339 (1) 2000 Initial Environmental Examination and Environmental Impact assessment regulations 2000**
- **National Environmental Quality Standards August-2000**
- **Factories Act 1934**
- **The West Pakistan Factories Canteen Rules 1959**
- **The West Pakistan Hazardous Occupation Rules 1963**
- **Oil & Gas Regulatory Authority (Technical Standards for Transmission) 2004**
- **Oil & Gas Regulatory Authority (Technical Standards for Distribution) 2004**
- **Oil & Gas Regulatory Authority (Performance Standards) 2004**
- **Oil & Gas Regulatory Authority Ordinance 2000**
- **Gas (Theft, Control and Recovery) ordinance 2014**
- **Petroleum Act 1934**

The source text provides a continuation of the list of applicable laws, regulations, and circulars relevant to Sui Northern Gas Pipelines Limited (SNGPL), including columns to indicate applicability, update dates, and signature spaces.

The list includes:

- **Petroleum Rules 1937**
- **Natural Gas Licensing Rule 2002**
- **Natural Gas Rules 1960**
- **Electricity Act 1910**
- **Electricity Rules 1937**
- **Civil Defense Rules 1951**
- **Explosive Rules 1940**
- **Workmen Compensation Act 2004**
- **Social Security Ordinance 1923**
- **National Environmental policy 1965**
- **National Drinking Water Quality Standards 2008**
- **National CDM Guidelines 2008**
- **SRO.528 (1) 2001 : National Environmental Quality Standard (self Monitoring & by Industry Rules 2001**
- **SRO.339 (1) 2000 PEPA Review of Initial Environmental Examination and Environmental Impact assessment 2000**
- **SRO.693 (1) 2001: Pollution Charge for Industry (Calculation and Collection) Rules,2001**
- **SRO.549 (1) 2000 : Amendments in S.R.O 742 (1) 93 related to NEQS for Liquid Effluents and Emission 2000**
- **SRO.1062 (1) 2010 : NEQS for Ambient Air Quality 2010**
- **SRO.1063 (1) 2010 : NEQS for Drinking Water Quality 2010**
- **SRO.1064 (1) 2010 : NEQS for Noise 2010**
- **Canal & Drainage Act 1873**
- **Explosives Rules 2010, Mineral & Industries Gas Safety Rules 20110 2011**
- **Prohibition of Smoking and protection of Non-Smokers Health Ordinance 2002. 2002**
- **Punjab Environmental Protection (BTS) Regulations / Concerned agency 2012**

The source text continues the list of applicable laws, regulations, and circulars relevant to Sui Northern Gas Pipelines Limited (SNGPL). The list also includes columns to indicate applicability, update dates, and signature spaces. The HSE Focal Point verifies the list.

The laws, regulations and circulars include:

- **Hazardous Occupation Rules 1963**
- **Punjab Food Authority Act- / Concerned agency 2011**
- **Boiler and Pressure Vessels Ordinance 2002**
- **Gas Cylinder Rules 1940**
- **CNG Rules 1992**
- **Civil Defense Special Power Rules - 1951**
- **Explosive Act 1984**
- **Factories Act 1934 / Punjab Factories Rules 1934**
- **Electricity Act 1910 / Electricity Rules 1910**
- **SRO.1013 (1) on Hospital Waste Management 2005**
- **Law of Local Land regarding the Road cut permission (e.g LDA / Lahore Cantonment Board / CDA etc)**

The source text provides information about legal and regulatory requirements, regulator/regulatory agencies, specific requirements such as operational permits and reporting, compliance status, document maintenance, and frequency related to SNGPL operations.

Here's a breakdown:

- **Factories Act-1934**
  - Regulator: PLD (Punjab Labor Department)
  - Section 33-1: Safety of building machinery and manufacturing process
  - Section 33-K: Precaution against dangerous fumes
  - Section 33-L: Explosive or inflammable dust, gas
  - Section 33-N: Notice of certain accidents
- **The Canal & Drainage Act, 1873**
  - Regulator: Irrigation & Drainage Department
  - Section 20 B: Cutting of supply for any land not being irrigated at site
  - Section 55: Power to prohibit obstruction or order their removal
  - Section 56: Power to remove obstruction after prohibition
  - Section 70: Fine of Rs. 200 or max. of three-month imprisonment for corrupting & fouling the water of any canal so as to render it less fit for the purpose for which it is ordinarily used

The source text details additional legal and regulatory requirements applicable to SNGPL (Sui Northern Gas Pipelines Limited), along with the relevant regulatory bodies and specific stipulations. The source text also provides space to record compliance, documentation, and frequency of checks.

Here's a breakdown of the regulations:

- **The Canal & Drainage Act, 1873**
  - Regulator: Irrigation & Drainage Department
  - Section 73: It is an offense to willfully damage or obstruct any canal or drainage or interfere with the supply and flow
- **The Pakistan Penal Code, 1860**
  - Section 268: Public nuisance
  - Section 277: Fouling water of public spring or reservoir
- **Punjab Local Government Ordinance, PLGO 2001, Fourth Schedule, Part-!**
  - Regulator: City District Government
  - Section 3: Discharging any dangerous chemical, inflammable, hazardous or offensive article in any drain, or public water course or public land in such manner as causes or is likely to cause danger to persons passing by or living or working in neighborhood, or risk or injury to properly
  - Section 9: Failure of industrial or commercial concerns to provide adequate and safe disposal of effluent or prevention of their mixing up with the supply sewerage system
  - Section 12: Cultivation of agriculture produce or crop, for supply or sale to public using such manure, or irrigating it with sewer waster or any such liquid as may be injuries to public health or offensive to the neighborhood

The source text details further legal and regulatory requirements applicable to SNGPL, along with the relevant regulatory bodies and specific stipulations. The source text also provides space to record compliance, documentation, and frequency of checks. Here's a breakdown of the regulations:

- **Pakistan Environmental Protection Act 1997**
  - Regulator: Environmental Protection Department
  - Section 11: Prohibition of certain discharges or emissions
    - a) No person shall discharge or emit or allow the discharge or emission of any effluent or waste or air pollutants or noise in an amount, concentration, or level which is in excess of the National Environmental Quality Standards (NEQS)
  - Section 12: Initial environmental examination and environmental impact assessment
    -
      1. No project shall start construction or operation unless he has filed with the Federal Agency an initial environmental examination or where the project is likely to cause an adverse environmental effect, an environmental impact assessment, and has obtained form the federal agency approved in respect thereof.
    -
      3. Every review of an environmental impact assessment shall be carried out with public participation.
  - Section 14: Handling of Hazardous substances subject to the previous of this act, no person shall

The source text provides details regarding legal and regulatory requirements applicable to SNGPL, along with the relevant regulatory bodies and specific stipulations, as well as space to record compliance, documentation, and frequency of checks.

Here's a breakdown of the regulations:

- **Pakistan Environmental Protection Act 1997**
  - Regulator: Environmental Protection Department
  - Section 14: Handling of Hazardous substances
    - No person shall generate, collect, consign, transport, treat, dispose of, store, handle, or import any hazardous substances except under a license issued by the Federal Agency and in such manner as may be prescribed.
  - Section 15: Regulation of motor vehicles
    - No person shall operate a motor vehicle from which air pollution or noise is being emitted in an amount, concentration, or level which is in excess of the National Environmental Quality Standards.
- **Factories Act-1934**
  - Regulator: Punjab Labor Department (PLD)
  - Section 13: Cleanliness
    - Every factory shall be kept clean and free from effluvia arising from any drain, privy, or nuisance.
    - Accumulation of dirt and effuse shall be removed daily by sweeping or by any other effective method from the floors and benches of work-rooms and from staircases and disposed of in a suitable manner.
    - The floor of every work-room shall be cleaned at least once a week by washing, using disinfectant where necessary, or by some other effective method.
- **Pakistan Environmental Protection Act 1997**
  - Regulator: Environmental Protection Department
  - Section 11: Prohibition of certain discharges or emissions
    - No person shall discharge or emit or allow the discharge or emission of any effluent or waste or air pollutants or noise in an amount, concentration or level which is in excess of the National Environmental Quality Standards (NEQS)
  - Section 12: Initial environmental examination and environmental impact assessment
    - No project shall start construction or operation unless he has filed with the Federal Agency an initial Environmental examination or where the project is likely to cause an adverse environmental effect, an environmental impact assessment, and has obtained form the federal agency approved in respect thereof.
    - Every review of an environmental impact assessment shall be carried out with public participation.

The source text outlines more legal and regulatory requirements for SNGPL, along with the relevant regulatory bodies and specific stipulations, and space to record compliance, documentation, and frequency of checks. Here's a breakdown of the regulations:

- **Factories Act-1934**
  - Regulator: Punjab Labor Department (PLD)
  - Section 13: Cleanliness
    - Every factory must be kept clean and free from effluvia arising from any drain, privy, or nuisance.
    - Accumulation of dirt and effuse must be removed daily by sweeping or another effective method from the floors and benches of work-rooms and from staircases and disposed of suitably.
    - The floor of every work-room must be cleaned at least once a week by washing, using disinfectant where necessary, or by some other effective method.
    - Where the floor is liable to become wet during manufacturing, drainage must be provided and maintained.
  - Section 14: Disposal of wastes and effluents
    - Effective arrangements must be made in every factory for the disposal of wastes and effluents due to the manufacturing process carried on therein.
  - Section 15: Ventilation & Temperature
  - Section 16: Dust and fume
    - In every factory where the manufacturing process gives off dust, fume, or another impurity likely to be injuries or offensive to workers, effective measures must be taken to prevent its accumulation in any work-room and its inhalation by workers.
    - If an exhaust appliance is necessary, it must be applied as near as possible to the origin of the dust, fume, or other impurity, and such point shall be enclosed as far as possible.
- **Pakistan Environmental Protection Act 1997**
  - Regulator: Environmental Protection Department
  - Section 14: Handling of Hazardous substances
    - No person shall generate, collect, consign, transport, treat, dispose of, store, handle, or import any hazardous substances except under a license issued by the Federal Agency and in such manner as may be prescribed.
  - Section 15: Regulation of motor vehicles
    - No person shall operate a motor vehicle from which air pollution or noise is being emitted in an amount, concentration, or level which is in excess of the National Environmental Quality Standards.
- **Pakistan Environmental Protection Act 1997**
  - Regulator: Environmental Protection Department
  - Section 11: Prohibition of certain discharges or emissions
    - No person shall discharge or emit or allow the discharge or emission of any effluent or waste or air pollutants or noise in an amount, concentration or level which is in excess of the National Environmental Quality Standards (NEQS)
  - Section 12: Initial environmental examination and environmental impact assessment

- No project shall start construction or operation unless he has filed with the Federal Agency an initial Environmental examination or where the project is likely to cause an adverse environmental effect, an environmental impact assessment, and has obtained form the federal agency approved in respect thereof.
- Every review of an environmental impact assessment shall be carried out with public participation.

The source text provides more legal and regulatory requirements for SNGPL, along with the relevant regulatory bodies and specific stipulations, and space to record compliance, documentation, and frequency of checks:

- **Factories Act-1934**
  - Regulator: Punjab Labor Department (PLD)
  - Section 13: Cleanliness
    - Every factory must be kept clean and free from effluvia arising from any drain, privy, or nuisance.
    - Accumulation of dirt and effuse must be removed daily by sweeping or another effective method from the floors and benches of work-rooms and from staircases and disposed of suitably.
    - The floor of every work-room must be cleaned at least once a week by washing, using disinfectant where necessary, or by some other effective method.
    - Where the floor is liable to become wet during manufacturing, drainage must be provided and maintained.
  - Section 14: Disposal of wastes and effluents
    - Effective arrangements must be made in every factory for the disposal of wastes and effluents due to the manufacturing process carried on therein.
  - Section 15: Ventilation & Temperature
  - Section 16: Dust and fume
    - In every factory where the manufacturing process gives off dust, fume, or another impurity likely to be injuries or offensive to workers, effective measures must be taken to prevent its accumulation in any work-room and its inhalation by workers.
    - If an exhaust appliance is necessary, it must be applied as near as possible to the origin of the dust, fume, or other impurity, and such point shall be enclosed as far as possible.
    - **No stationary internal combustion engine shall be operated unless the exhaust is conducted into open air and exhaust pipes are insulated to prevent scalding and radiation heat**.
    - **No internal combustion engine shall be operated in any room unless effective measures have been taken to prevent such accumulation of fumes there from as are likely to be injuries to the workers employed in the work-room**.
  - Section 18: Overcrowding
  - Section 19: Lighting
  - Section 20: Drinking Water
  - Section 21: Latrines and Urinals
  - Section 23: Precautions against contagious diseases.
  - Section 25: Precautions in case of fire
    - Every factory shall be provided with such means of escape in case of fire as may be prescribed.
- **Pakistan Environmental Protection Act 1997**
  - Regulator: Environmental Protection Department
  - Section 14: Handling of Hazardous substances
    - No person shall generate, collect, consign, transport, treat, dispose of, store, handle, or import any hazardous substances except under a license issued by the Federal Agency and in such manner as may be prescribed.
  - Section 15: Regulation of motor vehicles

        - No person shall operate a motor vehicle from which air pollution or noise is being emitted in an amount, concentration, or level which is in excess of the National Environmental Quality Standards.
- **Pakistan Environmental Protection Act 1997**
    - Regulator: Environmental Protection Department
    - Section 11: Prohibition of certain discharges or emissions
        - No person shall discharge or emit or allow the discharge or emission of any effluent or waste or air pollutants or noise in an amount, concentration or level which is in excess of the National Environmental Quality Standards (NEQS)
    - Section 12: Initial environmental examination and environmental impact assessment
        - No project shall start construction or operation unless they have filed with the Federal Agency an initial Environmental examination or where the project is likely to cause an adverse environmental effect, an environmental impact assessment, and has obtained form the federal agency approved in respect thereof.
        - Every review of an environmental impact assessment shall be carried out with public participation.

The source text details more requirements related to fire safety and means of escape in factories, as mandated by the Factories Act of 1934.

Key points include:

- Every factory must have prescribed means of escape in case of fire.
- If an inspector finds that a factory lacks the prescribed fire escape measures, they can order the manager to implement specific measures by a set date.
- Factory doors must not be locked or fastened in a way that prevents easy and immediate opening from the inside while anyone is in the room. Doors should open outwards or towards the nearest exit, and must not be obstructed during work hours.
- **Fire exits** that are not for ordinary use must be clearly marked in a language understood by most workers, or with effective and easily understood signs.
- Factories must have effective and clearly audible means of giving warning in case of fire to every person employed.
- A free passageway to each fire escape must be maintained for all workers in every room of the factory.
- In factories with more than ten workers above the ground floor, or where explosive or highly inflammable materials are used or stored, effective measures must be taken to ensure all workers are familiar with fire escape routes and trained in the routine to be followed in such cases.

The following regulations pertain to factories:

- **Section 25 outlines precautions against fire**: Every factory shall be provided with such means of escape in case of fire as may be prescribed.
- If it appears to the inspector that any factory is not provided with the means of escape prescribed under sub-section (!) he may serve on the manager or the factory an order in writing specifying the measures which should be adopted before a date specified in the order.
- In every factory the doors any room shall not be locked or fastened so that they can be easily and immediately opened from inside while any person is within the room, and all such doors unless they are of the sliding type, shall be constructed to open outwardly or where the door is between two room, in the direction or the nearest exit from the building and such door shall not be locked or obstructed while work is being carried on in the room and shall at all times be kept free from any obstruction.
- In every factory every window, door or other exits affording means of in case of fire, other than means of exit in ordinary use, shall be distinctively marked in a language understood by the majority of the workers or adequate size or by some other effective and clearly understood sign.
- In every factory there shall be provided effective and clearly audible means of giving warning in case of fire to every person employed.
- A free passageway giving access to each means of escape in case of fire shall be maintained for the use of all workers in every room of the factory.
- In every factory wherein more than then workers ordinary employed in any place above the ground floor, or explosive or highly inflammable material are used or stored, effective measures shall be taken to insure that all the workers are familiar with the means of escape in case of fire and have been adequately trained in the routine to be followed in such case.
- **Section 27 concerns work on or near machinery**.
- **Section 28 addresses the employment of young labor near machinery**.

The Factories Act of 1934, enforced by the Punjab Labor Department (PLD), includes the following sections:

- **Section 28** addresses the employment of young labor near machinery.
- **Section 29** concerns striking gear and devices for cutting off power.
- **Section 30** relates to self-acting machines.
- **Section 31** covers the casing of new machines:
    - In all machinery driven by power and installed in any factory after the commencement of the Labor Laws (Amendment) Ordinance 1972 (a0 every set screw, belt or key on any revolving shaft, spindle, wheel or pinion shall be son sunk, encased, or otherwise effectively guarded as to prevent danger.
- **Section 33 A** addresses Hoist & Lifts (C):
    - Every hoist way and lift way shall be sufficiently protected by an enclosure fitted with gates.
- **Section 33-E** pertains to pits, sumps, opening in floors.
- **Section 33-D** concerns floors, stairs, and means of access.
- **Section 33-F** relates to excessive weights.

The Factories Act includes regulations enforced by the Punjab Labor Department (PLD) pertaining to:

- **Factories Act-1934**:
  - **Section 33-G**: Protection of eyes.
  - **Section 33-H**: Powers to require specifications of defective parts or test of stability.
- **Factories Act-1978**:
  - **Section 26, 31 and 33-J para 61 (1) Fencing**: In every factory, all electrical circuits or part of such circuits any object electrically connected with then whether commonly or occasionally in an electrified condition, which by reason of their position could cause injury to any person, shall be protected adequately, either by non-metallic fencing or insulation or by both, in manner as to remove danger of injury.
  - **Section 25, 51 (1) Precaution against fire**: Every factory shall be provided with (b) buckets and chemical fire extinguisher at the following scale (i) bucket for floor space up to 6,000 square feet six bucket, for every 1,000 square feet of floor or a part thereof one additional bucket in excess of the first 6,000 feet, The buckets shall be painted red and kept permanently filled with water or sand.
  - **Section 21 para – 42 A (1)**: The factory should provide one wash basin for every twenty workers and soap & towels shall be provided at every wash basins for worker use.

1.0 PURPOSE

This procedure defines the responsibilities and process for identifying and investigating non-compliances with the SNGPL Integrated Management System, for taking action to mitigate any negative impacts caused, and for applying corrective actions.

2.0 SCOPE

All section and departments of SNGPL as defined in IMS Manual.

Here is the conversion of the provided table into a paragraph format:

Definitions: HSE stands for Health, Safety, Environment. CAR refers to Corrective Action Request. Non-Conformance / Non-compliance means non-fulfillment of defined requirements. Corrective Action is the action to eliminate the cause of detected non-conformity.

Responsibilities: The Management Representative (MR) holds responsibility. The Concerned DMR is responsible. The Concerned Focal Point is responsible. All individuals or groups have responsibilities.

Procedures: Where non-conformance is identified or a suggestion is raised for improvement by any individual or group, the identifier shall raise **Corrective Action Request (SNGPL-GPR010-F001)** and send it to MR /GM (HSE).

5.2 MR / GM (HSE) shall send **Corrective Action Request (SNGPL-GPR010-F001)** to concerned DMR for his recommendations. After recommendations, DMR shall forward it to MR for Approval.

5.3 If the raised Non-conformance (NC) is approved by MR, he records that Non-conformance into **Corrective Action Control (SNGPL-GPR010-F-002)** form.

5.4 MR /GM (HSE) will then send the **Corrective Action Control (SNGPL-GPR010-F-002)** to the Focal Point.

5.5 Focal Point will nominate the appropriate person to take the necessary actions to rectify the said Non-conformance (NC).

5.6 Focal Point will nominate appropriate person preferably a trained internal auditor for detailed investigation, root cause analysis and to suggest corrective action based on hierarchy on controls i.e. eliminating hazard,

substituting with less hazardous material, redesigning or modifying equipment or tools, developing procedures, improving the competence of affected workers, changing the frequency of use and using personal protective equipment along with target date within a period of maximum 02 months. One time extension of upto 01 month may be requested by HSE Focal point with justification from MR in case; the time limit exceeds to implement the correction action. Thereafter, CAR shall be converted to OHS/EMS Objective by HSE Focal point as per requirements of the respective IMS Procedure.

5.7 Focal Pointthen send the **Corrective Action Control (SNGPL-GPR010-F-002)** to MR /GM (HSE) for follow-up and shall execute and implement the committed corrective actions.

5.8 MR will nominate HSE Engineer for verification and close out.

5.9 MR shall maintain records of CAR and Non-Conformance / Non-Compliance in **CAR Log Sheet(SNGPL-GPR010-F-003)**.

5.10 EXTERNAL COMPLAINT/SUGGESTION:

5.10.1 MR is designated to receive all suggestions or complaints from external party / Customer / surrounding community / stakeholders / regulatory & compliance bodies about Environment, Safety and Health and raises **Corrective Action Request Control (SNGPL-GPR010-F001).**

5.10.2 **Corrective Action Request Control (SNGPL-GPR010-F001)** form is submitted to the concerned / HSE Focal point and follows 5.4 to 5.8.

5.10.3 After CAR Closing, MR shall intimate to interested party about the corrective measures taken as per procedure **internal / External Communication and consultation (SNGPL-GPR-007).**

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1. ISO 14001:2015, Element 10.1

6.2. ISO 45001:2018, Element 10.1

The related documentation consists of:

- **Corrective Action Request** (SNGPL-GPR010-F-001).
- **Corrective Action Control** (SNGPL-GPR010-F-002).
- **CAR Log Sheet** (SNGPL-GPR010-F-003).

1.0 purpose

This procedure defines the mechanism for;

- Monitoring and measurement of significant environmental aspects, impacts.
- OH&S hazards / risks associated with the SNGPL activities.
- Accident / Incident / Near miss reporting statistics
- Calibration and maintenance of monitoring Devices

2.0 SCOPE

2.1. All sites / departments of SNGPL as defined in IMS Manual

3.0 RESPONSIBILITIES:

3.1 Management Representative (MR)

3.2 Concerned Head of Department

3.3 EMS & OHSMS Deputy Management Representatives (DMRs)

4.0 PROCEDURES

4.1 The monitoring and measurement of key characteristics and environmental, health and safety performance associated with significant aspects, impacts / hazards, risks will be specified in EMS and OH&S Management Programs under the procedures **EMS Aspects & Impacts Identification, Setting of Objectives & Targets and Management Programs(SNGPL-EPR-001)** and **OH&S Risk Assessment, Objectives & Targets and Management Programs (SNGPL-HPR-001).**

4.2 Focal points will forward **HSE self-performance monitoring Report(SNGPL-GPR011-F-001)** on Quarterly basis to HSE department. This report covers key characteristics of Environmental, Occupational Health and Safety management system elements. This **HSE self-performance monitoring Report(SNGPL-GPR011-F-001)** will be evaluated by internal auditors during internal audit process. Further Assessment of HSE Focal points will be carried out annually on the basis of **HSE self-performance monitoring Report.**

4.3 Overall scoring percentage would be lessened to a lower level of performance in case of serious accidents like fatality, permanent disability/fracture, repeated LWDIs, serious environmental incident, repeated incidents of the same kind. HSE department will carry out quantitative and qualitative analysis of such incidents.

4.4 The monitoring and measurement of conformance to specified health, safety and environment objectives and targets will be accomplished through the internal system audit as specified in Procedureof **Internal Audit (SNGPL-GPR-004)**

and through the initiation of Corrective Action Requests, as specified in Procedure of **Corrective Actions (SNGPL-GPR-010).**

4.5 Operational controls will be monitored and measured as indicated in Common Procedures for **Noise Monitoring**, **Effluent Monitoring and Gaseous Emission Monitoring (SNGPL-EPR-002)**.

4.6 The methods, frequencies and responsible parties for completing the monitoring and measuring activities will be specified in environmental, health and safety management programs and Standard Operating Procedures.

4.7 Relevant areas and departments shall ensure that monitoring and measuring devices used for monitoring and measurement of processes and HSE are calibrated (internally or externally) and maintained at a frequency consistent with manufacturer's recommendations.

4.8 Upon receipt of master calibrated device or new measuring device, Related Department's representative shall verify the calibration certificate and status of device

4.9 All users of measuring Devices should ensure that the equipment is being properly used and kept in a good working condition and is in calibration state.

4.10 Any non-conformance found in measuring device should be reported to HSE / instrumentation Department for immediate action.

4.11 All in house calibration will be performed only with valid master calibrator whose calibration is traceable to national / international standard.

4.12 If measuring & test equipment does not need calibration, then maintenance department representative pastes a sticker of "CNR" on equipment.

4.13 Relevant Department shall maintain internal calibration records as necessary to prove conformance.

5.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

5.1 ISO 14001:2015, Clause 9.1.1

5.2 ISO 45001:2018, Clause 9.1.1

The related documentation includes the **HSE self-performance monitoring Report** (SNGPL-GPR011-F-001).

The data from the provided table, found within the HSE Self Performance Measuring and Monitoring Report (SNGPL-GPR011-F-001), is as follows:

- **1.4 What new Environmental aspects have been identified in the past quarter? (What controls were applied to reduce the impacts):**
  - New Aspects: 1. 2. 3. 4. 5.
  - Weight: 2
- **1.5 Context of the organization:**
  - Needs & Expectations, Compliance Obligations, Legal requirements, and other requirements: Last Reviewed On, Next Due Date
  - Weight: 2
  - Internal issues & risks and opportunities: Last Reviewed On, Next Due Date
  - Weight: 2
  - External issues & risks and opportunities: Last Reviewed On, Next Due Date
  - Weight: 2
- **1.6 Site Specific OHS Objectives & Targets (Give Statements or any Reference) Any New Objective identified during the Quarter? (Give Statement and any Reference):**
  - 1. 2. 3. 4.
  - Weight: 1.

Based on the provided HSE Self Performance Measuring and Monitoring Report (SNGPL-GPR011-F-001):

- **1.7 The extent to which OHS Objectives and targets were achieved:**
  - **(give completion %age)**. Objective Planning form SNGPL-HPR001-F-005, should be attached.
  - Weight: 1
- **1.8 Site-Specific EMS Objectives & Targets**
  - (Give Statements or any Reference) Any New Objective identified during the Quarter? (Give Statement and any Reference)
  - 1. 2. 3. 4.
  - Weight: 1
- **1.9 The extent to which EMS Objectives and targets were achieved**
  - **(give completion %age)**. (Objective Planning form SNGPL-HPR001-F-005, should be attached)
  - 1. 2. 3. 4.
  - Weight: 1

1.0 PURPOSE

This procedure defines the framework for preparing and responding to emergencies involving potential EMS & OHSAS related incidents / accidents at SNGPL.

2.0 SCOPE

All relevant activities, area and department of SNGPL as defined in HSE Manual.

3.0 DEFINITIONS

HSE	Health, Safety, Environment
HSC	HSE Site Committee
OH&S	Occupational Health & Safety
EMS	Environmental Management System

4.0 RESPONSIBILITIES:

4.1 HSE Focal Point

4.2 Management Representative (MR)

4.3 EMS & OHSAS Deputy Management Representatives (DMRs)

4.4 HSE Site Committee (HSC)

5.0 PROCEDURE:

5.1 IDENTIFICATION OF EMERGENCY SITUTATION:

5.1.1 Potential environmental, health & safety incidents and emergencies likely to occur at the facility shall be identified on yearly basis by HSC and documented according to **EMS Aspects & Impacts Identification** and **OH&S Hazards Identification and Risks Assessment(SNGPL-HPR-001)** as per Emergency Response and Planning requirements.

5.1.2Methods to respond to, mitigate and prevent all environmental, health and safety emergencies shall be established and maintained at each site of SNGPL and shall be communicated to HSE department by the HSE Focal Point.

5.1.3HSE Department is responsible to facilitate / guide all sites for developing and implementing the “Emergency Response Plan”.

5.1.4Roles and responsibilities for communications within the facility and for obtaining outside support services shall be established and maintained at each site via the Emergency Response Plan.

5.1.5Environmental, health and safety emergency methods and communications will be tested **at least bi-annually**. The HSE Site Committee shall prepare report and maintain records of these drills. Methods to respond to, mitigate and prevent environmental, health & safety emergencies shall be amended as required based on the results of these tests.

5.1.6Subsequent to environmental health & safety emergency, the cause of the emergency and corresponding emergency methods shall be reviewed. Corrective / Preventive actions will be identified and undertaken by implementing **Corrective Action (SNGPL-GPR-010)** procedure. Methods to respond to, mitigate and prevent releases that arise as a consequence of an environmental, health and safety emergency shall be amended as required and notified by MR.

5.1.7Where applicable regulatory agencies shall be notified by HSC assisted by HSE Department, of environmental, health and safety incidents consistent with procedure for **Internal / External Communication and Consultation (SNGPL-GPR-007)**.

5.2 EMERGENCY PLANS:

5.2.1Focal point shall identify **Emergency Response Plans** to meet / control when specified emergency situation arises. Emergency situation may be of any one or combination of two or more of the following:

5.2.1.1 Flood / Territorial Rains / Typhoons or Cyclone.
5.2.1.2 Terrorist Attacks / Bomb Threat
5.2.1.3 Fire
5.2.1.4 Earth Quake.
5.2.1.5 Oil Leakage / Spills.
5.2.1.6 Chemical Leakage / Spills.
5.2.1.7 Gas leakage Emergencies.
5.2.1.8 Flammable / toxic gas release.

5.2.2**Emergency response plan** and relevant procedures shall provide relevant information, procedural steps and responsibilities to combat the emergency situations and covers the following:

5.2.2.1 Identification of persons to take charge in case of emergency. 5.2.2.2 Details of actions taken by personnel during an emergency including those actions to be taken by external personnel who are on the site of emergency, such as contractors and visitors.
5.2.2.3 Responsibilities, authorities and duties of personnel with specific roles during the emergency, such as wardens, fire fighters, first aid staff, toxic spillage specialist (if needed) etc.

5.2.2.4 Evacuation procedures and plans.

5.2.2.5 Interface with external emergency services, such as fire station, Bomb disposal squad, Mutual Aid Emergency Response Plan (MAERP) between other companies etc.

5.2.2.6 Identification and location of hazardous materials and emergency actions required.

5.2.2.7 Communications with statutory bodies.

Communications with neighbors and public. 5.2.2.8

5.2.2.9 Protection of vital records and equipment.

5.2.2.10 Availability of necessary information during the emergency such as plant layout drawings, hazardous materials data, relevant procedures, standard work practices and emergency contact phone numbers etc.

5.2.2.11 Involvement of external agencies in emergency planning and response.

5.2.2.12 Emergency Response Plans should be reviewed by HSE Focal point on **annual basis**.

5.3EMERGENCY RESPONSE TEAMS:

Emergency Response Teams with their responsibilities are listed and they should be formed and remain available with their back up in case of emergency. On declaration of emergency, these Emergency Response teams will come into action immediately.

5.3.1 Incident Management Team (IMT).

Incident Management Team will be led by the HSE Focal Points and shall provide overall supervision and coordination for control of all emergencies.

IMT Shall:

- Provide support and adequate back up resource for emergency response organization.
- Report at the meeting point immediately on declaration of emergency and shall move to the incident site (if required and safe).
- Coordinate closely with Site Fire Fighting / First Aid Teams.
- Coordinate with local authorities / fire brigade / hospitals etc
- Preserve human life as far as possible without endangering the members of the team.
- Collect and provide (if required) information of injuries, fatalities and damages.
- Declare emergency clearance after completion of Emergency Response.

Team Leader: HSE Focal Points.

Members: All Sectional Heads, Admin Officer, Telecom representative for communications.

5.3.2 Fire Fighting Team (FFT)

Office staff or the personnel present in the office round the clock (shift duties) will preferably be the members of the Fire Fighting Team. They will

be responsible for immediate response to the emergency situation and shall assist IMT.

Fire fighting team (FFT) leaders / members should meet following criteria;

- Medically fit (Preferably not obese)
- Age below 45 years
  (Team leaders above 45 years of age may be nominated as a special case keeping in view their experience)
- Basic fire fighting training

Responsibility of Fire Fighting Team (FFT) includes:

- To check out the "Area of concern" and report back with findings immediately to IMT.
- Provide prompt initial response to control the emergency by using the available resources.
- Remain on site to meet the "IMT" and apprise them of the situation and provide assistance to "IMT" team leader.
- If required put on fire suits and breathing apparatus sets (if available).
- If the situation requires evacuation then assist in evacuation.

'Meeting Point' of Fire Fighting Team (FFT) should be defined in the site Emergency Response Plan.

Fire Fighting Team (FFT) of site should be documented as per format (**SNGPL-GPR012- Annexure-A)**.

Awareness regarding basic Fire Fighting should be imparted to Company Executives and Staff (Office / field) on regular basis by HSE department.

5.3.3 Medical Aid / First Aid Team

Medical Aid / First Aid Team shall be responsible to coordinate with IMT for first aid and emergency medical evacuation.

Medical Aid / First Aid team is to be led by a person trained in first aid shall provide first aid to the injured. If a doctor is deputed at any site then he will lead the first aid team.

Medical Aid / First Aid team will report at dispensary (if available) or at the meeting point as defined in Emergency Response Plan.

Medical Aid / First Aid Team of site should be documented as per format (**SNGPL-GPR012- Annexure-B)**.

Awareness regarding basic First Aid should be imparted to Company Executives and Staff (Office / field) on regular basis by HSE department.

5.4EMERGENCY COMBAT EQUIPMENT:

5.4.1HSE Department / HSE Focal Point shall identify emergency combat equipment. The lists of these equipments are prepared and maintained by HSC.

5.4.2HSE Focal Point shall ensure availability and operatability of emergency combat equipment at respective sites through tests / inspections at specified intervals. HSE focal point shall also ensure that appropriate records are maintained by related department.

5.4.3Emergency combat equipment includes but not limited to:

5.4.3.1 Alarm System
5.4.3.2 Emergency Lighting
5.4.3.3 Emergency Power Supply
5.4.3.4 Equipment for escape and safe refuge
5.4.3.5 Fire Fighting Equipment
5.4.3.6 First Aid Equipment
5.4.3.7 Emergency Communication Equipment and Facilities etc.

5.5 SCHEDULED / MOCK DRILLS:

5.5.1Scheduled Evacuation / Fire / First Aid Drills shall be conducted bi-annually according to respective plans. In plans, where required, participation of external agencies to be ensured.

5.5.2Evacuation Drill detail shall be documented on standard format **(SNGPL-GPR012-Annexure-C)** and to be communicated to HSE department for review.

5.5.3Emergency contact numbers list should be maintained on standard format (**SNGPL-GPR012- Annexure-D)**

5.5.4List of wardens should be maintained on standard format (**SNGPL-GPR012-Annexure-E).** Wardens should be medically fit and preferably below 45 years of age.

6.0 FIRE FIGHTING EQUIPMENTS:

HSE Focal Point is overall responsible that all fire fighting equipments (fire extinguishers, hydrant system, fire truck etc) are kept in good working conditions at all times through regular inspections / maintenance.

Admin department is responsible for inspection, maintenance and record keeping of all fire fighting equipments, however HSE Focal Point may nominate other department for inspection / maintenance where deemed necessary.

HSE department will monitor and provide necessary guidance / training.

6.1Fire Hydrant Equipments

Inspection shall be carried out on monthly basis and record should be maintained on **Fire Hydrant System Inspection Checklist** (**SNGPL-GPR012-F001**) by inspection team nominated by HSE Focal Point.

6.2 Fire Extinguishers:

6.2.1Portable Fire Extinguishers shall be installed in such manner that its top is **not more than 5 feet** above the floor. (Fire Extinguisher top 4.5 feet above floor is suggested).

6.2.2Inspection, re-filing, hydrostatic testing and maintenance of Fire Extinguishers shall be arranged by Admin / Maintenance / Civil department as per NFPA 10 standard.

6.2.3All Fire Extinguishers shall be inspected in-house on monthly basis and record shall be kept on **Fire Extinguishers Inspection checklist** (**SNGPL-GPR-012-F002**).

6.2.4Fire extinguishers Tag (**SNGPL-GPR012-Annexure-F**) shall be attached to fire extinguisher and updated on monthly basis.

6.2.5Maintenance / inspection of all Fire Extinguishers is required to be arranged from third party on **annual basis** or when indicated during in-house inspection. Third party name and date of maintenance / inspection should be pasted on each Fire extinguisher.

6.2.6All rechargeable Fire Extinguisher shall be hydrostatically tested from Third party as per following frequency;

According to the document "Identifying Emergency Situation, Emergency Preparedness and Response," the hydrostatic testing frequency for rechargeable fire extinguishers from a third party is as follows:

- **Water Type (Stored Pressure): 5 years**
- **AFFF (Aqueous Film Forming Foam): 5 years**
- **CO2 (Carbon dioxide): 5 years**
- **Wet Chemical: 5 years**
- **DCP with stainless steel shell: 5 years**
- **DCP with mild steel shell: 12 years**
- **Halogenated agents: 12 years**

6.2.7In no case fire extinguisher shall be recharged if it is beyond its specified hydrostatic test date.

6.2.8Procurement process for Fire extinguisher re-filling, maintenance or hydrostatic testing should be initiated **immediately (within 3 days after inspection) by Admin department** as per Company Policy / procedure.

6.2.9Empty / faulty fire extinguishers should be immediately replaced with operational fire extinguishers kept in store; in order to ensure adequate fire fighting arrangements at all times.

6.2.10All fire fighting equipments shall be scrapped / disposed off by respective indenting department as per Company policy / procedure after the end of their useful life as per NFPA code or if recommended during inspection. (Damaged Fire extinguishers before the end of their useful life may be scraped / disposed off if they are not re-useable).

7.0 SMOKE DETECTION EQUIPMENTS;

HSE Focal Point is overall responsible that all smoke detection equipments are kept in good working conditions at all times through regular inspections / maintenance.

Admin department is responsible for inspection, maintenance and record keeping of all smoke detection equipments, however HSE Focal Point may nominate other department for inspection / maintenance where deemed necessary.

HSE department will monitor and provide necessary guidance / training.

7.1 Smoke Detection and Fire Alarm Systems;

7.1.1 Inspection of overall smoke detection and fire alarm system will be carried out on **monthly** basis by inspection team nominated by respective HSE Focal Point.

7.1.2 Inspection team will document inspection findings on "**Smoke Detection and Fire Alarm System Inspection Checklist" (SNGPL-GPR-012-F003).**

7.1.3 Smoke system's "Control Panel" is to be checked **preferably on daily basis** by Inspection team member for observing system trouble / fault (if any) which should be addressed promptly.

7.2 Smoke Detectors (Stand Alone);

Smoke detectors (stand alone) must be inspected on **monthly basis** by Admin department representative or person nominated by HSE Focal Point. Inspection record should be maintained on **Smoke Detectors (Stand Alone) Inspection Checklist** (**SNGPL-GPR-012-F004**).

8.0 PROCUREMENT OF FIRE DETECTION / FIGHTING EQUIPMENTS:

8.1 HSE department shall procure fire detection and fighting equipments on annual basis as per Sites requirements / budgetary provisions. Other department may procure fire fighting / detection equipments after acquiring necessary Management approval under intimation to HSE department.

8.2 HSE Focal point shall arrange assessment of all fire fighting / detection equipments of respective site(s) as per NFPA / EN standards.

8.3 HSE Focal Point shall communicate status / requirements of fire detection / fighting equipments to HSE department on standard formats, **"Status of Fire Extinguishers (SNGPL-GPR012-F005) and "Status of Fire hydrant system / Smoke detection system (SNGPL-GPR012-F006)** at the start of every fiscal year.

9 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

9.1 ISO 14001:2015, Clause 8.2
9.2 ISO 45001:2018, Clause 8.2

10.0 RELATED DOCUMENTATION

Related Sites Emergency Response Plan	
Fire Hydrant System Inspection Checklist	(SNGPL-GPR-012-F001)
Fire Extinguisher Inspection Checklist	(SNGPL-GPR-012-F002)

Smoke Detection and Fire Alarm System Inspection Checklist (SNGPL-GPR-012-F003)
Smoke Detectors (Stand Alone) Inspection Checklist (SNGPL-GPR-012-F004) Status of Fire Extinguishers (SNGPL-GPR-012-F005) Status of Fire hydrants system / Smoke detection system (SNGPL-GPR-012-F006)

Fire Fighting Team	(SNGPL-GPR-012- Annexure-A)
Medical Aid / First Aid Team	(SNGPL-GPR-012- Annexure-B)
Evacuation Drill Details	(SNGPL-GPR-012- Annexure-C)
Emergency Contact Numbers	(SNGPL-GPR-012- Annexure-D)
List of Wardens	(SNGPL-GPR-012- Annexure-E)
Fire Extinguisher Tag	(SNGPL-GPR-012- Annexure-F)

1.0 PURPOSE

This procedure defines the method for controlling the EMS aspects and OH&S hazards related to contractors, their sub-contractors, outsourced functions and procurement in SNGPL.

2.0 SCOPE

All areas and departments carrying out procurement, authorizing contractors, outsourced functions to work on-site excluding contractors & outsourced functions providing clerical, accounting or other similar administrative services.

3.0 DEFINITIONS

IMS:	Integrated Management System based on EMS and OHSAS Standards
EMS	Environmental Management System
OH&S:	Occupational Health & Safety
HSE	Health Safety & Environment

4.0 RESPONSIBILITIES

4.1 All Related Focal Points / HODs

4.2 Contract Initiating Department

4.3 Contractor

5.0 PROCEDURE

5.1 The need for contractor services, outsource functions is identified and a request for **Contractor HSE Statement (SNGPL-GPR013-F-001)** shall be enclosed with tender documents by the initiating department. The initiating department would be responsible to get the **Contractor HSE Statement (SNGPL-GPR013-F-001)** filled by the contractor.

5.2 Information related to contractor on-site activities should be documented by the contractor in Contractor HSE Statement (SNGPL-GPR013-F-001).

5.3 Completed **Contractor HSE Statement (SNGPL-GPR013-F-001)** will be checked / maintained by initiating department to identify potential Environmental,

Occupational Health and Safety issues. The initiating department will send copy to concerned HSE Executive with comments if any.

5.4 The indenting / procurement department shall seek information from vendor / supplier (if required / applicable) regarding OH&S and environmental conditions pertaining to machinery / equipment / product / material / item being procured or services being hired.

5.5 Prior to on-site work, contractors shall:

5.5.1 Be provided with Contractor HSE Manual (both English & Urdu languages) by respective focal point or his designate to ensure their awareness of the SNGPL HSE Management System. Receiving / acknowledgement record of Contractor HSE Manual will be kept by initiating department.

5.5.2 Submit a completed **Contractor HSE Statement (SNGPL-GPR013-F- 001)** to the respective focal point or his designate.

5.6 TRAINING AND AWARENESS OF CONTRACT MANPOWER:

5.6.1 Prior to start of work on site the initiator or nominee shall interview the contractor site Engineer / Supervisor / Workerfor awareness and compliance for HSE requirements communicated vide contractor HSE Manual.

5.6.2 For major jobs (re-vamps, expansion project), it is ensured by concerned department that all contractors engineers / supervisors shall be trained before commencement of job / program. Same is applicable for technical / skilled workers.

5.6.3 Training record of contractor's employees can be verified by related Department and HSE department.

5.7 While on-site contractors shall conform to the SNGPL, HSE Management System and all applicable legal requirements. In case of non- compliance, following management approved penalties will be imposed;

a) Minimum level of age/experience/skill of contactor's staff/labor should be checked by our first line Executive and HSE Engineer against the relevant job.

b) Contractor's staff should use only those tools at site, which have prior verification from first line Executive & HSE Engineer

c) In case of any HSE violations, following penalties will be imposed:

i. 1st violation - warning
ii. 2nd violation - Fine of Rs. 100,000/-
iii. 3rd violation - Fine of Rs. 500,000/
iv. 4th violation - Suspension for a period of six months v. 5th violation - Blacklisting

5.8 Contractors shall maintain records as specified by the SNGPL's HSE Management System and by contract requirements.

5.9 For major jobs (re-vamps, expansion projects), contractor shall appoint safety supervisor for site.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS

6.1. ISO 14001:2015, Clause 8.1

6.2. ISO 45001:2018, Clause 8.1.4

7.0 RELATED DOCUMENTATION

- Contractor HSE Statement (SNGPL-GPR013-F-001)
- Contractors HSE Manual (English and Urdu languages)

1.0 Introduction

While working at SNGPL's site, it is your responsibility to ensure that your work is performed in a manner that is safe for people, property and environments. To fulfill this responsibility, Company expects that you will comply with these HSE Guidelines, other project-specific safety and environmental procedures that may apply (e.g., Laboratory Safety, building safety, Radiation Safety, Construction Safety, Road safety, etc.,) as well as all regulatory requirements. Work performed in a manner that endangers any person, property or environment is unacceptable.

1.1 Health, Safety and Environment Policy

SNGPL is committed to the Health and Safety of its employees, preservation of environment and continual improvement of HSE performance by reducing potential hazards, preventing pollution, conserving resources and adhering to applicable laws and regulations in all its activities related to transmission and distribution of natural gas.

1.2 All Contractors / suppliers are responsible for performing the work of contracts in conformance with all environmental, health and safety laws and regulations. Contractors shall be subject to the provisions of this Contractor HSE Manual, which has been prepared for the protection and safety of all persons, property and environments. This Contractor HSE Manual shall be provided to contractors / suppliers to communicate the safety and environment related information, to inform them of potential hazards, and to require that applicable laws, procedures, and precautions are adhered to.

1.3 SNGPL has a duty to all its employees to provide a safe environment and workplace. Because a contractor / supplier's work on SNGPL premises can potentially affect the safety of all persons and property, SNGPL is committed to hiring contractors / suppliers who take the safety of our employees, neighbours and property as seriously as we do. We are providing the following HSE manual to remind you of some of your specific responsibilities in this regard. The information provided within this handbook is advisory in nature and is not intended to replace the contractor / supplier safety or environmental procedures or requirements.

1.4 We expect that our contractors / suppliers will train, supervise, and direct their employees to be mindful, when performing work on SNGPL's premises, of the safety of all persons, properties and environments. The contractors / suppliers is required to ensure that his/her employees are familiar with applicable HSE requirements which include:

- HSE Hazards and risks
- General safety
- Basic first aid
- Use of Personal Protective Equipments (PPEs)

 Requirements of Work Permit
 Hazardous materials / chemicals awareness
Basic actions in case of emergency
 Basic fire fighting
 Safe driving.

2.0 GENERAL INFORMATION

2.1 Basic Safety and Security Rules

The following are some reasons for which an employee of a contractor / supplier may be temporarily or permanently removed from SNGPL premises:

 Possession or use of alcoholic beverages or illegal drugs.
 Possession of explosives, firearms, ammunition, and other weapons
Violation of any safety or security rules or requirements.
 Illegal dumping, handling, or disposal of hazardous materials
 Destruction or removal, without written permission, of any property belonging to SNGPL.
 Intimidating, threatening, harassing, impeding or interfering with an inspector, security officer, or SNGPL employee or designated representative
 Misuse of fire prevention and protection equipment
 Unauthorized removal or destruction of a safety barricade, handrail, guardrail, warning sign, fall protection, or other warning devices intended to protect employees or property.

2.2 Safety Permits and Procedures

The following operations may present a hazard to people or property. Therefore, you must obtain approval (PERMISSION TO WORK……PTW) through the SNGPL Contract Coordinator / representative. All safety requirements, precautions, PPEs or controls listed in PTW must be followed.

 Working on fire protection/detection systems
 Performing burning, welding, cutting, soldering, or other hot work.
 Working on gas pipe lines or associated equipment.
 Working on electrical, steam, chilled water systems or other energized systems Installing a temporary electrical service
 Working with hazardous chemicals (including solvents and paints)
 Working with, handling, transporting or generating hazardous wastes (including hospital biological waste, waste oil, chemicals, condensate etc.)
 Using a gas, diesel, or LP (propane) powered engine indoors
 Operating a power vehicle or self-propelled work platform
 Excavation/trenching
 Using radioactive sources or conducting field radiography (x-ray)
 Working with asbestos-containing materials

 Working on security systems
 Working with compressed air/gases
 Working on heating, ventilation, or air conditioning equipment
Working with chemicals, polishing or grinding
 Working at heights of more than 6 feet or roofs.
 Entering or working in confined spaces.
 Lifting or hoisting with cranes or hoists.
 Blasting operations.

2.3 HSE Performance monitoring

 The contractors / suppliers shall monitor HSE performance of their employees and activities.
 They shall in addition monitor all those performance monitoring actions agreed between SNGPL and the contractors / suppliers.

2.4 Housekeeping

 You must maintain good housekeeping. You must keep work areas neat, clean, orderly and free of excess trash and debris and never block walkways, stairs, exits, or create a tripping hazard.
 Cover and/or place guardrails around open holes, trenches, or excavations into which people may fall.
 Poor housekeeping at a job site may lead to an increased potential for safety hazards and an increased incidence of accidents, falls, cuts, spills, leaks, fires or electrocution.
 Do not work when tools, wires, materials are haphazardly spread out at the place of work.

2.5 Report Accident, Incident, Injury, or Illness

All work related accidents, incidents, injuries, and illnesses must be immediately reported to the SNGPL Contract Coordinator / representative / HSE department.

3.0 HAZARDOUS WASTE

3.1 Hazardous Waste Management

Hazardous waste generated by a Contractor / supplier as part of its work must be properly identified, stored and disposed of in accordance with all applicable laws. The Contractor / supplier must coordinate with its SNGPL representative to provide a list of hazardous waste(s) to be generated during the project, and to determine the location(s) available for hazardous waste storage.

The Contractor / supplier must also ensure, at a minimum:

proper labeling,
 adequate secondary containment,
 segregation of incompatible materials
 routine inspection of storage areas.

In addition, all hazardous waste containers shall be constructed of a material that is compatible with the waste, shall be in sound condition, and shall be kept securely closed to avoid spill or leakage.

3.2 Waste Disposal Documents

The Contractor / supplier is responsible for completing all waste disposal documents, required by SNGPL and regulatory requirements. This may relate to SNGPL own waste that is periodically removed for further disposal purposes, or waste created by contractor / supplier while performing a task at SNGPL premises.

3.3 Training

Contractor / supplier employees must be appropriately trained in hazardous waste procedures. In the event a Contractor / supplier encounters previously unidentified material that is reasonably believed to be hazardous (radioactive, Volatile, corrosive, flammable, explosive, biomedical, infectious, toxic), the Contractor / supplier shall immediately stop work in the affected area and report the condition to the Contract Coordinator / representative. At no time shall such material be disposed of in chutes, drains, pipes or in any other unauthorized manner.

3.4 Transportation and disposal of Hazardous Materials

All transportation of hazardous materials while on SNGPL property shall be conducted in accordance with SNGPL specified instructions. It shall not be disposed off to burn or be used in a manner that is harmful to people or environments. While transporting hazardous materials, contractor / supplier shall ensure that no harm is done to people or environments because of poor containers, packing, covering, lashing, fixing, loading, stacking or improper vehicle or mode of transport.

3.5 Spill Prevention and Control

- Based on the inventory of oil and hazardous chemicals that will be brought on-site, the Contractor / supplier shall have available equipment (e.g., secondary containment pallets, absorbent pads, absorbent booms, speed-dry) that is suitable and sufficient to control a potential spill/release.
- The Contractor / supplier is responsible for identifying outlets to the environment (e.g., sumps, storm/floor drains, etc.) and adequately minimizing spill potential to these areas.
- The Contractor / supplier is responsible for the proper storage of all flammable and combustible chemicals that are brought and/or stored on site to complete the work of this contract. Such storage may require the use of safety containers, safety cabinets, and/or secondary containment.
- The Contractor / supplier shall also ensure that any incompatible chemicals are safely segregated. The Contractor / supplier is responsible for maintaining and securing all chemical containers and all chemical storage areas. This requires selecting locations and methods to minimize exposure to rainfall, surface water, and the ground surface or subsurface.

 The Contractor / supplier must ensure that his/her employees are adequately trained in spill procedures outlined below.

 In the event of a release or spill, the Contractor / supplier must immediately inform SNGPL Contract coordinator / representative.

3.6 Air Emissions

All Contractor / suppliers must immediately report the following to the SNGPL Contract Coordinator / representative:

 Any maintenance or repairs to a combustion unit that could result in a change in overall emissions (e.g. burner replacement or fuel conversions)

 Any conditions discovered which could have resulted in an increase on air pollutant emissions.

 Contractor / supplier's activities should not cause unacceptable emissions (emissions not meeting NEQS).

 Contractor / suppliers shall immediately notify the Contract Coordinator / representative whenever they become aware of any unintentional or intentional release of CFCs or Halon.

3.7 Waste water discharges.

Contractor / supplier must ensure no waste water is discharged that violates NEQS.

 Waste water must NOT include any corrosive, flammable, or toxic substances.

3.8 Biological/Chemical/Radioactivity Hazards

Some SNGPL operations may involve the use of biological, chemical, or radioactive material that can be hazardous to persons or property, if not handled or disposed safely. Contractors / suppliers will mark with appropriate signs, the areas where work with biological, chemical, or radioactive materials is being performed.

The Contractor / supplier shall not disturb, damage or otherwise handle any suspect asbestos containing material.

The Contractor / supplier shall not sweep, dust, vacuum or mop dust or debris that is the product of a suspect asbestos containing material. The Contractor / supplier shall also not pick up or throw away any suspect asbestos-containing
waste or trash.

Sanding, grinding, drilling, brazing, scraping, polishing of floors and other dust emitting surfaces will be done by persons wearing appropriate PPEs.

3.9 Hazardous Materials and Hazard Communication

 Do not handle or use hazardous materials without providing training to the concerned employees.

 No solvents, paints, or similar flammable, toxic, or irritating materials may be used in SNGPL premises unless specifically approved by the SNGPL Coordinator / representative.
 Maintain adequate ventilation when paints or solvents are used.
 Use flammable solvents and materials with extreme caution.
 Isolate and store flammable paints and solvents in approved locations if inside buildings.
 The Contractor / supplier shall submit an inventory of all hazardous chemicals / liquids / materials that are brought on-site or sold to SNGPL. These should be accompanied by Material Safety Data Sheets (MSDS).
 The Contractor / supplier shall also ensure that all containers that are brought on site for the storage of hazardous chemicals (e.g., gas, paint, etc.) are labelled and inspected for correctness.
 The Contractor / supplier shall remove all hazardous chemicals that it brings on- site when work involving a specific hazardous chemical is complete.

4.0 SPECIFIC SAFETY REQUIREMENTS

4.1 Confined Space Entry

 Contractor / supplier will obtain PTW before entering / working in confined spaces.
If during the course of its work, the Contractor / supplier encounters a confined space that has not been previously identified by the SNGPL, it must immediately bring the space to the attention of the Contract Coordinator / representative, and delay entry until SNGPL has examined the space.
 When both SNGPL personnel and Contractor / supplier personnel are working in or near confined spaces, the Contractor / supplier shall coordinate all operation with the affected SNGPL personnel before entry.
 Advance notification is always required. Whether you enter a confined space with a SNGPL employee or not.

4.2 Lock-out / Tag-out (where applicable)

 As part of SNGPL's Lock-out/Tag-out Program standard locks and tags should be used to control the start-up of equipment that is being serviced or maintained by its employees. At no time shall the Contractor / supplier or its employees override any locks or tags that they encounter during the performance of its work.

 The Contractor / supplier is responsible for developing, implementing and maintaining his/her own Lock-out/Tag-out Program.

 The Contractor / supplier shall submit a copy of its Lock-out/Tag-out Program to the Contract Coordinator / representative before the start of any work.

4.3 General Electrical Safety

- Only qualified electricians are permitted to work on electrical systems and equipment that uses or controls electrical power.
- Do not operate electrical tools or equipment in wet areas or areas where potentially flammable dusts, vapors, gas, or liquids are present, unless specifically approved for the location.
- Should a circuit breaker or other protective device "trip," ensure that a qualified electrician checks the circuit and equipment and corrects problems before resetting the breaker.
- Erect barriers and post warning signs to ensure non-authorized personnel stay clear of the work area.
- Report hazards (lack of protective guards or covers, damaged equipment, etc.) to the SNGPL Contract Coordinator / representative immediately.
- Do not leave electrical boxes, switch gear, cabinets, or electrical rooms open when not directly attended.
- Insulate energized parts when covers have been removed or doors are ajar. Use of cardboard, plywood, or other flammable materials to cover energized circuits is prohibited.

4.4 Compressed Gas Cylinders

The following measures must be taken for the protection of persons and property:

- Valve protection caps must be in place when compressed gas or LPG cylinders are transported, moved, or stored.
- Close cylinder valves and replace valve covers when work is complete and when cylinders are empty or moved.
- Secure compressed gas cylinders in an upright position in a welding cart or to a solid object (using chains, straps, or a rigid retaining bar).
- Secure compressed gas cylinders on an approved carrier while being transported.
- Keep cylinders at a safe distance or shielded from welding or cutting operations. Do not place cylinders where they can contact an electrical circuit.
- Keep oxygen and flammable gas regulators in proper working order and a wrench in position on the acetylene valve when in use.
- If a leak develops in a cylinder and it cannot be immediately corrected, move the cylinder to a safe location outside the building.
- Cylinders must not be taken into or stored in confined spaces.
- Do not store hoses and regulators in unventilated or closed containers or areas.

4.5 Welding, Cutting, and Brazing

- Obtain Work Permit
- Inform SNGPL representative prior to the start of any welding/cutting/brazing work. Remove combustible materials from the area before beginning work.

 Install anti-flash back (safety/check) valves in both the oxygen/acetylene hoses at the regulator.
 Shield adjacent areas with welding partitions.
 Have a second person stand by with an approved fire extinguisher for welding and burning operations

4.6 Cranes and Rigging

 Each crane, rigging, or hoist brought onto SNGPL property must have an annual inspection testing performed by a certified testing agency.
 The operator is responsible for the proper placement of the crane in relationship to the load to be handled and the landing area so as to obtain the best rated lift capacity, and the installation and maintenance of crane swing radius protection. All operators must possess a valid crane / hoist operating / driving license as applicable.

4.7 Driving

 All contractor / supplier vehicles while in SNGPL premises or performing SNGPL duties must have valid driving license, and shall adhere to speed limits (applicable in that particular zone), and also comply with all other traffic and road safety regulations.

The Contractor/Supplier/Vendor shall prepare and maintain information including a clear method statement, regarding Contractor/sub-contractor activities, which outline the work to be undertaken and the method(s) for minimizing and maintaining environmental impacts, OH&S Hazards and maintaining compliance with HSE regulations.

To assist in organizing and maintaining information, background information sections have been included (section I, II, III). Sections can be modified or deleted as required when requesting a method statement from Contractors / subcontractors.

SNGPL's Personnel to Complete Sections I, II, and III
Suppliers to Complete Sections IV, V, and VI

This information pertains to **Section I, Your Information**, within the **Contractor / Supplier / Vendor HSE Statement** (SNGPL-GPR013-F001). This section requires the following details:

- **Name**
- **Phone Number**
- **Fax Number**
- **Department Name**

Section V. Contractor / Supplier / Vendor Method Statement:

Supplier / Contractor / Vendor is financially responsible for on-site HSE remediation actions resulting from incidents involving their employees and subcontractors. To minimize the risk of environmental accidents, please review and initial the items contained in the HSE Management Basics Table below:

The "Health, Safety and Environment Management Basics" table specifies several requirements for contractors working with Sui Northern Gas Pipelines Limited (SNGPL). These basics ensure that contractors prioritize the health and safety of their employees and the environment.

Here's a breakdown of the key points:

- **Contractor Responsibilities**:
  - Protect employee health.
  - Ensure job execution is safe.
  - Comply with laws and regulations.
  - Implement SNGPL's HSE procedures.
  - Provide a safe working environment.
  - Minimize job-related hazards and provide appropriate PPE.
- **Incident Reporting**:
  - Report all incidents (dangerous occurrences, injuries, fires, vehicle accidents, environmental incidents) to the Company within 24 hours.
- **Injury Treatment**:
  - Contractors arrange for treating their employees' injuries.
  - Notify the Company representative and report injury circumstances immediately.
- **Equipment Maintenance**:
  - Maintain mobile equipment (trucks, cranes, welding machines) in good condition.
  - Prevent materials from falling off equipment during transport.
  - Arrange for repairs if vehicles become immobilized.
- **Equipment Certification and Operation**:
  - Provide a certificate from a competent authority stating that all mobile heavy equipment is in good working condition before starting work.
  - Only licensed and qualified personnel operate contractor's equipment.

The "Health, Safety and Environment Management Basics" table outlines several requirements for contractors working with Sui Northern Gas Pipelines Limited (SNGPL). These requirements are designed to ensure contractors prioritize the health and safety of their employees and the environment.

Here's a breakdown of the key points:

- **Equipment Handling**: Company equipment must not be handled or tampered with by contractors. A company representative may grant permission under specific conditions, particularly in emergency situations.
- **Excavation Work**:
  - During excavation, contractors must avoid damaging underground piping, exercising extreme care when using power-driven equipment.
  - Accidental damage to lines must be reported to the Company representative immediately.
  - Excavations must be fenced or barricaded to prevent accidental falls.
  - Safety talks should be notified for contract employees during transportation.
- **Work Permits**: Contractors must obtain the appropriate permit from an authorized company executive before commencing work at designated company sites where work permit

procedures apply. Contractors are expected to follow Company rules and applicable laws while performing their work.

- **Personal Protective Equipment (PPE)**: Contractors must provide all staff with relevant PPE as specified by the Company for each job, and compliance is mandatory.
- **Job Site Maintenance**:
    - Contractors must keep job sites reasonably clean, free of rubbish and debris to prevent tripping or fire hazards.
    - Upon completion, the area must be left clean and orderly, with all contractor debris, equipment, and excess material removed.
- **Waste Disposal**: Contractors must dispose of all waste generated from their activities in an environmentally friendly manner, following the guidelines of the Pakistan Environmental Protection Act, 1997.
- **Information Provision**: Contractors/vendors/suppliers must provide information regarding Occupational Health & Safety (OH&S) and environmental conditions pertaining to machinery, equipment, products, materials, or services being hired.

Section VI. Supplier/Contractor/Vendor Certification: [review and sign]

I have reviewed and understand the information contained in this document. I also understand that *SNGPL's HSE* Personnel have the right to inspect our activities and those of our Suppliers/Contractors/Vendors with regards to our on-site activities. I further understand that activities pertaining to service and/or maintenance contracts may only require submission of this form on an annual basis.

1. Name
2. Title
3. Signature
4. Date

1.0 PURPOSE

To establish and maintain arrangements to ensure the effective application of controls and counter measures, wherever required controlling operational risks and environmental impacts, and potential risks to fulfill the HSE policy, objectives and legal requirements.

2.0 SCOPE

2.1 All sites of SNGPL as defined in IMS Manual.

3.0 DEFINITIONS

IMS:	Integrated Management System based on EMS and OHSMS
EMS	Environmental Management System
OHSMS	Occupational Health & Safety Management System
HSC	HSE Site committee
HSE	Health Safety and Environment
OH&S	Occupational Health & Safety

4.0 RESPONSIBILITIES

4.1 HSE Management Committee

4.2 Management Representative (MR)

4.3 EMS & OHSMS Deputy Management Representatives (DMRs)

4.4 HSE Site Committee

5.0 PROCEDURE

4.1 OPERATIONAL CONTROL WITH RESPECT TO HSE:

4.1.1 Operational risks and potential risks are identified through procedure **OH&S Risk Assessment, Objectives & Targets and Management Programs (SNGPL-HPR-001)**.

4.1.2 Significant environmental aspects and their impact are identified through procedure **EMS Aspects & Impacts Identification, Setting of Objectives & Targets and Management Programs(SNGPL-EPR-001)**.

4.1.3Standard operating procedures (Normal / Emergency) are developed and implemented to operate and control the parameters and operational risks and aspect/impacts at different sites / departments. Identified operational and potential risks and impact are combat to lower or eliminate hazards associated with it. Operation failure rate is minimized which could lead to incidents, accidents or other deviations from HSE policy, objectives and other requirements.

4.1.4A formal **List of Infrastructure facilities (SNGPL-GPR014-F001) at site** will be maintained by Admin representative and reviewed by HSE Focal point.

4.2 EMERGENCY CONTROL MEASURES:

4.2.1HAZARDOUS TASKS:

- HSE Site Committee is responsible to identify the task and OH&S hazard / Environmental impact associated to it. If hazard is obvious then task should fall under **work permit system** as per procedure **(SNGPL-HPR-003).** All hazardous tasks are performed through approved SOPs. In addition, personnel competence is ensured prior to work.

- If hazardous tasks are to be carried out through contractual agreements then procedure **contractor control (SNGPL-GPR-013)** is to be followed.

4.2.2HAZARDOUS MATERIALS:

- SNGPL has identified storage location of hazardous materials at the sites. All such storage locations are equipped with standard safety equipment (Fire fighting and safety equipments, monitoring and measuring equipment etc) to control and minimize risk and impacts associated with storage. Standard Operating Procedures are used to control access and handling of such hazardous materials.

- Materials safety data sheets (MSDS) and other relevant information that could be used in safe handling and identification & control of hazards are provided to concerned personnel.

4.2.3SAFE OPERATION OF PLANT AND EQUIPMENT:

All relevant areas, units and departments of SNGPL are using standard operating procedures (SOPs) for safe operations of plants and equipments. Standard operating procedures established at site / departmental levels, clearly stipulate:

1.Essential monitoring and control of site and equipment.
2.Authorized shutdown and startup procedures.
3.Availability and usage of OH&S and environment related steps and equipments.

4.Precaution in relation with OH&S and Environment.
5.Availability and safe handling of equipment (cranes, forklifts, hoists and other lifting devices).
6.Exhaust ventilation systems.
7.Proper use of PPE's.
8.Inspection and testing of OH&S related equipment.
9.Measuring, monitoring and inspections of site / equipment.
10.First aid system and clinical / medical facilities.

4.2.4SAFE MAINTENANCE OF PLANT AND EQUIPMENT:

All relevant sites / departments of SNGPL are using breakdown and preventive maintenance procedures to keep the site / equipment in safe operating conditions. The preventive maintenance schedule of Heavy machinery/ equipment shall be developed and maintained at site as per manufacturer's recommendations for its safe operation. Forms for physical inspection of Overhead cranes and chain pulley blocks will be filled at relevant sites on quarterly basis (SNGPL-GPR014 F-002). Standard Operating Procedures (For Maintenance) established for all the relevant sites / departments, clearly stipulate:

1.Provision, Control and Maintenance of site / equipment.
2.Provision, Control and Maintenance of PPEs.
3.Proper use of PPEs.

4.2.5TRAINING AND COMMUNICATION OF OH&S AND ENVIRONMENT RELATED ISSUES:

- It is departmental heads responsibility to identify training need as per Procedure **Training, Awareness and Competence of SNGPL Personnel for EMS & OHSAS (SNGPL-GPR-003)** and sends to MR for training and awareness of EMS related issues.

- EMS and OHSMS related awareness is being communicated to supplier and contractor as per respected departments SOP's.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

The provided text refers to **Clause 8.1 of ISO 14001:2015 and ISO 45001:2018** and details related documentation regarding **infrastructure and maintenance**.

- **Requirements:** The content relates to the requirements of **ISO 14001:2015, Clause 8.1** and **ISO 45001:2018, Clause 8.1**.
- **Related Documentation**:
  - **List of Infrastructure Facilities**: Documented in **SNGPL-GPR014-F001**.
  - **Preventive Maintenance Schedule of Chain blocks / Overhead Cranes**: Documented in **SNGPL-GPR014-F002**.

SNGPL-GPR014-F001 is a **List of Infrastructure Facilities**. It includes fields for site, date of updation, description/details, quantity, building/infrastructure location, machinery/equipment registration number/asset code, and vehicle registration number.

SNGPL-GPR014-F002 is an **Inspection Checklist of Chain Pulley Blocks/Overhead Cranes**. It includes the site, date, Chain Block/Overhead crane ID No, frequency, and capacity. The checklist includes items such as load lifting capacity, condition of hooks and safety latches, and the availability of SOPs.

1.0 PURPOSE:

To provide an effective approach for continuous HSE training.

2.0 SCOPE:

All activities, areas and departments of SNGPL.

3.0 RESPONSIBILITIES:

3.1 Focal point

3.2 All executives of the respective site.

4.0 PROCEDURE:

4.1 Focal point will ensure that all the executives of his domain read the Safety Talk personally.

4.2 All the executives of the respective site will arrange weekly short sessions for their concerned staff regarding Safety Talks. Training record will be verified by trainer on **Attendance Sheet(SNGPL-GPR003-F-003)**.

4.3 First line executive will give prior notice of the session with date and venue to his staff.

The executive imparting knowledge to staff for Safety Talks will ensure its complete 4.4 understanding to the participants through mutual discussion.

4.5 The first line executive will ensure that the session for Safety Talk should take at least 20 minutes and should not go beyond 1 hour.

4.6 HSE Engineer will randomly cross check delivered safety talks of respective site(s) for assessing effectiveness / authenticity.

Safety talk booklet soft form is available at web portal **(http://as prod.sngpl.com.pk)** 4.7

5.0 REQUIREMENTS OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

5.1 ISO 14001:2015, Clause 7.3

5.2 ISO 45001:2018, Clause 7.3

6.0 RELATED DOCUMENTATION:

6.1 Attendance Sheet (SNGPL-GPR003-F-003)

1.0 PURPOSE:

The purpose of this procedure is to ensure the safety of our pipe line network and ultimate gas losses from ruptures as a result of the activities carried out by outside (third party) agencies, Company's internal departments and sabotage activities. This procedure defines the mechanism to secure approval from regulatory agencies for operational activities carried out by SNGPL

2.0 SCOPE:

This procedure is applicable to Projects, Transmission and Distribution departments, and where there is any River / Canal / Roads & Highways / Railway crossings.

3.0 DEFINITIONS:

Gas Safety Management	To protect Transmission system, Distribution network of the Company from damages and gas losses due to ruptures, leakages as a result of the activities carried out by outside (third party) agencies, Company's internal departments and by sabotage activities.

Ruptures: To break, burst, or tear something, or become broken, burst, or torn.

MAOP Maximum Allowable Operating Pressure

4.0 RESPONSIBILITIES:

4.1 Management Representative (MR) shall ensure that the procedure is developed and revised when need arises.

4.2 Concerned Head of Department (HOD) shall ensure that the system is in place.

4.3 HSE Focal Point shall ensure that the procedure is implemented in true spirit and all the resources are available.

4.4 Distribution Department is Responsible:

4.4.1 To lay Distribution network in accordance with design drawings / Company's approved Distribution manual.

4.4.2 To operate Distribution network at approved MAOP.

4.4.3 To install pressure regulators at Domestic / Commercial and industrial consumers as per Company's approved Policy.

5.0 PROCEDURE:

5.1 Activities performed by Outside Agencies:

5.1.1 The operation section of Transmission and Distribution department is responsible for the communication of the below listed points to the outside agencies.

5.1.2 **No Objection Certificate (Undertaking)(SNGPL-GPR017-F002)** in writing shall be filled / communicated to outside agency before the execution of the job. In case of any damage to SNGPL pipeline network the outside agency shall bear the expenses due to pipeline damage and subsequent gas loss. FIR may be registered in case of pipeline damage.

5.1.3 Prior to execution of any job at Right of Way or SNGPL acquired land, the outside (third party) agency shall intimate SNGPL and apply for ***No Objection Certificate (Undertaking)(SNGPL-GPR017-F002*)**.

5.1.4 Demarcation of existing buried gas pipelines shall be the responsibility of SNGPL before the execution of any activity adjacent to ROW / STREET by outside agency/individual.

5.1.5 A meeting shall be carried out between the Operation department (Transmission/ Distribution) of SNGPL and the outside (third party) agency requiring any activity to be carried out on SNGPL acquired land for finalizing the nature of activity, time schedule and for exchanging as-built drawings of the network where the activity is going to be carried out.

5.1.6 At the time of execution of the activity, the SNGPL representative shall be present at site with relevant information and drawings, strictly for monitoring that the work is done as per the given drawings and shall not be implied to absolve the third party from liability.

5.1.7 Operation departments (Transmission/ Distribution) shall ensure the presence of Site Engineer / Pipeline supervisor/ Pipe Line Attendant (PLA) at the time of the execution of the activity at site. In case of any rupture incident, the matter shall be investigated by a team comprising of HSE / Operations / Maintenance engineers. The team shall be nominated by HSE Focal point and if negligence of the Site Engineer / Pipeline supervisor / PLA is found, the concerned Site Engineer / Pipeline supervisor / PLA on duty shall be held responsible and disciplinary action can be started against him.

5.2 Activities performed by Internal Departments:

5.2.1 All departments are bound to intimate the Operation department (Transmission / Distribution) before the execution of any activity at site.

5.2.2 The meeting shall be arranged for exchanging as-built drawings of the said routes where the activity is going to be carried out. Moreover the time and schedule will also be finalized mutually.

5.2.3 Site Engineer /PLA shall ensure his presence at site during the execution of construction activities in accordance with mutually agreed drawings.

5.2.4 In case of any damage to pipe line network by the department performing the jobs, the Warning letter will be issued to them by the concerned Focal Point and further necessary action will be taken if required.

5.2.5 Same as given at 5.1.7

5.3 Pipeline ruptures due to sabotage activities:

5.3.1 Transmission department is responsible for the patrolling at ROW by concerned engineer / patrolling staff and/or law enforcing security agencies on Transmission system for effective monitoring.

5.3.2 Transmission department shall develop liaison on special request basis with the security agencies in this regard.

5.3.3 Transmission / Compression departments are responsible to operate the Gas Transmission pipe lines in accordance with the approved (MAOPs) by P & D department.

5.3.4 Transmission department shall ensure proper maintenance of acquired / purchased ROW without any encroachment in accordance with approved manual of Transmission department.

5.4 Record of **Gas Safety Management Activity Performa(SNGPL-GPR017-F001)** shall be maintained by Operations department (Transmission/ Distribution).

5.5 All communications in connection with NOC, and specifically those with the relevant regulatory agencies, shall be undertaken in conformance with procedure **Communication, Participation and Consultation (SNGPL-GPR-007)**

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

The provided text relates to **Gas Safety Management** and references **ISO 45001:2018, Clause 8.1.1 and 9.1.1**.

- **Requirements:** The content relates to the requirements of **ISO 45001:2018, Clause 8.1.1 and 9.1.1**.
- **Gas Safety Management**: The procedure ensures the safety of the pipeline network and prevents gas losses resulting from activities by outside agencies, internal departments, and sabotage. It also defines the process for securing approval from regulatory agencies for SNGPL's operational activities.
- **Communication**: All communications related to No Objection Certificates (NOCs), specifically with regulatory agencies, must follow the procedure outlined in "Communication, Participation and Consultation (SNGPL-GPR-007)".
- **Related Documentation**:
    - **Gas Safety Management Activity Performa (SNGPL-GPR017-F001)**.

- **No Objection Certificate (Undertaking) (SNGPL-GPR017-F002)**.

The **Gas Safety Management Activity Performa (SNGPL-GPR017-F001)** includes fields such as the name of the outside agency or company department, meeting date and time, whether documents/drawings and affidavits were exchanged, the number of days the activity was carried out, whether a pipeline attendant was deputed, and whether the job was completed safely.

The **No Objection Certificate (Undertaking) (SNGPL-GPR017-F002)** includes fields such as the name of the company, particulars of the person giving the undertaking, the instrument through which the person is authorized, and an undertaking to adhere to safety regulations.

1.0 PURPOSE:

This Procedure defines the mechanism for:

- Determination of external and internal issues that are relevant to its purpose and that affect its ability to achieve the intended outcomes of its integrated management system
- Determination of interested parties, their needs and expectations and Company's compliance obligations
- Determination of scope of Integrated Management System

2.0 SCOPE:

This Procedure is applicable for all areas, units, departments, activities and services of SNGPL.

3.0 definitions:

The definitions provided relate to **Sui Northern Gas Pipelines Limited (SNGPL)** and its **Integrated Management System (IMS)**. The definitions clarify terms associated with **environmental and safety management**.

Key definitions include:

- **Environmental Management System (EMS)**: A management system component used to handle environmental aspects, meet compliance obligations, and address risks and opportunities.
- **Interested Parties**: Any person or group that can affect, be affected by, or believes they are affected by a decision or activity.
- **Compliance Obligations**: Legal requirements an organization must follow, as well as other requirements it chooses to adopt.
- **HSE**: Health, Safety, and Environment.
- **IMS**: An Integrated Management System based on EMS and Occupational Health and Safety Management Systems (OHSMS).
- **EMS**: Environmental Management System.
- **OHSMS**: Occupational Health and Safety Management System.

4.0 RESPONSIBILITIES:

4.1 IMS Management Representative (MR)

4.2 EMS/OHSMS Deputy Management Representatives (DMRs)

4.3 Concerned Departmental Head / HSE Focal Point

4.4 Sectional Head

4.5 HSE Site Committee

5.0 PROCEDURE:

5.1Determination of external and internal issues

5.1.1 HSE Focal Point and HSE site committee are responsible for determination of external and internal issues that are relevant to its purpose and that affect its ability to achieve the intended outcomes of its integrated management system. Such issues shall include OHS and environmental conditions being affected by or capable of affecting the organization.

5.1.2 HSE Focal Point will maintain **List of** internal issues along with risks and opportunities on form **(SNGPL-GPR017-F001)** and list of external issues along with risks and opportunities on form **(SNGPL-GPR017-F002)**. HSE Focal point will send a copy of forms **(SNGPL-GPR017-F001)** and **(SNGPL-GPR017-F002)** to MR for monitoring purpose.

5.1.3 HSE Focal Point will maintain List of interested parties, their needs and expectations, compliance obligations, legal and other requirements along with risks and opportunities on form **(SNGPL-GPR017-F003)**.HSE Focal point will send a copy of form **(SNGPL-GPR017-F003)** to MR for monitoring purpose.

5.1.4 HSE Focal Point will ensure that the site Integrated Management System covers the Scope as defined in IMS Manual.

5.1.5 HSE Focal Point shall ensure compliance to IMS procedures, SNGPL-GPR-009, Operational Control procedure, Aspects identification procedure for continual improvement of the site integrated management system.

5.1.6HSE Department shall review the information sent by HSE Focal Point and may recommend any changes / improvements.

5.1.7The lists will be reviewed by HSE Focal point shall review forms **(SNGPL-GPR001-F001), (SNGPL-GPR017-F002)** and **(SNGPL-GPR017-F003)** on Annual Basis if no change occurs in the system.

5.1.8HSE Focal Point shall determine Risk and Opportunities against Compliance obligations on form **(SNGPL-GPR017-F003).**

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1. ISO 14001:2015, Clause 4.1,4.2

6.2. ISO 45001:2018, Clause 4.1, 4.2

7.0 RELATED DOCUMENTATION

7.1 List of internal issues	(SNGPL-GPR017-F-001)
7.2 List of external issues	(SNGPL-GPR017-F002)
7.3 Needs and Expectations & Compliance Obligations	(SNGPL-GPR017-F-003)

1.0 PURPOSE:

This procedure describes the mechanism for:

1. Identification of operational and potential OH&S hazards, its significance, evaluation and risk assessment.
2. Determining OH&S opportunities, Other Risk and Other opportunities

2.0 SCOPE:

All activities, areas and departments of SNGPL as defined in IMS Manual.

3.0 definitions

The definitions you've provided relate to **Occupational Health & Safety (OH&S)** within the context of Sui Northern Gas Pipelines Limited (SNGPL). These definitions are crucial for understanding risk management and safety protocols within the organization.

Here's a breakdown of the key terms:

- **OH&S:** Occupational Health & Safety.
- **OH&S Hazards:** A **source, situation, or act** with the potential for harm in terms of human injury or ill health, or a combination of these.
- **Risk:** The **effect of uncertainty**.
- **OH&S Risks:** The combination of the likelihood of a hazardous event or exposure(s) occurring and the severity of injury or ill health that can be caused by the event or exposure(s). It is a **combination of likelihood and severity**.
- **Other Risks:** Relate to the establishment, implementation, operation, and maintenance of the OH&S management system.
- **OH&S Opportunity:** A circumstance or set of circumstances that can lead to improvement of OH&S performance.
- **Acceptable Risk:** Risk that has been reduced to a level that can be endured by the organization, considering its legal obligations and its own OH&S policy.
- **OH&S Risks Assessment:** The overall process of estimating the magnitude of risk and deciding whether or not the risk is tolerable. It involves **estimating risk magnitude** and **determining risk tolerability**.

- **Ill health:** An identifiable, adverse physical or mental condition arising from and/or made worse by a work activity and/or work-related situation.
- **Incident:** A work-related event(s) in which an injury or ill health (regardless of severity) or fatality occurred, or could have occurred.
    - An accident is an incident that has given rise to injury, ill health, or fatality.
    - An incident where no injury, ill health, or fatality occurs may also be referred to as a "near-miss", "near-hit", “close call” or "dangerous occurrence".
    - An emergency situation is a particular type of incident.
- **Safety:** Freedom from unacceptable risk of harm.
- **OH&S Objective:** Occupational Health and Safety goals arising from the H&S Policy that SNGPL sets itself to achieve.
- **OH&S Target:** Detailed performance requirement quantified where applicable, that arise from the OH&S objectives and need to be set and met in order to achieve those objectives.
- **OH&S Management Program:** The means, time frames, and personnel responsible for achieving an objective and target.

RESPONSIBILITIES:

- HSE Focal Point
- Management Representative (MR)
- OHSAS Deputy Management Representative (DMR)
- OHS Risk Assessment Team

5.0 PROCEDURE:

5.1 OH & S HAZARD IDENTIFICATION AND RISK ASSESSMENT:

5.1.1. Occupational Health & Safety hazard and risk assessment of all the Company's premises and sites / activities shall be performed by **OHS Risk Assessment Team** comprising of respective department / section / site Incharge, First line executive and HSE Executive in consultation with respective staff (Subordinates / Casuals).

5.1.6 OH&S hazards resulting in OH&S risks and OH&S opportunities that can further result in other risks and other opportunities for the organization will be identified.

5.1.2. Followingfactors (but not limiting itself to) shall be considered while performing OHS risk assessment;

a) Legislative and regulatory requirements
b) Workplace Infrastructure, equipments and materials, whether provided by the Company or others.
c) Workplace process design, machinery / equipments, operating procedures / manuals
d) Human behavior, capabilities and other human factors.

e)Routine and non-routine activities
f)Activities of all personnel having access to the workplace (including subcontractors and visitors)
g)Past relevant incidents, internal or external to the site, including emergencies, and their causes.
h)Social factors (including workload, work hours, victimization, harassment and bullying), leadership and the culture in the organization;
i)Development in knowledge and technology

5.1.3.All potential and existing hazards of Company premises and activities of sites are to be identified in the absence of any control on **Hazard identification check sheet for OH&S (SNGPL-HPR01-F-001).**

5.1.4.OH & S Risk assessment of Company premises and activities of sites shall be documented on **OH&S Risk Assessment Sheet (SNGPL-HPR01-F-002)**

5.1.5.HSE Focal Point should communicate 'Hazard identification check sheet for OH&S' (SNGPL-HPR01-F-001) and 'OH&S Risk Assessment Sheet' (SNGPL-HPR01-F-002) to MR for review.

5.1.7Hazard identification check sheet for OH&S (SNGPL-HPR01-F-001) and OH&S Risk Assessment Sheet (SNGPL-HPR01-F-002) shall be maintained and reviewed by HSE Focal Point **at least annually**. New hazards identified during review should be added and any hazard eliminated will be deleted from the list.

5.1.8OH & S Risk Assessment shall be performed prior to start of any activity.

5.1.9OH & S Risk assessment should be updated accordingly in case of any changes in the existing facility/equipment/process etc**.**

5.1.10The risks will be assessed and documented on 'OH&S Risk Assessment Sheet (SNGPL-HPR01-F-002)'using the guideline provided in the **Risk Assessment Chart (SNGPL-HPR01-CH-001**).

5.1.11Risk rating 9 and above should be considered Un-Acceptable risk and needs to be controlled.

5.1.12Control Measures will be taken on **OH&S Risk Assessment Sheet (SNGPL-HPR01-F-002)** to convert Un-acceptable Risks to Acceptable Risks according to following hierarchy:

a)Elimination **b)** Substitution **c)** Engineering Controls
d)Signage/warnings and/or administrative Controls
e)Personal Protective Equipment

5.1.13Action plans of other risks and OH&S and other opportunities shall be maintained on CAR (Corrective Action Request) and by setting Objectives & Targets whichever is decided suitable by HSE focal point and HSE site committee.

5.1.14If risks cannot be converted into Acceptable Risks then a new facility/equipment/process to be identified to reduce the impact of risks.

5.2 ESTABLISHINGANDMAINTAININGOBJECTIVESANDTARGETS:

5.2.1The MR / DMR-OHSAS shall select OH&S Objectives for all identified potential and operational hazards on **list of selected objectives for OH&S (SNGPL-HPR01-F-003)**. Objectives and targets shall be consistent with the **SNGPL** HSE policy.

5.2.2During establishing the objectives and targets consideration shall be given to following but not limited to:

5.2.2.1Results of Hazard identification, risk assessment and means of risk control.
5.2.2.2Other risks and OH&S and other opportunities
5.2.2.3Legal and other requirements.
5.2.2.4Technological Options

5.2.2.5Financial, Operational and Business requirements

5.2.2.6Views of employee and other interested parties.

5.2.2.7Information from employee, OH&S Consultants, review and improvement activities in the workplace.
5.2.2.8Analysis of performance against previously established OH&S Objectives.
5.2.2.9Post records of OH&S non-conformance, accidents, Incidents and property damages.

5.2.2.10 Results of management reviews.

5.2.2.11 Results of consultation with workers

5.2.3In establishing objectives and targets consideration shall be reviewed **at least yearly** and will be reported in **Management Review Meeting (SNGPL-GPR-005)** by MR. The management reviews shall endorse the SNGPL's OH&S Objectives and targets.

5.2.4On the basis of selected objectives, HSE Focal Point will plan each objective on **OH&S Objective Planning (SNGPL-HPR01-F-004)** in consultation with MR/OHSAS-DMR. This will include development of strategies and action plans, which are documented and communicated to all concerned. Strategies and actions clearly stipulate the following as appropriate:

5.2.4.1Tasks to achieve objectives.

5.2.4.2Individuals responsible for delivering OH&S objectives.

5.2.4.3Allocation of appropriate resources (Financial, Human,

Equipment, Logistics etc.)

5.2.4.4Any training needs.

5.2.4.5Consultation of relevant personnel on expected changes.

5.2.4.6Incase of alterations or modifications in work practices,

Processes, equipment or material, plan for new hazard

Identification and risk assessment exercise.

5.2.5**OH&S Objective Planning (SNGPL-HPR01-F-004)** shall be prepared by HSE Focal Point, reviewed by HOD and approved by MR.

5.2.6Responsibility shall be identified for each relevant function / task on format OH&S Objective Planning (SNGPL-HPR01-F-004). HSE Focal point is overall responsible for timely completion of respective OH & S objective.

5.2.7The MR in consultation with OHSAS-DMR shall maintain **OH&S Objectives Status (SNGPL-HPR01-F-005)** andwill regularly monitor and review the progress of OH&S objective.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1 ISO 45001:2018, Clause 6.1, 6.1.1,6.1.2,6.1.3,6.2

7.0 RELATED DOCUMENTS:

7.1 Hazard identification check sheet for OH & S (SNGPL -HPR01-F-001)

The documents listed relate to **Occupational Health and Safety (OH&S) risk assessment, objective setting, and planning** within Sui Northern Gas Pipelines Limited (SNGPL).

Key documents include:

- **OH & S Risks Assessment Sheet (SNGPL-HPR01-F-002)**: This sheet is used to document the OH&S risk assessment of company premises and activities. It includes sections for:
    - Identifying safety and health hazards and potential impacts.
    - Applying controls and determining residual risk.
    - Identifying opportunities and other risks.

  The risk rating 9 and above should be considered unacceptable risk and needs to be controlled.

- **List of Selected Objectives for OH&S (SNGPL-HPR01-F-003)**: This document is a list of OH&S objectives selected for a given fiscal year.
- **OH & S Objective Planning (SNGPL-HPR01-F-004)**: This document outlines the planning for achieving specific OH&S objectives. It includes sections for:
    - Defining the objective and methodology.
    - Setting a completion date.
    - Identifying required resources and training needs.
- **OH & S Objectives Status (SNGPL-HPR01-F-005)**: This document tracks the status of OH&S objectives, including approval dates, completion dates, and any revisions.
- **Risk Assessment Chart (SNGPL-HPR01-CH-001)**: This chart provides guidelines for assessing risks, considering both the likelihood and effect on health/life. The effect on health/life is rated on

a scale of 1 to 5, with 5 indicating injuries or illness involving permanent total disability, chronic or irreversible illness, or death.

Rating

LIKELIHOOD/PROBABILITY (L) FOR BASE RISK

The excerpt details the **Likelihood/Probability (L) rating scale** used in SNGPL's **O**ccupational **H**ealth & **S**afety (**OH&S**) Risk Assessment Chart. This scale is used to evaluate both the base risk and residual risk associated with potential hazards.

- **Incident Occurrence**: Ranges from Highly Unlikely (1) to Very Likely (5).
- **Operational Failure**: Considers whether **Standard Operating Procedures (SOPs)** are developed and followed, or not.
- **Inappropriate Design**: Assesses if systems are designed for a more severe duty than experienced, versus being constructed to standards lower than the current norm.
- **Materials/Parts**: Evaluates the quality of parts/material compared to industry norms, and if severe service conditions apply.
- **Competence of Operator**: Determines if operators are well-trained and skilled, or untrained and unskilled.
- **Likelihood/Probability (L) for Residual Risk**:
    - 5: Occurs on a monthly or more frequent basis at SNGPL.
    - 4: Occurs between once in a quarter and once in the last 6 months at SNGPL.
    - 3: Occurs between once a year and once in the last 3 years at SNGPL.
    - 2: Has occurred at least once in the last 5 years at SNGPL.
    - 1: Has occurred at least once within industry history.

This Likelihood/Probability scale is a component of the **Risk Assessment Chart (SNGPL-HPR01-CH-001)**, which provides guidelines for assessing risks [109, 7.6]. The overall risk is determined using the formula **R = L x H**, where L is the Likelihood and H is the Effect on Health. A risk rating of 9 and above is considered unacceptable and needs to be controlled.

EFFECT ON HEALTH / LIFE (H)

5 Injuries or illness involving permanent total disability, chronic or irreversible illness or death.

4. Injuries / illness resulting in permanent partial disability.

3. Injuries / illness requiring in hospitalization or temporary reversible illness. 2.

Minor injuries / illness requiring only minor supportive treatment.

1. Cause no effect

OVERALL RATING OF RISK (R)

The overall risk is determined as per below mentioned formula: **Risk =**

Likelihood (Effect on health)

R = L X H

Risk rating 9 and above should be considered unacceptable risk and needs to be controlled

The excerpt presents a **Hazard Identification Check Sheet for OH&S** used by Sui Northern Gas Pipelines Limited (SNGPL). It is designed to identify potential hazards across various categories at a specific site, process, activity, or task.

The check sheet includes fields to record the following information:

- **Site/Process/Activity/Task Details**:
  - Location
  - Description
  - Duration
  - Number of personnel working
  - Tools/Equipment Used
- **Hazard Identification**:
  - The form lists a variety of hazards, categorized into types, with a Yes/No checkbox for each to indicate its presence.
  - The different categories of hazards listed in the checklist are:
    - **Ergonomic Hazards (ERG)**: Examples include poor workplace design, inappropriate posture, and handling loads.
    - **Fall Hazards (FAL)**: Examples include foreign objects on walking surfaces, uneven surfaces, slippery surfaces, and working at height.
    - **Mechanical Hazards (MEC)**: Examples include body contact with sharp edges, shearing machine hazards, crushing hazards, and unguarded machines.
    - **Heat & Temperature Hazards (HAT)**: Examples include heat conduction, heat convection, and excessive exposure to the sun.
    - **Pressure Hazards (PRE)**: Examples include design/construction errors, overpressure, and mechanical breakdown.
    - **Electrical Hazards (ELE)**: Examples include non-insulated wire, absence of earthing, and static electricity discharge.
    - **Pneumatic Hazards (PNE)**: Includes compressed air lines.
    - **Impact & Acceleration (IAA)**: Includes falling objects and the movement of lifters/cranes/vehicles.
    - **Toxicity & Explosion (TOX)**: Includes airborne toxic substances and spills from containers.
    - **Radiation Hazards (RAD)**: Includes radiography, handling radioactive material, UV radiation, and electromagnetic radiation.
    - **Chemical Hazards (CHE)**: Includes irritants, toxic substances, and carcinogens.
    - **Fire Hazards (FIR)**: Includes hot work, open fire, and vehicle movement near flammable vapors.
    - **Noise Hazards (NOI)**: Includes prolonged exposure to noise levels greater than 85 dBA without PPE.
    - **Vibration Hazards (VIB)**: Includes the use of power tools and maintenance work.
    - **Biological Hazards (BIO)**: Includes biological waste, drugs and Virus, Bacteria, Parasites, Insects, Poisonous or Diseased animals.
    - **External Hazards**: Includes insecure area.
    - **Other Hazards**: Includes mental stress, fatigue and Radiations due to Visual Display Units (VDU's).
- **Signatures**:
  - The form requires signatures from the First Line Executive, HSE Executive, and Sectional In-charge, along with their names and designations.

The completed checklist is used as part of the **OH&S risk assessment process** to identify and mitigate hazards, as outlined in SNGPL's OH&S procedures.

The excerpt from the **Hazard Identification Check Sheet for OH&S** lists various electrical, pneumatic, impact & acceleration, toxicity & explosion, and radiation hazards. This form is used by Sui Northern Gas Pipelines Limited (SNGPL) to identify potential hazards at a specific site, process, activity, or task.

Here's a breakdown of the hazards listed:

- **Electrical Hazards (ELE)**:
  - Non-insulated wire
  - Deteriorated/loose wire
  - Absence/inadequate earthing
  - Working with electrical equipment on a damp floor
  - Static electricity discharge
  - Lightning strikes
  - Absence of explosion/fire-proof devices
  - Working near electrical installation
  - Inadequate support of pressurized pipelines
- **Pneumatic Hazards (PNE)**:
  - Compressed air lines
- **Impact & Acceleration (IAA)**:
  - Falling objects from height
  - Falling objects on a moving machine
  - Movement of Lifters/cranes/vehicles
- **Toxicity & Explosion (TOX)**:
  - Airborne toxic substances
  - Spills from container or damage to a pipe carrying toxic substance
  - Improper storage and handling
  - Leakage of oxygen diluting gases
  - Lack of ventilation in rooms containing toxic substances
  - Un-insulated source carrying current / charge / spark
- **Radiation Hazards (RAD)**:
  - Radiography
  - Handling & storage of radioactive material
  - UV radiation (Laser, welding arcs, UV lamps, high-temperature processes)
  - Electromagnetic radiation generated from power lines

The document SNGPL-HPR01-F-001 is designed to identify these and other potential hazards so they can be addressed as part of SNGPL's OH&S risk assessment process.

The excerpt from the **Hazard Identification Check Sheet for OH&S** lists various chemical, fire, noise, vibration, biological and external hazards, in addition to oil burners and metal parts cleaning. This form is used by Sui Northern Gas Pipelines Limited (SNGPL) to identify potential hazards at a specific site, process, activity, or task.

Here's a breakdown of the hazards listed:

- **Chemical Hazards (CHE)**:
  - Irritant
  - Toxic
  - Carcinogenic
  - Spillage / loss of containment
- **Fire Hazards (FIR)**:
  - Hot work

    - Open fire
    - Vehicle movement near flammable vapors
    - Smoking
    - Use of mobiles near flammable environment
    - Static charge
    - Oil Spillage /Gas Leakage / loss of containment
    - Lighting
    - Explosion
    - Improper storage of flammable materials
- **Noise Hazards (NOI)**:
    - Prolonged exposure to noise levels greater than 85 dBA without PPE
- **Vibration Hazards (VIB)**:
    - Use of power tools
    - Maintenance work
- **Hazards**:
- Oil Burners
- Cleaning metal parts
- **Biological Hazards (BIO)**:
    - Biological waste
    - Drugs (antibiotics etc)
    - Virus, Bacteria, Parasites, Insects, Poisonous or Diseased animals
- **External Hazards**:
    - Insecure Area (Bomb Threat, kidnapping, Theft etc)
- **Other Hazards**:
    - Mental Stress
    - Fatigue
    - Radiations due to Visual Display Units (VDU’s)

The document SNGPL-HPR01-F-001 is designed to identify these and other potential hazards so they can be addressed as part of SNGPL's OH&S risk assessment process.

1.0 PURPOSE:

The purpose of this procedure is to ensure that repair, maintenance, modification or construction work in Transmission, Distribution & Projects is carried out safely & does not result into any injury, fire, property damage, material loss or an environmental incident.

2.0 SCOPE:

It covers all sites of Transmission, Distribution & Projects Department for the activities mentioned in Annexure "A", "B" & "C".

3.0 DEFINITION, ABBREVIATIONS & CONCEPTS:

PPE: Personal Protective Equipment

Explosivity: Tendency to undergo violent or explosive decomposition under appropriate conditions of reaction or initiation.

REQUIREMENTS: 4.0

Personal Protective Equipments

Tool Box

Fire Fighting Equipment

Mobile Communication Equipment

Explosivity Test Meter

Warning signs/ flashing cones / Barricading Tapes

RESPONSIBILITIES: 5.0

5.1 Focal Point will ensure that the system is in place and all required resources are available to the concerned/ available staff.

5.2 Section Head will ensure that resources are provided and monitoring of safety check list is carried out.

5.3 Executive (If available at site) / Site supervisor will ensure that safety check list is filled and the job is carried out in a safe manner.

5.4 HSE department will provide guidance to the department to reduce the potential risks for the execution of job.

5.5 HSE department will review & update the procedures.

6.0 PROCEDURE:

6.1 Separate forms for the Transmission, Distribution & Projects sites have been developed.

6.2 HSE Focal Point shall ensure that all the tools are inspected once in a month & record is maintained on **Monthly Tools Inspection checklist**, **(SNGPL-HPR003-F-004)**. All broken tools shall be returned immediately to stores for replacement. Store Department shall be responsible to segregate the broken / damaged tools in a separate place with proper identification.

6.3 For each activity site supervisor will ensure that the recommended form is used.

6.4 Site supervisor will ensure that all the requirements for the specified job as mentioned in Annexure "A", Annexure "B" & Annexure "C" has been fulfilled, e.g. Provision of PPE's, Fire Fighting Equipment etc.

6.5 Site supervisor will ensure that the necessary precautionary measures have been adopted before the execution of job.

6.6 Site supervisor will brief the executor about the hazards associated with the job and the precautions taken according to check list to mitigate these hazards.

6.7 Site supervisor / Executive will fill the checklist before starting the job.

6.8 Filled check list after the completion of job is to be kept in Record.

6.9 Number of check lists filled in a month will be mentioned in monthly HSE Report.

7.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

7.1 ISO 45001:2018, Clause 8.1

8.0 RELATED DOCUMENTS:

List of Jobs Transmission	(SNGPL-HPR-003-Annexure-A)
List of Jobs Distribution	(SNGPL-HPR-003-Annexure-B)
List of Jobs Projects	(SNGPL-HPR-003-Annexure-C)
Safety check list for Transmission	(SNGPL-HPR003-F-001)
Safety check list for Distribution	(SNGPL-HPR003-F-002-A)
Safety check list for Distribution	(SNGPL-HPR003-F-002-B)
Safety check list for Distribution	(SNGPL-HPR003-F-002-C)

Safety check list for Projects (SNGPL-HPR003-F-003-A)

Safety check list for Projects (SNGPL-HPR003-F-003-B)

Safety check list for Projects (SNGPL-HPR003-F-003-C)

Safety check list for Projects (SNGPL-HPR003-F-003-D)

Safety check list for Projects (SNGPL-HPR003-F-003-E)

Safety check list for Projects (SNGPL-HPR003-F-003-F)

Safety check list for Projects (SNGPL-HPR003-F-003-G)

Safety check list for Projects (SNGPL-HPR003-F-003-H)

Safety check list for Projects (SNGPL-HPR003-F-003-I)

Safety check list for Projects (SNGPL-HPR003-F-003-J)

Safety check list for Projects (SNGPL-HPR003-F-003-K)

Safety check list for Projects (SNGPL-HPR003-F-003-L)

Safety check list for Projects (SNGPL-HPR003-F-003-M)

Monthly Tools Inspection checklist (SNGPL-HPR003-F-004)

1. Welding / Hot Welding

2. Sleeving

3. Hot Tapping

4. Stoppling

5. Commissioning / Decommissioning

6. Pigging

7. Coat / Wrap

8. Lowering of Live Lines

9. Hot cutting and Cold Cutting Operations.

10. Metering

11. Radiography

12. Maintenance of valve assemblies

Separate checklists attached for Serial # 4 and 9 1.

Construction of Mains

2. Tie – Ins

3. Commissioning

4. Coat / Wrap and Dope Yard

5. Excavations

6. Welding

7. Testing

8. Construction of Service Lines

9. Metering

1. Blasting

2. Excavation

3. Stringing

4. Lowering-In

5. Grading

6. Welding

7. Radiography

8. Back Filling

9. Tie-Ins

10. Crossings (River / Canal/ Nullah)

11. Testing/ Pigging

12. Working near overhead Power Transmission Lines 13.

Boring

The excerpt presents a **Safety Check List for Distribution**, specifically for the activity/job of **Cleaning, Coating, and Wrapping of Line Pipe at a Dope Yard**. It appears to be a checklist to be filled out by a supervisor or person in charge at the site. The checklist includes the following items:

- Is a copy of the **SOP available** with the team for the specific job?
- Is **fire-fighting equipment placed close by**?
- Is the **area cordoned off**?
- Are **electrical switches tagged**?
- Are all **necessary equipment/tools required for the job available and in safe working condition**?
- Is **required Personal Protective Equipment available**?
- Is **someone assigned the responsibility of continuously monitoring the situation**?
- Are **all possible sources of ignition in control**?
- Are **necessary precautions being taken in handling, hauling, loading, unloading, and placing the pipe**?
- Is **pipe stacked on an even base in an orderly fashion**?
- Are **vehicles and equipment placed at a safe distance from the job site and parked aside and job is being carried out causing least hurdle to traffic flow**?

The supervisor/executive present at the site is to fill out this checklist before starting the activity.

.

The excerpt details a **Safety Check List for Distribution** with a focus on **Metering** activities. It is intended to be completed by the supervisor or person in charge at the site.

The form includes fields for:

- Name of Supervisor/In-charge at Site
- Designation and SN (Serial Number)
- Section

The checklist includes the following safety measures:

- Is a copy of the **SOP available** with the team for the specific job?
- Is a **relevant approved drawing available at site**?
- Are **all relevant valves checked** and all relevant isolating valves closed, tagged, and blinds inserted where necessary?
- Is the **right person doing the right job**?
- Has the **explosivity test been carried out**?
- Is the **working area properly isolated/ cordoned off** by using reflecting cones and barricading tape, and are Caution/Warning sign boards installed at both ends of the working area?
- Is **fire-fighting equipment (fire extinguisher) placed close by** and in good working condition?
- Are **all required equipment/tools for the job available and in safe and good working condition**?
- Is **required Personal Protective Equipment (PPEs) available**?
- Is **someone assigned the responsibility of continuously monitoring the situation**?
- Are **explosion-proof tools and lights being used** for the job?
- Are **all possible sources of ignition in control** (e.g., smoking, mobile phones near live lines, etc.)?
- Are **vehicles and equipment placed at a safe distance** from the job site and parked aside, and is the job being carried out causing the least hurdle to traffic flow?
- Is **adequate ventilation provided** for the job being carried out in a confined area?
- During air testing, drilling, purging, and commissioning of TBS, are **all working personnel at a safe location**?

The form also lists the following activities to be carried out:

1. Installation of CMS
2. Testing
3. Purging
4. Painting
5. Testing/Purging and Commissioning of TBS
6. Modification/ Maintenance of TBS/CMS/pressure regulating valve
7. Any other (to be specified)

There is also a space for signatures of the Supervisor and Executive In-charge. The checklist is to be filled out before starting the activity by the concerned supervisor/executive present at the site.

The excerpt provides a **Project Safety Check List specifically for Blasting operations**, intended to be completed by the supervisor or person in charge at the site.

The form includes fields for:

- Name of Supervisor/In-charge at Site
- Designation and SN (Serial Number)
- Date and Location

The checklist includes the following safety measures:

1. Is rock drilled to appropriate depth and proper charge placed in hole?
2. Are recommended personal protective equipment in use?
3. Is area cordoned off?
4. Is everybody present at the site understands blasting signals?
5. Is everybody at the site instructed to remain at least 300 meters away from the blasting zone?
6. Are all communities notified around the area of the blasting zone?
7. Are necessary precautions being taken to transport, handle, and store explosives according to regulations?
8. Is everyone instructed not to return to the blast zone until all clear is signaled?
9. Is it ensured that smoking is not carried out in the blast zone?
10. Is it ensured that loaded holes never remain unattended?
11. Is the person carrying out blasting is certified or competent and experienced?
12. Are warning signs detailing the blasting operation erected on all accesses to the blast area?
13. Are necessary precautions taken to minimize flying rocks?
14. Is everyone instructed not to remove, relight, and disturb any fuse or any part of a misfired charge?

The form also has space for the signatures of the Supervisor and Executive In-charge. The checklist is to be filled out before starting the activity by the concerned supervisor/executive present at the site.

The excerpt provides a **Project Safety Check List for Excavation**, intended to be completed by the supervisor or person in charge at the site.

The form includes fields for:

- Name of Supervisor/In-charge at Site
- Designation and SN (Serial Number)
- Date and Location

The checklist includes the following safety measures:

1. Are **required personal protective equipments in use**?
2. Is **everyone instructed to stay within the operator's line of vision**?
3. Are **steps/slope provided in the ditch for ease of entry/exit**, especially for emergency rescue?
4. Is the **trench being supported properly**?
5. Is **everyone instructed not to walk on material over the ditch and on the edges of the ditch**?
6. Are **all lines (communication, gas, water, electricity) identified prior to the start of excavation**?
7. Is it ensured that **pointed tools are not being used to locate the underground lines**?
8. Is **everyone instructed not to attempt rescue with mechanical equipment if any excavation fails**?

The form also has space for the signatures of the Supervisor and Executive In-charge. The checklist is to be filled out before starting the activity by the concerned supervisor/executive present at the site.

1.0 PURPOSE

To establish a procedure for SNGPL employees in order to defines the guidelines regarding general safety rules.

2.0 SCOPE

This Procedure is applicable to all employees (direct or indirect) of SNGPL. .

3.0 DEFINITIONS

HSE	Health, Safety, Environment
HOD	Head of Department

4.0 RESPONSIBILITIES:

4.1 HSE Focal Points are responsible for overall implementation of this procedure. **4.2** HSE Engineers are responsible for imparting necessary HSE trainings to concerned.

5.0 PROCEDURES

5.1 GENERAL SAFETY

- Employees must know and observe all safety rules applicable to their work.
- All incidents involving near miss, minor injury, lost work day injury, fire, equipment damage, ruptures or substantial emissions must be reported to the supervision immediately.
- All unsafe conditions must be reported /corrected at the earliest.
- The following are prohibited on the job.
    - Horseplay or fighting.
    - Running or jumping except in extreme emergencies.
    - Firearms.
    - Smoking outside areas designated for the purpose.
    - Tampering with equipment.
- Employees must be properly clothed while at work, for example, loose clothing, dangling sleeves, neckties, etc., must not be worn when working in the operating areas.
- Employees should observe all regulatory signs at all times.
- Employees must follow prescribed job/operating procedure for carrying out various jobs.
- Employees should use proper tools required for the job.
- Any person present in or passing through an area must observe the rules applicable in that area.
- Equipment must not be operated unless all guards are in place.
- Guards should always be reinstalled immediately after maintenance/servicing of a machine.
- Employees should keep clear of suspended loads, or work being performed at elevations.

- Safety interlocks must not be bypassed except by written permission of supervision.
- Only authorized personnel may operate plant equipment.
- In the areas where Work Permit system is effective, proper work permit must be obtained before commencing any kind of maintenance work.
- All installations / equipments / doors / machinery / must be labeled.

5.2 HOUSE KEEPING, FIRE PREVENTION & CONTROL

- Good housekeeping standards must be maintained at all times.
- Each employee must clean up his job area at the end of the day or when the job is completed.
- Materials must not be placed where it will obstruct doors, aisles, passageways, stairs, platforms, ladders and Fire Fighting equipment.
- Material should not be left where it will create tripping hazard.
- Clean up any spills promptly.
- Fire Fighting equipment must not be moved from designated location unless there is an emergency.
- Employees must know the locations of fire extinguishing equipment and know how to use it effectively.
- Only dry powder and carbon dioxide (CO_2) should be used to extinguish an electrical fire. Water is hazardous because it is a conductor of electricity and for this reason can not be used on an electrical fire.
- Know your specific duties as per fire fighting procedure.
- Partially used or empty extinguishers must be recharged promptly.
- At all times know the exact location of exits by which you can leave an area.
- Switch off engines and engine driven equipment when refueling vehicles.

5.3 ELECTRICAL SAFETY

- Only authorized and qualified personnel are permitted to perform work of an electrical nature.
- As far as possible, electricians should avoid working on electric equipment which is energized.
- Before the start of an electrical job, the circuit breaker or isolating device should be switched off and tagged.
- Live circuits should be handled carefully despite presence of protective insulation. The authorized employees performing electric work should use rubber gloves and have their sleeves rolled down.
- Employees performing electric work should ensure that the surroundings of electric installations stay as dry as possible.
- Electrical equipment, stationery or portable, must be properly grounded.
- Electric sub-stations shall be kept locked. Only authorized persons are permitted inside electric sub-stations.
- Sub-stations shall be kept clean and free of dirt and moisture.
- Sub-stations are not to be used as a materials store room.

5.4 COMPRESSED CYLINDERS (OXYGEN/ ACETYLENE/ CO2 / LPG)

- All cylinders shall be labeled properly.
- Empty cylinders must be placed / stored horizontally.
- When in transit or in use or stored, filled cylinders must be placed in an upright position and properly secured so they can not fall or be knocked over. Filled cylinders should be chained to a wall for safety; cylinders are best chained individually to the wall to allow one to be selected without unsecuring the rest.
- Filled Cylinders shall not be stored or placed near hot equipment / places where high temperatures may occur, near live electrical equipment / grounding cables or in direct sunlight.
- Cylinders shall not be dropped, struck against or permitted to strike each other violently. Damage to the cylinder or its valve could result in disastrous jet propulsion of the cylinder.
- Cylinders shall never be moved without first removing the regulator.
- Caps shall always be put on cylinders when the cylinders are not in use or are being transported.
- Oxygen cylinders should be handled properly so that oil, grease or any other readily combustible substance does not come in contact with oxygen.
- All cylinders shall be tested as per manufacturer's recommendation / NFPA / EN Codes.
- Do not use compressed air for any purpose other than for which it is intended.
- Never use compressed air to blow off dust from your clothes or body. This can cause skin or other injuries.
- Do not clean machines and work benches with compressed air, use a brush or vacuum cleaner.
- Make sure that your compressed air tools, hoses and fittings are working properly. If not, report the fault to your Incharge.
- Do not leave hoses lying around for others to trip over.

5.5CNG CYLINDERS OF VEHICLES:

- Use only the approved brands, imported, seamless brand New CNG cylinders manufactured as per **NZS 5454-1989 standard**.
- Purchase and install it from the CNG Stations authorized/ licensed by OGRA.
- Get CNG cylinder test certificate from the CNG licensee after conversion of vehicle to CNG.
- Get vehicle's CNG system inspected **at least once in a year** from trained personnel available at CNG Stations for examination of the cylinder, piping CNG kit, all components, leakage testing as well as performance of the CNG system to ensure its safe operation.
- Never ask for refueling beyond the allowable maximum pressure of **200 Bars** under any circumstances. In case any CNG station is found dispensing CNG at excess pressure, it may be reported to OGRA for strict action against the station to ensure public safety. Do not smoke during refueling in the vehicle.

- Ensure that the CNG cylinder installed in the vehicle is within the periodic test life, **which is 5 years**. In order to determine the validity of the cylinders, approach to nearest CNG Station or Hydro Carbon Development Institute of Pakistan (HDIP's) office. In case the cylinder requires testing contact nearest HDIP testing labs.

5.6 POWERED TOOLS

- Check cords for mechanical damages prior to use. Defective cords may cause serious electric shocks, painful burns or even can be fatal.
- Keep both the number and length of extension cords to a minimum.
- Do not lay cords across aisles and traveling areas since it creates tripping hazards. Keep cords away from heat and chemicals. Damaged cords are no longer water resistant. The insulation can absorb water resulting in a short circuit.
- Electric hand tools which are not explosion proof should never be used in an explosive environment.
- Goggles or face shields should be worn when using electric hand tools.
- Before using, the tools must be checked for any defects and returned if found defective.
- Users are not allowed to perform any repair to pneumatic and electrical hand tools, unless authorized to do so.
- Only skilled technicians are allowed to renew grinding wheels.
- Maximum speed of a grinder should not be exceeded, wherever specified.
- Excessive force which may result in jamming of the grinder should be avoided. This can cause cracks and breakage of the wheels which may seriously injure the user.
- While using jack hammer make sure the chisel used is properly secured. Care should be taken to limit the chips from flying by using portable shields.
- Safety guards must be used with grinders.

5.7 WELDING SAFETY

- Welder should ensure that his working area is not wet.
- Welder must be wearing proper clothing.
- Welding near flammable or combustible material should be avoided. Any flying sparks and hot slag should be contained
- Fire extinguisher must be kept close by for any eventuality.
- Ensure that cables and connections are in good condition and firmly attached.
- Do not use gas cylinders as work supports. Do not let gas cylinder be exposed to heat.
- Open cylinder valves slowly and close valves when gas is not being used.
- Make sure the welding equipment bench or work piece are properly earthed particularly when two or more welding machines are connected to the same structure.
- When grinding, chipping or inspecting a hot weld, protective glasses must be worn.

5.8 DRIVING SAFETY

- At beginning of each day, the driver shall check the following:
    - Fuel
    - Water

- Engine Oil which should be maintained at maximum level.
- Checks made to see that there are no loose parts or abnormal noises.
- Brakes and steering: To see that these are in working order.
- Examine tyres for cuts, flints. Make sure tyres have sufficient tread and are properly inflated.
- Lights, traffic indicators, wind screens and wipers to be in working order. Regularly clean wipers with a damp cloth.

- No vehicle shall be used on the public highway unless:
  - The driver is in possession of a valid driving license.
  - The vehicle is licensed for use on public highway and equipped with number plates at rear and front, and complies with the Government Road Traffic requirements.
- Always obey the speed limits; driving too fast is the No. 1 cause of accidents.
- Motorcyclists should use the lane designated for lesser speed. Horseplay or high speed on motorcycles is very dangerous leading to serious accidents.
- Overtaking should not be done at cross-roads, corners or other dangerous points.
- All road signs shall be observed and specific applicable rules should be followed
- Drivers and passengers must wear seat belts or safety helmet in case of motorcycles.
- No vehicle shall be driven into an area where explosion or fire risk exists such as operating areas of Compressor Stations, unless specifically authorized to do so through a work permit.
- Before reversing a vehicle, the driver shall take particular care to ensure that there is no obstruction in the path.
- Reflectors must be present on back of welding plants / compressors.
- Valid and approved Vehicle Fitness Certificate must be present in vehicles.
- The best advice is to avoid driving in bad weather (Rain, Fog, Snow etc), if it is still important to drive follow the safety instructions given below:

Driving Safety in Rain;

a. Drive in the tyre prints of the car ahead. During rain, a car / motorcycle is riding on a thin layer of water between the tyres and the road. The water in tyre prints has already been displaced, so the tyres get better road grip.

b. If in a skid, do not brake heavily, jerk the steering wheel or panic. Turn steering wheel into the direction of the skid and gently brake.

c. Ensure that the wipers are working properly. Drivers in accident say they couldn't see because their wipers smeared their windshields on a rainy day.

d. Reduce speed and maintain sufficient distance in between vehicles so that safe distance is maintained in case of emergency stop. Fog creates a visual illusion of slow motion when vehicle may actually be speeding.

e. Be aware of the spray coming from passing and oncoming vehicles. It may blind the driver temporarily, so anticipate this by increasing the speed of the wipers.

f. Never drive through deep water on a flooded road. If drive through deep puddles, gently press the brake a couple of times afterward to dry the brakes.

g.Use the right edge of the road or painted road markings as a guide.

Driving Safety in Fog;

a.In thick fog, drive with reduce speed and crack open window and listen for traffic you cannot see. Never drive with just parking/ fog lights on.

b.Drive with lights on low beam. High beams will only be reflected back off the fog and actually impair visibility even more.

c.Be cautious, fog can become thicker without warning and without being noticed until it is too late to react.

d.Know how to defrost the car. Before turning on the defroster and blower, move the heat control to "hot" and allow the engine to warm up first. If the windshield starts to fog on the inside, open a side window slightly and turn the defroster to a higher speed. Use air conditioner, if possible, to reduce humidity and moisture collecting on the window.

Driving Safety in Snow;

a.Tyre chains are recommended during snow storm, packed snow on roads or when tyres grip on road reduces or when it became difficult to control the vehicle.

b.Tyre chains should always be carried in the trunk during the appropriate times of the year and only mounted on the vehicle when required by driving conditions or required by law.

c.Make sure to fit the chains to the driving wheels, which are the back wheels on rear wheel drive cars and front wheels on front wheel drive cars. If in doubt, check in the car user's manual. To retain as much of the normal handling characteristics of 4WD vehicles as possible, tyre chains should be installed on all four tyres.

d.Make sure the chains are suitable for the wheel diameter and tyre size of the vehicle. If possible, practice fitting the chains in good conditions, so that you understand how to fit the chains and won't be placed in a difficult situation in bad weather conditions.

e.Tyre pressure should be 25 PSI or higher when using chains. Tyre manufactures recommend that cars with radial tyres shouldn't travel faster than 40 km/h when fitted with chains. Stop and check the tension of the chains after driving about 200 meters.

5.9 LADDERS

- Ladders must only be used to gain access or for carrying out simple operations.
- Ladders should not be used as a replacement of scaffolding. Wherever justified proper scaffolding as per standard should be provided.
- Ladders must be inspected by the user for defects prior to use. Defective ladders shall not be used and must be repaired.
- A straight ladder must be placed with its feet approximately ¼ of the height where ladder is supported.
- Ladders must be secured at the top (preferably) or at the bottom, or held by another employee while in use to prevent slippage.

- When ascending or descending ladders, the user must face the ladder and keep a firm grip on the rungs.
- When working from ladders, these shall be placed so that the work is safely within reach.
- Ladders must not be placed in front of doors, in passageways or in the vicinity of vehicular traffic unless appropriate barriers and / or warning signs are erected.
- Metal ladders shall not be used inside electrical sub-stations, enclosures or at areas where electrical contact could be made.
- Ladders should never be painted as this may hide defects.
- Portable ladders must be taken down and stored at the designated places when the job is done.

5.10 HOISTING AND RIGGING

- Hoisting and rigging equipment must be checked for any defects prior to use. Any defects found should be reported immediately to the supervisor.
- All power driven hoists must be operated by qualified personnel.
- Power hoists must be properly installed and anchored to prevent movement when operating and to prevent the hoists from slipping.
- During hoisting operation, all personnel must stay clear of loads and no one should be beneath the load or boom.
- Guy lines must not be attached to equipment, pipelines, tanks, or other supports for anchoring unless waiver is obtained from an authorized person.
- Slings, rope, cable, and chain must be properly protected from sharp edges before taking a strain. Care must be exercised to prevent kinks in cables or ropes.
- Standard hand signals must be used when directing hoisting operations.
- The signal man should always stay in clear view of hoist or crane operator, and at a safe distance away from the load being lifted or hoisted.
- Hoisting of personnel must only be done in a protective working cage, wearing of safety belt is mandatory.

5.11 HEAVY MOBILE EQUIPMENTS

- The driver must possess a valid driving license.
- Loads must be secured while being transported. A warning mark must be used on any load that extends beyond the sides, front, or rear of a vehicle.
- When a truck is being loaded or unloaded by a crane or power shovel, all occupants must dismount from the truck and stand clear of the load.
- Riding on crane blocks or crane loads is prohibited.
- Operators must not leave crane cabs without disengaging the clutch and engaging all safety locks.
- Cranes with long boom must be secured against high winds.
- Crane booms and booms on the motorized equipment must not be operated closer than six feet from live high voltage overhead electrical wires.
- Operators must check wire ropes daily.
- Safety switches should not be bypassed.

- Controls of the crane should be tested for proper working.
- Machine load rating should never be exceeded.
- Do not use hoist line around load, always use certified wire slings.
- When a driver leaves his vehicle, the hand brakes must be set. Whenever possible, equipment must not be left unattended while the motor is running.
- Vehicles must not be reversed until the operator has checked to see if the way is clear. If unable to see behind his vehicle, the operator must enlist the aid of another person to act as a guide while backing-up.
- Before doing any work under a vehicle, it must be properly blocked. Jacks are not adequate.
- Reverse horn must be functional.
- Truck cranes must be properly blocked and be on firm footing before lifting a heavy load with a low boom. Employees must stand clear of the crane's swing and keep out from under suspended loads.
- Forklift operators should ensure that:
    - Load is not in raised position during travel.
    - Load does not obstruct his vision.
    - Horn is used frequently at corners/bends.

5.12 OFFICE SAFETY

- A high standard of good housekeeping should be maintained in the office.
- Office floors and stairways should be kept dry and free from tripping hazards.
- Drawers of office desks and filing cabinets should not be left open after use. Opening too many drawers on one filing cabinet at the same time may cause the cabinet to overturn.
- Filing cabinets should be located so that the drawers do not open outwards into aisles.
- Telephone wires and cables to appliances should be placed in a manner that they do not pose tripping hazards.
- Electrically powered office machines must be correctly installed. Electric cords and plugs should be examined regularly and should be replaced if damaged or worn.
- Repairs to office machines must not be attempted by unauthorized personnel.
- Damaged furniture should be repaired immediately.
- Know what to do in case of fire. Know your building evacuation plan.
- The office should be adequately lighted including all stairways, corridors, etc. Lighting should be arranged to avoid dark shadows in access ways.
- Many accidents have been caused by people tilting their office chair too far backwards.
- Avoid use of pins for fastening papers. Use paper clips or staples.
- To avoid cuts, pickup paper at the corners and not at the sides.
- Employees should not walk about carrying pens, pencils knives, or scissors with points exposed.
- Do not use waste-basket as an ash-tray.
- If work has to be done at a height, office chairs, boxes etc. should not be used as a make shift arrangement. Proper step ladder or a step stool should be used.

- Heavy objects should not be placed on top of almirahs or other high shelves.
- Before leaving office after work all appliances should be switched off and plugs disconnected from the mains.

5.13 PERSONAL PROTECTIVE EQUIPMENT

- Employees should wear prescribed Personal Protective Equipment in the designated areas.
- Employees should ensure that the personal protective equipment is kept in neat and clean condition.
- Any damage to personal protective equipment must be brought to the attention of supervisor.
- Employees who are issued Uniforms by the Company should wear them while on duty.
- Employees who are issued Safety Shoes by the Company should wear them while on duty.
- Contract employees should also wear all specified personal protective equipment in the designated areas.

5.14 ENVIRONMENTAL PROTECTION

- Make sure that the limits of National Environmental Quality Standard (NEQS) are not exceeded with regards to effluents, emissions and noise.
- The construction of any new project should only be commenced after conducting the Initial Environmental Examination/ Environmental Impact Assessment (IEE/ EIA) and securing permission from the respective provincial Environmental Protection Agency (EPA).
- General principles of energy conservation must be followed.
- All gas turbines, power generating units and other fuel consuming equipments should be operated at high fuel efficiencies.
- Switch off AC and turn off the lights if you are leaving the room for extended period.
- When buying new electrical equipment, make sure it is energy–efficient, e.g. energy star for computers, energy saver bulbs, etc.
- The concept of 3R's for waste management must be followed. As for as possible all kinds of waste must be "Reduced", "Reuse" and "Recycled".
- Avoid wastage of paper. Use recycled paper whenever possible.
- Collect recyclable trash such as paper, newspapers, plastic bottles and soda cans in separate containers to facilitate economic recycling.

5.15 OTHERS

- Handling of pyrophoric dust, which is encountered at different stages of pipelines operations, should be handled in a very careful manner to avoid auto ignition in atmosphere.
- Employees should familiarize themselves with the proper techniques of lifting and carrying objects.

- Employees should not attempt to move furniture or lift other heavy objects which are beyond their strength.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1.ISO 45001:2018, Clause 4.4

7.0 RELATED DOCUMENTATION

7.1 Inspection Checklist of Portable Ladder (SNGPL-HPR-004-F001)

1.0 PURPOSE:

The purpose of this Procedure is to prevent occupational injuries and sickness to SNGPL employees by controlling occupational hazard; as far as reasonably practicable. PPEs should only be prescribed to provide additional protection, when a hazard continues to exist even after the following control measures have been applied in the following hierarchy of controls:

- Eliminate the hazard;
- substitute with less hazardous processes, operations, materials or equipment;
- use engineering controls and reorganization of work;
- Use administrative controls, including training;
- Use adequate personal protective equipment.

2.0 SCOPE:

These guidelines apply to all employees, operations, functional areas and offices throughout SNGPL and address only head, eye, face, ear, respiratory, hand and foot protection. Departmental PPEs assessment attached as **Annexure A, B, C, D, E, F, G, H**. PPEs assessment of any area / activity which are not covered in aforementioned Annexures shall be performed by the respective Focal Point.

3.0 definitions

The definitions related to health and safety include:

- **HSE Site Committee (HSC)**.
- **Occupational Health & Safety (OH&S)**: Refers to the health and safety in the workplace.
- **Hazard**: Defined as anything with a potential to cause harm or a working condition that can lead to illness, injury, or death of a person.
- **Personal Protective Equipment**: Equipment that protects employees from health and safety hazards resulting from contact with chemical, radiological, physical, electrical, mechanical, and other hazards that cannot practically be removed from the work area.
- **Worker**: All management/non-management persons on the payroll of SNGPL i.e. Executive, SN, or Casual.

4.0 RESPONSIBILITIES:

- HSE Department
- Focal Points
- All Employees

5.0 PROCEDURE:

5.1 HEAD PROTECTION:

5.1.1 Head protection is necessary in areas where there is a risk of injury from the following typical hazards.

- Falling or flying material.
- Sharp objects or corners at head level.
- Striking overhead beams or loads.

5.1.2Safety helmets / hats protect the head from impact and penetration. It is mandatory for employees as well as visitors to wear safety helmet in areas/ situations where the above mentioned hazards exist.

5.1.3 Color Coding will be as follows;

- White for executive and visitor
- Yellow for staff
- Blue for Quality Assurance
- Red for Fire Fighting Team

5.2 EYE PROTECTION:

5.2.1 Suitable safety glasses/ goggles shall be used when employees/visitors are exposed to the following typical hazards.

- Flying particles from chiseling, milling, sawing, turning, shaping, cutting, etc.
- Handling of chemicals/ chemicals dust.
- Use of pressurized air or pneumatic load.
- Handling of hot solids, liquids, or molten metals.
- Intense light radiation from gas or electric arc welding, oxygen cutting, laser use, etc.
- Repair or servicing of any vehicle.

5.2.2 Prevention of eye injuries requires that employees/visitors who may be in eye hazard designated areas/situations wear safety glasses /goggles. Safety goggles can also be used over sight glasses.

5.3 FACE PROTECTION:

5.3.1 Suitable face shields/visors shall be used when the employees/visitors are exposed to the following typical hazards.

- Flying particles.
- Handling of chemicals/ chemicals dust.
- Handling of hot solids, liquids, or molten metals.
- Gas or electric arc welding.
- Chemical gases or vapors.

5.3.2 Prevention of face injuries requires that employees/visitors who may be in face hazard designated areas/situations wear face shields/visors.

5.4 HEARING PROTECTION:

5.4.1 In areas/ activities where noise level cannot be reduced to acceptable level (80 dBA) through design improvement in the machines, use of hearing protection is mandatory for employees and visitors to avoid permanent impairment of hearing.

5.5 RESPIRATORY PROTECTION:

Proper respiratory protection is mandatory for employees/visitors where the following typical hazards for the respiratory system exist.

- Insufficient oxygen to maintain life.
- Particulate matter in surrounding air.
- Chemicals dust.
- Toxic gases.

5.6 HAND PROTECTION:

5.6.1 Suitable gloves shall be used when employees/visitors are exposed to the following typical hazards.

- Activities in which a potential threat of cuts, punctures and severe abrasions.
- Activities in which a potential threat of thermal or chemical burn.
- Activities in which skin can absorb harmful substance.
- While working on electric wires.

5.6.2 Hand gloves may be divided into three broad categories, as follows:

- General purpose gloves are intended for everyday use.
- Heavy duty gloves for heavy mechanical jobs or where sharp edged material is handled.
- Special purpose gloves e.g. electrical safety gloves (thin rubber gloves tested on a certain voltage), Gloves for handling hazardous chemicals (rubber gloves), welder gloves (leather gloves), heat resistant gloves (synthetic fiber), etc.

5.6.3 Gloves shall not be worn while working on rotating machines i.e. lathes, drills, grinder and other similar machines.

5.7 FOOT PROTECTION:

Safety shoes or boots are mandatory by employees/visitors where the followings typical hazards for foot injury exist.

- Work areas where carrying or handling materials i.e. packages, objects, parts or heavy tools etc.
- Activities where objects might fall onto the feet i.e. construction, excavation etc.
- Activities in which materials or equipment could potentially roll over the feet i.e. pipe handling etc.

5.8 UNIFORMS/ GENERAL CLOTHING:

5.8.1 Employees who have been provided company uniform shall wear the uniform.

5.8.2 Those employees who have not been provided uniform shall not wear loose or baggy clothing, turbans, and scarfs etc. while at work. Loose or baggy apparels are particularly very dangerous where moving or rotating machines are involved such as in machine shops, during construction, Compression Stations, Coating Plant, CP Plant and Co-Gen Plant.

5.9 STANDARDS:

All PPE will be of safe design and construction for the work to be performed and shall be maintained in a sanitary and reliable condition. Only those items of protective equipment that meet international standards will be procured or accepted for use.

5.10 PROCUREMENT / ISSUANCE / RECORD KEEPING:

5.10.1 Procurement

HSE department has been authorized by management on centralized budget control of Personal Protective Equipments (PPEs) for optimum and efficient utilization of budget. HSE Focal Points shall ensure timely procurement of PPEs for their respective areas through HSE department. Procurement of PPE's shall be carried out as per PPRA / Company rules.

5.10.2 Issuance

- Concerned executive is authorized to issue required PPEs to employees working under his domain. Issuance of PPEs is to be documented / maintained on PPEs Distribution Register which should be maintained as per attached PPEs Distribution Performa (SNGPL-HPR005-F001).
- Utilization period detail of PPEs is attached as **Annexure-F**.

5.10.3 Record keeping

- HSE department will keep record of PPEs procured through centralized procurement.
- First line executive is responsible maintaining PPEs issuance record.
- HSE Focal Point is overall responsible for record keeping of PPEs received from HSE department and issued at respective site.

6.0 REQUIREMENT OF, ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1 ISO 45001:2018, Clause 8.1.2

The related documents for PPE (Personal Protective Equipment) include:

- **SNGPL-HPR005-F001**: PPE's Distribution Proforma
- **Annexure A**: PPE's requirement for Compression
- **Annexure B**: PPE's requirement for Transmission
- **Annexure C**: PPE's requirement for Distribution
- **Annexure D**: PPE's requirement for Projects
- **Annexure E**: PPE's requirement for Coating Plant
- **Annexure F**: PPE's requirement for CMS (Central Meter Workshop)
- **Annexure G**: PPE's requirement for CCC (Corrosion Control Centre)
- **Annexure H**: PPE's requirement for Co-Generation B-2 (Head Office)
- **Annexure I**: PPEs Utilization Period

The **utilization periods** for various PPE (Personal Protective Equipment) are defined as follows:

- **2 years**:
  - Safety Helmet
  - Ear Muff
  - Face Mask (Half / Full)
  - Gloves Rubber – Electrical
  - Heat Resistance Gloves
  - Welding Shield with Hard Hat
- **1 year**:
  - Safety Shoes - (Executives / Casual)
  - Gum Shoes (Rubber)
  - Fluorescent Jackets
  - Safety Spectacles Black
  - Safety Goggles White
  - Glove Rubber - Chemical
- **6 months**:
  - Coverall / Dungaree (Casual)
- **2 months**:
  - Ear Plug with Cord
- **Undefined - depends on use**:
  - Barricading Tape
  - Glove Cotton (Pair)
  - Welding Gloves (Pair)
  - Filter (Particulate / Gaseous)
  - Safety Cones
  - Dust Mask
  - Welding Mask
  - Fire Blanket
  - Safety Harness

1.0 PURPOSE

To establish a procedure and define the requirements and responsibilities for the control of modifications to the installed / commissioned process equipment and pipeline network, in order to ensure that modifications are designed and implemented according to appropriate standards and do not compromise health, safety or environment and that their economic justification is adequately reviewed.

2.0 SCOPE

- This Procedure shall be applicable to all modifications carried out to installed/ commissioned process equipment and pipeline network in Transmission and Distribution (including Valve assemblies, SMS's, TBS's, CMS's, Regulating stations and Repeater stations) and within the boundary limits of Compressor Stations, CP Plant, Coating Plant and Co-Gen plant.

- This procedure does not authorize bypassing of any existing departmental requirement of taking necessary approvals for various types of modification.

.

3.0 definitions

The definitions related to **plant and equipment modification** include:

- **Health, Safety, Environment (HSE)**.
- **Head of Department (HOD)**.
- **Modification**: Any change, whether temporary or permanent, to plant and equipment, pipeline network, process materials, operating procedure, operating conditions which is outside the normal methods of operation and maintenance.
- **Emergency Change**: A change which must be implemented immediately, in an emergency situation, in order to prevent major injury or damage to personnel, environment, or equipment. An example is overriding the control action in the field by forcing actuated valves to stop, start, or divert flow.
- **Initiator**: An executive who initiates a Modification Form.
- **Documentation Controller**: Person responsible for maintaining records of various modifications within the respective department; may be an executive nominated by the Focal Point of that site.
- **Scrutiny Committee**: Nominated by the HSE Focal Point; the HSE Site Committee may be assigned this responsibility by the Focal Point; the initiator of the modification will also work as a member of the Scrutiny Committee for the review of the respective modification. The Scrutiny Committees in the respective areas will be responsible for carrying out the review of the modification, and in due course, at least two members will be provided with necessary training in Hazop.

.

4.0 RESPONSIBILITIES:

4.1 Related Focal Point
4.2 Emergency Committee

5.0 PROCEDURE

5.1 The Initiator shall fill in the top portion of the Modification Form and the items 1.1 to 1.2. He shall provide justification and description of the proposed modification, supported by sketches and other documentation.

5.2 The Initiator shall secure the approval of the Focal Point to refer/ take the proposal to the Scrutiny Committee for Review.

5.3 Scrutiny Committee shall fundamentally question whether the Modification is required at all. The Scrutiny Committee shall ensure that the Modification has been thoroughly defined and the justification is sound. It will review the economic viability and consider and define all possible hazards.

5.4 If the Scrutiny Committee is satisfied that the Modification is justified, the members will sign in the relevant space on the modification form and the form will be passed on to HSE Focal Point.

5.5 The HSE Focal Point will assign the concerned section/ department to develop the drawings (if required) and to carry out the Modification.

5.6 Subsequent to the commissioning, the respective HSE Focal Point will be responsible to ensure that various changes are made on all relevant drawings as well as in the operating/ maintenance procedures by all concerned.

5.7 The Modification Form along with all relevant documents/drawings will be sent to the respective Documentation Controller, who will keep these in the record. A copy of updated drawing of modification (as built) is to be sent to relevant department for their record.

5.8 After commissioning, the modification will be declared complete and will be accordingly signed off by the initiator on the Modification Form.

5.9 GENERAL

5.9.1 No modification work, except, in the event of emergency as described under 5.4 above, will be commenced without proper authorization as per procedure.

5.9.2All requests for modifications shall be documented and controlled using a Modification Form.

5.9.3The respective Document Controller shall be responsible for maintaining an up-to-date record of all modifications.

5.9.4As far as possible, the Authorized Signatory will not delegate his authority. However on occasions when an Authorized Signatory is clearly not available at site for extended period, his replacement, as authorized by the Focal Point shall be responsible to carry out the required functions.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

The related documentation regarding **Plant & Equipment Modification** includes the **Modification Form (SNGPL-HPR006-F-001)**. This is related to **ISO 45001:2018, Clause 8.1.1**. A **modification** is defined as any change, whether temporary or permanent, to plant and equipment, pipeline network, process materials, operating procedure, operating conditions which is outside the normal methods of operation and maintenance.

1.0 PURPOSE:

The purpose of this procedure is to ensure the safe operation of vehicles / abnormal vehicles, welding plants and compressors in order to prevent incidents and associated injuries / losses.

2.0 SCOPE:

This procedure will be applicable at all sites across the Company for all types of company owned / hired; vehicles / abnormal vehicles, welding plants and compressors.

3.0 DEFINITIONS, ABBREVIATIONS & CONCEPTS:

3.1 Abnormal Vehicles:

Abnormal vehicles are those vehicles defined by the site which need special consideration by virtue of their size, weight or the fact that they are capable of being extended outside their normal envelope. Examples of Abnormal Vehicles are:

- Mobile Cranes / Vehicles that have lifting facilities
- Heavy Vehicles
- Vehicles specially designed to carry skips and other containers
- Excavators & Dozers

3.1.1 Mobile Cranes

All vehicles equipped with jib equipment whether fixed or telescopic and capable of lifting loads by hoisting a block and hook system including heap arms mounted on Lorries.

3.1.2 Heavy Vehicles

Heavy Vehicles (including abnormal load) other than cranes are vehicles which exceed any one of the following:

a. Gross Weight of 44 tones
b. Length of 16.5 meters
c. Width of 2.9 meters
d. Height of 4.2 meters

3.1.3 Vehicles specially designed to carry skips and other containers

a. Prime mover with Trolley
b. Fork Lift Trucks
c. Pipe Layers etc.

3.1.4 Excavators & Dozers

An **Excavator** is an engineering vehicle consisting of an articulated arm (boom, stick), bucket & cab mounted on a pivot (a rotating platform) atop an undercarriage with tracks or wheels.

A **Dozer** includes a blade and all associated structural elements, normally mounted in front of a self-propelled machine for scrapping and pushing materials through forward motion of the machine.

Escort: 3.2

A banks man shall be given the task of escorting a vehicle while on the site.

3.3 **Freeways:**

Freeways are roads which are designated as suitable for Abnormal Vehicles to travel unescorted.

3.4 **Vehicle Accident:**

All minor or major accidents involving SNGPL owned vehicles or the vehicles engaged by the company for its operation.

3.5 **Fitness Certificate:**

Certificate of vehicle / abnormal vehicle and welding / compressor filled by concerned executive and approved by HSE department on monthly basis, prior to its operation based merely on general physical inspection. (Note: It does not certify any mechanical part / operation or any mechanical defect is not taken into consideration).

4.0 RESPONSIBILITIES:

4.1 Focal Point will ensure that the system is in place and all required resources are available.

4.2 Admin Officer, In-charge or Maintenance Engineer (ME) incase of construction spreads, will ensure that resources are provided as per Fitness certificates. On sites where Admin Officer is not posted, HSE Focal Point will ensure provision of resources as per Fitness certificate.

4.3 Executive / Supervisor shall acquire approval of Fitness certificates of concerned vehicle / abnormal vehicle, welding plant and compressor from HSE department and shall ensure that approved and valid Fitness Certificates are present in vehicle.

4.4 Concerned Executive / Incharge shall ensure that respective driver / operator are competent and trained.

4.5 HSE department shall approve validity for one month of each vehicle / abnormal vehicle, welding plant and compressor for its safe operation.

4.6 Admin Officer, In- charge will ensure:

- Monitoring of logbook on monthly basis.
- The driver / operator have a valid license for the specified categories of the vehicle.
- The driver / operator have a company ID Card.
- The driver / operator is qualified, experienced and fit to operate the assigned vehicle.
- The documents (including logbook) of vehicle are complete and available with the driver / operator.
- The driver / operator are given safety briefing / training of defensive driving courses on weekly basis.
- The vehicle emission and the noise test for the Company and the hired vehicle are carried out on annual basis.

4.7 Maintenance Supervisor shall maintain the preventive maintenance program that shall be applied to all Company owned vehicles / abnormal vehicles, welding plants and compressors in accordance with the manufacturer's specification and keep record in maintenance tracking system.

4.8 Concerned contractor shall be responsible for respective hired vehicles / abnormal vehicles, welding plants and compressors preventive maintenance program covering all mechanical and safety aspects.

4.9 Driver / Operator shall be trained, competent / certified and responsible for condition and operation within safe limits of respective vehicles / abnormal vehicles, welding plants and compressors.

4.10 HSE department will review & update the procedures.

5.0 PROCEDURE:

5.1 Transport / Maintenance supervisor shall ensure that all the requirements for the vehicles / abnormal vehicles, welding plants and compressors have been fulfilled.

5.2 Executive / In-charge shall ensure that the necessary precautionary measures have been adopted as mentioned in the **Vehicle/ Heavy Mobile Equipment Fitness Certificate (SNGPL-HPR-007-F-001)** and **Welding Plant / Compressor Fitness Certificate (SNGPL-GPR-007-F-002).**

5.3 Fitness Certificates shall be filled for each company owned / hired vehicle / abnormal vehicle, welding plant and compressor by the concerned executive with the help of concerned supervisor. Concerned executive will acquire approval from concerned HSE executive prior to its operation.

5.4 All company owned / hired; vehicles / abnormal vehicles, welding plants and compressors shall be operated after approval of HSE department.

5.5 Valid and approved Fitness Certificate is to be kept in respective vehicle / abnormal vehicle, welding plant and compressor.

5.6 Expired Fitness Certificates is to be kept in Record by concerned department for 6 months. Fitness Certificates of vehicle/ abnormal vehicle, welding plant and compressor engaged in any accident is to be retained and a copy is to be sent to HSE department.

5.7 Number of Fitness Certificates issued in a month will be mentioned in monthly HSE Report.

6.0 SAFE OPERATION OF LIFTING EQUIPMENTS:

6.1 GENERAL PRECAUTIONS:

6.1.1 Fitness certificate shall be filled before start of lifting activity.

6.1.2 Load lifting testing of all Lifting equipments shall be carried out on annual basis or as per manufacturer's recommendations.

6.1.3 Safety must always be the first concern for the operator. Unsafe condition shall be immediately reported to supervisor.

6.1.4 Effective fire preventive measures such as earthing and grounding shall be ensured. Adequate fire fighting equipments such as fire extinguishers shall be appropriately placed.

6.1.5 Never remove the fuel tank filler caps or refill the fuel tanks while the engine is running. A spark or flame could result in a fire or explosion.

6.1.6 Do not jump on or off the machine.

6.1.7 Sleeping or sitting under the machine shall be strictly prohibited.

6.1.8 Never rush towards the work area as hurrying can lead to accidents.

6.1.9 Any overhead wires shall be considered energized line unless and until otherwise indicated and confirmed.

6.1.10 Lifting equipment shall be parked in safe and guarded areas.

6.1.11 Clear direction signs/ marking of site shall be carried out to avoid unnecessary traffic movements.

6.1.12 The safe working load shall be clearly indicated on all lifting gear, equipment, or on tag fastened on the equipment.

6.1.13 Proper PPE shall always be worn by the staff. Wearing jewelry and loose fitting clothing shall be prohibited.

6.1.14 Pedestrians / Outsiders must be prohibited from entering into cordon off areas where lifting is in operation. Safe distance from the machine shall be ensured.

6.1.15 Only competent, qualified and trained operators shall be authorized to use the lifting equipments.

6.1.16 Traffic flow patterns should be understood by the operator on the job and should always follow the flagman or signal.

6.1.17 Only the operator shall be permitted to ride on the machine when it is in operation.

6.2 Safe Operation of Gantry Cranes:

6.2.1 It shall be ensured that gantry cranes and associated equipment are fit for use.

6.2.2 All lifts shall be made slowly to remove all slack from the hoist ropes.

6.2.3 Before lifting or traversing the load, operator shall ensure that the slings, shackles, rings and any other lifting accessories are carefully inspected for their integrity and correctly applied.

6.2.4 Never start the trolley or bridge motions until the load is of the ground and will safely pass by, or over, floor equipment or obstacles.

6.2.5 Always start and stop the crane slowly so as to avoid excessive swinging of load.

6.2.6 Ensure that all loads hoisting is made with the hoist ropes in the vertical position. Never pick up loads that may swing out of control or can create side pull on the crane.

6.2.7 Loads that are unsafe should never be moved. Long extended loads should have a tag line attached to keep the movements under control.

7.0 SAFE OPERATION OF COMPRESSORS;

Inspection and maintenance of all operational Compressors in the Company shall be carried out as per manufacturer's recommendations which include inspection of vessel, gauges and pressure relief valves.

8.0 Preventive Maintenance Of Vehicle / abnormal vehicle, welding plant and compressors:

8.1 A preventive maintenance program shall be applied to all company owned Vehicles / abnormal vehicles, welding plants and compressors as per concerned departmental manual and proper record is to be kept on standard formats by respective department.

8.2 Hired Vehicle / abnormal vehicle, welding plant and compressors that stays with the company will also follow this program covering all mechanical and safety aspects.

8.3 HSE department shall inspect preventive and maintenance record on as when required basis.

9.0 REQUIREMENTS OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

9.1ISO 45001:2018, Clause 8.1

9.2 ISO 14001:2015, Clause 8.1

10.0RELATED DOCUMENTS:

10.1 Vehicle/ abnormal vehicle Fitness Certificate (SNGPL -HPR007-F-001)

10.2 Welding Plant / Compressor Fitness Certificate (SNGPL -HPR007-F-002)

Comments (If any):

The information presented appears to be fields from a **Vehicle/abnormal vehicle Fitness Certificate** form. The form is used to inspect company-owned or hired vehicles and abnormal vehicles and is filled out by a First Line Executive and approved by the Respective HSE Executive.

Key fields on the form include:

- **Registration No.**
- **Company / Contractor**
- **Contractor Name**
- **Site / Location**
- **Department**
- **Driver Name / Designation / Age**
- **Make / Model**
- **Type of Vehicle / abnormal vehicle**
- **Date of Inspection**
- **Validation Date: From To**

The form also includes a checklist to assess various safety aspects of the vehicle:

- General condition of the vehicle
- Mechanical defects
- Seat belt
- Tyre condition and pressure
- Steering, clutch, and brakes
- Windscreen, side mirrors, and wiper/washer
- Lights and indicators
- Horns
- Fluid levels (engine oil, brake oil, coolant)
- Battery condition
- Seat and paint condition
- Cleanliness
- Load securing
- Engine smoke
- Lifting equipment load testing
- Visual inspection for looseness of nuts and bolts
- Toolbox
- Driving license
- First aid box
- Fire extinguisher

There is also a section for comments.

The excerpt shows the section of the **Vehicle/abnormal vehicle Fitness Certificate** where the **First Line Executive** who checked the vehicle and the **Respective HSE Executive** who approved the vehicle provide their names, designations, signatures, and dates. The form is used to inspect company-owned or hired vehicles and abnormal vehicles.

1.0 PURPOSE:

The purpose of this guideline is to ensure the safety of employees and to prevent damage to line pipe (Mild Steel / Poly Ethylene) during loading, unloading, stacking, storage and transportation.

2.0 SCOPE

It covers the activity of loading, unloading, stacking, storage and transportation of line pipe (MS/PE), chemicals, pipe line fittings etc. across the Company by the haulage contractors, ditching contractors or Company's own resources.

3.0 RESPONSIBILITIES:

3.1 Stores Officer / I/c Stores
3.2 Site Supervisor
3.3 Yard Supervisor
3.4
Haulier (Company contracted by the supplier to undertake the delivery) 3.5
Driver / Operator
3.6 Construction spread representative (where available)

4.0 GENERAL SAFETY REQUIREMENTS / INSTRUCTIONS FOR MS / PE PIPE:

4.1 I/c Stores / Stores Officer / Yard Supervisor shall ensure presence his during pipe handling by carriage contractor or company staff and also ensure the following;
4.1.1Pipes shall be safely stacked in the designated Store yard / Yard area.
4.1.2Pipes of same diameters shall be stacked together in pyramid shape.
4.1.3Loading/ unloading workers are fit for job, wearing tight clothes and relevant PPE's (safety shoes, gloves and helmets etc)
4.1.4Lifting Capacity of the crane / fork lifter is sufficient to meet the operational requirements in terms of weightage of pipe length / roll.
4.1.5Dropping & dragging of pipe / rolls shall not be permitted.

4.2 All pipes shall be loaded and unloaded mechanically using crane or fork lift trucks.
4.3 Fork lifters may be used provided that the arms of the fork lift are covered by suitable pads preferably rubber.
4.4 Crane / Fork Lifter should be fully operational without any defect.
Crane Operator shall check the wire rope is of optimum capacity, size, strength, 4.5 condition of steel wire rope and condition of hydraulic system of crane before lifting of pipe.
4.6 Pipes / Rolls should be properly placed and fastened on the trailer before departing from site. Use of suitable ropes, belts and chain boomers should be ensured.
4.7 Guide rope(s) may be required for coils as well as pipe lengths. The person(s) holding the guide rope(s) shall always maintain a safe distance from the product that is being stabilized.
4.8 The line pipe / pipe rolls shall be loaded, unloaded, transported in a manner to avoid injury to the workers and damage to the pipe and coating.

4.9 Belts/ slings when used shall be cleaned to remove hard materials such as stones, gravel etc.

4.10 Two types of side supports may be used with trailers.

4.10.1 Minimum 05 Nos. fixed vertical side supportswith height of 4′ to 5′ should be used at each side of the trailer. Proper tying of side supports should be ensured.

4.10.2 The trailer must have minimum two saddle supports lying on bed and hold by sides of bed. The saddle supports should be made of Hot rolled C-Channel of MS with minimum Depth 8″. Width 3″ x Thickness 3/8″. Minimum 2″ dia yarn rope may be used for fastening of saddle supports with trailer bed. Height of side supports should be minimum 28″.

4.11 All loaded vehicles and the crane shall follow the NHA guidelines for speed.

4.12 Load on trailers, vehicles should not exceed axle weight.

4.13 All personnel and vehicular traffic shall be kept at a safe distance from the loading / unloading area.

4.14 Any party involved in the loading / unloading process has the right to stop at anytime if they believe there is a risk to safety.

4.15 Driver / Operator is responsible for undoing the load securing devices. The securing devices should only be removed from the product that is to be imminently off-loaded. It is the responsibility of the person off-loading (e.g. crane operator) the goods to ensure that the off-loading process is carried out safely. Check the load to assure that all wedges are in place and secured. The wedges are not to be removed before unloading.

4.16 Driver / Operator and its helper are the only person authorized to access the trailer. Under no circumstances will it be acceptable that any person is on the bed of the vehicle when loading/unloading operations are in progress. It is good practice to wear safety helmets fitted with a chin strap.

4.17 In case of delivery of pipes through supplier; haulier should provide a safe means of access to/from the trailer bed.

4.18 Everyone on site has a personal responsibility to behave safely, to the best of their ability.

5.0 Specific safety requirements / instructions for Mild Steel (MS) Pipe:

5.1 Pipes having diameters 4” and above shall be lifted through cranes. Hooks may also be used for handling the pipes provided they have sufficient width and depth to fit the inside of the pipe and covered with soft material like rubber.

5.2 For lifting of pipes having diameter lesser than 4”, skilled 04 persons shall be deputed for job with alternate shifting schedule.

5.3 For lifting of pipes having diameter 4” and above, skilled 06 persons shall be deputed for job, in which 02 persons are on trailer, 02 persons on yard for hooking up the slings to pipes, 01 person deputed for crane operation and 01 person as signaling man.

5.4 Coated MS pipes may be handled by means of slings and belts of proper width (minimum 60 mm) made of non-metallic/ non abrasive materials.

5.5 Coated pipes shall be placed efficiently and smoothly on the trailer to avoid mechanical damages (face dents, surface dents, scratch etc.) Rolling, skidding or dragging shall be strictly forbidden. The ends of the pipe during handling and stacking shall always be protected with bevel guards.

5.6 Shifting of pipe to be done with trailers driven by prime movers. Number of maximum loaded pipe should conform to the following tabulation.

The excerpt specifies the **maximum number of pipes to be loaded** based on their diameters, along with remarks regarding the use of saddle supports:

- 4" diameter: **210**
- 6" diameter: **130**
- 8" diameter: **80**
- 10" diameter: **60**
- 12" diameter: **40**
- 16" diameter: **27**
- 18" diameter: **21**
- 20" diameter: **20**
- 24" diameter: **15**
- 30" diameter: **09**, increased to **10** when using saddle supports to increase bed width.
- 36" diameter: **05**, increased to **06** when using saddle supports to increase bed width.
- 42" diameter: **03**, increased to **05** when using saddle supports to increase bed width.

5.7 For loose Pipes bundle it must have at least two MS strips of 3mm thickness and 15mm width and should be properly welded.

5.8 For tight Pipes bundle it must have at least five MS bail hoops of 1 mm thickness and 25mm width and should be properly pressed.

5.9 Each bundle must consist maximum of following Nos. of pipes;

Ø 4”	10 nos.
Ø 6”	10 nos.
Ø 8”	08 nos.
Ø 10”	06 nos.
Ø 12”	05 nos.

5.10 At least three pipes must be hooked up of a bundle in all cases.

6.0 Specific safety requirements / instructions for Polyethylene (PE) Pipe

6.1 Polyethylene pipes / products shall be treated in a similar level of caution as perceived heavier steel pipe products and require the**same stringent** health and safety controls.

6.2 Polyethylene pipes can melt when heated. **PE pipes shall not be stored under direct sunlight** as ultra violet rays will react with the substances and make some different composition of the existing material which will depreciate the quality. It is necessary to store the PE pipes under the shed without direct exposure to sunlight.

6.3 The PE pipe coils can distort under load particularly at elevated temperatures. PE pipe coils shall be laid flat on a continuous surface and should only be stacked to a height where the bottom coils do not become distorted.

6.4 PE pipe is extremely slippery when wet and icy. Caution is to be observed in such weather conditions.

6.5 PE pipe is susceptible to scouring from sharp edges so the coils should not be dragged across bitumen and concrete. Under no circumstances PE pipes shall be pushed or rolled from the vehicle bed.

6.6 When wire ropes or chains are employed to secure the load, the PE pipe coils should be suitably protected against scouring.

6.7 Most trailers have a natural downward slope from the front of the trailer to the end of the trailer. It is suggested to begin unloading from the front of the trailer to the back to allow the strapped coils to stay in place.

7.0 Stockpiling Pipe

7.1 Only personal directly involve in pipe handling operations should enter the stockpile site.

7.2 Support skids should be sufficiently leveled prior to placing the pipe to ensure integrity of the piles and provision must be made to prevent pipe from accidently rolling off the storage rack.
Pipe racks must be substantially constructed and placed level on a solid foundation.

7.3

7.4 The pipe shall extend one meter (three feet) beyond cross timbers and employees shall work at the ends of pipe keeping hands clear.

7.5 Rolling pipe into a stock pile should be strictly prohibited.

7.6 Short lengths (3 meters shorter than maximum length) are to be stockpiled on top rung only.

7.7 Skid stakes shall be used at each skid line to prevent the possibility of the stockpile collapsing.

8.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

8.1 ISO 45001:2018, Clause 8.1

9.0 RELATED DOCUMENTATION:

Nil

1.0PURPOSE:

The purpose of this procedure is to ensure the safe operations of the Company by maintaining health of work force and to mitigate common health risks through medical screenings and control of communicable diseases.

2.0SCOPE:

This procedure is applicable to the following employees/staff at all sites of SNGPL:

i) All drivers operating Company vehicles including hired vehicle drivers.
ii) All food handlers and canteen staff.
iii)Janitorial staff.
Hygiene Cards. iv)
v) Employees exposed to noise.
vi) Staff exposed to radiation.
vii)Employees exposed to dust fumes and radiation.
viii)Computer operator of IT/MIS.

3.0DEFINITIONS ABBREVIATIONS AND CONCEPTS:

HSE:	Health, Safety and Environment.
Refraction:	To check eye sight.
ECG:	Electrocardiogram.
Occupational Health Surveillance:	Occupational Health Surveillance is a combination of clinical Examination and laboratory tests.
Clinical Examination:	Clinical examination is medical assessment carried out by a Doctor.

4.0RESPONSIBILITIES:

4.1 Focal Point:

Focal point has the primary responsibility to ensure that:

4.1.1 Required tests and investigations are carried out in accordance with the Occupational Health surveillance Matrix. (Annexure-B).

4.1.2 The record of each screening is maintained by the Admin department in order to ensure that the employees/contractor staff is not suffering from any medical disorder.

The examining doctor will rule out the disease on the basis of history, clinical 4.1.3 examination and lab test reports.

4.2 HSE DEPARTMENT:

HSE department is responsible for the following:

4.2.1 To review and update the procedure.

4.2.2 To review OH Surveillance, provide counseling and training wherever and wherever need arise.

4.2.3 To give recommendations on the basis of health screening reports.

4.3CONTRACTOR:

Contractor is responsible:

4.3.1 To ensure compliance with this procedure for carrying out health screening as defined in occupational health screening matrix

5.0 PROCEDURE:

5.1 HSE Focal Point through respective section (HRS) shall arrange for the health surveillance as per requirement of the occupational health surveillance matrix (Annexure-B).

5.2 The Company doctor shall fill up the clinical examination Performa (Annexure-C) and assess fitness of worker.

5.3 If the Company doctor feels that worker requires any other specific lab investigations, he shall send the filled examination form to HSE department for further evaluation and recommendations. For further referral to the lab investigations shall be made by HSE department.

5.4 Laboratory investigations shall be carried out by Company's listed laboratories. If listed laboratories are not present in a certain area than other renowned laboratories may be consulted for lab investigations.

5.5 If any employee is found to be suffering from any communicable/contagious or infections disease, he/she shall not be sent back to work until declared medically fit.

5.6 Vehicles are to be hired after ensuring that health screening of driver is carried out.

6.0RELATED DOCUMENTATION:

6.1	Nominated employees	SNGPL-HPR009-Annexure-A
6.2	Occupational Health surveillance Matrix	SNGPL-HPR-009-Annexure-B
6.3	Clinical examination Performa	SNGPL-HPR-009-Annexure-C
6.4	Hygiene cards Performa	SNGPL-HPR-009-Annexure-D

Informed consent

Please read this following informed consent and sign if you agree.

I declare that all information that I provided in this questionnaire is true and complete to the best of my knowledge. I agree that this information as well as the result of my medical examination including the appropriate fitness assessment will be provided to the authorized OH doctor of the company on request. I agree that my medical data will be transferred also to other medical doctors authorized by my potential employer.

I take note of my responsibility to inform the company doctor about changes in my state of health, in order to enable her/him to fulfill her/him responsibilities as to the employee protection law. I recognize that I am responsible for the consequences of concealment of those appropriate facts.

1.0PURPOSE:

The purpose of these guidelines is:

- To protect the employee's health against occupational health hazards due to exposure from nose, dust, fumes, vapors, radiation, extreme of temperature and ergonomic related hazards.
- To prevent any work related disorder.
- To screen out those who are already suffering from various occupational disorders.

2.0SCOPE:

Occupational health guidelines are applicable at all sites/offices of SNGPL.

3.0RESPONSIBILITIES:

3.1**Focal Point shall be responsible for:**

3.1.1Implementation of the Occupational Health Guidelines in their work area.
3.1.2Resolution and correction of identified OHS hazards.
3.1.3Identifying and reporting to HSE department all employees having complaints of musculoskeletal pain symptoms, respiratory system, fatigue, heat stress and hearing loss.
3.1.4Communicating findings to HSE department for review and action.
3.1.5Record keeping.

3.2**Executives Shall be responsible to:**

3.2.1To participate in worksite evaluations, signs/symptom surveys and OHS hazard analysis.
3.2.2The first line executives shall be responsible for getting the checklist filled properly and record keeping of it.

3.3**HSE Department shall be responsible for the following:**

3.3.1Provision of guidelines to the Focal Points for better understanding of Occupational Health. Conducting periodic workplace reassessments as required by Focal Point or as determined by HSE department.
3.3.2Reviewing, updating, and evaluating the overall effectiveness of the Occupational Health Guidelines.
3.3.3To arrange training of employees in the use of PPE and proper body mechanics in their work setting.

3.4 **Employees shall be responsible for the following:**

3.4.1 Filling of relevant checklist on as and when required basis. 3.4.2
Timely communicate any development of signs and symptoms.

4.0 HEARING CONSERVATION:

The Hearing Conservation Guideline applies to all sites of SNGPL .The purpose of Hearing Conservation guidelines is to protect employees against possible noise induced hearing loss while performing their duties.

4.1Guidelines:

4.1.1HSE Focal Points with the support of HSE Engineer shall arrange to carry out complete Noise level survey on annual basis of each site/location having potential of noise hazard or having risk of noise as per Environmental Quality Standards. The copies of noise level survey record shall be sent to HSE department and be retained for period of three years.

4.1.2 HSE Focal Points shall clearly define areas where Noise level exceed as per Environmental Quality Standards and these areas are to be designated as High Noise Areas. In designated areas, requirement of mandatory hearing protection shall be identified by sign or other marking at the entrance of the area and employees shall be made aware of these signs. The hearing protection such as ear muffs and ear plugs are to be put on before entering the designated area of high noise at all the time.

4.1.3 The use of hearing protection gear shall be mandatory for all the employees selected and categories of work enumerated as condition of employment.

4.1.4 Any worker not wearing the hearing protection deliberately while working in the high noise area will be counseled by the respective department supervisor/executive. Repeated non compliance in wearing hearing protection in high noise areas may be considered a violation of the code of conduct which may lead to disciplinary measures.

4.1.5 Regular checking of hearing protection shall be observed for their maintenance and replacement (if damaged) by concerned supervisor/executive. The individual who discovers any damage to hearing protectors shall immediately report to concerned supervisor/executive.

4.1.6 An annual audiometric testing to detect degradation in hearing ability will be arranged by concerned Focal Point and reports be sent to HSE department for further evaluation, noise control recommendation and rehabilitation.

5.0 HEAT STRESS:

The purpose of these guidelines is to provide an orderly procedure for the protection of employees, whenever working in heat stress areas that could be hazardous to their physical well being and ability to work. Under hot weather conditions; following recommended actions shall be observed:

5.1 Guidelines:

5.1.1 Younger workers be selected because they can withstand hot climate better than older ones (above forty years of age and obese workers) who require a longer conditioning period to effectively adapt to the heat exposure.

5.1.2 Workers having medical history of cardiac (Heart) diseases, hypertension (High blood pressure), diabetes and renal calculi (kidney stones or gravel) shall only be allowed restricted work in extreme hot weather.

5.1.3 Workers having history of intake of medicines for cardiac diseases; renal calculi (kidney stones etc) and depression and alcohol intake shall only be allowed restricted work under hot climate.

5.1.4 Workers who report having fever, vomiting or diarrhea is an indication to suspend the individual to work in hot environment. If any co-worker observes that some worker is having signs of heat related injuries he should seek medical help for his colleague.

Use mechanical aids for manual lifting where possible to avoid physical exertion.

5.1.5

5.1.6 Use cooling fans where possible. If worker feels tired, weak or dizzy, he shall take a break and after improvement in his condition, job rotation be done.

5.1.7 Use temporary shades to avoid direct heat. The preferred method of fluid replacement is 200-300ml of cool water after every 30 minutes. Fluid/ beverages with caffeine should be avoided. Water intake can be increased by taking lemonade (1/2-1 teaspoonful of salt + 2 Table spoon sugar + 1 lemon (squeezed).

5.1.8 When temperature reaches an excessively high level; physical work be curtailed. 5.1.9 If an individual is working in the heat without being acclimatized and continue to work at the same pace, a heat disorder is likely to develop. Acclimatization is to be provided for few days with reduced work load for all new hires or personal returning from work.

5.1.10 Regular counseling and imparting of awareness shall be carried out by the First line Executives and HSE Engineers as per SNGPL-HPR010-Annexure-A.

6.0RESPIRATORY PROTECTION:

The Respiratory Conservation Guideline applies to all sites of SNGPL where there is exposure of workers to dust, fumes and vapors.

6.1Guidelines:

6.1.1 Persons having asthma, emphysema, reduced pulmonary function, severe hypertension, coronary artery disease, cerebral blood vessel disease, epilepsy and claustrophobia are not permitted to use the respirators. Person having beard cannot maintain good fit of mask and respirator.

6.1.2 Full face mask respirators shall be used for operators involved in mercaptan usage, sand blasting operator, dope yard dope kettle operator, operators engaged in slinging operation at dope yard.

Half face mask respirators shall be used by metering workshop operators, painters and all those exposed to dust, fumes and vapors.

N95 mask shall be used by the personnel exposed to dust and welding fumes.

Manufacturer instructions is to be followed for wearing the full face/half face mask in order to get effective protection.

6.1.3 During the use of the respirator, it shall been sure that it must snugly fit on the face. The face piece –to-face seal is tight and there is no leakage. The fitness of the respirator must be checked each time it is used.

6.1.4 Persons having beard or a skin problem should particularly be more careful. Immediately leave the work area and replace the respirator if breathing becomes difficult, there is dizziness or other distress, Irritation, smell or taste of the contaminant

is sensed in work area. If good seal is not obtained with a respirator try another size face piece.

6.1.5 Do not remove the respirator while being exposed to the contaminated air as it will get damaged.

6.1.6 The respirator shall be stored at a cool dry place. Protect the rubber parts from contact with oil and grease. Do not store respirator in contaminated area. It is better to have a sealed container to store in the cartridge filter.

6.1.7 All those exposed to dust, fumes and vapors shall undergo pulmonary function test arranged by HSE Department after every two years. Clinical assessment of employees and any further recommendation shall be carried out by HSE department. Clinical record will be maintained by HSE department.

7.0 ERGONOMICS AT WORKPLACE:

The general guidelines applies to all sites of SNGPL for the identification, evaluation, and control of ergonomic and environmental risk factors in the workplace to maximize employee health, safety, efficiency and productivity by matching the requirements of the job with the abilities of the worker.

7.1 Guidelines:

7.1.1 Ergonomic Checklist (SNGPL-HPR010-F001)shall be filled on annual basis and record shall be maintained in separate files. Ergonomic analysis of work areas identified by employees or management is to be documented.

7.1.2Illumination level survey of workplaces shall be done on annual basis.

7.1.3 Following factors shall be considered for assessing illumination of workplace:

a) Task to be done. B) Equipment and furniture and used in tasks. c) Human factors. d) Area to be lit.

7.1.4 Save energy by combining natural light from windows and skylights with artificial light. Provide additional lighting only in specific areas that need it, instead to maintain a high overall level.

7.1.5Indoor air quality shall be done on as and when required basis (SNGPL-HPR010-F002)

7.2 Repetitive Stress Injury (RSI):

7.2.1 At work, the body aches and individuals feel tired, but symptoms disappear when away from work. The aches and fatigue do not interfere with the ability to work. The injured area aches and feels weak soon after the start of work. The injured area aches and feels weak, even at rest or while asleep. Even light duties are very difficult. RSI's are caused by repetitive stress, and can often be fixed by removing the stressor. But it is not always easy to find the problem. In order to identify the cause of RSI and to ensure that RSI is effectively dealt, following are the ways to be adopted.

7.2.2 A checklist attached as (SNGPL-HPR-F001) is to be filled by all employees initially and afterwards whenever required on the basis of task performed.

7.3Visual Display Terminal:

7.3.1 Keep feet flat on the floor (using a footrest, if necessary), and lean into the backrest at all times. Keep the back in good alignment.

7.3.2 The space between the front edge of the seat and the back of the knee should be the span of two to three fingers. This will minimize pressure on the underside of leg.

7.3.3 While seated, bend elbows to 90 degrees and relax the shoulders. If thearmrests do not allow for this position, do not use them while keying or using the mouse.

7.3.4 Over reaching above or below the shoulder level can lead to aches and pains. Minimize the risk of injury by having the items frequently used closer to hand. For example moving the telephone at easily accessible point or placing the frequently-used binders on the desk rather than on an overhead shelf.

7.3.5 The work surface should be free of clutter. Remove unnecessary files and office supplies. The legs should be allowed to move freely underneath the desk. The trash cans, record files, loose electric cables and boxes should not be placed under the desk.

7.3.6 Avoid sitting for long periods of time. Try to alternate between sitting, standing and walking while working, or simply get up and stretch. Ref to Computer and desk stretches (SNGPL-HPR010-Annexure-B).

7.4 Computer Adjustments:

7.4.1 Position the monitor directly in front when the head is in neutral position and the eyes are looking forward. Tilt monitor down if glare is noted on the screen. Adjust the screen height. Monitors should be at eye level or just slightly below eye level. Place the monitor 18" to 30" from the eyes, or use the arm's length rule: The monitor should be placed at the persons extended arm length distance. If the font is too small, consider enlarging the font size. Consider adjustment of the monitor's brightness and contrast for better viewing.

7.4.2 Position the keyboard so the wrists are straight when elbows are 90 degrees. Keep the wrist relaxed and straight. When possible, use the keyboard instead of the mouse to perform computer commands. Learn the shortcuts for the operating system to minimize wrist strain and boost productivity.

Position the mouse at the same height as the keyboard. Keep it within easy reach 7.4.3 .Holding a mouse and typing on a keyboard shouldn't take too much effort. A light grip on the mouse and a light key stroke will keep wrist pain to a minimum. Keep elbows as close to the body as possible and move the mouse with the whole arm, initiating movement from the shoulder.

7.4.4 By looking at a computer screen for extended periods of time can cause eyestrain. For a few seconds every hour, focus on something farther away Eye strain can also be caused by uncorrected vision. Have eyes regularly checked..

7.1.5 All computer operators of IT/MIS department whose job requires using computers for eight hours shall have refraction testing on annual basis.

8.0 Food Handling and Safety:

The purpose of these guidelines is to define and maintain a uniform procedure for handling, usage, storage and disposal of food waste in a systemic manner across SNGPL for protection of end users from food items that could be hazardous to their physical well being and ability to work. At food handling sites i.e. canteen, kitchenette, tea making areas and company messes; following food safety recommended actions shall be observed:

8.1 Guidelines:

8.1.1 Caution is required to purchase green grocery as per daily requirement and consumption only. For food items/ consumable products selection and purchase; refer to provincial food authority's official websites e.g.www.pfa.gop.pk & www.kpfsa.gov.pk on time to time basis.

8.1.2 Canteen contractors who are registered as food vendors with Food Regulatory Authority shall be preferred as food handling contractors.

8.1.3 Storage of green grocery for prolonged period is required to be discouraged. Fresh food prepared on the same day is required to be served. Only dry grocery food items which require storage are to stored in closed, air tight labeled containers in shelves at six inches above floor level and two inches away from wall. Date all food items and containers to observe first in first out food safety principal.

8.1.4 All food handlers are required to observe good personal hygiene i.e. scalp and beard hair covered with cap/ hair net, nails trimmed, scalp, beard, mustache hair clipped, teeth brushed, wear daily washed clean clothes/ apron/ close toed non slip shoes /observe gloves usage during food service and not wear any necklace/bracelet/ring at food handling site. They are also required to follow hand washing practices with soap and water for twenty seconds before preparing food, after usage of toilets, handling of waste, cleaning of refrigerator or freezer, usage of pesticides, dressing of any wound and after cleaning food service tables.

8.1.5 Substance abuse i.e. smoking, paan, niswar ,gutka and chewing gum etc. should be avoided at food handling site by food handlers and canteen customers.

8.1.6 Follow housekeeping practices as in accordance with HSE IMS Manual procedure (SNGPL-HPR-012-F001&F002).For insects/rodents management, insecticides are to be stored and used as per manufacturer guidelines in presence of representative of Administration Department. All kitchen gadgets/utensils are required to be cleaned / washed with soap liquid or bar, scrubbed and rinsed after each use. Wipe clean all non food contact surfaces i.e. table surfaces/table covers, chairs, table spices jars with clean cloth before and after each service.

8.1.7 Health screening of food handlers is required to be carried out as per HSE IMS Manual procedure (SNGPL-HPR-009) .Food waste is to be stored in pedal on /lined waste bins at point of waste generation and then for final disposal in closed/ lined waste container. Canteen waste disposal is to be done as in accordance with (SNGPL-EPR-004).For availability and usage of potable safe drinking water at food handling sites (SNGPL-HPR-013) is required to be followed.

8.1.8 Seek first aid in case of burns, cut/abrasion/sprain or strain in accordance with HSE IMS Manual procedure (SNGPL-HPR-011).Food handlers who report having fever, vomiting or diarrhea is an indication to suspend the individual to work at food handling site and should seek medical assistance.

8.1.9 Regular counseling and imparting of awareness shall be carried out by the concerned Admin supervisors and Site HSE Engineers about hazards related to improper food handling leading to gastro-intestinal problems.

9.0 Safe handling of radioactive Source and Radiographic Activity:

The purpose of these guidelines is to ensure safety and health of personnel during handling, transportation and storage of radioisotopes and carrying out radiographic activity.

9.1 QA Department shall contract the radiography contractors having valid license from PNRA.

9.2 The radiography contractor is responsible to submit reports to QA Department as per PNRA requirements including safe radiography SOP at site, emergency response , reports of health surveillance , Personal film badge result and dosimeter record etc

9.3 Radiation Safety checklist (**SNGPL-HPR003-F003-G**) shall be filled by site supervisor and executive in charge present at site before start of radiography activity for safe operation of this activity.

9.4 QA Department shall ensure that radiographic activity at site is being done as per PNRA requirement / contract with SNGPL

9.5 HSE Focal Point shall ensure through its line management the following:

9.5.1 Focal point will delegate responsibility to contractor regarding radioactive source usage and will provide the space for storage of radioactive source with suitable distance away from residential areas.

9.5.2Focal point will not allow any of its vehicles to be used for the transport of radioactive source.

9.5.3In case of any accident/fire involving radioisotope and stolen / missing radioisotope Focal Point will liaison with contractor for reporting of incident to PNRA.

9.5.4Focal point will help in emergency response in emergencies i.e. evacuation of masses in case of any medical emergencies regarding radioactive source usage and its activity. Focal point will ensure that radioactive source is not stored in any vehicle at its site of operation.

9.6 HSE Engineer will:

9.6.1 Make random inspection to monitor that **Safety Checklist for Radiography (**SNGPL-HPR003-F003-G**)** is properly filled.

9.6.2 Coordinate for training to radiographer regarding personal dosimeter usage, film badge wearing, PPEs usage, occupational health risks of exposure, emergency response management and maintenance of training records as well.

11.0REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS

11.1ISO 14001:2015, Clause 8.1,8.2

11.2 ISO 45001:2018, Clause 8.1.1, 8.1.2, 8.1.3, 8.2

12.0 **RELATED DOCUMENTATION:**

Types of heat injuries, their signs and symptoms and first aid measures.	(SNGPL-HPR-010-Annexure-A)
Computer and Desk Stretches	(SNGPL-HPR-010-Annexure-B)
Ergonomic Checklist	(SNGPL-HPR-010-F001)
Indoor Air Quality Status form	(SNGPL-HPR-010-F002)

The sources provide information on heat-related injuries, their signs and symptoms, and first aid measures.

Heat Cramps:

- **Signs and Symptoms:** Muscle cramps in the arms, legs, and/or stomach, along with excessive sweating.
- **First Aid:** Move the person to a cool, shady area, loosen clothing to allow air contact, have them slowly drink at least 500 ml of cool water, and monitor the person.

Heat Exhaustion:

- **Signs and Symptoms:** Heavy sweating with pale, moist, cool skin, headache, weakness, dizziness, loss of appetite, heat cramps, nausea (with or without vomiting), urge to defecate, chills, confusion, and tingling in the hands and/or feet.
- **First Aid:** Move the person to a cool, shady area, loosen or remove protective clothing, have them slowly drink at least 500 ml of cool water, elevate their feet, seek medical assistance if symptoms continue, and monitor until medical help arrives.

Heat Stroke:

- **Signs and Symptoms:** This is a medical emergency. The person stops sweating, has red, flushed, hot skin, headache, dizziness, nausea, fast pulse, may develop seizures and mental confusion, and may collapse and become unconscious.
- **First Aid:** Move the person to a cool, shady area, loosen clothing, remove outer garments and protective clothing if possible, immediately start cooling the person by fanning and massaging extremities and skin, elevate their legs, if conscious, have them slowly drink at least 500 ml of cool water, seek medical aid, continue cooling while awaiting transport and continue first aid while en route.

1.0 PURPOSE:

The purpose of this procedure is to ensure that effective and timely First Aid and emergency treatment is given to the employees across the company for Occupational / Work related injuries, illnesses and Non occupational medical emergencies.

2.0. SCOPE:

These guidelines apply to all employees, operations, functional areas and offices throughout SNGPL.

3.0 DEFINITIONS AND ABBREVIATIONS:

IMS	Integrated Management System
CPR	Cardio -Pulmonary Resuscitation
DHQ	District Head Quarter
THQ	Tehsil Head Quarter
CMH	Combined Military Hospital.

4.0. RESPONSIBILITIES:

4.1 Focal Points:

Focal points have the primary responsibility to ensure that:-

4.1.1System for first aid and treatment of work related injuries like burns, snake bites, motor vehicle accidents and medical emergencies is in place and functional. All the required support and resources are readily available.

4.1.2In case of injury at remote site, the In-charge of the Site or Activity will take necessary steps for safe and immediate transportation of the injured to the nearby hospital /clinic/doctor, which is available in the vicinity.

4.1.3Where Admin Department Representative is not available, an executive is to be assigned the duty to implement this procedure.

4.2 Administration Department:

Admin Department In-charge has the primary responsibility to ensure that:-

4.2.1First aid boxes are placed at easily accessible identified location and are filled in ready-to-use mode.

4.2.2 At least two trained First Aiders names with contact phone number are pasted on the right corner and contents list of the First-Aid box on the left corner of the First Aid box (SNGPL-HPR011-Annexure-A) along with the monthly inspection checklist (SNGPL-HPR011-F002).

4.2.3 A First-Aid box Usage Log Sheet (SNGPL-HPR011-F001)form is placed inside the first aid box to log the First-Aid cases.

4.2.4 A Stretcher and First-Aid box are inspected on monthly basis as per InspectionCheck list for Stretcher & First Aid Box (SNGPL-HPR011-F002).

4.2.5 First-Aid Box and stretcher location are mentioned and clearly marked in Emergency Evacuation plan of all respective Sites.

4.2.6 Admin Department In-charge will maintain the following:

4.2.6.1 Name and contact numbers of the person In-charge of First-Aid.

4.2.6.2 List of the persons who are trained in First-Aid and CPR, this list with photographs should be displayed on the notice board.

4.2.6.3 Data about blood groups of the employees.

4.2.6.4 List and contact numbers of all the nearby dispensaries / clinics / hospitals and teaching hospitals with particular reference to which type of medical emergencies, they are capable to handle.

4.2.6.5 List of all different Ambulance Services.

4.2.6.6 All of the above mentioned data should be at easily accessible place.

4.2.6.7 Communication of any work related/occupational injury on monthly basis.

4.2.6.8 Arrangement for emergency treatment of those who are injured is to be made at the nearby Doctors/Clinics/Hospitals.

4.2.7 In case where an ambulance has to be deployed, it shall have a dispenser and shall contain 02 Oxygen Cylinders. Maintenance of ambulance wherever applicable for rapid response in case of injury/illness as per follows:

i. Ambulance first aid box items availability as per ambulance first aid box contents list (SNGPL-HPR011-Annexure-E).

ii. Inspection of ambulance equipments as per (SNGPL-HPR011-F006)

4.3 Admin department:

Admin department is responsible for availability of stretcher, refilling of Oxygen Cylinder and first aid Box and safe disposal of expired first aid items.

4.4 HSE department:

HSE department is responsible for the review, update of the procedure and related training.

5.0 PROCEDURE:

5.1 In case of injury, First-Aid is to be provided by the trained first aider or dispenser:

5.1.1 In case injured needs further treatment, transportation is to be carried out to the near-by hospital /clinic in ambulance if available or by utilizing some comfortable transport under supervision and escort of the trained First-Aider and in coordination with In-charge Admin department or representative of Admin Department.

5.1.2 In case of injury at remote site, where proper medical facility is not available, the In-charge of the site will take necessary steps for safe and

immediate transportation of the injured to the nearby hospital/clinic/doctor available at the vicinity .This incident /accident will be reported according to the procedure of Incident Reporting and Investigation (SNGPL-GPR-008).

5.1.3 In case the doctor refers the victim to some other hospital, then the victim should be shifted to that hospital after taking written referred slip from the doctor who has examined the patient along with the detail of the treatment given.

5.1.4 In case of snake and dog bite occurring at remote sites, victim is to be shifted to nearby CMH, DHQ Hospital or THQ Hospital (this theme is written in order of preference, where treatment facility for such cases is available).The victim will come to work after getting immunization/inoculation fitness certificate from the doctor who has given final treatment to the injured.

5.1.5 Any work related Occupational injury/illness /Communicable /Contagious diseases /some emergency referral which require first aid provision/hospitalization should be communicated to the HSE department within 24 Hours according to the requirement of incident/accident procedure.

5.2 Incase at work place any employee who has to visit dispensary/sick bay, excluding emergency cases, should take slip with him duly signed by his supervising executive. Patient visiting the Dispensary / Sick bay will be logged in Daily Attendance Sheet for Occupational Health For Dispensaries / Sick Bay (SNGPL-HPR011-F003) byDispenser. Monthly attendance summary will be sent to HSE department.

CLEANING OF DISPENSARY/ SICK BAY: 5.3

Floor	Cleaning/ Wet mopping daily General Washing Weekly
Doors	Frequent cleaning of door knobs and dry mopping followed by wet mopping daily General Cleaning Weekly
Walls	General Cleaning on Weekly basis
Ventilators Ceilings and Lights	Dry mopping followed by wet mopping weekly Dry mopping on monthly basis.

General requirement for sick bay / Dispensary are attached as **(**SNGPL-HPR-011-Annexure B, C and D**)**.

5.4 All surgical instruments are to be cleaned with water followed by decontamination and sterilization.

5.5 DISPOSAL OF MEDICAL WASTE:

Medical Waste will be disposed off according to EMS Standard (ISO 14001:2015). Method already defined in IMS manual is to be adopted for disposal of Non Hazardous and Hazardous Waste.

5.6 NOTIFICATION OF ANY COMMUNICABLE AND CONTAGIOUS DISEASE:

If any Communicable and Contagious Disease erupts (or the case is identified), it is to be notified to Site In-charge and HSE department for necessary advise through form Notification of any Communicable and Contagious Disease. (SNGPL-HPR011-F004).

5.7 Calibration of any medical equipment will be arranged by Administration Department.

Oxygen cylinder will be inspected by HSE Engineer and Admin Department 5.8 representative in accordance with the Oxygen Cylinder Inspection Performa (SNGPL-HPR011-F005).

6.0 TRAINING:

HSE Focal Point shall arrange for the first aid training of their employees in coordination with HR and HSE Department.

7.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

7.1 ISO 45001:2018, Clause 8.2

The related documentation for **Emergency Treatment of Occupational and Non-Occupational Medical Emergencies** includes:

- **First-Aid box Usage Log Sheet** (SNGPL-HPR011-F001)
- **Inspection Check list for Stretcher & First Aid Box** (SNGPL- HPR011-F002)
- **Daily Attendance Sheet for Occupational Health for Dispensaries / Sick Bay** (SNGPL-HPR011-F003)
- **Notification of any Communicable and Contagious Disease** (SNGPL-HPR011-F004)
- **Oxygen Cylinder Inspection Performa** (SNGPL-HPR011-F005)
- **First Aid Box Contents List** (SNGPL-HPR011-Annexure-A)
- **Requirement for Sick Bay / Dispensary** (SNGPL-HPR011-Annexure B)
- **Dispenser first response Kit Content List** (SNGPL-HPR011-Annexure C)
- **Medical Equipment to be available at Dispensary / Sick Bay** (SNGPL-HPR011-Annexure D)

The excerpt details the **contents list for a first aid box**. The items and quantities to be included are:

- Cotton roll gauze 1 inch (finger): One packet
- Cotton roll gauze 2, 4, 6 inches: One packet each
- Crepe bandage: 2
- Cotton wool: 1 packet
- Pyodine antiseptic solution: 1
- Adhesive plaster: 1
- Triangular bandages (40 in. x 40 in. x 56 in): 6
- Safety pins: 2 Pair large size with safety lock
- Splints of “6” different sizes: 6
- Polyfax skin ointment: 1
- Saniplast First aid bandages: 1 packet of 100 bandages
- Dressing scissor (straight edges): 1
- Burn cream (Germaine or quench or flamazine cream): 1
- Iodex if not available, then Voltral emulgel: 1
- Disposable polythene gloves: 1 packet
- Tourniquet: 1’inch x 24’inch

As per ANSI standard the Sick Bay / Dispensary should be:

(a) Located near the work area or areas it is to serve.

(b) Easily accessible to workers at all times.

(c) Able to accommodate a stretcher.

(d) Close to bathroom facilities.

(e) Kept clean and sanitary.

(f) With adequate lighting, ventilation and heating arrangements.

(g) Clearly identified as First-Aid Facility and appropriately marked with how and where to access the First-Aider.

(h) Used only to administer First-Aid or health related services and equipped with:

(i) A communication system.
(ii) A sink with cold/ warm running water.
(iii) Eye wash equipment, if it is a work site.
(iv) A bed with mattress , 2 pillows and two bed side waste baskets, one white color for non hazardous waste and second yellow basket for infectious waste.
(v) First-response kit of dispensary doctor contents list attached as Annexure-B

The excerpt you provided describes the **contents list for a Dispenser first response Kit**. The items and their quantities are as follows:

- Cotton roll gauze 1, 2, 4, 6 inch: **1 packet each**
- Crepe bandage: **2**
- Cotton wool: **1 packet**
- Pyodine antiseptic solution: **1**
- Adhesive plaster, Dressing scissor (with non curved edges): **1 each**
- Tourniquet 2”x 24” long (Non elasticized): **1**
- Arm Sling: **2**
- Safety pins: **2 Pairs**
- Polyfax skin ointment: **1**
- Saniplast First aid bandages: **1 Packet**
- Nitroderm Patch: **2**
- Any Burn cream (Dermazine cream etc.): **2**
- Disposable plastic polythene gloves: **1 packet**
- Sterile eye dressing (individually packaged): **2**
- Tab Disprin: **10**
- Tab Angisid: **10**
- Glucometer with alcohol swabs, lancet and strips: **1 set**
- 25% Dextrose Water 20 ml: **2**
- Disposable syringes: **1ml, 3ml, 5ml (Two each), 20ml & 50ml (One each)**
- Voltral emulgel: **1**
- Surgical mask: **One packet**

List:

- Oxygen cylinder/with all the accessories.
- Blood pressure apparatus.
- Glucometer.
- Stethoscope.
- ENT set.
- Umbo bag.
- Mouth piece.
- Tongue depressors (Disposable) and flash light.
- Nebulizer.
- Patients couch (with adjustable head and foot ends).
- Patients stool (Revolving and height adjustable).
- I/v stand.
- Sterilizer.
- Dressing trays (02 no).
  (02 no) (Medium size). •

Kidney trays

- Surgical knife. (01 no).
- Forceps. (01 no).
- Dressing scissors of 2 sizes.
- Waste disposal cans with lids three color coded (white for municipal waste, yellow for infectious waste and red for glass waste / sharps) pedal on waste bins.
- Needle cutter
- Used syringes safety box for disposal
- Three Color coded liners of waste baskets.
- Dressing bowls small, medium and large size. (1 each).
- Wooden splints. One set.
- Needle holders. (01 no).
- Instruments drum. (01 no).
- Dressing drum. (01 no).
- Blanket. (01 no).
- Stretcher with straps (01 No).
- Water proof waste bags (plastic). (one packet)

The excerpt details the **contents list for an ambulance first-aid box**. The items and their quantities are as follows:

- **Cotton roll gauze 1 inch (finger)**: One packet
- **Cotton roll gauze 2, 4, 6 inches**: One packet each
- **Crepe bandage**: 2
- **Cotton wool**: 1 packet
- **Pyodine antiseptic solution**: 1
- **Adhesive plaster**: 1
- **Triangular bandages (40 in. x 40 in. x 56 in)**: 6
- **Safety pins**: 2 Pair large size with safety lock
- **Splints of "6" different sizes**: 6
- **Polyfax skin ointment**: 1
- **Saniplast First aid bandages**: 1 packet of 100 bandages
- **Dressing scissor (straight edges)**: 1
- **Burn cream (Germaine or quench or flamazine cream)**: 1
- **Iodex if not available then Voltral emulgel**: 1
- **Disposable polythene gloves**: 1 packet
- **Tourniquet**: 1'inch x 24'inch
- **Tab Angisid**: 10 tablets
- **Tab Disprin**: 10 tablets
- **Face Mask**: One pkt

1.0 PURPOSE:

To define a mechanism for conducting HSE Site Committee Meetings and House Keeping Inspections for overall improvement in HSE Management System.

2.0 SCOPE:

It is applicable to all sites across the Company as defined in IMS Manual.

3.0 definition:

The definitions related to **HSE Site Committee & Housekeeping Inspection** include:

- **Focal Point**: The in-charge of the Region/Section/Spread/Compression.
- **Lavatory**: A basin or similar vessel used exclusively for washing of the hands, arms, face, and head.
- **Toilet facility**: A fixture maintained within a toilet room for the purpose of defecation or urination, or both.
- **Toilet room**: A room maintained within or on the premises of any place of employment, containing toilet facilities for use by employees.
- **Urinal**: A toilet facility maintained within a toilet room for the sole purpose of urination.
- **Food handling sites**: Canteens, messes, kitchenettes, and tea-making areas.

4.0 RESPONSIBILITY:

4.1 **Focal Point**:

Focal Point is overall responsible for implementation of this procedure in true spirit.

4.2 **Admin department:**

Admin Incharge of respective site shall ensure following;

4.2.1 Area is designated and identified for waste disposal as per Solid Waste Management Procedure (SNGPL-EPR-004) and arrangements for further disposal of this waste are adequate.

4.2.2 Sanitation activities performed by the worker are supervised at all times and any discrepancy from the standards is communicated to the contractor for corrective action (in writing) and HSE department for reference.

4.2.3 Monthly visits to canteens and kitchenettes shall be carried out by the representative of Focal Point, In charge Admin / HSE Engineer and write observations on Check list for Food Handling Sites and Food Handlers (SNGPL-HPR-012 -F001).

4.2.4 Notify HSE Focal point and HSE Department immediately if suspect any discrepancy from the guidelines and detect any occupational and communicable diseases.

4.2.5 Ensure through sanitation supervisor that garbage and refuse heaps are not found at areas other than the designated areas.

4.2.6 Ensure that adequate numbers of sanitation workers are engaged for sanitation.

4.2.7 Ensure that this procedure is communicated to all sanitary contractors and workers and the procedure and contractor HSE statement is made part of the documents when engaging the sanitary Contractors.

4.2.8 Ensure that food handling site is being maintained by contractor as per requirement of general cleaning of food handling site requirement (SNGPL-HPR012-F002).

4.2.9 Monitor food handling site (s) under his domain on monthly basis and report anomalies to HSE Focal Point and HSE Head Office (if required).

4.3 Sanitation Contractor

Responsibilities of sanitation contractor are given below;

4.3.1 Maintain highest degree of hygienic and sanitary conditions at the work place throughout the working hours and in times of need.

4.3.2 Ensure hiring of workers of sound health status in accordance with requirements of occupational health surveillance matrix.

4.3.3 Ensure that workers are properly trained to perform duties before sending them to duty stations and to participate in the required training, if required by HSE Department.

4.3.4 Follow and monitor hygienic aspects of food handling sites and good personal hygiene of food handlers (hair cut, close shoes and neat clothes/uniform).

4.3.5 Arrange for provision of aprons, caps, gloves to be used for cooks and food handlers.

4.3.6 Ensure that food handling site is being cleaned and maintained as per requirement of general cleaning of food handling site requirement (SNGPL-HPR-012-F002).

4.4 SanitationWorker:

Responsibilities of sanitation worker are given below;

4.4.1 Ensure good sanitation and hygienic status of the area assigned to him for cleaning, maintaining and proper disposal of waste.

4.4.2 Observe the timings required by the hiring authority and clean the area before the start of office timings and at the end of his duty.

4.4.3 Perform his daily assigned work and get DailyCleaning and Waste Disposal Checklist For Sanitation Staff (SNGPL-HPR012- F003**)** signed by the representative of Focal Point on daily basis.

4.4.4 Report to his supervisor if suffering from any disease/injury and if he meets an accident. The Sanitation Contractor or his representative is responsible to bring this matter in the notice of In-charge Admin.

4.4.5 Line the trash bins/cans and drums with recyclable disposable plastic bags on daily basis and shall also clean and wash the bins on daily basis.

4.4.6 Wear his uniform / PPEs at all the time during his duty hours.

4.4.7 Daily clean and wash (if required) the floor/ carpeted walls/ toilet rooms/ rest rooms/ washing facility/ urinals/ trash cans/ garbage drums/ halls/ hall ways and open spaces.

4.4.8 Place / dispose waste in the area of his duty at designated place (s) and shall not throw the waste at an isolated place and near important installations.

4.4.9 Do not come to duty under affect of any alcohol, drugs and prohibited substances and if reported by somebody shall be discharged from duties.

4.4.10 Abide by all the health, safety and environment rules communicated to him during training sessions.

4.4.11 Do not involve in any security related issues and out of law activities at the site.

4.5 HSE Department:

HSE department shall be responsible for the following:

4.5.1 Provide technical advice and guidance to all departments on potential risks associated with housekeeping, sanitation workers, food handlers and food handling sites.

4.5.2 Provide counseling and training whenever the need arises.

4.5.3 Review and update the procedure.

.

5.0 HSE SITE COMMITTEE:

5.1 HSE Site committee shall consist of In-charge Admin, HSE Engineer and any other Sectional Head (s) as nominated by HSE Focal Point.

5.2 HSE Focal point and HSE site committee shall be responsible for overall monitoring of HSE activities and HSE performance at Site.

5.3 HSE Focal Point shall chair 'HSE site committee meeting' at a frequency of two months. Prior notice is to be given in this regard.

5.4 Agenda of meeting shall include following points;

a) Review of last Site Committee Meeting.
b) Accidents status / Corrective actions status of suggested recommendations.
c) Housekeeping Inspection Report / Corrective action status of each highlighted anomaly.
d) Non conformance Reports (NCRs) status.
e) OHS / Environmental Objectives and Targets status.
f) Corrective and Preventive Action Requests (CPARs) status.
g) Safety Talks status and selection of safety talks for next 2 months
h) Routine Safety Audit (RSA) status.
i) Status of Emergency related equipments (First aid box, smoke systems, fire fighting equipments etc).
j) Any other Site specific HSE related issue.

5.5 HSE Focal point shall document 'attendance' of Site committee meeting on standard format SNGPL-HPR012-F004and 'minutes of the meeting' on standard format SNGPL-HPR012-F005. Ensure prompt issuance to all concerned. Send a copy of the minutes of the meeting to the respective HOD and GM (HSE).

5.6 HSE Focal Point shall maintain record of 'minutes of the meeting' and ensure implementation of the actions agreed in the meetings.

5.7 HSE Focal point and HSE site committee shall follow up line management for the implementation of various HSE procedures at the Site. Development of the HSE procedure shall be primarily done by HSE Department.

5.8 It is responsibility of 1st line executive to communicate minutes of meeting to the relevant staff (subordinate/ casual) and other interested parties for their input and subsequent corrective actions.

6.0 HSE HOUSEKEEPING INSPECTION:

6.1 HSE Focal Point shall communicate 'Annual HSE Housekeeping Inspection Schedule' to HSE Head Office at the start of each fiscal year. All office premises (Company owned and hired) under the domain of HSE Focal point shall be covered.

6.2 Schedule should be devised in such manner that main Regional offices / Transmission Sections / Project Camps and sub area offices etc visited at least in 02 months. CSCs/ CCs / repeater stations etc is visited at least twice in a fiscal year.

6.3 HSE Site Committee shall carry out Housekeeping inspections as per annual schedule approved by HSE Focal point.

6.4 HSE Site Committee shall promptly submit Housekeeping Inspection Report to HSE Focal point duly signed by each committee member. Each Housekeeping inspection report shall be discussed as an agenda point in HSE Site Committee Meeting.

6.5 Safety guidelines mentioned in HSE Procedure 'General Safety Management' (SNGPL-HPR-004) should be considered while performing Housekeeping inspections.

7.0 RECORD KEEPING:

Daily Cleaning and Waste Disposal Checklist For Sanitation Staff (SNGPL-HPR- -F003) shall be signed by the department/section/room in charge on daily basis to avoid poor sanitary status at offices, workshops, food handling areas, store yards, pipes yards, scrap yards and other locations and shall be sent to HSE Department on monthly basis. Record shall be kept by Admin department for one year.

8.0 REQUIREMENTS OF ENVIRONMENT HEALTH AND SAFETY STANDARDS:

8.1 ISO 14001:2015, Clause 6.1.2.1 9.1
8.2 ISO 45001:2018, Clause 6.1.2.1, 9.1

The related documentation for **HSE Site Committee & Housekeeping Inspection** includes:

- **Checklist of Food Handling Sites and Food Handlers** (SNGPL-HPR012-F001)
- **General cleaning of food handling sites requirement** (SNGPL-HPR012-F002)
- **Daily Cleaning and Waste Disposal Checklist for Sanitation Staff** (SNGPL-HPR012-F003)
- **Attendance sheet of meeting** (SNGPL-HPR012-F004)
- **Minutes of Meeting** (SNGPL-HPR012-F005)

The excerpt provides a **checklist for food handling sites and food handlers**. The checklist includes items to assess the cleanliness and condition of various aspects of the food handling environment.

The items to check include:

1. **Walls**: Indicate if smooth and clean or dirty and include the date of last lime washing.
2. **Floor**: Indicate if smooth and clean or dirty.
3. **Door (Hinges)**: Indicate if clean or dirty.
4. **Door knobs**: Indicate if clean or dirty.
    - **Door mats**: Indicate if clean or dirty.
5. **Ceiling**: Indicate if clean or dirty, fixed, or needs partial fixing.
6. **Exhaust Fan**: Indicate if clean or dirty.
    - **Local exhaust ventilation**: Indicate if clean or dirty.
    - **General exhaust ventilation**: Indicate if clean or dirty.
7. **Food Preparation Area**: Indicate if clean or dirty.
    - **Racks**: Indicate if clean or dirty.
    - **Shelves**: Indicate if clean or dirty.
    - **Taps**: Indicate if clean or dirty.
    - **Washing facility**: Indicate if clean or dirty.
8. **Food Cooking Area**:
    - **Cutting**: Indicate if clean or dirty.
    - **Knives**: Indicate if clean or dirty.
    - **Cooking utensils**: Indicate if clean or dirty.

The excerpt you provided continues the **checklist for food handling sites and food handlers**, focusing on potable water, food storage, utensils, and dining areas. This checklist is part of ensuring HSE (Health, Safety, and Environment) standards are met.

The items to check include:

- **Potable Water Being Used**: Specify if tap water, mineral water, or filtered water is in use, and record the date of the last drinking water tests.
- **Raw Food Washing Facility**: Indicate if the facility is clean or dirty.
- **Different Food Preparation Gadgets**: Indicate if clean or dirty.
- **Food/Storage Area**: Indicate if clean or dirty.
    - Utensils
    - Water dispenser (daily cleaning)
    - Fridge / deep freezer (Twice a Week Cleaning)
    - Flour Storage
    - Vegetables Storage
- **Utensils**:
    - Pots: Indicate if clean or dirty.
    - Storage Shelves of pots: Indicate if clean or dirty.
- **Mop**: Indicate if clean or dirty.
- **Crockery**: Indicate if clean, dirty, or damaged.
- **Storage racks**: Indicate if clean or dirty.
- **Cutlery**: Indicate if clean or dirty.
- **Trays**: Indicate if clean or dirty.
- **Dining Area**:
    - Table: Indicate if clean or dirty.
    - Table's covers: Indicate if clean or dirty.
    - Chairs: Indicate if clean, dirty, or need repair.

The excerpts provide a continuation of the **checklist for food handling sites and food handlers**, focusing on hand washing and utensil-washing facilities, the presentation of food handlers, and the general cleaning schedule for food handling sites.

Checklist Items:

- **Hands Washing Facility**:
    - Wash basin: Indicate if clean or dirty.
    - Soap: Indicate if present or not present.
    - Towels: Indicate if clean or dirty.
- **Utensils Washing Facility**:
    - Washing area: Indicate if clean or dirty.
    - Washing Liquid / Soap: Indicate if present or not present.
    - Washing scrubber / scourer: Indicate if present or not present.
- **General Presentation of Food Handlers**:
    - Hair: Indicate if properly cut or trimmed.
    - Cap: Indicate if worn or not worn.
    - Nails: Indicate if properly cut or not properly cut.
    - Apron (Cooks): Indicate if present or not present.
    - Gloves: Indicate if worn or not worn.

- Shoes: Indicate if uniform shoes or casual shoes.

General Cleaning Schedule for Food Handling Sites:

- **Floor**: Dry and wet mopping in the morning and evening or when required.
- **Door**: Dry mopping followed by wet mopping twice daily (morning and evening).
- **Cooking area / food preparation area**: Scrubbing/cleaning at least twice daily or when required.
- **Service area**: Washing and scrubbing at least twice daily or when required.
- **Utensils washing area**: Scrubbing and washing at least twice daily or when required.
- **Storage area (Dry, raw, cooked food)**: Cleaning, washing, and scrubbing (if required) at least twice daily or when required.
- **Walls**: Lime washed bi-annually.
- **Lights**: Dry mopping once a week.
- **Ventilators**: Dry mopping once a week.
- **Ceiling**: Dry mopping once a week.
- **Refrigerator**: Cleaning (morning and evening or when required) and deep cleaning once a week.
- **Microwave**: Cleaning (morning and evening or when required) and deep cleaning once a week.
- **Water Dispenser/ Water Cooler**: Cleaning/ Washing/Scrubbing (Morning + Evening or on when required) and Deep Cleaning Once a week.
- **Stove**: Scrubbing/cleaning at least twice daily or when required.
- **Kitchenette Wash Basin**: Cleaning/ Washing/Scrubbing At least Twice daily or on when required.
- **Kitchenette / Canteen Water Drainage**: Maintain Good Flow At least Twice daily or on when required and Ensure removal of any clogging.

The general cleaning schedule for food handling sites includes:

- **Refrigerator**: Cleaning (morning and evening or when required) and deep cleaning once a week.
- **Microwave**: Cleaning (morning and evening or when required) and deep cleaning once a week.
- **Water Dispenser/Water Cooler**: Cleaning/ Washing/Scrubbing (Morning + Evening or on when required) and Deep Cleaning Once a week.
- **Stove**: Scrubbing/cleaning at least twice daily or when required.
- **Kitchenette Wash Basin**: Cleaning/ Washing/Scrubbing At least Twice daily or on when required.
- **Kitchenette / Canteen Water Drainage**: Maintain Good Flow At least Twice daily or on when required and Ensure removal of any clogging.

1.0 PURPOSE:

The purpose of this procedure is to ensure the provision of safe drinking water to all the employees at workplace.

2.0 SCOPE:

It is applicable at all the sites of SNGPL (operations and control).

3.0 DEFINITIONS AND ABBREVIATIONS:

Potable Water:	The water which meets the National Environment quality standards prescribed by Pakistan Environment Protection Department. Water sources can be tap water, surface water or ground water.

4.0 RESPONSIBILITIES:

4.1 FOCAL POINT:

The Focal Point shall ensure the continuous provision of potable water at all the areas of its domain.

4.2 ADMINISTRATION DEPARTMENT:

4.2.1 The Admin department at site shall ensure potable water arrangements according to the requirements and general instruction laid down in this procedure.

4.2.2 The Admin department shall arrange for drinking Water Quality test as per frequency requirement.

4.3 HSE DEPARTMENT:

4.3.1 The drinking water at any site shall not be declared fit to drink until the water quality report of the respective site is declared fit by HSE Department.

4.3.2 The HSE Department with the help of the Focal Point shall raise awareness about drinking water safety and its conservation throughout the Company.

5.0 REQUIREMENTS:

Potable water quality tests of all the sites are required to be carried out to ensure safe drinking water supply to all SNGPL sites/offices:

5.1 Water quality testing is done to ensure safe drinking water and its frequency shall be on annual basis at all locations having filtration units installed to ensure safe drinking water supply. In case of repeater stations, compressor stations , customer service centers and complaint centers or such locations ,it is preferred that alternate arrangement of potable

water from nearby Government/ Community operated filtration system or water dispenser system from Private Vendors may be arranged. All such sites who have alternate arrangement other than in house filtration system shall arrange for Drinking Water Quality report from the concerned authority/company from where the drinking water is being arranged.

5.2 The frequency of sampling is as follows:

5.2.1 For all drinking water points where filtration units are installed, Chemical & Microbiological analysis of drinking water quality test shall be done only after water filtration.

5.2.2 At all Sites where the filtration unit is not available, two samples shall be taken, one from the source and the other from tap after water storage (underground /over head tanks) for water testing.

5.2.3 At all Sites where only three stage filtration unit is installed, two samples shall be taken, one from tap after water storage (underground /over head tanks) and one after three stage filtration unit for water testing.

5.3 The samples shall not be taken by SNGPL employees; these shall preferably be collected by the testing laboratory representatives. For sampling purpose two samples shall be taken, one from the source and the other from tap after filtration according to the following procedure:

5.3.1 Clean and wash hands and taps with soap.
5.3.2 Let the tap water running for 1-2 minutes before taking water sample.
5.3.3 Take sterilized water bottle and fill it with water and after filling it close its cap.

5.3.4 Label the water bottle as mentioned below:

5.3.4.1 Time and place of water sample.
5.3.4.2 Source of water before filtration and after filtration.
5.3.4.3 Send the water sample to laboratory for analysis as early as possible.

5.4 The tests are to be done from renowned laboratories list attached as (SNGPL-HPR026-Annexure-A).

5.5 Water quality test report should include following two examination reports:

5.5.1 Chemical examination.
5.5.2 Microbiological examination.

(Parameters to be checked for Potable Drinking Water are attached as **(SNGPL-HPR013-Annexure-A).**

5.6 Drinking Water supply pipes shall be checked regularly and repairs should be carried out immediately in case any leakage is detected.
5.7 The animals shall be kept away from drinking water storage areas.
5.8 Drinking water storage sites shall be at least 15feet away from sewerage lines as per OSHA requirement.
Extreme care shall be taken to save drinking water from rodents and during spray of 5.9 pesticides.

6.0 GENERAL INSTRUCTIONS:

6.1 POTABLE WATER:

6.1.1 The water provided shall be fresh and potable, suitably cool, and in sufficient amounts, taking into account the air temperature, humidity, and the nature of the work performed, in order to meet the needs of all employees.

6.1.2 Potable drinking water shall be placed in locations readily accessible to all employees, by steps such as removing any barriers by making the access distance as short as reasonable, however multiple drinking water points shall be avoided and make the water station inviting by provision of shade.

6.1.3 Portable containers used to dispense drinking water shall be capable of being tightly closed, and shall be equipped with a tap.

6.1.4 Water shall not be taken out by dipping hands in drinking water containers. 6.1.5 On construction sites without any running water, safe potable water dispensers/coolers shall be provided.

6.1.6 For employees working in the heat, provision shall be made for cooling the drinking water during the hot weather by effective means and arrangements shall also be made for its continuous and un interrupted supply.

6.1.7 Any container used to distribute drinking water shall be clearly marked as “Drinking Water Container” and shall not used for any other purpose.

6.1.8 All Drinking Water points shall be legibly marked "Drinking Water Point" in a language understood by the majority of the workers.

6.1.9 The common drinking cup is prohibited unless cleaned and washed.

6.1.10 Where single service cups (to be used but once) are supplied, both a sanitary container for the unused cups and a receptacle for disposing of the used cups shall be provided.

6.1.11 In case of non-potable water results due to microbiological analysis, following procedure is to be followed:

- Search for any leakage of water pipes leading to contamination.
- Clean the water storage tanks and disinfect with chlorine tablets (33mg Tab for 20 liters of water and 3.3grams chlorine tab for 500 gallon of drinking water reservoir).
- Change water filters.

- Carry out water quality tests.

6.1.12 Outlets for non potable water, such as water for industrial or firefighting purposes only, shall be identified by signs, to indicate clearly that the water is unsafe and is not to be used for drinking and cooking purposes.

6.1.13 There shall be no cross-connection, open or potential, between a system furnishing the potable water and a system furnishing the non potable water.

6.2. For cleaning /purification and disinfection of water tanks (Under ground / Over head water tanks), following procedure shall be followed:

Shut off valve to distribution lines.

6.2.1 Clean inside surface of tank with brush to remove dirt / algae. Rinse inside surfaces of tank with clean water. Remove the washed water.

6.2.2 Disinfect the inside surfaces of the tank by using Sodium hypochlorite solution.

6.2.3 Fill the tank with water and then drain water from tank for flushing purpose. Fill it with fresh pre-filtered water. Add disinfectant as mentioned above and give it standing time of thirty minutes before opening the supply ,check the status of free chlorine by commercially available chlorine status color comparator.

6.2.4 Open valve to distribution lines.

6.2.5 Cleaning should be done on weekends, with prior warning to users, that water supply shall remain suspended for one day.

6.2.6 Cleaning and disinfection of water tank should be done twice a year or as required especially in rainy season or Gastrointestinal Diseases epidemic. Record should be maintained on **Water Tank Cleaning & Purification Log (SNGPL-HPR 013-F001)**. The frequency can be revised in coordination with HSE Department.

6.2.7 Fill the **Water Tank Cleaning & Purification Log (SNGPL-HPR013-F001)** twice a year and send copies to HSE department.

6.2.8 Record of **Water Tank Cleaning & Purification Log (SNGPL-HPR013-F001)** will be retained for a period of 02 Years.

6.3 Following methods shall be carried out for water filters replacement:

6.3.1 Always replace the filters with branded quality elements.

6.3.2 Shut off upstream valve of water supply t filters.

6.3.3 Open the external plastic covers of water filters with its designed tools.

6.3.4 Wash and remove dirt from inside surfaces of plastic covers.

6.3.5 Change the first stage filters (sediment cartridge) once every month, change 2nd stage filter (activated carbon cartridge) and third stage (ultra violet lamp) after three months or when ever drinking water is having any un pleasant taste or on any fault.

6.3.6 After changing the filters tighten the plastic cover properly, after replacing the filters check its operation especially the ultra violet lamp through its blinking light.

6.3.7 The point where water filter is placed shall be legibly marked as “Drinking water point” in a language under stood by the majority of workers.

6.3.8 Do not forget to switch off water filters and water coolers after office hours for its effective operation.

6.3.9 The filters of drinking water filtration units and membrane of RO Plant change dates shall be available with Admin Department.

6.3.10 Water filters shall be changed on and as per required frequency. Record shall be maintained on water filter change log **(SNGPL-HPR013-F002)** and copies of it shall be sent to HSE department, this record will be retained for a period of five year.

6.3.11 Reverse osmosis filtration plant water filters cartridges, membrane replacement and membrane sanitization and cleaning shall be done as per R.O Plant manufacturer specifications.

7.0REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

7.1ISO 45001:2018, Clause 8.1

8.0RELATED DOCUMENTATION:

8.1	Parameters to be checked for Potable Drinking Water	(SNGPL-HPR013-Annexure-A)
8.2	Water Tank Cleaning & Purification Log	(SNGPL-HPR013-F001)
8.3	Water filters replacement record	(SNGPL-HPR013-F002)

- **Chemical examination (Parameters to be checked for Potable Drinking Water are as under):**

The parameters to be checked for **potable drinking water quality** include:

Physical:

- Color
- Taste
- Odor
- Turbidity
- PH
- Total Dissolved Solids (TDS)
- Total Hardness as CaCO3

Chemical Essential Inorganic:

- Arsenic (As)
- Chloride
- Chromium
- Copper

Chemical Toxic Inorganic:

- Fluoride (F)
- Lead (Pb)
- Nickel
- Nitrate
- Nitrates (NO3)
- Residual Chlorine (at consumer end)
- Zinc

- **Microbiological examination (Parameters to be checked for Potable Drinking Water are as under):**

The parameters to be checked for potable drinking water quality using microbiological examination include:

- **Total Colony Count**: The permissible limit is less than 500 cfu / ml.
- **Total Coliform**: The permissible limit is 0/100ml.
- **E. Coli or thermo-tolerant coliform**: The permissible limit is 0/100ml.

1.0PURPOSE:

The purpose of this procedure is to focus primarily on unsafe Acts which accounts for 94% of accidents and unsafe conditions and their rectification.

2.0SCOPE:

This procedure is applicable to all sites and offices of SNGPL.

3.0 PROCEDURE:

3.1 All First Line Executives shall carry out RSA on weekly basis.

3.2 All Sectional Incharges will ensure that the required RSAs are being carried out in accordance with defined frequency.

3.3 All respective HSE Focal Points should ensure that the system is in place and RSA's are being regularly carried out in their respective areas.

3.4 RSA's should be carried out for 20-30 minutes.

3.5 A list of the **Usual Observation Items to conduct RSA (SNGPL-HPR014-Annexure A)** is attached for reference purpose only.

3.6 **RSA Form (SNGPL-HPR014-F001**) should be used for recording the findings and to facilitate follow up on the planned action.

3.7 For carrying out the RSA**:**

3.6.1 The respective executive should visit his own area for 20-30 minutes.

3.6.2 The only purpose of this short visit should be RSA and it should not be combined with the review of any other job functions.

3.6.3 The executive should focus on Unsafe Acts as well as Unsafe Conditions.

3.8 If the executive observes an Unsafe Act, he should talk to the employees as follows:

3.7.1 Arrange to handle it on the spot if it is minor e.ge scattered hose, loose tripping hazard, naked electric wire etc.

3.7.2 Make a note and follow up later for corrective action.

3.9 On return to the office the executive should fill up **RSA Form (SNGPL-HPR014-F001)** for record purpose. (Example given below, to fill the form).

The excerpt provides examples of **unsafe acts (USA)** and **unsafe conditions (USC)** observed during a Routine Safety Audit (RSA) and the actions taken or planned to address them.

- **Worker Wearing Loose Clothes**: This is an example of an Unsafe Act (USA), and the action taken was to discuss it as per procedure. Wearing loose clothing can pose a safety risk, especially around moving machinery or equipment.
- **Worker Tries to Reach Too Far on Ladder**: This is also an example of an Unsafe Act (USA), and the action taken was to discuss it as per procedure. Overreaching on a ladder can lead to falls and injuries.
- **Water Hose Lying Scattered**: This is an example of an Unsafe Condition (USC), and the action taken was to roll up the hose and put it in a rack. Hoses lying scattered can create tripping hazards.

4.0 REQUIREMENT OF ENVIRONMENT,HEALTH AND SAFETY STANDARDS:

The source refers to clause **6.1.2 of ISO 45001:2018** and lists related documentation for Routine Safety Audits (RSA).

The related documentation includes:

- **Usual Observation Items to conduct RSA** (SNGPL-HPR014-Annexure A)
- **RSA Form** (SNGPL-HPR014-F001)

Typical Observation Items

1. Is employee wearing proper clothing?
2. Is the employee wearing prescribed (by the site management) protective equipment for head, eyes, ear, foot etc?
3. Is proper job procedure being followed?
4. Is the employee using proper tools?
5. Are the tools in safe conditions?
6. Is there a chance for the employee to fall, slip, trip or strike against an object or hit by something?
7. Any other unsafe condition or anything which can go wrong and result in an incident?

1.0 PURPOSE:

The purpose of this guideline is to provide standard color codes for the identification of the pipelines carrying Hazardous & Non-Hazardous fluid for smooth SNGPL operations across the Company.

2.0 SCOPE:

2.1 It is applicable to all above ground pipelines (does not include Industrial, Commercial & Domestic service lines) installed at all sites of Compression, Transmission, Distribution, CP Plant, Co generation Head Office & Coating Plant UCH Sharif.

3.0 DEFINITIONS:

HSC HSE Site Committee

ANSI American National Standards Institute

4.0 RESPONSIBILITIES:

4.1 Management Representative (MR)
4.2 OHSAS Deputy Management Representative (DMR)
4.3 HSE Focal Point
4.4 Admin Department / Civil
4.5 HSE Site Committee (HSC)

.

5.0 PROCEDURE:

5.1 HSE Focal Point shall be responsible to ensure the proper color coding of the pipes as per Standards.

5.2 HSE Focal Point or his designated representative shall be responsible for the identification of the Pipes to be painted.

5.3 HSE Focal Point / Concerned Admin representative shall be responsible to ensure the painting of the identified Pipes / streams as mentioned in clause 5.6.

5.4 Inspection for compliance with guidelines shall be carried out on biannual basis by any representative of HSE Focal Point.

5.5 Respective HSE Executive shall ensure that procedure is implemented adequately and report any anomaly found to respective HSE Focal Point / HSE Head Office.

5.6 HSE Focal Point / Concerned Admin representative will be responsible to maintain a record of the Painting of pipes on **Inspection of Color Coding of Pipes (SNGPL-HPR015-F001)** and it will be updated accordingly.

5.7 Color schemes based on ANSI Standard for Color Code is to be adopted as per Annexure-A.

6.0 REQUIREMENT OF ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1 ISO 45001:2018, Clause 6.1.2

The source indicates the related documentation for **guidelines for color coding of pipes**. This documentation includes:

- **Inspection of Color Coding of Pipes** (SNGPL-HPR015-F001)
- **Recommended Color Codes** (SNGPL-HPR015-Annexure-A)

1.0 PURPOSE:

This procedure describes

- The mechanism for the identification of EMS aspects and evaluation of their impacts upon the environment
- The framework within which the SNGPL shall establish and maintain EMS objectives & targets and EnvironmentalManagement Programs.

2.0 SCOPE:

All activities, areas and departments of SNGPL as defined in IMS Manual.

3.0 DEFINITIONS, ABBREVIATIONS AND CONCEPTS:

SNGPL	Sui Northern Gas Pipelines Limited
EMS	Environmental Management System
HSC	HSE Site Committee
Environment:	Surrounding in which SNGPL operates, including air, water, land, natural resources, Flora, wildlife, human and their interrelation.
EMS Aspect:	Elements of an organizations activities or products or services that can interact with the environment
Significant EMS Aspect	An aspect, which has a significant environmental impact.
EMS Impact	Any change to the organization's, whether adverse or beneficial, wholly or partially resulting from an organization's EMS Aspects.
Control EMS Aspects	Control EMS aspects are aspects that SNGPL can directly manage through its organizational structure and responsibilities
Influenced EMS Aspects	Influenced EMS aspects are aspects generated on-site that the SNGPL does not directly control, but over which the SNGPL has same authority (i.e. through contractual obligations) or persuasion.
EMS Objective	Overall environment goal, arising from the HSE Policy, that SNGPL sets itself to achieve, and which is required where practicable.
EMS Target	Detailed performance requirement quantified where applicable to the SNGPL or parts thereof that arises from the environmental, objectives and needs to be set and met in order to achieve those objectives.
EMS Management Program	The means, time frames and personnel responsible for achieving an objective and target.

The **responsibilities and authorities** related to environmental management and the Environmental Management System (EMS) are distributed among several key roles and teams. These are:

- **HSE Focal Point**: Responsible for environmental management at their respective sites. They identify environmental aspects and impacts and ensure compliance with environmental regulations.
- **EMS Risk Assessment Team**: This team, comprising the department/section/site in-charge, a first-line executive, and an HSE executive, conducts environmental risk assessments.
- **Management Representative (MR)**: The General Manager (HSE) serves as the Management Representative (MR). The MR is responsible for the EMS, proposing policies, updating management on performance, tracking laws and regulations, and coordinating training needs.
- **EMS Deputy Management Representative (DMR)**: Assists in IMS implementation, aspect and impact identification, setting objectives, monitoring programs, and regulatory compliance.
- **HSE Site Committee (HSC)**: The HSE Focal Point nominates executives/employees to form this committee. The HSC identifies environmental aspects, recommends control measures, and defines environmental objectives and targets.
- **Employees**: All employees are responsible for conforming to the control measures detailed for their specific department activities.

5.0 PROCEDURE:

5.1 IDENTIFICATION OF EMS ASPECTS:

5.1.1.Environmental risk assessment of all the Company's premises and sites / activities shall be performed by **EMS Risk Assessment Team** comprising of respective department / section / site Incharge, First line executive and HSE Executive in consultation with respective staff (Subordinates / Casuals).

5.1.2.Significant environmental aspects resulting in risks and opportunities associated with either adverse environmental impacts (threats) or beneficial environmental impacts (opportunities) will be identified.

5.1.3. Environmental aspects of the activities, products and services that can be controlled and those that can be influenced will be identified alongwith their associated environmental impacts, considering a life cycle perspective.

5.1.4.Any change including planned or new developments and new or modified activities and services will be taken into account while determining environmental aspects.

5.1.4 The HSC shall identify the specific environmental aspects from the following general aspect categories, but not necessarily be limited to this list.

a)Air Emissions
b)Wastewater Discharges
c)Liquid & Solid Wastes
d)Energy Usage
e)Storm water Discharges
f)Water Usage

g)Noise
h)Odor
i)Natural Environment
j)Land Condition
k)Radiation

5.1.5 Following shall be considered while identifying Environmental aspects by an assessment of the, activities and services, together with consideration of the actual and potential effects of:

a)Air Emissions to atmosphere
b)Water usage and discharges to surface water groundwater and sewers
c)Land Contamination caused by spillages, etc.
d)The production, re-use, recycling and disposal of controlled and special wastes
e)The storage and management of materials
f)Activities upon local ecology of operations, sites and premises
g)The visual impact of sites and buildings
h)Environmental Noise pollution
i)Energy use and management
j)Use of transport and vehicles
k)Material used
l)Organization and site information
m)Legal issues, other requirements and compliance obligations
n)Existing environmental management
o)Raw materials
p)Packaging
q)Office activities
r)Landscaping and infrastructure
s)abnormal conditions and reasonably foreseeable emergency situations
t)Internal and external issues that are relevant to Company's purpose and that affect its ability to achieve the intended outcomes of its environmental management system. Such issues shall include environmental conditions being affected by or capable of affecting the organization.
u)Requirements of interested parties, their needs and expectations which become compliance obligation of the organization
v)Other relevant issues such as odors, particulates, lighting & pests

5.1.6 Record of the aspects identified shall be maintained and reviewed by the HSC **at least annually** or whenever need arises to identify any new aspect (s) that should be added and any old aspect (s) that should be deleted.

5.1.7 Once the impacts have been identified they are prioritized in terms of their environmental impacts to assist in using them for identifying risks and opportunities, 2) evaluate the effectiveness of these actions setting objectives and targets and for identifying operational control procedures or actions. Each aspect identified shall be assigned a significance rating to indicate the relative importance if its related environmental impacts. The significance rating shall be used to define those impacts which shall be controlled through environmental objectives and targets, or by the implementation of operational control procedures. Actions taken to address significant

environmental aspects, compliance obligations and risks & opportunities would be considered for integration and implementation into environmental management system processes or other business processes. These actions will be evaluated for their effectiveness.

5.1.6 Impacts shall be assessed by the HSC using the following method:

- All aspects which are legitimate concerns of major stakeholders and the Company shall be regarded as significant, if necessary controls have not been implemented.
- All aspects which are subject to environmental legislation or compliance obligations of interested parties shall be regarded as significant, and therefore noted as having a high impact/risk, if there is a breach or potential breach of legislation.
- All aspects where insufficient information is available to make a reasoned judgement shall be regarded as significant until further information is available.
- The risk evaluation process is to be carried out by competent / trained Personnel
- The risk assessment methodology is assessed using the Environmental Risk Assessment Chart SNGPL-EPR01-CH-001
- The intention is to reduce the impact "As Low As Reasonably Practicable" (ALARP)
- Having assigned a priority score for each environmental aspect and Impact the following table suggests timeframes for managing different Priority environmental aspects and impacts. (Actual timeframe should be agreed with consultation of HOD and MR)

Total score	Level of significance	Risk	Action	Timeframe
1 – 9	Low level of concern	Low	Long term	1 year +
10 – 15	Medium level of concern	Medium	Medium term	Within 6 months
16 – 20	High level of concern	High	Short term	Within 3 months

5.1.7 The opportunities arising from environmental aspects identification and subsequent risk assessment will be documented on Environmental Risk Assessment form (SNGPL-EPR001-F001).

5.2 ESTABLISHING AND MAINTAINING OBJECTIVES AND TARGETS.

5.1.5. The MR / DMR-EMS shall select EMS Objectives for all identified Significant environmental aspects, risks and opportunities associated with either adverse environmental impacts (threats) or beneficial environmental impacts (opportunities) and Compliance obligations and maintain **list of selected objectives for EMS (SNGPL-EPR01-F-003)**. Objectives and targets shall be consistent with the SNGPL HSE Policy.

5.2.2 In establishing objectives and targets, consideration shall be reviewed at least once in year by the HSE Management Committee and reported at the **Management Review Meeting (SNGPL-GPR-005)** by IMS MR. The Management review shall endorse the SNGPL EMS Objectives and targets.

5.2.3 EMS Objective Planning (SNGPL-EPR01-F002) shall be prepared by HSE Focal Point, reviewed by HOD and approved by MR.

5.2.4 The MR in consultation with EMS-DMR shall maintain EMS **Objectives Status (SNGPL-EPR01-F-004)** andwill regularly monitor and review the progress of EMS objective.

6.0 REQUIREMENT OF QUALITY, ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1 ISO 14001:2015, Element 6.1, 6.1.1, 6.1.2, 6.1.3, 6.1.4, 6.1.5, 6.2, 6.2.1, 6.2.2

The **related documents** for environmental management, specifically concerning **EMS aspects & impacts identification, setting of objectives & targets and management programs**, are:

- **Environmental Risk Assessment**: SNGPL- EPR01-F-001
- **Selected Environmental Objective Planning**: SNGPL -EPR01-F-002
- **List of Selected Objectives for EMS**: SNGPL -EPR01-F-003
- **EMS Objectives Status**: SNGPL -EPR01-F-004
- **Environmental Risk Assessment Chart**: SNGPL -EPR01-CH-001

Rating

LIKELIHOOD/PROBABILITY (L)

5 Occurs on a monthly or more frequent basis at SNGPL

4 Occurs between once in six months and once a year at SNGPL

3 Occurs between once a year and once in two years at SNGPL

2 Has occurred at least once in the last five years at SNGPL

1 Has occurred at least once within industry history

SEVERITY / CONSEQUENCE (S)

5 Work Stop on account of Notice from Environmental Legislation/enforcement authorities or Management decision to stop work due to severe environmental damage

4 Warning from Environmental Legislation/enforcement authorities

3 Environmental Impact leading to complaints from public/employees

2 Minor environmental impact, no public/employees concern

1 Cause no effect on environment

OVERALL RATING OF RISK (R)

The overall risk is determined by the product of above TWO FACTORS, LIKELYHOOD & CONSEQUENCE.

R = L X S

The Environmental Aspect with Risk rating 9 and above should be considered significant and needs to be controlled.

1.0 PURPOSE:

This procedure describes the mechanism for

- Environmental monitoring requirements as per National Environmental Quality Standards (NEQS) associated with Company's operations
- Determines the monitoring frequencies and responsibilities.

2.0 SCOPE:

This procedure is applicable to various operations of the Company as per form **Locations/ operations for Environmental Monitoring (SNGPL-EPR002-F-003).**

3.0 DEFINITIONS, ABBREVIATIONS AND CONCEPTS:

SNGPL	Sui Northern Gas Pipelines Limited
EMS	Environmental Management System
NEQS	National Environmental Quality Standards
Environment:	Surrounding in which SNGPL operates, including air, water, land, natural resources, Flora, wildlife, human and their interrelation.

4.0 RESPONSIBILITIES AND AUTHORITIES:

4.1 Focal Points
4.2 HSE Department
4.3 HSE SITE Committee (HSC)

5.0 PROCEDURE:

5.1 HSE DEPARTMENT:

5.1.1 HSE Department is responsible for the following;

5.1.1.1 To support Focal Points in the identification of sampling points.

5.1.1.2 To consolidate the reports received from Focal Points.

5.1.1.3 To submit the reports to concerned EPA as per reporting requirement.

5.1.1.4 HSE Executive may support HSE Focal Point by arranging / carrying out environmental monitoring using Company's own equipment for the purpose (where necessary) in order to comply with the legal requirements.

5.1.1.5 To conduct the 5% Quality Assurance sampling.

5.1.1.6Deviations with reference to NEQS will be identified and quantified.

5.1.1.7Based on the findings, an action plan for required improvement will be developed and presented in the HSE Management Committee.

5.2 FOCAL POINTS:

Focal Points have the primary responsibility for the implementation of Environmental Monitoring Procedure in their respective work area. This involves ensuring that:

5.2.1All sampling points regarding air emissions, effluent disposal and Noise Monitoring are identified as given in **Locations/ operations for Environmental Monitoring (SNGPL-EPR002-F-003).** Necessary advice may be secured from HSE Department.

5.2.2EPA recommended Environmental Laboratory is engaged to carryout the sampling/ analysis of the effluent and emission for the parameters as given in **Parameters for Environmental Monitoring (SNGPL-EPR002-F-002)**. **List of the EPA recommended laboratories** is also given in **(SNGPL-EPR002-F-001).**

5.2.3 Noise Levels are measured with the Noise level meters provided by the HSE Department.

5.2.4Copy of the results is forwarded to HSE department.

6 REQUIREMENT OF QUALITY, ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1 ISO 14001:2015, Element 6.1, 6.1.1, 6.1.2, 6.1.3, 6.1.4, 6.1.5, 6.2, 6.2.1, 6.2.2

7.0 RELATED DOCUMENTS:

The related documents for environmental monitoring include the list of some of the EPA recommended laboratories SNGPL-EPR02-F-001 and the parameters for Environmental Monitoring SNGPL-EPR02-F-002. Also listed are locations/operations for environmental monitoring and noise level survey/monitoring of stacks SNGPL-EPR02-F-003, the noise mapping chart SNGPL-EPR02-F-004, SNGPL-EPR02-CH-001, and noise monitoring of vehicles / moveable machinery SNGPL-EPR02-F-005.

The list of some of the EPA Recommended Laboratories includes the following:

1. SGS
2. Laboratory of Institute of Environmental Engineering and Research
3. PCSIR
4. Global Environmental Lab (GEL)
5. ECTECH Environmental Consultants
6. EPA Laboratory, Peshawar

The locations and operations for environmental monitoring:

1. **Air Emission Monitoring**: At **Compressor Stations**, **Coating Plants**, **CP Plant Kot Lakhpat**, **Co Gen Plant H/O**, **Distribution**, **Transmission**, and **Projects**, the sampling locations are **Generators, Welding Plants, Heavy Machinery / Operational Equipment, All Turbines exhaust Stacks** which should be done Annually.
2. **Ambient Air Quality**: In **Company Offices** with **Offices installed with; HVAC System, Printing and / or Photocopying equipment, Processes having bad impact on air quality at work place**, ambient air quality should be monitored Annually.
3. **Waste Water Monitoring**: At **Compressor Stations**, the sample will be collected from the disposal drain/ drains discharging industrial or municipal wastewater from the boundary wall, and should be collected from the ultimate disposal point, done Annually.

The locations and operations for environmental monitoring include:

- **Noise Monitoring / Mapping**: At **Compressor Stations** (which also include Generators, Welding Plants etc), **Transmission Sections Offices**, **SMSs**, and **Any other location / equipment deem necessary**, the noise level will be measured at the points nearest to the source of noise at the boundary wall, following the Noise Mapping Chart – SNGPL-EPR-002-CH-001 using the Form for Noise Monitoring - SNGPL-EPR-002-F-004 & F-005, and this should be done Annually.
- **Environmental Monitoring of Vehicles**: For **All Vehicles Company Owned / Hired**, environmental monitoring including Exhaust Emissions testing, Noise monitoring and Smoke test should be done Annually.

1.0 PURPOSE:

The purpose of this procedure is to:

- Enable SNGPL to achieve its corporate commitment and meet its statutory responsibility to the environment protection and maintain high quality in the preparation of Initial Environmental Examination (IEE) and Environmental Impact Assessment (EIA) within the SNGPL.
- Assist SNGPL employees to undertake environmental evaluation that assess environmental impacts objectively and comprehensively related to project implementation and operation. Note: This procedureshould be read in conjunction with the Environment Protection Guidelines ref: HSE 04/01.Further advice from HSE Department may be sought regarding IEE/ EIA.

2.0 SCOPE:

All activities, areas and departments of SNGPL as defined in IMS Manual **which intends to undergo any such activity which comes under the scope of Pakistan Environmental Protection Agency (Review of IEE and EIA) Regulations, 2000.**

3.0 DEFINITIONS, ABBREVIATIONS AND CONCEPTS:

SNGPL	Sui Northern Gas Pipelines Limited
EMS	Environmental Management System
HSC	HSE SITE Committee
EPA Act	Environmental Protection Act 1997
OGRA	Oil & Gas Regularity Authority
EIA	Environmental Impact Assessment
IEE	Initial Environmental Examination
Consultant	Pre-qualified environmental consultant

4.0 RESPONSIBILITIES AND AUTHORITIES:

4.1 HSE Management Committee
4.2 Management Representative (MR)
4.3 HOD
4.4 HSE SITE Committee (HSC)

5.0 PROCEDURE:

5.1 Initial Environmental Examination and Environmental Impact Assessment Regulatory Requirement.

The SNGPL's statutory responsibility to consider and assess the impacts of its projects and to minimize their damage to the environment is imposed by law. The Act which has the most significance is the Environmental Protection Act, 1997 (EPA Act). Clause 12 of PEPA pertains to new projects is reproduced below:

5.1.1No proponent of a project shall commence construction or operation unless he has filed with the Government Agency an **initial environmental examination (IEE)** or, where the project is likely to cause an adverse environmental effect, an **environmental impact assessment (EIA),** and has obtained from the Government Agency approval in respect thereof.

5.1.2Projects requiring an IEE

A proponent of a project falling in any category listed in Schedule I (Regulation 3 Pak-EPA attached) shall file an IEE with the Government Agency, and the provisions of section 12 shall apply to such projects.

5.1.3Projects requiring an EIA

A proponent of a project falling in any category listed in Schedule II (Regulation 4 Pak-EPA attached) shall file an EIA with the Government Agency, and the provisions of section 12 shall apply to such project.

5.1.4Projects NOT requiring an IEE or EIA

A proponent of a project not falling in any category listed in Schedule I and II shall not be required to file an IEE or EIA:
Provided that the proponent shall file –

(a) An EIA, if the project is likely to cause an adverse environmental affect,

(b) For projects not listed in Schedules I and II in respect of which the Government Agency has issued guidelines for construction and operation, an application for approval accompanied by an undertaking and an affidavit that the aforesaid guidelines shall be fully complied with.

5.1.5The Government Agency shall;

(a) Review the initial environmental examination and accord its approval, or require submission of an environmental impact assessment by the proponent; or

(b) Review the environmental impact assessment and accord its approval subject to such conditions as it may deem fit to impose, or require that the environmental impact assessment be re-submitted after such modifications as may be stipulated, or reject the project as being contrary to environmental objectives.

5.1.6Oil & Gas Regulatory Requirement

According to clause 16.1 the licensee shall conform to the requirements of the Pakistan Environmental Protection Act, 1997 (XXXIV of 1997), as amended from time to time. OGRA have tended to place a stricter interpretation on this law in the license to consider environmental impacts.

5.2 Initial Environmental Examination and Environmental Impact Assessment:

5.2.1 HOD is responsible to ensure:

- The process of environmental analysis.
- The decision whether the proposed project is required IEE or EIA with the help of zoning of protected areas, together with other available information with provincial and local governments.
- The preparation of the scope of work according to the attached guidelines (Annex: A) in consultation with HSE department.
- The engagement of a consultant as per company policy through competitive bidding among the consultants, as pre qualified by HSE Department.
- HSE Department will Pre qualify the consultants, as per Company's laid down procedures on as and when required basis.

5.2.2 HSE Department is responsible for the following.

- Reviewing and updating the IEE/EIA guidelines whenever required.

5.3 SNGPL Projects which require Initial Environmental Examination (IEE) Most SNGPL projects require comprehensive analysis and assessment with mitigation plan of the proposed project. Unless otherwise specified, it should be assumed that initial environmental examination is required for:

- Construction of new pipelines and related infrastructure by, or on behalf of, the SNGPL
- Construction of new Compressor Stations
- Construction of new Dope Yards
- Construction of new Project / Project Camp

Note: If there is any doubt whether an activity requires IEE or EIA, advice may be sought from HSE Department.

5.4 SNGPL Projects which require Environmental Impact Assessment (EIA)

Some projects may include works on classified, protected areas like wild life or forest century etc. will require Environmental Impact Assessment. For example,

- Pipeline construction through Changa Manga Forest will require EIA instead of IEE.
- Oil & Gas transmission, gathering and storage system are listed in schedule I of the EPA guidelines on environmental assessment and required IEE instead of EIA unless located in environmentally sensitive areas.

The requirements for quality, environment, health, and safety standards related to Initial Environmental Examination (IEE) and Environmental Impact Assessment (EIA) are based on **ISO 14001:2015, Element 6.1, 6.2**. The related documents include:

- **IEE / EIA Guidelines**
- **Schedule I (Regulation 3) Pak-EPA** (List of Projects requiring an IEE)
- **Schedule II (Regulation 4) Pak-EPA** (List of Projects requiring an EIA)

Annexure "A"

Guideline/ Procedure for Carrying out IEE / EIA

A Requirement of Environmental Protection Act 1997

Following are the requirement of Environmental Protection Act 1997

1. No proponent of a project shall commence construction or operation unless he has filed with the Federal Agency an initial environmental examination (IEE) or, project is likely where the project is likely to cause an adverse environmental effect, an environmental impact assessment (EIA), and has obtained from the Federal agency approval in respect thereof.

2. The Federal Agency shall;

a) Review the initial environmental examination and accord its approval, or require submission of an environmental impact assessment by the proponent; or

Review the environmental impact assessment and accord its approval subject to such condition as it may deem fit to impose, or require that the environmental impact assessment be re-submitted after such modification as may be stipulated, or reject the project as being contrary to environmental objectives.

B Procedure to be followed for IEE/ EIA by head of Departments

1. Based upon above mentioned Environment Protection Act 1997, decision should be taken whether IEE or EIA is required for the proposed project. HSE department may be consulted in this regard. 2. Engage consultant from the pre qualified consultants (Annex: B) as per company policy.
3. Submission of IEE / EIA to concerned Environment Protection Act Agency (EPA).
4. Follow up on EPA.
5. No physical work until No Objection Certificate (NOC) from EPA.

C Involvement of HSE Department

1. Draft copy of IEE/EIA will be submitted to HSE Department for comments.
2. NOC obtained will be forward to HSE Department.

1.0PURPOSE:

This procedure defines the methodology for the management and disposal of waste generated at all sites of SNGPL in a manner that protects human health and the environment.

2.0SCOPE:

This procedure covers all the solid waste being generated at all SNGPL sites.

3.0DEFINITIONS, ABBREVIATIONS AND CONCEPTS:

SOLID WASTE YARD:	An area developed for the storage of waste being generated at the site.
HAZARDOUS WASTE:	Hazardous wastes are wastes that pose a threat to human health or the environment if they are improperly stored, transported, treated or disposed. To manage hazardous wastes appropriately, there must be systematic control of how they are collected, stored, transported, treated, recovered and disposed. Waste which exhibits any of the hazardous characteristics (i.e. Ignitability, Corrosivity or Toxicity) is hazardous waste and is subject to all of the EPA's storage and disposal regulations.
CORROSIVE WASTE**:**	These wastes (primarily acids and bases) are technically defined as having a pH of less than 2.0 or greater than or equal to 12.5. In addition, any liquid waste which corrodes steel at a rate greater than 6.35 mm (0.25 inch) per year at a test temperature of 130 ^{o}F (55 ^{o}C) is also defined as Corrosive.
TOXIC WASTE:	The waste that have the potential of being poisonous or harmful to humans or other living organisms. The characteristic of toxicity is determined through quantitative laboratory analysis, according to TCLP. Wastes which exhibit TCLP concentrations of any listed compound in excess of the threshold limits established by EPA are by definition hazardous wastes**.**
TCLP:	Toxicity Characteristic Leaching Procedure. EPA determined that "mercury can migrate from municipal solid waste landfills in harmful concentrations and reach human drinking water sources. EPA developed the Toxic Characteristic Leaching Procedure to determine the toxicity of waste. TCLP is designed to simulate the leaching a waste which undergoes if disposed in a sanitary landfill. This test includes Mercury, Lead, Cadmium, and other hazardous materials. Passing this test for mercury, for instance, requires a yield of less than 0.2 mg/l upon completion of test.
EPA:	Environmental Protection Agency.
NON HAZARDOUS WASTE:	Any waste that does not exhibit any of the four characteristics of the hazardous waste is treated as non-hazardous waste. This waste constitutes; Food waste, Glass, Metal, Paper/wood/cardboard, Plastic, Rubber, Textiles, Styrofoam/foam, rubber, PVC cables/hoses/plastic waste etc.
DEBRIS:	It is the waste generated from construction work i.e. sand, blocks, wooden pieces etc.

4.0RESPONSIBILITIES AND AUTHORITIES:

4.1 Head of Department / Site Incharge

4.2 HSE Site Committee

4.3 Concerned Admin. Deptt. Representative

5.0 PROCEDURE:

5.1 Hazardous Waste Management at site:

5.1.1 Hazardous wastes at site include; contaminated sand, Hospital / dispensary waste, Oily cotton rags, Empty drums / bottles of hazardous chemicals, Used Oil

5.1.2 All the hazardous waste being generated from the site is collected in yellow drums which should be placed in prominent positions of site. It is important that the concerned Area Admin Department representative accurately complete the **Hazardous Waste Label** and ensure that label is pasted on each drum of hazardous waste.

5.1.3 Yellow hazardous waste drums are shifted to the yard whenever filled. The waste of the yellow drums is dumped in the **hazardous waste yard** and drums are placed back to its original location at the site.

5.1.4Empty drums / bottles of the hazardous chemicals are stored in the Hazardous waste yard. These drums (Metal / Plastic) are shifted to the Hazardous waste yard by concerned department. Empty bottles, oily rags and contaminated / leaked cans of oil and chemicals are accumulated in the cotton bags and are dumped in the Hazardous waste drums placed in the site.

5.1.5Trays must be available / installed at specific areas before collection of used oil. Relevant PPE's (mask, gloves and goggles) must be used during handling used oil. Area / machinery must be cleaned after collection of oil.
In case of spillage / leakage, areas / machinery should be cleaned and all spilled/leaked oil should be properly collected. In case of spillage/leakage, sand may be used for absorption of oil to avoid land contamination. The contaminated sand is to be disposed as Hazardous waste.

5.1.6Admin Officer/Engineer Maintenance shall ensure that secondary containment is provided under all Oil drums stored at site. Admin Officer/Engineer Maintenance shall be responsible to maintain the collection / disposal record of used oil handed over to Stores, on the form Used Oil Record (SNGPL-EPR004-F003).

5.1.7Concerned Stores executive shall be responsible to maintain the record of final collection / disposal of oil.

5.1.8 **Hazardous Waste Disposal Request** Form **(SNGPL-EPR004-F001)** is duly filled by the HSE Site Committee member clearly mentioning nature and quantity of the waste.

5.1.9 Administration representative checks and sign the request and the material is shifted to the stores.

5.1.10 Dispensary Waste generated at site is required to be segregated in three color coded waste baskets i.e yellow for infectious/ hazardous waste, red for sharps and white basket for non hazardous general waste. Infectious waste collected in yellow waste basket is hazardous waste. It contains; gauze dressings, bandages etc. This waste is collected by dispensary staff in sealed, labeled hazardous waste yellow color bags. Needle cutter waste containing cut end of steel portion of syringes for injection and used syringes plastic portion will be collected separately in yellow colored safety box. Sharps like glass ampoules of used injection vials etc will be collected in Red bag. Medical Officer / dispenser are responsible for the proper segregation and collection in white, yellow and red bags. Admin Department is responsible for safe disposal of the medical waste.

5.2 Non-Hazardous Waste Management at site:

5.2.1 The Non-hazardous waste is dumped in the green drums which should be placed in prominent positions of sites. It is important that the concerned Area Admin Department representative ensures that label is pasted on each drum of non-hazardous waste.

5.2.2 Non-hazardous waste in green drums is shifted to the non-hazardous waste yard. Admin representative keeps the record of all the municipal waste and submit the record to the HSE Site Committee on monthly basis. Hazardous waste shall not be dumped in those green drums.

5.2.3 Debris will be shifted to **Debris Yard.**

5.3 WasteYards:

5.3.1A Solid Waste Management Yard should be established at those sites where the hazardous waste is generated. All types of solid wastes are collected in this waste yard and separated according to their nature. There are three separate yards according to nature of waste.

- Hazardous Waste Yard
- Non-Hazardous Waste yard
- Debris Yard

5.3.2All the Scrap material is shifted to the Scrap Yard developed near solid waste yards. It constitutes; Metal chip, Discarded pipes and fittings, Tyres, Iron plates, Welding rods, Wooden pieces, Empty drums (non hazardous chemicals), empty cylinders, Winding wires, Cans, Fused tube lights / bulbs, Bearings, Plywood pieces etc

5.3.3Administration representative keeps the record of scrape at yard and material which is shifted to the stores.

5.3.4 If there is no hazardous waste generated at site, there is no need to developed hazardous waste yards. **For Non-Hazardous waste, site will follow local government waste collection practices / laws.**

5.3.5 All the Waste Disposed off at the site will be recorded at **Waste Disposal Record** form **(SNGPL-EPR-004-F002)** by the Administration representative.

5.4 Precautions:

5.4.1 Leather gloves, Safety shoes and Coverall are required for the person handling the Non-Hazardous waste.

5.4.2 Leather / PVC gloves, Safety shoes, **Safety goggles,** Coverall / PVC suit and appropriate Gas Masks are required for the person handling the Hazardous waste.

Avoid manual handling of the filled drums as it may cause the injury. 5.4.3

6.0 REQUIREMENT OF QUALITY, ENVIRONMENT, HEALTH AND SAFETY STANDARDS:

6.1 ISO 14001:2015, Clause 8.1

7.0 RELATED DOCUMENTS:

7.1 Hazardous Waste disposal Form	SNGPL-EPR004-F-001
7.2 Waste Disposal Record	SNGPL-EPR004-F-002
7.3 Used oil record	SNGPL-EPR004-F-003
7.4 Hazardous Waste Label	
7.5 Non-Hazardous Waste Label	