

SIEMENS - ANALOG IN LAB: INPUT CONDITIONS LIST WORKSHEET

An instruction with a single **asterisk *** is within the holding circuit.

Instructions with double **asterisks **** are in parallel.

COMPLETE THE INSTRUCTIONS AND TAGS

MAIN OB1

NETWORK 1:

Unconditional Call to Function Analog Gauge

NETWORK 2:

Unconditional Call to Function Block Conveyor Control

FUNCTION ANALOG GAUGE

NETWORK 1:

Instruction to Normalize the Value

_____	Minimum Normalized value
_____	Simulated Analog Input
_____	Maximum Normalized value
_____	Out Normalized value

continue

Instruction to Scale the Value

_____	Engineering Unit minimum value
_____	Normalized value
_____	Engineering Unit maximum value
_____	Scaled output value

FUNCTION BLOCK CONVEYOR CONTROL

NETWORK 1: CONVEYOR MOTOR (Requires holding circuit)

_____	_____	Part feed error indicator to break the holding circuit.
_____	_____	Stop pushbutton to break the holding circuit.
_____*	_____	Start pushbutton.
_____	_____	Holding Circuit

NETWORK 2: PART A ERROR

_____	_____	Input proximity switch that detects part A.
_____	_____	An instruction that determines if the height sensors reads a value that is at or above for a set point for a double part A.

NETWORK 3: PART B ERROR

_____	_____	Input proximity switch that detects part B.
_____	_____	An instruction that determines if the height sensors reads a value that is at or above for a set point for a double part B.

NETWORK 4: ERROR (Set Output)

____ ** _____ PART A ERROR detected.

____ ** _____ PART B ERROR detected.

NETWORK 5: ERROR (Reset Output)

_____ Input for operator reset.