

STUDIO 5000 - ANALOG IN LAB: INPUT CONDITIONS LIST WORKSHEET

An instruction with a single **asterisk *** is within the holding circuit.

Instructions with double **asterisks **** are in parallel.

COMPLETE THE INSTRUCTIONS AND TAGS

MAIN ROUTINE

RUNG 0:

Unconditional Call to routine **Scaling**

RUNG 1:

Unconditional Call to routine **ConveyorControlRoutine**

SCALING ROUTINE

RUNG 0:

Add-On Instruction HEIGHT_SCALE

CONVEYOR CONTROL ROUTINE

RUNG 0: CONVEYOR MOTOR (Requires holding circuit)

_____	_____	Part feed error indicator to break the holding circuit.
_____	_____	Stop pushbutton to break the holding circuit.
_____*	_____	Start pushbutton to break the holding circuit.
_____	_____	Holding Circuit

RUNG 1: PART A ERROR

Input proximity switch that detects part A.

An instruction that determines if the height sensors reads a value that is at or above for a set point for a double part A.

RUNG 2: PART B ERROR

Input proximity switch that detects part B.

An instruction that determines if the height sensors reads a value that is at or above for a set point for a double part B.

RUNG 3: ERROR (Latched Output)

_____ **

PART A ERROR detected.

_____ **

PART B ERROR detected.

RUNG 4: ERROR (Unlatched Output)

Input for operator reset.