KP3S Pro Filament Sensor Bracket

Colson

VIEW IN BROWSER

updated 26. 4. 2023 | published 26. 4. 2023

Summary

Bracket for placing the filament sensor on top of the Z axis

0.94 hrs	1 pcs	0.15 mm	0.40 mm	PET	7 g	Kingroon KP3S

3D Printers   >   3D Printers - Upgrades

Tags: filamentguide   filamentsensor   kp3s   kp3spro

Bracket that allows for placing the KP3S Pro's filament sensor on top of the printer, allowing for the placement of filament dehydrators and other enclosed filament spools directly next to the printer. Extending the filament sensor cable requires 2x3 M-to-F Dupont Wires, which can be plugged into the filament sensor with ease.
To install the bracket, simply use the two large screws from the top of the Z axis to bolt it into place. Run the extension cables through the backside of the Z axis beam, using the twist-to-lock cable brackets to secure it in place.
Enjoy!

Model files

filamentsensorbracketv321.stl

kp3s_cablebracketv6.stl

Print files

kp3s-pro-filament-sensor-bracket-and-cable-kit.gcode

✧ PET   ⬇ 0.40 mm   ≡ 0.15 mm   ⏱ 0.94 hrs   ⚖ 7 g   🖥 Prusa MINI / MINI+

License Ⓒ

This work is licensed under a
Creative Commons (4.0 International License)

Attribution-ShareAlike

✖ | Sharing without ATTRIBUTION
✔ | Remix Culture allowed
✔ | Commercial Use
✔ | Free Cultural Works
✔ | Meets Open Definition