

HSS 611 - Week 14: Text-as-data

2023-11-27

Agenda

- Pattern matching with regex
 - Introduction to key approaches
- Text normalization
 - Tokenization
 - Stopwords
 - Lemmatization/stemming
- Representing and comparing texts
 - Count vectors
 - TF-IDF
 - Cosine similarity
- Word embeddings
 - Vector semantics
 - Pretrained embeddings

Pattern matching with regex

Matching substrings

- Finding and counting substrings

```
print("strawberry".find("berry"))  
print("strawberry".count("berry"))
```

5

1

Pattern matching with regex

Matching substrings

- Finding and counting substrings
- `find()` returns -1 for non-match

```
print("strawberry".find("better"))  
print("strawberry".count("better"))
```

-1

0

Pattern matching with regex

Matching substrings

- Returns the first match

```
print("berryberrystrawberry".find("berry"))
```

0

Pattern matching with regex

Matching substrings

- List of 80 fruits

```
import pandas as pd
url = 'https://raw.githubusercontent.com/taegyoon-kim/programming_dhcss_23fw/main/fruit.csv'
fruit = pd.read_csv(url, header = None)[0].to_list()
print(len(fruit))
print(fruit[0])
```

80

apple

Pattern matching with regex

Matching substrings

- Use list comprehension to extract matches

```
[i for i in fruit if i.find("berry") > -1]
```

```
['bilberry',  
 'blackberry',  
 'blueberry',  
 'boysenberry',  
 'cloudberry',  
 'cranberry',  
 'elderberry',  
 'goji berry',  
 'gooseberry',  
 'huckleberry',  
 'mulberry',  
 'raspberry',  
 'salal berry',  
 'strawberry']
```

Pattern matching with regex

What is regex?

- A sequence of characters that forms a flexible search pattern
- Can be used to check if a string contains the specified search pattern

```
import re  
mo = re.search(r'berry', 'strawberry.')  
print(type(mo))
```

```
<class 're.Match'>
```


Pattern matching with regex

Extraction into a list

```
print(mo)
print(mo.group())
```

```
berries = [i for i in fruit if re.search(r'berry',i)]
print(berries)
```

```
c = re.compile(r'berry') # *compile* the pattern into an object
berries = [i for i in fruit if c.search(i)]
```

```
<re.Match object; span=(5, 10), match='berry'>
```

```
berry
```

```
['bilberry', 'blackberry', 'blueberry', 'boysenberry', 'cloudberry', 'cranberry']
```

Pattern matching with regex

Multiple matches

```
mo_m = re.search(r'berry',"berryberrystrawberry")
print(mo_m.group()) # returns the first match

mo_m2 = re.findall(r'berry',"berryberrystrawberry")
print(mo_m2) # this is a list of strings
```

```
berry
['berry', 'berry', 'berry']
```

Pattern matching with regex

Square brackets for “or”

- Square brackets for “or”: matches “any one of” the characters in [].
- Read data first

```
url = 'https://raw.githubusercontent.com/taegyoon-kim/programming_dhcss_23fw/main/data/sentences.csv'
sentences = pd.read_csv(url, header = None, sep = '@')[0].to_list()
print(len(sentences))
print(sentences[0])
```

720

The birch canoe slid on the smooth planks.

Pattern matching with regex

Square brackets for “or”

- For beat, heat, peat

```
c = re.compile(r' [bhp]eat ')
l_mo = [i for i in sentences if c.search(i)]
for i in l_mo:
    print(i)
```

The heart beat strongly and with firm strokes.
Burn peat after the logs give out.
Feel the heat of the weak dying flame.
A speedy man can beat this track mark.
Even the worst will beat his low score.
It takes heat to bring out the odor.

Pattern matching with regex

Square brackets for “or”

- Use `-` to indicate a range of contiguous characters

```
c = re.compile(r' [b-p]eat ')\nl_mo = [i for i in sentences if c.search(i)]\nfor i in l_mo:\n    print(i)
```

The heart beat strongly and with firm strokes.
Burn peat after the logs give out.
Feel the heat of the weak dying flame.
A speedy man can beat this track mark.
Even the worst will beat his low score.
Pack the records in a neat thin case.
It takes heat to bring out the odor.
A clean neck means a neat collar.

Pattern matching with regex

Square brackets for “or”

- Match anything but one of the characters in the square brackets

```
c = re.compile(r' [^bhp]eat ')\nl_mo = [i for i in sentences if c.search(i)]\nfor i in l_mo:\n    print(i)
```

Pack the records in a neat thin case.
A clean neck means a neat collar.

Pattern matching with regex

“Or” over multi-character patterns

- We can use | operator
- Parentheses can be used to indicate parts in the pattern

```
c = re.compile(r'(black|blue|red)(currant|berry)')  
l_mo = [i for i in fruit if c.search(i)]  
l_mo
```

```
['blackberry', 'blackcurrant', 'blueberry', 'redcurrant']
```

Pattern matching with regex

The group() attribute

```
c = re.compile(r'(black|blue|red)(currant|berry)')
mo = c.search('blackberry')
print(mo.group(0))
print(mo.group(1))
print(mo.group(2))
```

blackberry

black

berry

Pattern matching with regex

Special characters and the backslash

- Let's create a random example string

```
eg_str = 'Example STRING, with numbers (12, 15 and also 10.2)?! Wow, two sentences.'
```

Pattern matching with regex

Special characters and the backslash

- There are several characters that have a special meaning in regex, and (may) have to be escaped in order to match the literal character
- They include `^`, `$`, `.`, `*`, `+`, `|`, `!`, `?`, `(`, `)`, `[`, `]`, `{`, `}`, `<`, and `>`

Pattern matching with regex

Special characters and the backslash

- For example, `.` means “any character but a newline”

```
allchars = re.findall(r'.', eg_str)
print(allchars)
```

```
['E', 'x', 'a', 'm', 'p', 'l', 'e', ' ', 'S', 'T', 'R', 'I']
```

```
allperiods = re.findall(r'\.', eg_str)
print(allperiods)
```

```
['.', '.']
```

Pattern matching with regex

Special characters and the backslash

- For example, `.` means “any character but a newline”

```
matches = re.findall(r'a.', eg_str)
print(matches)
matches = re.findall(r'a\.', eg_str)
print(matches)
```

```
['am', 'an', 'al']
```

```
[]
```

Pattern matching with regex

Class shorthands

- “\w” (any alphanumeric character), “\s” (any space character), and “\d” (any numeric digit)
- The capitalized versions of these are used to mean “anything but” that class

```
# any alphanumeric character
matches = re.findall(r'\w', eg_str)
print(matches)
```

```
# any non-alphanumeric character
matches = re.findall(r'\W', eg_str)
print(matches)
```

['E', 'x', 'a', 'm', 'p', 'l', 'e', 'S', 'T', 'R', 'I', 'N
[' ', ' ', ' ', ' ', ' ', ' ', '(', ' ', ' ', ' ', ' ', ' ', ' ', ' '.

Pattern matching with regex

Class shorthands

```
# any whitespace character
matches = re.findall(r'\s',eg_str)
print(matches)
```

```
# any non-whitespace character
matches = re.findall(r'\S',eg_str)
print(matches)
```

```
[' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ']  
['E', 'x', 'a', 'm', 'p', 'l', 'e', 'S', 'T', 'R', 'I', 'N']
```

Pattern matching with regex

Class shorthands

```
# any digit character
matches = re.findall(r'\d',eg_str)
print(matches)
```

```
# any non-digit character
matches = re.findall(r'\D',eg_str)
print(matches)
```

```
['1', '2', '1', '5', '1', '0', '2']
```

```
['E', 'x', 'a', 'm', 'p', 'l', 'e', ' ', 'S', 'T', 'R', 'I']
```

Pattern matching with regex

Quantifiers: * (zero or more of the previous)

```
# any string of zero or more digits
matches = re.findall('\d*', eg_str)
print(matches)
```

```
['', '', '', '', '', '', '', '', '', '', '', '', '', '', '', ''
```


Pattern matching with regex

Quantifiers: + (one or more of the previous)

```
matches = re.findall('\d+', eg_str) # any string of zero or more digits
print(matches)
```

```
['12', '15', '10', '2']
```

Pattern matching with regex

Quantifiers: $\{n\}$ $\{n,m\}$ and $\{n,\}$

- $\{n\}$ = “exactly n ” of the previous
- $\{n,m\}$ = “between n and m ” of the previous
- $\{n,\}$ = “ n or more” of the previous

Pattern matching with regex

Quantifiers: {n} {n,m} and {n,}

```
# 3 x's
matches = re.findall(r'x{3}','x xx xxx xxxx xxxxx')
print(matches)

# 3 or 4 x's
matches = re.findall(r'x{3,4}','x xx xxx xxxx xxxxx')
print(matches)

# 3 or more x's
matches = re.findall(r'x{3,}','x xx xxx xxxx xxxxx')
print(matches)

['xxx', 'xxx', 'xxx']
['xxx', 'xxxx', 'xxxx']
['xxx', 'xxxx', 'xxxxx']
```

Pattern matching with regex

Quantifiers: ? (zero or one of the previous)

```
c = re.compile(r' [bp]?eat ')
matches = [i for i in sentences if c.search(i)]
matches
```

```
['The heart beat strongly and with firm strokes.',
 'Burn peat after the logs give out.',
 'A speedy man can beat this track mark.',
 'Even the worst will beat his low score.',
 'Quench your thirst, then eat the crackers.']
```

Pattern matching with regex

Quantifiers

- `.+` is a greedy quantifier that matches one or more of any character as many times as possible
- `.+?` is a non-greedy quantifier that matches as few characters as possible

```
matches = re.findall(r'\(.\+\\)',  
'(First bracketed statement) Other text (Second bracketed statement)')  
print(matches)
```

```
['(First bracketed statement) Other text (Second bracketed statement)']
```

Pattern matching with regex

Quantifiers

- `.+` is a greedy quantifier that matches one or more of any character as many times as possible
- `.+?` is a non-greedy quantifier that matches as few characters as possible

```
matches = re.findall(r'\(.*?\)',  
'(First bracketed statement) Other text (Second bracketed statement)')  
print(matches)
```

```
['(First bracketed statement)', '(Second bracketed statement)']
```

Pattern matching with regex

Quantifiers

- `.+` is a greedy quantifier that matches one or more of any character as many times as possible
- `.+?` is a non-greedy quantifier that matches as few characters as possible

```
matches = re.findall(r'x.+x','x xx xxx xxxx xxxxx')  
print(matches)
```

```
matches = re.findall(r'x.+?x','x xx xxx xxxx xxxxx')  
print(matches)
```

```
['x xx xxx xxxx xxxxx']
```

```
['x x', 'x x', 'xx x', 'xxx', 'xxx']
```

Text normalization

Caveat

- The objective of text normalization is to clean up text and transform it into meaningful units of analysis
- A specific combination of techniques to be employed is highly dependent on your research question
- You always need to ask yourself what impact your decisions would have on subsequent analyses

Caveat

PA

Text Preprocessing For Unsupervised Learning: Why It Matters, When It Misleads, And What To Do About It

Matthew J. Denny¹ and Arthur Spirling²

¹ 203 Pond Lab, Pennsylvania State University, University Park, PA 16802, USA. Email: mdenny@psu.edu

² Office 405, 19 West 4th St., New York University, New York, NY 10012, USA. Email: arthur.spirling@nyu.edu

Abstract

Despite the popularity of unsupervised techniques for political science text-as-data research, the importance and implications of preprocessing decisions in this domain have received scant systematic attention. Yet, as we show, such decisions have profound effects on the results of real models for real data. We argue that substantive theory is typically too vague to be of use for feature selection, and that the supervised literature is not necessarily a helpful source of advice. To aid researchers working in unsupervised settings, we introduce a statistical procedure and software that examines the sensitivity of findings under alternate preprocessing regimes. This approach complements a researcher's substantive understanding of a problem by providing a characterization of the variability changes in preprocessing choices may induce when analyzing a particular dataset. In making scholars aware of the degree to which their results are likely to be sensitive to their preprocessing decisions, it aids replication efforts.

Keywords: statistical analysis of texts, unsupervised learning, descriptive statistics

Text normalization

Tokenization

- A token is an instance of a sequence of characters in a document that are grouped together as a useful semantic unit
- Tokenization is the task of segmenting running text into tokens
- The very start of downstream NLP tasks
- NLTK (Natural Language ToolKit), among many others, offers useful tools for tokenization

Text normalization

Import NLTK and Punkt Tokenizer

- There are a wide range of tokenizers
- They differ in various aspects
 - E.g., handling punctuation, special characters, or numbers
- See the official document of [Punkt Tokenizer](#)

```
import nltk
#nltk.download('punkt') # import Punkt Tokenizer
from nltk.tokenize import sent_tokenize
from nltk.tokenize import word_tokenize
```

Text normalization

```
text = ""Altman announced a few weeks ago at OpenAI's first-ever developer day  
print(text)
```

Altman announced a few weeks ago at OpenAI's first-ever developer day that the OpenAI has also worked with Microsoft to roll out ChatGPT-like technology across OpenAI and iPhone designer Jony Ive had also reportedly been in talks to raise

Text normalization

```
sentences = sent_tokenize(text) # a.k.a sentence segmentation
for s in sentences:
    print(f"{s}\n")
```

Altman announced a few weeks ago at OpenAI's first-ever developer day that the OpenAI has also worked with Microsoft to roll out ChatGPT-like technology across OpenAI and iPhone designer Jony Ive had also reportedly been in talks to raise

Text normalization

```
tokenized = word_tokenize(sentences[1])  
for i in tokenized:  
    print(i)
```

OpenAI
has
also
worked
with
Microsoft
to
roll
out
ChatGPT-like
technology
across
Microsoft
,
s
products
.

Text normalization

Stop words

- Stop words are the words that are filtered out (due to insignificance)
- For the previous example, the words like 'the' or 'an' are not quite meaningful
- Again, however, it depends upon the nature of the task you are working on
- E.g., topic modeling vs. language modeling

Text normalization

Stop words

```
from nltk.corpus import stopwords
#nltk.download('stopwords')
print(len(stopwords.words('english')))
print(stopwords.words('english')[0:10])
```

179

```
['i', 'me', 'my', 'myself', 'we', 'our', 'ours', 'ourselves', 'you', "you're"]
```


Text normalization

Stop words

```
tokens = word_tokenize(sentences[1])

tokens_no_sw = [t for t in tokens if not t.lower() in stopwords.words('english')]

print(tokens)
print(tokens_no_sw)
```

```
['OpenAI', 'has', 'also', 'worked', 'with', 'Microsoft', 'to', 'roll', 'out', 'ChatGPT-like', 'technology']
['OpenAI', 'also', 'worked', 'Microsoft', 'roll', 'ChatGPT-like', 'technology', 'across', 'Microsoft', '']
```

Text normalization

Lemmatization

- Lemmatization is identifying the base form of a word, irrespective of its surface variations
 - 'am', 'are', and 'is' share the same lemma 'be'
 - 'dog', 'dogs', and 'doggy' share the same lemma 'dog'
- Built on morphological parsing (splitting words into morphemes)

Text normalization

Lemmatization

```
from nltk.stem import WordNetLemmatizer
#nltk.download('wordnet')

tokens = ['cats', 'doing', 'lives', 'has',
'going', 'legislate', 'asocial', 'flew', 'friendly', 'loved']

wordnet_lemmatizer = WordNetLemmatizer()
tokens_lemma = [wordnet_lemmatizer.lemmatize(w) for w in tokens]

print(tokens)
print(tokens_lemma)
```

```
['cats', 'doing', 'lives', 'has', 'going', 'legislate', 'asocial', 'flew', 'friendly', 'loved']
['cat', 'doing', 'life', 'ha', 'going', 'legislate', 'asocial', 'flew', 'friendly', 'loved']
```

Text normalization

Stemming

- Stemming is a simpler but cruder method (lemmatization algorithms are be complex)
- Consists of chopping off word-final affixes
- There are various stemming algorithms as well

Text normalization

Stemming

```
from nltk.stem import PorterStemmer
```

```
tokens_stem_p = []
```

```
ps = PorterStemmer()
```

```
for w in tokens:
```

```
    root = ps.stem(w)
```

```
    tokens_stem_p.append(root)
```

```
print(tokens)
```

```
print(tokens_stem_p)
```

```
['cats', 'doing', 'lives', 'has', 'going', 'legislate', 'asocial', 'flew', 'friendly', 'loved']
```

```
['cat', 'do', 'live', 'ha', 'go', 'legisl', 'asoci', 'flew', 'friendli', 'love']
```

Text normalization

Stemming

```
from nltk.stem import LancasterStemmer

tokens_stem_l = []

ls = LancasterStemmer()
for w in tokens:
    root = ls.stem(w)
    tokens_stem_l.append(root)

print(tokens)
print(tokens_stem_p)
print(tokens_stem_l)
```

```
['cats', 'doing', 'lives', 'has', 'going', 'legislate', 'asocial', 'flew', 'friendly', 'loved']
['cat', 'do', 'live', 'ha', 'go', 'legisl', 'asoci', 'flew', 'friendli', 'love']
['cat', 'doing', 'liv', 'has', 'going', 'legisl', 'asoc', 'flew', 'friend', 'lov']
```

Text normalization

No single answer to how we should go about this

- It is a good practice to understand what happens under the hood at each step of the process (tokenization -> stop words -> lemmatization/stemming)
- One approach is not only think in advance deductively which combination would be most suitable but also run robustness analyses built on different combinations
- Another (less ideal but easier) approach is to (critically) follow “the norm”

Representing and comparing texts

The BoW model (the bag-of-words model)

- The BoW model is a model of text represented as an unordered collection of words
- Converting running text to BoW data in the form of a DTM (document-term matrix)

Representing and comparing texts

The BoW model (the bag-of-words model)

- Count vectors

Document D1	<i>The child makes the dog happy</i> the: 2, dog: 1, makes: 1, child: 1, happy: 1
Document D2	<i>The dog makes the child happy</i> the: 2, child: 1, makes: 1, dog: 1, happy: 1



	child	dog	happy	makes	the	BoW Vector representations
D1	1	1	1	1	2	[1,1,1,1,2]
D2	1	1	1	1	2	[1,1,1,1,2]

Representing and comparing texts

Count vectors

- Most easily done in Python with CountVectorizer from the ML library **scikit-learn**

```
from sklearn.feature_extraction.text import CountVectorizer
```

```
url = 'https://raw.githubusercontent.com/taegyoon-kim/programming_dhcss_23fw/main/inaugural_df.csv'
inaugural_df = pd.read_csv(url)
```

```
print(len(inaugural_df))
print(inaugural_df.head())
```

58

	docnames	text
0	1789-Washington	Fellow-Citizens of the Senate and of the House...
1	1793-Washington	Fellow citizens, I am again called upon by the...
2	1797-Adams	When it was first perceived, in early times, t...
3	1801-Jefferson	Friends and Fellow Citizens: Called upon to...
4	1805-Jefferson	Proceeding, fellow citizens, to that qualifica...

Representing and comparing texts

Count vectors

- See [here](#) for attributes (tokenization/normalization is included in the class!)

```
vectorizer = CountVectorizer() # many text normalization decisions here
dtm = vectorizer.fit_transform(inaugural_df['text'])
dtm # 58 * 9046 (vocabulary)
```

```
<58x9046 sparse matrix of type '<class 'numpy.int64'>'
  with 43638 stored elements in Compressed Sparse Row format>
```

Representing and comparing texts

Count vectors

```
vocab = vectorizer.get_feature_names_out(inaugural_df['text'])  
print(vocab[0:30])  
print(vocab[-10:])
```

```
['000' '100' '120' '125' '13' '14th' '15th' '16' '1774' '1776' '1778'  
 '1780' '1787' '1789' '1790' '1800' '1801' '1812' '1815' '1816' '1817'  
 '1818' '1826' '1850' '1861' '1868' '1873' '1880' '1886' '1890']  
['your' 'yours' 'yourself' 'yourselves' 'youth' 'youthful' 'zeal'  
 'zealous' 'zealously' 'zone']
```

Representing and comparing texts

Count vectors

```
print(dtm.shape)
print(dtm.size) # non-zero elements

import numpy as np
1 - (float(dtm.size) / np.prod(dtm.shape))
```

(58, 9046)

43638

0.9168274032340451

Representing and comparing texts

Count vectors

```
sum_words = dtm.sum(axis = 0) # a 1 x 9046 matrix
words_freq = [(word, sum_words[0, idx]) for word, idx in vectorizer.vocabulary_.items()]
words_freq = sorted(words_freq, key = lambda x: x[1], reverse = True)

words_freq[0:10]
```

```
[('the', 9821),
 ('of', 6889),
 ('and', 5207),
 ('to', 4423),
 ('in', 2726),
 ('our', 2146),
 ('that', 1748),
 ('we', 1740),
 ('be', 1452),
 ('is', 1430)]
```

Representing and comparing texts

Count vectors

```
vectorizer_nostop = CountVectorizer(stop_words = 'english')  
dtm_nostop = vectorizer_nostop.fit_transform(inaugural_df['text'])  
dtm_nostop
```

```
<58x8771 sparse matrix of type '<class 'numpy.int64'>'  
  with 36009 stored elements in Compressed Sparse Row format>
```

Representing and comparing texts

Count vectors

```
sum_words_nostop = dtm_nostop.sum(axis=0) # a 1 x 9211 matrix
words_freq_nostop = [(word, sum_words_nostop[0, idx]) for word, idx in vectorizer_nostop.vocabulary_.items()]
words_freq_nostop = sorted(words_freq_nostop, key = lambda x: x[1], reverse = True)

words_freq_nostop[0:10]
```

```
[('government', 591),
 ('people', 566),
 ('great', 338),
 ('world', 337),
 ('states', 324),
 ('nation', 311),
 ('shall', 310),
 ('country', 303),
 ('peace', 254),
 ('new', 252)]
```


Representing and comparing texts

Count vectors

```
vectorizer_2g = CountVectorizer(ngram_range=(2, 2))  
dtm_2g = vectorizer_2g.fit_transform(inaugural_df['text'])  
dtm_2g
```

```
<58x63676 sparse matrix of type '<class 'numpy.int64'>'  
  with 106560 stored elements in Compressed Sparse Row format>
```

Representing and comparing texts

Count vectors

```
sum_words_2g = dtm_2g.sum(axis=0) # a 1 x 63676 matrix
words_freq_2g = [(word, sum_words_2g[0, idx]) for word, idx in vectorizer_2g.vocabulary_.items()]
words_freq_2g = sorted(words_freq_2g, key = lambda x: x[1], reverse=True)
```

```
words_freq_2g[0:10]
```

```
[('of the', 1712),
 ('in the', 790),
 ('to the', 699),
 ('of our', 604),
 ('and the', 461),
 ('it is', 315),
 ('by the', 307),
 ('for the', 304),
 ('to be', 300),
 ('the people', 263)]
```

Representing and comparing texts

TF-IDF vectors

- Counter vectors consider the frequencies of words
- However, some words are too frequent: the, a, an, etc.
- We want to weight how unique a word is in the corpus

Representing and comparing texts

TF-IDF vectors

TF-IDF VECTORIZATION



	text	tf	idf
0	Eddard Stark is a king in the north.	1	3
1	A king but one king; kings are everywhere.	2	3
2	Hodor was different : he was not a king.	1	3
3	But the North could not change without him.	0	3

	king	was	the	not	a	he	one	north	kings	is	in	him	everywhere	A	different	could	change	but	are	Stark	North	Hodor	Eddard
0	0.333333	0.0	0.5	0.0	0.5	0.0	0.0	0.0	1.0	0.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0	0.0	0.0	1.0
1	0.666667	0.0	0.0	0.0	0.0	0.0	0.0	1.0	0.0	1.0	0.0	0.0	0.0	1.0	1.0	0.0	0.0	0.0	1.0	1.0	0.0	0.0	0.0
2	0.333333	2.0	0.0	0.5	0.5	1.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	1.0	0.0
3	0.000000	0.0	0.5	0.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	1.0	1.0	0.0	0.0	0.0	1.0	0.0

Representing and comparing texts

TF-IDF vectors

$$w_{i,j} = tf_{i,j} \times \log \left(\frac{N}{df_i} \right)$$

tf_{ij} = number of occurrences of i in j

df_i = number of documents containing i

N = total number of documents

Representing and comparing texts

TF-IDF vectors

```
import pandas as pd

url = 'https://raw.githubusercontent.com/taegyoon-kim/programmer99/master/news.csv'
news_df = pd.read_csv(url, sep = ';')
news_df = news_df.sample(1000)
```

Representing and comparing texts

TF-IDF vectors

news_df

	No	News Title	Category
28830	28831	Walter Dean Myers, celebrated young adult auth...	Entertainment
22851	22852	Alabama unemployment rises to 6.4 percent in F...	Business
30525	30526	'Sharknado 2: The Second One:' Read what other...	Entertainment
46976	46977	Lea Michele Dating: 'Louder' Singer's New Boyf...	Entertainment
56098	56099	One of the best iOS email clients is now avail...	Technology
...
4431	4432	Austin Mahone Takes The Stage At The 2014 Kids...	Entertainment
1091	1092	Apple and Google call patent dispute truce	Technology
17932	17933	'True Blood' season 7 episode 4 preview: Track...	Entertainment
45422	45423	Fuel prices dip downward	Business
12886	12887	Supreme Court limits federal regulation of gre...	Business

Representing and comparing texts

TF-IDF vectors

```
from sklearn.feature_extraction.text import TfidfVectorizer

tf_idf_model = TfidfVectorizer().fit(news_df['News Title'])

word_id_list = sorted(
    tf_idf_model.vocabulary_.items(),
    key = lambda x: x[1], reverse = False
)

word_list = [x[0] for x in word_id_list]

tf_idf_df = pd.DataFrame(
    tf_idf_model.transform(news_df['News Title']).toarray(),
    columns = word_list,
    index = news_df['No'])
```


Representing and comparing texts

TF-IDF vectors

tf_idf_df

No	02	04	08	10	100	11	110	117	12	13	...	zambians	z
28831	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
22852	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
30526	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
46977	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
56099	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
...
4432	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
1092	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
17933	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
45423	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0
12887	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0

Representing and comparing texts

Comparing texts with cosine similarity

$$\cos(\theta) = \frac{\mathbf{A} \cdot \mathbf{B}}{\|\mathbf{A}\| \|\mathbf{B}\|} = \frac{\sum_{i=1}^n A_i B_i}{\sqrt{\sum_{i=1}^n A_i^2} \sqrt{\sum_{i=1}^n B_i^2}}$$

- It ranges from -1 (opposite) to 0 (orthogonal) to 1 (identical)

```
from sklearn.metrics.pairwise import cosine_similarity
```

Representing and comparing texts

Comparing texts with cosine similarity

```
tf_idf_model = TfidfVectorizer().fit(news_df['News Title'])

word_id_list = sorted(
    tf_idf_model.vocabulary_.items(),
    key = lambda x: x[1], reverse = False
)
word_list = [x[0] for x in word_id_list]

tf_idf_df = pd.DataFrame(
    tf_idf_model.transform(news_df['News Title']).toarray(),
    columns = word_list,
    index = news_df['No'])
```

Representing and comparing texts

Comparing texts with cosine similarity

```
from sklearn.metrics.pairwise import cosine_similarity

cos_sim_mat = cosine_similarity(tf_idf_df, tf_idf_df)
cos_sim_df = pd.DataFrame(
    cos_sim_mat,
    columns = news_df['No'],
    index = news_df['No'])
cos_sim_df.head()
```

No	28831	22852	30526	46977	56099	41670	31460	3713
No								
28831	1.0	0.0	0.000000	0.000000	0.000000	0.048518	0.000000	0.0
22852	0.0	1.0	0.000000	0.000000	0.000000	0.000000	0.000000	0.0
30526	0.0	0.0	1.000000	0.000000	0.104795	0.053462	0.000000	0.0
46977	0.0	0.0	0.000000	1.000000	0.037844	0.000000	0.000000	0.0
56099	0.0	0.0	0.104795	0.037844	1.000000	0.053866	0.045341	0.0

Representing and comparing texts

Comparing texts with cosine similarity

```
edges = []
for i in range(len(cos_sim_df)):
    for j in range(i+1, len(cos_sim_df)):
        weight = cos_sim_df.iloc[i, j]
        edges.append((cos_sim_df.index[i], cos_sim_df.columns[j], weight))

edges_df = pd.DataFrame(edges, columns = ["source", "target", "weight"])
edges_df.head()
```

	source	target	weight
0	28831	22852	0.000000
1	28831	30526	0.000000
2	28831	46977	0.000000
3	28831	56099	0.000000
4	28831	41670	0.048518

Representing and comparing texts

Comparing texts with cosine similarity

```
edges_df_m1 = pd.merge(
    edges_df, news_df[['No', 'Category']],
    left_on = 'source',
    right_on = 'No',
    how = 'left')

edges_df_m2 = pd.merge(
    edges_df_m1, news_df[['No', 'Category']],
    left_on = 'target',
    right_on = 'No',
    how = 'left')

edges_df_m2['comb'] = edges_df_m2['Category_x'] + '-' + edges_df_m2['Category_y']

edges_df_m2.groupby('comb')['weight'].agg('mean').sort_values(ascending = False)
```

comb	
Technology-Technology	0.012829
Medical-Medical	0.011560
Entertainment-Entertainment	0.010230
Business-Business	0.009184
Entertainment-Technology	0.007170
Technology-Business	0.007043
Business-Technology	0.006878
Technology-Entertainment	0.006840
Medical-Technology	0.006420
Business-Medical	0.006369
Technology-Medical	0.006031
Entertainment-Medical	0.006014
Entertainment-Business	0.005955
Medical-Business	0.005810

Word embeddings

Vector semantics

- Vector semantics starts with learning representations of the meaning of words
- Distributional hypothesis: words that occur in similar contexts tend to have similar meanings (from the 1950s in linguists' work such as Harris 1954)
- The very beginning of vector semantics dates back at least to Osgood et al. (1957) where words were represented in a 3-dimensional vector space (valence, arousal, dominance)

	Valence	Arousal	Dominance
music	7.67	5.57	6.5
heartbreak	2.45	5.65	3.58

Word embeddings

What are word embeddings?

- Word embeddings refer to short dense vectors for representing words (Word2vec, BERT, etc.)
- They are used to position a word as a point in a multidimensional semantic space

Word embeddings

What are word embeddings?

- A paradigm shift from the traditional BoW approach
- Employ neural networks to learn word associations from a large corpus of texts (instead of (weighted) counts, word embeddings)
- Explicitly considers context (not “contextual embeddings” like BERT though)

Word embeddings

What are word embeddings?

- Many useful applications
 - Discover the relationships between words (compute their similarity)
 - Track changes in meaning
 - Other applications like text classification or clustering
- Note that dimensions are not interpretable

Word embeddings

Word2Vec

- A set of algorithms (CBOW and SGNS) for learning word representations from a corpus

Word embeddings

Pre-trained embeddings

- <https://code.google.com/archive/p/word2vec/>
- <https://nlp.stanford.edu/projects/glove/>
- <https://fasttext.cc/docs/en/english-vectors.html>