
Optimization of Surface Wave Excitation

Cameron Connolly - Electrical Engineering

April 17th, 2025



MURF 2025 Symposium

What are Surface Waves?

Electric and Magnetic Energy Traveling Along a Surface

- Stick to the surface — they don't fly off into the air
- Cause coupling between antenna elements — leading to distortion of signals
- Energy trapped in surface waves don't contribute to radiated power

[1,2]



Surface Waves Affect You




Real World Impact:

Imagine a future where

- All Wi-Fi is received through Satellite
- Your phone stays connected in remote locations

[3,4]




Why They're Undesirable:

- Wasted energy during antenna radiation
- Surface waves interfere with other antennas on an array

Synthesis of Surface-Wave Launcher


1. Objective



Create a PCB that:

- Propagates a surface wave on a substrate


2. Simulation



Use electromagnetic simulation to:

- Optimize the propagation of surface waves

3. Fabrication




Milling equipment:

- In house manufacturing of the PCB using lab equipment


[1,5]

Electromagnetic Simulation

- Substrate - Rogers 6010
- SMA connectors
- Microstrip Feedline
- Matching Section



Visualization of Electric Fields





[5,6]

Transmission and Reflection Measurements


Vector Network Analyzer (VNA)

- Measure reflection and transmission power: scattering parameters
- Used to evaluate how electrical signals propagate through a device
- Evaluates signals by sweeping frequency




S-parameters

- Similar trends and magnitude
- Lower S_{11} ; less power is being reflected, therefore more efficient
- Higher S_{21} ; more power is making it to the output port




Measure of power reflected back towards the input port



Measure of power transmitted through the device, to the output port



Electro-Optic Measurements

- ▶ Simultaneous amplitude and phase detection
- ▶ $E(x, y, z)$ vector field measurement using tangential and normal probes
- ▶ 10 MHz - 40 GHz bandwidth




Animation of E_z

- MATLAB animations
- Animates the phase change of the electric field
- Simulation and measurements E_z are normalized to the same scale
- Plotted on the actual design
- Almost identical results!



Simulation of E_z



Measurement of E_z

Investigation of Electromagnetic Bandgap Materials (EBGs)

Optimal EBG structure for surface wave termination and propagation


- EBGs can stop surface waves
- Provide frequency selective behavior
- Reduce coupling of antenna array elements



[8]

Conclusion

- Researched surface waves
- Designed and simulated a surface wave launcher
- In house manufactured the launcher
- Compared simulated and measured results to confirm existence of surface waves



References

- [1] S. C. Dunkley, On the Application of Surface Waves: Redefining the Physical Layer of Communication, BEng dissertation, Dept. Electron. and Electr. Eng., Univ. of Surrey, Guildford, UK, 2016.
- [2] C. Angulo and W. Chang, "The launching of surface waves by a parallel plate waveguide," in IRE Transactions on Antennas and Propagation, vol. 7, no. 4, pp. 359-368, October 1959, doi: 10.1109/TAP.1959.1144706.
- [3] J. Foust, "Vast to use Starlink for space station broadband communications," SpaceNews, <https://spacenews.com/vast-to-use-starlink-for-space-station-broadband-communications/> (accessed Apr. 11, 2025).
- [4] D. Werner, "Cesiumastro wins SDA contract for link 16 antennas," SpaceNews, <https://spacenews.com/cesiumastro-wins-sda-contract-for-link-16-antennas/> (accessed Apr. 11, 2025).

References

- [5] V. G. -G. Buendia, S. K. Podilchak, G. Goussetis and J. -L. Gomez-Tornero, "A TM₀ surface wave launcher by microstrip and substrate integrated waveguide technology," 2017 11th European Conference on Antennas and Propagation (EUCAP), Paris, France, 2017, pp. 3859-3862
- [6] V. G. Buendía and S. K. Podilchak, "Simple surface-wave launching by parallel-plate and microstrip feeding for leaky-wave antennas and other planar guided-wave applications," 12th European Conference on Antennas and Propagation
- [7] D. M. Pozar, Microwave Engineering. Hoboken, NJ: Wiley, 2012.
- [8] M. Long, P. Wang, H. Fang, and W. Hu, "Progress, challenges, and opportunities for 2D material based photodetectors," Advanced Functional Materials, vol. 29, no. 19, Sep. 2018

Acknowledgements

Dr. Peter Aaen

Dr. Gaberiel Santamaria-Botello

Dr. Atef Elsherbeni

Dr. Art Morris

Jackson Willner

Connor Denney

Steffen Kross

Ethan Hansen

Questions?

→ **MINES.EDU**

Cameron Connolly
Electrical Engineering

(715) 305-4276
connollyhergert@mines.edu



**COLORADO SCHOOL OF
MINES®**

**MANIPULATING SURFACE WAVES TO
IMPROVE ANTENNA ARRAY
PERFORMANCE**