


REV	DATE	DESCRIPTION
A	2026-10-24	INITIAL RELEASE




FRONT (Y SIDE)



RIGHT (END B)



BACK (KIT SIDE), END A RIGHT



ISOMETRIC 1:20

NOTES:
1. TOLERANCES PER ISO 2768-mK UNLESS OTHERWISE SPECIFIED.
2. L = D - 127 (D = X AXIS SPACING), L 615 … 2100, TOL +-0.2. DRAWN AT L = 1500.
3. STOCK EN AW-6082-T6 RECT. TUBE 200x80x10 (EN 755-9), 14.03 kg/m, INNER CORNER R <= 4.
4. BACK FACE (KIT SIDE) AND FRONT FACE (Y SIDE) MACHINED, FLATNESS 0.05.
5. BACK ENDS = ELGT-BS-160 PROFILE PATTERN FOR EHAM-AK-L9-160-L9-160-ML/-MR; END A PINNED, END B SCREWS ONLY.
6. FRONT = ELGT-BS-120 PROFILE UNDERSIDE: Y CENTRE AT L/2 + Y_POS, DRIVE FLANGE xf = L/2 + Y_POS + (STROKE + 216)/2.
7. Y SCREW HOLES AT xf - (81.5 + k x 100), k = 0,1,2 AND kmax-2 … kmax, kmax = INT((STROKE + 100)/100).
8. DRAWN FOR Y STROKE 300, Y_POS 0 (xf = 1008). Y SCREWS ISO 4762 M6x16 + ISO 7092 WASHER, HEADS INSIDE.
9. BACK WALL: ACCESS HOLES DIA 12 THRU, ON THE Y SCREW HOLE AXES (SCREW HEAD, WASHER, KEY).
10. Y PINS ISO 8734 6x18 PRESSED IN FRONT WALL. FINISH ANODIZED NATURAL 10-15 um; H7 REAMED AFTER ANODIZING.

Y BEAM X160 / Y120	SCALE 1:4 MM THIRD ANGLE
BR-ELGT-BS-160-ELGT-BS-120-2	SHEET 1 OF 1 REV A drawing