


REV	DATE	DESCRIPTION
A	2026-10-26	INITIAL RELEASE



SIDE



FRONT FACE (CARRIED AXIS SIDE)



ISOMETRIC 1:6

NOTES:
1. TOLERANCES PER ISO 2768-mK UNLESS OTHERWISE SPECIFIED.
2. MATERIAL EN AW-6082-T6 (ALT. 6061-T6) PLATE. ANODIZED NATURAL 10–15 um; H7 BORES REAMED AFTER ANODIZING.
3. MASS 4.61 kg. ORIGIN = EGC-185 SLIDE HOLE PATTERN CENTRE ON THE BACK FACE.
4. BACK FACE (ON EGC-185 SLIDE) AND FRONT FACE X = 22 (EGC-185 PROFILE): FLATNESS 0.02, PARALLEL 0.03.
5. BREAK EDGES 0.3, INNER CORNERS R <= 1.
6. BASE: 8× ISO 4762 M8×20 FROM THE FRONT + 8× M6×25 (2 THRU ZBH-9), FITTED BEFORE THE CARRIED AXIS.
7. CARRIED: 8× ISO 4762 M6×25 FROM THE BACK INTO NST-8-M6 SLOT NUTS.
8. LEDGE 4 HIGH ALONG ONE EGC-185 PROFILE SIDE (SQUARES IT); ITS UPPER END HEAD ABOVE THE PLATE.
9. RELIEF GROOVE 3 × 1.5 IN THE FRONT FACE ALONG THE LEDGE (PROFILE EDGE).
10. ZBH-9 BORES AT (Y, Z) = (60, 20) AND (-60, -20).

ADAPTER PLATE 185/185	SCALE 1:2 MM THIRD ANGLE
BR-EGC-185-EGC-185-2	SHEET 1 OF 1 REV A drawing