


REV	DATE	DESCRIPTION
A	2026-10-26	INITIAL RELEASE




TOP



ISOMETRIC 1:2.56



FRONT



RIGHT

NOTES:
1. TOLERANCES PER ISO 2768-mK UNLESS OTHERWISE SPECIFIED.
2. MATERIAL EN AW-6082-T6 (ALT. 6061-T6) PLATE. ANODIZED NATURAL 10-15 um; H7 BORES REAMED AFTER ANODIZING.
3. DRAWN: BR-EGC-80-EGC-70-1-ML. BR-EGC-80-EGC-70-1-MR = MIRROR IMAGE (Y -> -Y), SAME DIMENSIONS. MASS 0.90 kg EACH.
4. FOOT UNDERSIDE (ON EGC-80 SLIDE) AND WALL FACE X = -34 (CARRIED PROFILE): FLATNESS 0.02,
5. WALL FACE PERPENDICULAR TO FOOT UNDERSIDE 0.03; LEDGE TOP Z = 20 PARALLEL TO FOOT UNDERSIDE 0.03.
6. ORIGIN = SLIDE HOLE PATTERN CENTRE (BETWEEN THE CENTRING BORES). BREAK EDGES 0.3, INNER CORNERS R <= 1.
7. FOOT: 4x ISO 4762 M5x16 + 2x M6x16 (2 THRU ZBH-9) INTO THE SLIDE, FITTED BEFORE THE CARRIED AXIS.
8. WALL: 6x ISO 4762 M5x12 INTO NST-5-M5 SLOT NUTS (EGC-70 UNDERSIDE SLOTS).
9. CARRIED AXIS SIDE FACE ON THE LEDGE, ITS NEAR END HEAD BEHIND THE WALL END (Y < -35).
10. ZBH-9 BORES AT (X, Y) = (20, 0) AND (-20, 0).

ANGLE BRACKET 80/70	SCALE 1:2 MM THIRD ANGLE
BR-EGC-80-EGC-70-1-ML	SHEET 1 OF 1 REV A drawing