


REV	DATE	DESCRIPTION
A	2026-10-26	INITIAL RELEASE



SIDE



FRONT FACE (CARRIED AXIS SIDE)



ISOMETRIC 1:3

NOTES:
1. TOLERANCES PER ISO 2768-mK UNLESS OTHERWISE SPECIFIED.
2. MATERIAL EN AW-6082-T6 (ALT. 6061-T6) PLATE. ANODIZED NATURAL 10-15 um; H7 BORES REAMED AFTER ANODIZING.
3. MASS 0.66 kg. ORIGIN = EGC-80 SLIDE HOLE PATTERN CENTRE ON THE BACK FACE.
4. BACK FACE (ON EGC-80 SLIDE) AND FRONT FACE X = 15 (EGC-70 PROFILE): FLATNESS 0.02, PARALLEL 0.03.
5. BREAK EDGES 0.3, INNER CORNERS R <= 1.
6. BASE: 8× ISO 4762 M5×16 FROM THE FRONT + 2× M6×16 (2 THRU ZBH-9), FITTED BEFORE THE CARRIED AXIS.
7. CARRIED: 4× ISO 4762 M5×12 FROM THE BACK INTO NST-5-M5 SLOT NUTS.
8. LEDGE 4 HIGH ALONG ONE EGC-70 PROFILE SIDE (SQUARES IT); ITS UPPER END HEAD ABOVE THE PLATE.
9. ZBH-9 BORES AT (Y, Z) = (20, 0) AND (-20, 0).

ADAPTER PLATE 80/70	SCALE 1:1 MM THIRD ANGLE
BR-EGC-80-EGC-70-2	SHEET 1 OF 1 REV A drawing