

Package ‘tagbio’

December 3, 2019

Type Package

Title tagbio: methods for interacting with the tag.bio analysis platform

Version 0.1.0

Author J Ireland

Maintainer tag.bio <j@tagbio.com>

Description This library allows users to work with data from the tag.bio analysis platform directly from R.

License MIT

Encoding UTF-8

LazyData true

Depends

VignetteBuilder knitr

biocViews ThirdPartyClient

Date/Publication 2019-11-26

RoxygenNote 7.0.1

R topics documented:

addResult	1
getTagData	2
tagbio.data-class	3
tagbio.result-class	3

Index	4
--------------	----------

addResult	<i>Add data to a tagbio.result.</i>
-----------	-------------------------------------

Description

This method adds results to a tagbio.result object.

Usage

```
addResult(tagResult, resultData, resultType)
```

Arguments

tagResult	tagResult object
resultData	data.frame or file path to results data
resultType	either data.frame, jpeg, pdf, png, svg

Value

updated tagResult object

See Also

[tagbio.data](#)

Examples

```
addResult(tagresult, "my_pdf_file.pdf", type = "pdf")
```

getTagData

Retrieve data from a tag.bio flux capacitor

Description

Retrieve data from a tag.bio flux capacitor

Usage

```
getTagData(fcUrl, apiKey, arguments, protocolName = "download")
```

Arguments

fcUrl	flux capacitor API URL
apiKey	flux capacitor API key for authentication
arguments	a list of arguments to specify the API query
protocolName	name of protocol. Default is "download".

Value

A tagbio.data object with data.frame populated by query

See Also

[tagbio.result](#), [getTagData](#)

Examples

```
getTagData(FC_URL, API_KEY, list(expression = c("A1CF", "A2M"),
  clinical_categorical_variables = c("clinical.SAMPLE_ID")))
```

tagbio.data-class	<i>An S4 class representing data from the tag.bio platform</i>
-------------------	--

Description

The tagbio.data class holds tagbio.data as a data.frame attribute of the object. tagbio.data objects are typically created through a getTagData query or created directly from the flux capacitor and passed to a user defined method. The tagbio.data object may optionally have a list of parameters defined. This list is typically populated by the flux capacitor and is used to direct user defined methods.

Slots

data.frame a data frame typically retrieved from tag.bio
parameters a list of parameters from tag.bio

tagbio.result-class	<i>An S4 class representing data to return to the tag.bio platform</i>
---------------------	--

Description

The tagbio.result class allows the user to return data to the tag.bio platform. It is typically only used in user-defined protocol methods called from the flux capacitor.

Slots

data.frame a dataframe of results
jpeg path to a jpeg file
pdf path to a pdf file
png path to a png file
svg path to a svg file

Index

`addResult`, [1](#)

`getTagData`, [2](#), [2](#)

`tagbio.data`, [2](#)

`tagbio.data (tagbio.data-class)`, [3](#)

`tagbio.data-class`, [3](#)

`tagbio.result`, [2](#)

`tagbio.result (tagbio.result-class)`, [3](#)

`tagbio.result-class`, [3](#)