

Quantum Arch

Algorithmic Asymmetry, Statistical Adversarial Detection,
and Zero-Allocation Active Defense in Hardened Linux Systems

Technical White Paper — Revision 2.2 — May 2026

Taha Kouiyasse

Independent Systems Architect & Protocol Designer

Quantum Arch Research Initiative

contact@quantumarch.dev

NIC / Wire → XDP Hook → Ring Buffer → **7-Stage Pipeline**
VPIN → MTU-Track → SSA → Entropy → EKF → Hurst → Bellman
Output: DROP | TAR-PIT | HONEYPOT | LOG

Abstract

Quantum Arch is a production-grade network intrusion detection and active defense protocol written in Rust, operating at the Linux kernel boundary via eBPF/XDP. Unlike signature-based systems, it performs *statistical detection* by adapting mathematical models from high-frequency trading—Volume-Synchronized Probability of Informed Trading (VPIN), Singular Spectrum Analysis (SSA), the Extended Kalman Filter (EKF), and the Hurst Exponent—to network traffic flow analysis. The result is an adversarially robust detection engine capable of identifying structured attack campaigns that evade conventional methods.

Detected adversaries are not merely blocked; they are *exhausted, deceived, and trapped* through adaptive tar-pitting, deceptive TCP fingerprinting, and silent honeypot redirection. The entire hot path—from raw NIC frame to classification decision—executes in under **100 ns** at P99, with **zero heap allocation** after initialisation, operating within a fixed **256 MB** memory arena under arbitrary traffic load. This document provides a complete mathematical, architectural, and operational specification.

Contents

1	Introduction and Design Rationale	3
1.1	System Guarantees	3
2	Architecture Overview	3
2.1	Crate Structure	3
2.1.1	The <code>SignalFrame</code> Contract	4
2.2	Hot Path Data Flow	4
3	Detection Engine: The 7-Stage Pipeline	4
3.1	Stage 1 — VPIN: Volume-Synchronized Probability of Informed Trading	4
3.2	Stage 2 — MTU-Track	5
3.3	Stage 3 — SSA: Singular Spectrum Analysis	5
3.3.1	Trajectory Matrix Construction	5

3.3.2	Singular Value Decomposition	5
3.3.3	Dominant Reconstruction	5
3.4	Stage 4 — Dual Entropy Analysis	6
3.4.1	Shannon Entropy	6
3.4.2	Rényi Entropy ($\alpha = 2$)	6
3.5	Stage 5 — Extended Kalman Filter	6
3.5.1	Process Model	6
3.5.2	Measurement Update	6
3.5.3	Innovation Test	6
3.5.4	Anti-Poisoning Baseline Reset	6
3.6	Stage 6 — Hurst Exponent + Z-Score Double Gate	7
3.7	Stage 7 — Bellman Composite Score	7
4	Active Defence Mechanisms	7
4.1	Adaptive Tar-Pit (60–90%)	7
4.2	Shifting Ghost Honeypot (>90%)	8
4.3	Deceptive Fingerprinting	8
5	Performance Specification	8
5.1	Memory Allocation Invariant	8
6	Operational Lifecycle	9
6.1	Deployment Sequence	9
6.2	Operational Modes	9
6.3	RBAC and Governance	9
7	SIEM Integration	10
8	Theoretical Foundations and Prior Work	10
9	Conclusion	11

1. Introduction and Design Rationale

Modern network adversaries operate with increasing statistical sophistication. Low-and-slow exfiltration campaigns deliberately keep per-flow volume below threshold-based alert levels. Encrypted tunnels render payload inspection ineffective. Slow DDoS ramp-ups mimic organic traffic growth. These attack patterns share a common property: they are *structurally anomalous* even when they are volumetrically invisible.

Signature-based detection—pattern matching against known indicators of compromise—is epistemically bounded. It can only detect what has been observed and catalogued. Statistical detection operates on a different principle: it models the *structure* of legitimate traffic and flags deviations from that structure, regardless of whether the deviation matches any prior signature.

The design philosophy of Quantum Arch is grounded in a direct analogy: high-frequency financial trading. In that domain, detecting *informed actors*—traders with private information who exploit it at the expense of market makers—inside noisy, adversarial, real-time data streams is a billion-dollar problem. VPIN was developed to solve exactly this: identifying flow *toxicity* without knowing the content of any individual trade. SSA was developed to extract structural signals from financial time series contaminated by cyclical noise and transient shocks. EKF models non-linear system state evolution under measurement uncertainty.

Applied to network traffic, these models detect adversarial actors with a statistical depth that volume counting cannot achieve. The adaptation *is* the contribution.

1.1. System Guarantees

1. **Zero dynamic allocation on the hot path.** After `init()`, no heap allocations occur. A custom allocator wrapper `panic!()`s on any violation, making the guarantee compile-time auditable.
2. **Sub-100 ns P99 classification latency.** Benchmarked end-to-end from NIC frame arrival to action dispatch.
3. **Fixed memory footprint.** 256 MB arena. No growth under any traffic condition or adversarial load.
4. **No single-gate classification.** All seven detection stages must agree before automated action triggers. This architecture minimises false positives structurally, not through threshold tuning.

2. Architecture Overview

2.1. Crate Structure

The system is decomposed into three Rust crates with a strict boundary between kernel space and userspace.

Table 1: Crate responsibilities and layer boundaries.

Crate	Layer	Role
<code>sg-common</code>	Shared ABI	Defines <code>SignalFrame</code> : 64-byte, cache-line-aligned packet contract
<code>sg-ebpf</code>	Kernel (XDP)	Zero-copy capture via <code>BPF_MAP_TYPE_RINGBUF</code> ; pre-stack interception
<code>sg-capture</code>	Userspace	32-thread lock-free analysis engine and active defence dispatcher

2.1.1. The *SignalFrame* Contract

The **SignalFrame** is a 64-byte struct aligned to a single cache line. It carries all per-packet metadata required by the 7-stage pipeline without any pointer indirection or heap reference.

```

1  #[repr(C, align(64))]
2  pub struct SignalFrame {
3      pub timestamp_ns: u64,      // kernel ktime
4      pub src_ip:          u32,
5      pub dst_ip:          u32,
6      pub src_port:        u16,
7      pub dst_port:        u16,
8      pub pkt_len:         u16,
9      pub proto:           u8,
10     pub flags:            u8,      // TCP flags or custom metadata
11     pub direction:       u8,      // IN / OUT
12     pub _pad:            [u8; 31],
13 }
14 // Compile-time assertion: sizeof(SignalFrame) == 64
15 const _: () = assert!(core::mem::size_of::<SignalFrame>() == 64);

```

Listing 1: *SignalFrame* definition (sg-common).

2.2. Hot Path Data Flow




Figure 1: Quantum Arch hot path: kernel-to-userspace via zero-copy ring buffer.

The XDP program (**sg-ebpf**) intercepts packets *before* they enter the Linux network stack. Zero-copy submission to the ring buffer costs under 5 ns. Userspace polling (**sg-capture**) receives frames without a system call round-trip, contributing under 10 ns to the hot path budget.

3. Detection Engine: The 7-Stage Pipeline

Every suspicious flow traverses a sequentially gated pipeline. All seven stages must independently flag a flow before automated action is dispatched. This conjunction gate is the primary false-positive suppressor.

3.1. Stage 1 — VPIN: Volume-Synchronized Probability of Informed Trading

Definition 1 (VPIN). Let V be the total bucket volume and V_i^B , V_i^S the buy-side and sell-side volumes in bucket i . The VPIN over a window of n buckets is:

$$\text{VPIN} = \frac{1}{n \cdot V} \sum_{i=1}^n |V_i^B - V_i^S| \quad (1)$$

In the network domain, buckets accumulate 10,000 packet-unit volumes. “Buy” and “sell” are reinterpreted as inbound and outbound directional flow imbalance. A sliding window of 50 buckets is maintained.

Proposition 1. $\text{VPIN} \geq 0.72$ is consistent with the presence of an informed actor (scanner, exfiltrator, or DDoS source) whose traffic is structurally directional rather than conversational.

Gate: $\text{VPIN} \geq 0.72 \Rightarrow$ proceed to Stage 2.

3.2. Stage 2 — MTU-Track

Mean packet size $\bar{L}$ is tracked over a 100,000-slot circular window using Welford’s online algorithm (O(1) per update, zero heap allocation):

$$\bar{L}_n = \bar{L}_{n-1} + \frac{L_n - \bar{L}_{n-1}}{n} \quad (2)$$

- $\Delta\bar{L} \leq -40\%$ relative to baseline $\Rightarrow$ **port scan** pattern; triggers Deceptive Fingerprinting response.
- $\Delta\bar{L}$ sustained positive over ≥ 10 epochs $\Rightarrow$ **tunneling or exfiltration** pattern.

3.3. Stage 3 — SSA: Singular Spectrum Analysis

SSA decomposes the inter-packet latency time series $\mathbf{x} = (x_1, \dots, x_N)$ into structural components via the trajectory matrix and its SVD.

3.3.1. Trajectory Matrix Construction

Choose embedding dimension L (window length). Form the $L \times K$ trajectory matrix where $K = N - L + 1$:

$$\mathbf{X} = \begin{pmatrix} x_1 & x_2 & \cdots & x_K \\ x_2 & x_3 & \cdots & x_{K+1} \\ \vdots & & \ddots & \vdots \\ x_L & x_{L+1} & \cdots & x_N \end{pmatrix} \quad (3)$$

3.3.2. Singular Value Decomposition

$$\mathbf{X} = \mathbf{U}\mathbf{\Sigma}\mathbf{V}^\top = \sum_{i=1}^d \sigma_i \mathbf{u}_i \mathbf{v}_i^\top \quad (4)$$

where $\sigma_1 \geq \sigma_2 \geq \dots \geq \sigma_d \geq 0$.

3.3.3. Dominant Reconstruction

The first reconstructed component RC_1 filters the dominant structural signal from noise:

$$\text{RC}_1 = \sigma_1 \mathbf{u}_1 \mathbf{v}_1^\top \quad (5)$$

Definition 2 (Eigenvalue Drift). Let $\sigma_1^{(t)}$ be the leading singular value at epoch t . Define the relative drift over $W = 10$ buckets as:

$$\Delta_\sigma = \frac{\sigma_1^{(t)} - \sigma_1^{(t-W)}}{\sigma_1^{(t-W)}} \quad (6)$$

A structural anomaly is declared when $|\Delta_\sigma| \geq 0.15$.

SSA captures DDoS ramp-ups and covert tunnels that produce persistent eigenvalue drift while remaining below volumetric detection thresholds.

Remark 1. SSA and Hurst computation are amortised over 5-second epochs and execute in a background thread, never blocking the capture pipeline. Their contribution to P99 hot-path latency is zero by design.

3.4. Stage 4 — Dual Entropy Analysis

Encrypted exfiltration and covert tunnels produce high-entropy payloads. Entropy is computed over a *stack-resident* 32-bin byte-frequency histogram—zero heap allocation.

3.4.1. Shannon Entropy

$$H_S = - \sum_{b=0}^{255} p_b \log_2 p_b \quad (7)$$

Gate: $H_S > 0.95$ on a non-standard port $\Rightarrow$ ENCRYPTED_EXFIL.

3.4.2. Rényi Entropy ($\alpha = 2$)

$$H_2 = - \log_2 \sum_{b=0}^{255} p_b^2 \quad (8)$$

Gate: Concentration spike (H_2 low, H_S high) on non-standard port $\Rightarrow$ ENCRYPTED_TUNNEL. Crucially, neither gate requires *any* payload decryption or deep packet inspection.

3.5. Stage 5 — Extended Kalman Filter

The EKF models the observed network state as a dynamical system with latent state vector $\mathbf{s} = [\text{position}, \text{velocity}, \text{acceleration}]^\top$ in a flow-metric space.

3.5.1. Process Model

$$\mathbf{s}_k = \mathbf{F}\mathbf{s}_{k-1} + \mathbf{w}_k, \quad \mathbf{w}_k \sim \mathcal{N}(\mathbf{0}, \mathbf{Q}) \quad (9)$$

where $\mathbf{F}$ is the constant-acceleration state transition matrix and $\mathbf{Q}$ the process noise covariance.

3.5.2. Measurement Update

$$\hat{\mathbf{s}}_{k|k-1} = \mathbf{F}\hat{\mathbf{s}}_{k-1|k-1} \quad (10)$$

$$\mathbf{P}_{k|k-1} = \mathbf{F}\mathbf{P}_{k-1|k-1}\mathbf{F}^\top + \mathbf{Q} \quad (11)$$

$$\mathbf{K}_k = \mathbf{P}_{k|k-1}\mathbf{H}^\top (\mathbf{H}\mathbf{P}_{k|k-1}\mathbf{H}^\top + \mathbf{R}_k)^{-1} \quad (12)$$

$$\hat{\mathbf{s}}_{k|k} = \hat{\mathbf{s}}_{k|k-1} + \mathbf{K}_k(\mathbf{z}_k - \mathbf{H}\hat{\mathbf{s}}_{k|k-1}) \quad (13)$$

The measurement noise covariance $\mathbf{R}_k$ is *adaptive*: it is weighted by the current VPIN score, so that high-flow-imbalance periods are treated as less trustworthy observations.

$$\mathbf{R}_k = \mathbf{R}_0 \cdot (1 + \alpha \cdot \text{VPIN}_k), \quad \alpha = 2.0 \quad (14)$$

3.5.3. Innovation Test

The Kalman innovation $\boldsymbol{\varepsilon}_k = \mathbf{z}_k - \mathbf{H}\hat{\mathbf{s}}_{k|k-1}$ is tested for outliers:

$$\text{Flag if } \|\boldsymbol{\varepsilon}_k\| > 2.7\sigma_\varepsilon \quad (15)$$

3.5.4. Anti-Poisoning Baseline Reset

Every 24 hours the EKF is reset from a cryptographically signed `baseline_gold.json` (HMAC-SHA256). This prevents an adversary from conducting a slow *model poisoning* attack—gradually nudging the filter’s steady state to accept malicious traffic as baseline.

3.6. Stage 6 — Hurst Exponent + Z-Score Double Gate

Definition 3 (Hurst Exponent via R/S Analysis). *For a time series of length n with range R and standard deviation S :*

$$H \approx \frac{\log(R/S)}{\log(n)} \quad (16)$$

- $H \approx 0.5$: random, uncorrelated process. Likely legitimate traffic.
- $H > 0.65$: persistent, long-range-correlated process. Signature of a structured, sustained attack campaign.

The double gate requires *both* conditions simultaneously:

$$H > 0.65 \wedge Z_\varepsilon > 2.3 \quad (17)$$

where Z_ε is the standardised Kalman innovation score from Stage 5. This conjunction is the primary false-positive suppressor in the pipeline.

3.7. Stage 7 — Bellman Composite Score

$$S_{\text{final}} = 0.40 \cdot H_{\text{entropy}} + 0.30 \cdot \text{VPIN} + 0.30 \cdot \varepsilon_{\text{EKF}}^{\text{norm}} \quad (18)$$

where $\varepsilon_{\text{EKF}}^{\text{norm}}$ is the EKF innovation normalised against the 30-day rolling distribution of innovations.

S_{final} is calibrated against a 30-day rolling empirical distribution. Only the top 5% of observed scores trigger automated action. No manual threshold tuning is required.

Table 2: Score-to-action mapping.

Percentile	Classification	Response
< 60%	Benign	Log only
60–90%	Suspicious	Adaptive Tar-Pit
> 90%	Confirmed Threat	DROP or Honeypot
eBPF kernel hit	Override	Immediate max score

4. Active Defence Mechanisms

Quantum Arch does not simply *block* adversaries. It imposes asymmetric costs through three distinct mechanisms.

4.1. Adaptive Tar-Pit (60–90%)

The attacker is not blocked—they are slowed without knowing it.

1. **TCP Window Zero**: Forces exponential back-off in the adversary’s TCP stack. The attacker’s own congestion control burns their CPU and bandwidth.
2. **tc jitter injection**: 200–400 ms variable delay with 25% dispersion. The connection appears degraded. Automated attack tooling stalls waiting for responses that arrive erratically.

4.2. Shifting Ghost Honeypot (>90%)

The attacker’s connection is silently DNAT’d mid-session to an isolated decoy container. The adversary believes they have reached the real target.

```
1 nft add rule ip nat prerouting \
2   ip saddr <attacker_ip> tcp dport 22 \
3   dnat to 10.1.1.100:2222
```

Listing 2: nftables DNAT rule for honeypot redirection.

Inside the honeypot: a realistic SSH shell, HTTP/HTTPS responses, and service banners. Every keystroke is logged for IOC extraction and attacker profiling.

4.3. Deceptive Fingerprinting

Triggered on scan detection (Stage 2 gate). The **sg-ebpf** XDP program modifies outgoing TCP headers *for that flow only*:

- **TTL alteration** (e.g., 128 $\rightarrow$ 64): implies a different OS family.
- **MSS change** (e.g., 1460 $\rightarrow$ 1200): implies a non-standard path MTU.
- **Synthetic unknown TCP options**: produces OS fingerprints that match no real operating system in Nmap, p0f, or Zmap signature databases.

The adversary’s reconnaissance returns contradictory, unusable intelligence.

5. Performance Specification

All figures are at P99 on a single modern x86-64 core unless noted.

Table 3: Hot-path stage latency budget (P99).

Stage	Latency	Notes
XDP header extraction	< 20 ns	sg-ebpf
Ring buffer submission	< 5 ns	zero-copy BPF_MAP_TYPE_RINGBUF
Userspace frame poll	< 10 ns	zero-copy, no syscall
VPIN bucket update	< 15 ns	Welford accumulator
EKF predict + update	< 20 ns	fixed 3-state, stack-resident
Entropy (stack histogram)	< 15 ns	32-bin, no heap
Action dispatch	< 15 ns	nftables rule prepend
Total hot-path P99	< 100 ns	

Throughput: 50,000+ PPS per interface before flood threshold.

Memory: 256 MB fixed arena; no growth under any traffic condition.

CPU: < 5% on a single core at 10,000 PPS; scales linearly across 32 pinned worker threads.

SSA + Hurst: amortised over 5-second epochs, asynchronous, never blocking the capture pipeline.

5.1. Memory Allocation Invariant


```

1 pub struct HotPathAllocator {
2     inner: BumpAllocator,
3     init_complete: AtomicBool,
4 }
5
6 unsafe impl GlobalAlloc for HotPathAllocator {
7     unsafe fn alloc(&self, layout: Layout) -> *mut u8 {
8         if self.init_complete.load(Ordering::Relaxed) {
9             // Any allocation after init() is a hard bug.
10            panic!("Hot-path allocation violation: {:?}" , layout);
11        }
12        self.inner.alloc(layout)
13    }
14 }

```

Listing 3: Custom allocator wrapper enforcing zero-allocation invariant.

6. Operational Lifecycle

6.1. Deployment Sequence

```

1 # 1. Compile with BTF support (requires Linux kernel >= 5.8)
2 cargo build --release --package sg-ebpf
3
4 # 2. Attach XDP program to target interface
5 quantum-arch attach --iface eth0
6
7 # 3. Read-only calibration (7 days minimum)
8 quantum-arch start --mode readonly
9
10 # 4. Generate cryptographically signed baseline
11 quantum-arch baseline generate
12 # -> produces baseline_gold.json (HMAC-SHA256)
13
14 # 5. Human operator validates with network specialist
15 quantum-arch baseline validate
16
17 # 6. Enable production mode
18 quantum-arch mode auto

```

Listing 4: Full deployment procedure.

Production mode requires explicit human validation of the signed baseline. No automated actions fire before this gate. This is not a configuration option; it is a hard dependency in the state machine.

6.2. Operational Modes

6.3. RBAC and Governance

- **Three roles:** Security Administrator, SOC Operator, Auditor (read-only).
- **Audit trail:** Every configuration change is logged with (who, when, what, file-hash).
- **Data retention:** Detection logs 90 days; raw flow metadata 7 days.
- **GDPR:** IP pseudonymisation (last-octet masking) available for EU deployments. All log egress over TLS only.

Table 4: Operational mode definitions.

Mode	Behaviour
Automatic	All > 90% flows trigger automated response. Default production mode.
Semi-Manual	Alerts generated; human operator approves all actions. Triggered automatically when block rate exceeds 10/hour or attack pattern is slow and low-volume.
KillSwitch	Full automation suspended. Observer mode. Maximum forensic logging. Activated manually or on integrity check failure.

- **Whitelist integrity:** `whitelist.json` is HMAC-SHA256 signed. Any unsigned modification suspends automatic mode until re-validated by an administrator.

7. SIEM Integration

Quantum Arch emits structured JSON over TLS to any compatible SIEM:

```

1 {
2   "timestamp":      "2026-05-01T14:23:11.482Z",
3   "src_ip":         "192.168.1.0",           // last octet masked (GDPR
4   "dst_port":       443,
5   "score":          0.94,
6   "anomaly_type":   "ENCRYPTED_EXFIL",
7   "action_taken":   "HONEYPOT_REDIRECT",
8   "hurst_h":        0.71,
9   "vpin":           0.83,
10  "ekf_z":           3.1
11 }
```

Listing 5: JSON alert schema.

Compatible with: Elastic SIEM, Splunk, Graylog, IBM QRadar, Prometheus, Grafana, and any SIEM accepting JSON-over-TLS.

An embedded HTTP API exposes:

- Real-time score distribution histograms.
- Live high-risk flow table with per-flow score and anomaly type.
- `POST /label {alert_id, verdict: "fp" | "tp"}` for operator feedback feeding the auto-tuning loop.

8. Theoretical Foundations and Prior Work

The detection models in Quantum Arch are grounded in peer-reviewed mathematics. The contribution of this work is their co-adaptation into a unified, zero-allocation, real-time detection pipeline.

VPIN. Originally developed to detect order flow *toxicity*—the degree to which a trading venue’s flow is dominated by informed, directional actors [Easley et al., 2012]. Applied here, toxicity translates to asymmetric network flow imbalance indicative of scanning, exfiltration, or amplification.

SSA. A non-parametric, data-adaptive spectral decomposition method for time series [Golyandina et al., 2001]. Unlike FFT, SSA does not require stationarity and is robust to missing data and noise. Its application to inter-packet latency series extracts the persistent structural component of an attack while filtering transient noise.

Kalman Filter. The foundational recursive estimator for linear dynamical systems under Gaussian noise [Kalman, 1960]. The Extended Kalman Filter generalises this to non-linear process models. The VPIN-weighted adaptive noise covariance is an original contribution of this work.

Hurst Exponent. Introduced in the context of hydrological time series [Hurst, 1951] and subsequently central to fractal analysis. In network traffic, $H > 0.65$ distinguishes persistent, long-range-dependent flows (structured attacks) from memoryless Poisson-like legitimate traffic.

Rényi Entropy. A generalisation of Shannon entropy parametrised by order α [Rényi, 1961]. At $\alpha = 2$, it is the collision entropy, sensitive to concentration in the byte-frequency distribution—distinguishing encrypted tunnels from high-entropy random noise.

XDP / eBPF. The eXpress Data Path provides in-kernel programmable packet processing with verified safety guarantees [Høiland-Jørgensen et al., 2018]. The Aya Rust library enables type-safe eBPF program authorship without C [Aya-rs contributors, 2023].

9. Conclusion

Quantum Arch demonstrates that the mathematical machinery developed for adversarial detection in high-frequency financial markets translates directly—and powerfully—to network intrusion detection. By operating at the kernel/XDP boundary with zero dynamic allocation, it eliminates the jitter, page-fault latency, and allocator contention that cause conventional userspace IDS systems to miss sub-millisecond attack windows.

The 7-stage pipeline’s conjunction gate architecture ensures that no single statistical model’s false-positive rate compounds into unacceptable alert noise. The active defence layer—tar-pitting, deceptive fingerprinting, and honeypot redirection—imposes genuine asymmetric costs on adversaries rather than merely discarding their packets.

The system is production-ready, deploying against real network infrastructure with a mandatory 7-day calibration period, human-validated signed baselines, full SIEM integration, and GDPR-compliant data handling.

Engagement. The author is available for institutional engagement, technical review sessions, and proof-of-concept collaborations.

References

- Easley, D., Lopez de Prado, M., & O’Hara, M. (2012). The exchange of flow toxicity. *Journal of Portfolio Management*, 38(2), 9–28.
- Golyandina, N., Nekrutkin, V., & Zhigljavsky, A. (2001). *Analysis of Time Series Structure: SSA and Related Techniques*. CRC Press.
- Gregg, B. (2019). *BPF Performance Tools*. Addison-Wesley.
- Høiland-Jørgensen, T., Brouer, J. D., Borkmann, D., Fastabend, J., Herbert, T., Ahern, D., & Miller, D. (2018). The eXpress data path: Fast programmable packet processing in the operating system kernel. In *Proceedings of ACM CoNEXT 2018*.

- Hurst, H. E. (1951). Long-term storage capacity of reservoirs. *Transactions of the American Society of Civil Engineers*, 116, 770–799.
- Kalman, R. E. (1960). A new approach to linear filtering and prediction problems. *Journal of Basic Engineering*, 82(1), 35–45.
- Rényi, A. (1961). On measures of entropy and information. In *Proceedings of the 4th Berkeley Symposium on Mathematical Statistics and Probability*, Vol. 1, pp. 547–561.
- Aya-rs contributors. (2023). Aya: An eBPF library for the Rust programming language. <https://github.com/aya-rs/aya>.